

TITLE 18. ENVIRONMENTAL QUALITY

CHAPTER 11. DEPARTMENT OF ENVIRONMENTAL QUALITY
WATER QUALITY STANDARDS**ARTICLE 1. WATER QUALITY STANDARDS FOR
SURFACE WATERS**

Article 1, consisting of Appendices A through C, repealed April 24, 1996 (Supp. 96-2).

Article 1, consisting of Section R18-11-103, reserved effective April 24, 1996 (Supp. 96-2).

Article 1, consisting of Sections R18-11-105 and R18-11-106, and Appendices A and B, adopted April 24, 1996 (Supp. 96-2).

Article 1, consisting of Sections R18-11-101 and R18-11-102, R18-11-104, R18-11-107 through R18-11-109, R18-11-111 through R18-11-113, R18-11-115, R18-11-117 and R18-11-118, R18-11-120 and R18-11-121, amended effective April 24, 1996 (Supp. 96-2).

Article 1, consisting of Sections R18-11-101 through R18-11-121 and Appendices A through C, adopted effective February 18, 1992 (Supp. 92-1).

Article 1, consisting of Section R18-11-101, repealed effective February 18, 1992 (Supp. 92-1).

Article 1 consisting of Section R9-21-101 renumbered as Article 1, Section R18-11-101 (Supp. 87-3).

Section

R18-11-101.	Definitions
R18-11-102.	Applicability
R18-11-103.	Repealed
R18-11-104.	Designated Uses
R18-11-105.	Tributaries; Designated Uses
R18-11-106.	Net Ecological Benefit
R18-11-107.	Antidegradation
R18-11-107.01.	Antidegradation Criteria
R18-11-108.	Narrative Water Quality Standards
R18-11-108.01.	Narrative Biological Criteria for Wadeable, Perennial Streams
R18-11-108.02.	Narrative Bottom Deposit Criteria for Wadeable, Perennial Streams
R18-11-108.03.	Narrative Nutrient Criteria for Lakes and Reservoirs
R18-11-109.	Numeric Water Quality Standards
R18-11-110.	Salinity Standards for the Colorado River
R18-11-111.	Analytical Methods
R18-11-112.	Outstanding Arizona Waters
R18-11-113.	Effluent-Dependent Waters
R18-11-114.	Mixing Zones
R18-11-115.	Site-Specific Standards
R18-11-116.	Resource Management Agencies
R18-11-117.	Canals and Urban Park Lakes
R18-11-118.	Dams and Flood Control Structures
R18-11-119.	Natural Background
R18-11-120.	Enforcement
R18-11-121.	Schedules of Compliance
R18-11-122.	Variances
R18-11-123.	Discharge Prohibitions
Appendix A.	Numeric Water Quality Standards
Appendix B.	Surface Waters and Designated Uses
Appendix C.	Site-Specific Standards

ARTICLE 2. REPEALED

Article 2, consisting of Sections R18-11-201 through R18-11-205, adopted effective February 18, 1992 (Supp. 92-1).

Article 2, consisting of Sections R18-11-201 through R18-11-214 and Appendices A and B, repealed effective February 18, 1992 (Supp. 92-1).

Article 2 consisting of Sections R9-21-201 through R9-21-214 and Appendices A and B renumbered as Article 2, Sections R18-11-201 through R18-11-214 and Appendices A and B (Supp. 87-3).

**ARTICLE 3. RECLAIMED WATER QUALITY
STANDARDS**

Article 3, consisting of Sections R18-11-301 through R18-11-309 and Table A, adopted by final rulemaking at 7 A.A.R. 870, effective January 22, 2001 (Supp. 01-1).

Article 3 heading repealed effective April 24, 1996 (Supp. 96-2).

Article 3, consisting of Sections R18-11-301 through R18-11-304 repealed effective February 18, 1992 (Supp. 92-1).

Article 3 consisting of Sections R9-21-301 through R9-21-304 renumbered as Article 3, Sections R18-11-301 through R18-11-304 (Supp. 87-3).

Section

R18-11-301.	Definitions
R18-11-302.	Applicability
R18-11-303.	Class A+ Reclaimed Water
R18-11-304.	Class A Reclaimed Water
R18-11-305.	Class B+ Reclaimed Water
R18-11-306.	Class B Reclaimed Water
R18-11-307.	Class C Reclaimed Water
R18-11-308.	Industrial Reuse
R18-11-309.	Reclaimed Water Quality Standards for an Unlisted Type of Direct Reuse
Table A.	Minimum Reclaimed Water Quality Requirements for Direct Reuse

ARTICLE 4. AQUIFER WATER QUALITY STANDARDS

Section

R18-11-401.	Definitions
R18-11-402.	Repealed
R18-11-403.	Analytical Methods
R18-11-404.	Laboratories
R18-11-405.	Narrative Aquifer Water Quality Standards
R18-11-406.	Numeric Aquifer Water Quality Standards: Drinking Water Protected Use
R18-11-407.	Aquifer Water Quality Standards in Reclassified Aquifers
R18-11-408.	Petition for Adoption of a Numeric Aquifer Water Quality Standard
Appendix 1.	Repealed
Appendix 2.	Repealed
Appendix 3.	Repealed
Appendix 4.	Repealed
Appendix 5.	Repealed
Appendix 6.	Repealed
Appendix 7.	Repealed

ARTICLE 5. AQUIFER BOUNDARY AND PROTECTED USE CLASSIFICATION

New Article 5 consisting of Sections R18-11-501 through R18-11-504 and Section R18-11-506 adopted effective October 22, 1987.

Section

- R18-11-501. Definitions
- R18-11-502. Aquifer boundaries
- R18-11-503. Petition for reclassification
- R18-11-504. Agency action on petition
- R18-11-505. Public participation
- R18-11-506. Rescission of reclassification

ARTICLE 6. IMPAIRED WATER IDENTIFICATION

Article 6, consisting of Sections R18-11-601 through R18-11-606, made by final rulemaking at 8 A.A.R. 3380, effective July 12, 2002 (Supp. 02-3).

Section

- R18-11-601. Definitions
- R18-11-602. Credible Data
- R18-11-603. General Data Interpretation Requirements
- R18-11-604. Types of Surface Waters Placed on the Planning List and 303(d) List
- R18-11-605. Evaluating a Surface Water or Segment for Listing and Delisting
- R18-11-606. TMDL Priority Criteria for 303(d) Listed Surface Waters or Segments

ARTICLE 1. WATER QUALITY STANDARDS FOR SURFACE WATERS

R18-11-101. Definitions

The following terms apply to this Article:

1. "Acute toxicity" means toxicity involving a stimulus severe enough to induce a rapid response. In aquatic toxicity tests, an effect observed in 96 hours or less is considered acute.
2. "Agricultural irrigation (AgI)" means the use of a surface water for crop irrigation.
3. "Agricultural livestock watering (AgL)" means the use of a surface water as a water supply for consumption by livestock.
4. "Annual mean" is the arithmetic mean of monthly values determined over a consecutive 12-month period, provided that monthly values are determined for at least three months. A monthly value is the arithmetic mean of all values determined in a calendar month.
5. "Aquatic and wildlife (cold water) (A&Wc)" means the use of a surface water by animals, plants, or other cold-water organisms, generally occurring at an elevation greater than 5000 feet, for habitation, growth, or propagation.
6. "Aquatic and wildlife (effluent-dependent water) (A&Wedw)" means the use of an effluent-dependent water by animals, plants, or other organisms for habitation, growth, or propagation.
7. "Aquatic and wildlife (ephemeral) (A&We)" means the use of an ephemeral water by animals, plants, or other organisms, excluding fish, for habitation, growth, or propagation.
8. "Aquatic and wildlife (warm water) (A&Ww)" means the use of a surface water by animals, plants, or other warm-water organisms, generally occurring at an elevation less than 5000 feet, for habitation, growth, or propagation.
9. "Arizona Pollutant Discharge Elimination System (AZPDES)" means the point source discharge permitting program established under 18 A.A.C. 9, Article 9.

10. "Assimilative capacity" means the difference between the baseline water quality concentration for a pollutant and the most stringent applicable water quality criterion for that pollutant.
11. "Clean Water Act" means the Federal Water Pollution Control Act [33 U.S.C. 1251 to 1387].
12. "Criteria" means elements of water quality standards that are expressed as pollutant concentrations, levels, or narrative statements representing a water quality that supports a designated use.
13. "Critical flow condition" means the lowest flow over seven consecutive days that has a probability of occurring once in 10 years (7 Q 10).
14. "Deep lake" means a lake or reservoir with an average depth of more than 6 meters.
15. "Designated use" means a use specified in Appendix B of this Article for a surface water.
16. "Domestic water source (DWS)" means the use of a surface water as a source of potable water. Treatment of a surface water may be necessary to yield a finished water suitable for human consumption.
17. "Effluent-dependent water (EDW)" means a surface water, classified under R18-11-113, that consists of a point source discharge of wastewater. An effluent-dependent water is a surface water that, without the point source discharge of wastewater, would be an ephemeral water.
18. "Ephemeral water" means a surface water that has a channel that is at all times above the water table and flows only in direct response to precipitation.
19. "Existing use" means a use attained in the waterbody on or after November 28, 1975, whether or not it is included in the water quality standards.
20. "Fish consumption (FC)" means the use of a surface water by humans for harvesting aquatic organisms for consumption. Harvestable aquatic organisms include, but are not limited to, fish, clams, turtles, crayfish, and frogs.
21. "Full-body contact (FBC)" means the use of a surface water for swimming or other recreational activity that causes the human body to come into direct contact with the water to the point of complete submergence. The use is such that ingestion of the water is likely and sensitive body organs, such as the eyes, ears, or nose, may be exposed to direct contact with the water.
22. "Geometric mean" means the n th root of the product of n items or values. The geometric mean is calculated using the following formula:

$$GM_Y = \sqrt[n]{(Y_1)(Y_2)(Y_3)\dots(Y_n)}$$
23. "Hardness" means the sum of the calcium and magnesium concentrations, expressed as calcium carbonate (CaCO₃) in milligrams per liter.
24. "Igneous lake" means a lake located in volcanic, basaltic, or granite geology and soils.
25. "Intermittent water" means a stream or reach that flows continuously only at certain times of the year, as when it receives water from a spring or from another surface source, such as melting snow.
26. "Mixing zone" means an area or volume of a surface water that is contiguous to a point source discharge where dilution of the discharge takes place.
27. "Oil" means petroleum in any form, including crude oil, gasoline, fuel oil, diesel oil, lubricating oil, or sludge.
28. "Outstanding Arizona water (OAW)" means a surface water that is classified as an outstanding state resource water by the Director under R18-11-112.
29. "Partial-body contact (PBC)" means the recreational use of a surface water that may cause the human body to come into direct contact with the water, but normally not to the point of complete submergence (for example, wading or boating). The use is such that ingestion of the water is not likely and sensitive body organs, such as the

- eyes, ears, or nose, will not normally be exposed to direct contact with the water.
30. "Perennial water" means a surface water that flows continuously throughout the year.
 31. "*Pollutant*" means fluids, contaminants, toxic wastes, toxic pollutants, dredged spoil, solid waste, substances and chemicals, pesticides, herbicides, fertilizers and other agricultural chemicals, incinerator residue, sewage, garbage, sewage sludge, munitions, petroleum products, chemical wastes, biological materials, radioactive materials, heat, wrecked or discarded equipment, rock, sand, cellar dirt, and mining, industrial, municipal, and agricultural wastes or any other liquid, solid, gaseous, or hazardous substance. A.R.S. § 49-201(29)
 32. "Practical quantitation limit" means the lowest level of quantitative measurement that can be reliably achieved during a routine laboratory operation.
 33. "Reference condition" means a set of ecological measurements from a population of relatively undisturbed waterbodies within a region that establish a basis for making comparisons of biological condition among samples.
 34. "Regional Administrator" means the Regional Administrator of Region IX of the U.S. Environmental Protection Agency.
 35. "Regulated discharge" means a point-source discharge regulated under an AZPDES permit, a discharge regulated by a § 404 permit, and any discharge authorized by a federal permit or license that is subject to state water quality certification under § 401 of the Clean Water Act.
 36. "Riffle habitat" means a stream segment where moderate water velocity and substrate roughness produce moderately turbulent conditions that break the surface tension of the water and may produce breaking wavelets that turn the surface water into white water.
 37. "Run habitat" means a stream segment where there is moderate water velocity that does not break the surface tension of the water and does not produce breaking wavelets that turn the surface water into white water.
 38. "Sedimentary lake" means a lake or reservoir in sedimentary or karst geology and soils.
 39. "Shallow lake" means a lake or reservoir, excluding an urban lake, with a smaller, flatter morphology and an average depth of less than 3 meters and a maximum depth of less than 4 meters.
 40. "Significant degradation" means:
 - a. The consumption of 20 percent or more of the available assimilative capacity for a pollutant of concern at critical flow conditions, or
 - b. Any consumption of assimilative capacity beyond the cumulative cap of 50 percent of assimilative capacity.
 41. "Surface water" means a water of the United States and includes the following:
 - a. A water that is currently used, was used in the past, or may be susceptible to use in interstate or foreign commerce;
 - b. An interstate water, including an interstate wetland;
 - c. All other waters, such as an intrastate lake, reservoir, natural pond, river, stream (including an intermittent or ephemeral stream), creek, wash, draw, mudflat, sandflat, wetland, slough, backwater, prairie pothole, wet meadow, or playa lake, the use, degradation, or destruction of which would affect or could affect interstate or foreign commerce, including any such water:
 - i. That is or could be used by interstate or foreign travelers for recreational or other purposes;
 - ii. From which fish or shellfish are or could be taken and sold in interstate or foreign commerce; or
 - iii. That is used or could be used for industrial purposes by industries in interstate or foreign commerce;
 - d. An impoundment of a surface water as defined by this definition;
 - e. A tributary of a surface water identified in subsections (41)(a) through (d); and
 - f. A wetland adjacent to a surface water identified in subsections (41)(a) through (e).
 42. "Total nitrogen" means the sum of the concentrations of ammonia (NH₃), ammonium ion (NH₄⁺), nitrite (NO₂), and nitrate (NO₃), and dissolved and particulate organic nitrogen expressed as elemental nitrogen.
 43. "Total phosphorus" means all of the phosphorus present in a sample, regardless of form, as measured by a persulfate digestion procedure.
 44. "Toxic" means a pollutant or combination of pollutants, that after discharge and upon exposure, ingestion, inhalation, or assimilation into an organism, either directly from the environment or indirectly by ingestion through food chains, may cause death, disease, behavioral abnormalities, cancer, genetic mutations, physiological malfunctions (including malfunctions in reproduction), or physical deformations in the organism or its offspring.
 45. "Urban lake" means a manmade lake within an urban landscape.
 46. "Use attainability analysis" means a structured scientific assessment of the factors affecting the attainment of a designated use including physical, chemical, biological, and economic factors.
 47. "Wadeable" means a surface water can be safely crossed on foot and sampled without a boat.
 48. "Wastewater" does not mean:
 - a. Stormwater,
 - b. Discharges authorized under the De Minimus General Permit,
 - c. Other allowable non-stormwater discharges permitted under the Construction General Permit or the Multi-sector General Permit, or
 - d. Stormwater discharges from a municipal storm sewer system (MS4) containing incidental amounts of non-stormwater that the MS4 is not required to prohibit.
 49. "Wetland" means an area that is inundated or saturated by surface or groundwater at a frequency and duration sufficient to support, and that under normal circumstances does support, a prevalence of vegetation typically adapted for life in saturated soil conditions. A wetland includes a swamp, marsh, bog, cienega, tinaja, and similar areas.
 50. "Zone of passage" means a continuous water route of volume, cross-sectional area, and quality necessary to allow passage of free-swimming or drifting organisms with no acutely toxic effect produced on the organisms.

Historical Note

Former Section R9-21-101 repealed, new Section R9-21-101 adopted effective January 29, 1980 (Supp. 80-1). Amended effective April 17, 1984 (Supp. 84-2). Amended effective January 7, 1985 (Supp. 85-1). Amended by adding subsection (C) effective August 12, 1986 (Supp. 86-4). Former Section R9-21-101 renumbered without change as Section R18-11-101 (Supp. 87-3). Former Section R18-11-101 repealed, new Section R18-11-101 adopted effective February 18, 1992 (Supp. 92-1). Amended effective April 24, 1996 (Supp. 96-2). Deleted first definition to R18-11-101(32) "Navigable Water", previously printed in error (Supp. 96-3). Amended by final rulemaking at 8 A.A.R. 1264, effective March 8, 2002 (Supp. 02-1). Amended by final rulemaking at 9 A.A.R. 716, effective April 8, 2003

(Supp. 03-1). Amended by final rulemaking at 14 A.A.R. 4708, effective January 31, 2009 (Supp. 08-4).

R18-11-102. Applicability

- A.** The water quality standards prescribed in this Article apply to surface waters.
- B.** The water quality standards prescribed in this Article do not apply to the following:
1. A waste treatment system, including an impoundment, pond, lagoon, or constructed wetland that is a part of the waste treatment system;
 2. A man-made surface impoundment and any associated ditch and conveyance used in the extraction, beneficiation, or processing of metallic ores that is not a surface water or is located in an area that once was a surface water but is no longer a surface water because it has been and remains legally converted, including:
 - a. A pit,
 - b. Pregnant leach solution pond,
 - c. Raffinate pond,
 - d. Tailing impoundment,
 - e. Decant pond,
 - f. Pond or a sump in a mine pit associated with dewatering activity,
 - g. Pond holding water that has come into contact with a process or product and that is being held for recycling,
 - h. Spill or upset catchment pond, or
 - i. A pond used for onsite remediation;
 3. A man-made cooling pond that is neither created in a surface water nor results from the impoundment of a surface water; or
 4. A surface water located on tribal lands.

Historical Note

Adopted effective February 18, 1992 (Supp. 92-1).
Amended effective April 24, 1996 (Supp. 96-2).
Amended by final rulemaking at 8 A.A.R. 1264, effective March 8, 2002 (Supp. 02-1). Amended by final rulemaking at 14 A.A.R. 4708, effective January 31, 2009 (Supp. 08-4).

R18-11-103. Repealed

Historical Note

Adopted effective February 18, 1992 (Supp. 92-1).
Repealed effective April 24, 1996 (Supp. 96-2).

R18-11-104. Designated Uses

- A.** The Director shall adopt or remove a designated use or subcategory of a designated use by rule.
- B.** Designated uses of a surface water may include full-body contact, partial-body contact, domestic water source, fish consumption, aquatic and wildlife (cold water), aquatic and wildlife (warm water), aquatic and wildlife (ephemeral), aquatic and wildlife (effluent-dependent water), agricultural irrigation, and agricultural livestock watering. The designated uses for specific surface waters are listed in Appendix B of this Article.
- C.** Numeric water quality criteria to maintain and protect water quality for the designated uses are prescribed in Appendix A, R18-11-109, R18-11-110, and R18-11-112. Narrative water quality standards to protect all surface waters are prescribed in R18-11-108.
- D.** If a surface water has more than one designated use listed in Appendix B, the most stringent water quality criterion applies.
- E.** The Director shall revise the designated uses of a surface water if water quality improvements result in a level of water quality that permits a use that is not currently listed as a designated use in Appendix B.
- F.** In designating uses of a surface water and in establishing water quality criteria to protect the designated uses, the Director shall take into consideration the applicable water quality standards for downstream surface waters and shall ensure that the water quality standards that are established for an upstream

surface water also provide for the attainment and maintenance of the water quality standards of downstream surface waters.

- G.** A use attainability analysis shall be conducted prior to removal of a designated use or adoption of a subcategory of a designated use that requires less stringent water quality criteria.
- H.** The Director may remove a designated use or adopt a subcategory of a designated use that requires less stringent water quality criteria, provided the designated use is not an existing use and it is demonstrated through a use attainability analysis that attaining the designated use is not feasible for any of the following reasons:
1. A naturally-occurring pollutant concentration prevents the attainment of the use;
 2. A natural, ephemeral, intermittent, or low-flow condition or water level prevents the attainment of the use;
 3. A human-caused condition or source of pollution prevents the attainment of the use and cannot be remedied or would cause more environmental damage to correct than to leave in place;
 4. A dam, diversion, or other type of hydrologic modification precludes the attainment of the use, and it is not feasible to restore the surface water to its original condition or to operate the modification in a way that would result in attainment of the use;
 5. A physical condition related to the natural features of the surface water, such as the lack of a proper substrate, cover, flow, depth, pools, riffles, and the like, unrelated to water quality, precludes attainment of an aquatic life designated use; or
 6. Controls more stringent than those required by § 301 (b) and § 306 of the Clean Water Act [33 U.S.C. § 1311 and § 1316] are necessary to attain the use and implementation of the controls would result in substantial and widespread economic and social impact.

Historical Note

Adopted effective February 18, 1992 (Supp. 92-1).
Amended effective April 24, 1996 (Supp. 96-2).
Amended by final rulemaking at 8 A.A.R. 1264, effective March 8, 2002 (Supp. 02-1).

R18-11-105. Tributaries; Designated Uses

The following water quality standards apply to a surface water that is not listed in Appendix B but that is a tributary to a listed surface water.

1. The aquatic and wildlife (ephemeral) and partial-body contact standards apply to an unlisted tributary that is an ephemeral water.
2. The aquatic and wildlife (cold water), full-body contact, and fish consumption standards apply to an unlisted tributary that is a perennial or intermittent surface water and is above 5000 feet in elevation.
3. The aquatic and wildlife (warm water), full-body contact, and fish consumption standards apply to an unlisted tributary that is a perennial or intermittent surface water and is below 5000 feet in elevation.

Historical Note

Adopted effective April 24, 1996 (Supp. 96-2). Section heading amended per instructions of the Department of Environmental Quality, August 9, 1996 (Supp. 96-3).
Amended by final rulemaking at 8 A.A.R. 1264, effective March 8, 2002 (Supp. 02-1).

R18-11-106. Net Ecological Benefit

- A.** The Director may, by rule, modify a water quality standard on the ground that there is a net ecological benefit associated with the discharge of effluent to support or create a riparian and aquatic habitat in an area where water resources are limited. The Director may modify a water quality standard for a pollutant if it is demonstrated that:
1. The discharge of effluent creates or supports an ecologically valuable aquatic, wetland, or riparian ecosystem in an area where these resources are limited;

2. The ecological benefits associated with the discharge of effluent under a modified water quality standard exceed the environmental costs associated with the elimination of the discharge of effluent;
 3. The cost of treatment to achieve compliance with a water quality standard is so high that it is more cost effective to eliminate the discharge of effluent to the surface water. The discharger shall demonstrate that it is feasible to eliminate the discharge of effluent that creates or supports the ecologically valuable aquatic, wetland, or riparian ecosystem and that a plan to eliminate the discharge is under active consideration;
 4. The discharge of effluent to the surface water will not cause or contribute to a violation of a water quality standard that has been established for a downstream surface water;
 5. All practicable point source discharge control programs, including local pretreatment, waste minimization, and source reduction programs are implemented; and
 6. The discharge of effluent does not produce or contribute to the concentration of a pollutant in the tissues of aquatic organisms or wildlife that is likely to be harmful to humans or wildlife through food chain concentration.
- B.** The Director shall not modify a water quality criterion for a pollutant to be less stringent than a technology-based effluent limitation that applies to the discharge of that effluent. The discharge of effluent shall, at a minimum, comply with applicable technology-based effluent limitations.

Historical Note

Adopted effective April 24, 1996 (Supp. 96-2). Amended by final rulemaking at 8 A.A.R. 1264, effective March 8, 2002 (Supp. 02-1).

R18-11-107. Antidegradation

- A.** The Director shall, using R18-11-107.01 and this Section, determine whether there is degradation of water quality in a surface water on a pollutant-by-pollutant basis.
- B.** Tier 1: The level of water quality necessary to support an existing use shall be maintained and protected. No degradation of existing water quality is permitted in a surface water where the existing water quality does not meet the applicable water quality standards.
- C.** Tier 2: Where existing water quality in a surface water is better than the applicable water quality standard the existing water quality shall be maintained and protected. The Director may allow degradation of existing water quality in the surface water, if the Director makes all of the following findings:
1. The water quality necessary for existing uses is fully protected and water quality is not lowered to a level that does not comply with applicable water quality standards,
 2. The highest statutory and regulatory requirements for new and existing point sources are achieved,
 3. All cost-effective and reasonable best management practices for nonpoint source pollution control are implemented, and
 4. Allowing lower water quality is necessary to accommodate important economic or social development in the area where the surface water is located.
- D.** Tier 3: Existing water quality shall be maintained and protected in a surface water that is classified as an OAW under R18-11-112. Degradation of an OAW under subsection (C) is prohibited.
- E.** The Director shall implement this Section in a manner consistent with § 316 of the Clean Water Act [33 U.S.C. 1326] if a potential water quality impairment associated with a thermal discharge is involved.

Historical Note

Adopted effective February 18, 1992 (Supp. 92-1). Amended effective April 24, 1996 (Supp. 96-2). Amended by final rulemaking at 8 A.A.R. 1264, effective March 8, 2002 (Supp. 02-1). Amended by final rulemaking at 14 A.A.R. 4708, effective January 31, 2009 (Supp. 08-4).

R18-11-107.01. Antidegradation Criteria

- A.** Tier 1 antidegradation protection.
1. Tier 1 antidegradation protection applies to the following surface waters:
 - a. A surface water listed on the 303(d) list for the pollutant that resulted in the listing,
 - b. An effluent dependent water,
 - c. An ephemeral water,
 - d. An intermittent water, and
 - e. A canal listed in Appendix B.
 2. A regulated discharge shall not cause a violation of a surface water quality standard or a wasteload allocation in a total maximum daily load approved by EPA.
 3. Except as provided in subsections (E) and (F), Tier 1 antidegradation review requirements are satisfied for a point-source discharge regulated under an individual AZPDES permit to an ephemeral water, effluent dependent water, intermittent water, or a canal listed in Appendix B, if water quality-based effluent limitations designed to achieve compliance with applicable surface water quality standards are established in the permit and technology-based requirements of the Clean Water Act for the point source discharge are met.
- B.** Tier 2 antidegradation protection.
1. Tier 2 antidegradation protection applies to a perennial water with existing water quality that is better than applicable water quality standards. A perennial water that is not listed in subsection (A)(1) nor classified as an OAW under A.A.C. R18-9-112(G) has Tier 2 antidegradation protection for all pollutants of concern.
 2. A regulated discharge that meets the following criteria, at critical flow conditions, does not cause significant degradation:
 - a. The regulated discharge consumes less than 20 percent of the available assimilative capacity for each pollutant of concern, and
 - b. At least 50 percent of the assimilative capacity for each pollutant of concern remains available in the surface water for each pollutant of concern.
 3. Antidegradation review. Any person proposing a new or expanded regulated discharge under an individual AZPDES permit that may cause significant degradation shall provide the Department with the following information:
 - a. Alternative analysis.
 - i. The person seeking authorization for the discharge shall prepare and submit a written analysis of alternatives to the discharge. The analysis shall provide information on all reasonable, cost-effective, less-degrading or non-degrading discharge alternatives. Alternatives may include wastewater treatment process changes or upgrades, pollution prevention measures, source reduction, water reclamation, alternative discharge locations, groundwater recharge, land application or treatment, local pretreatment programs, improved operation and maintenance of existing systems, seasonal or controlled discharge to avoid critical flow conditions, and zero discharge;
 - ii. The alternatives analysis shall include cost information on base pollution control measures associated with the regulated discharge and cost information for each alternative;
 - iii. The person shall implement the alternative that is cost-effective and reasonable, results in the least degradation, and is approved by the Director. An alternative is cost-effective and reasonable if treatment costs associated with the alternative are less than a 10 percent increase above the cost of base pollution control measures;

- iv. For purposes of this subsection, “base pollution control measures” are water pollution control measures required to meet technology-based requirements of the Clean Water Act and water quality-based effluent limits designed to achieve compliance with applicable water quality standards;
- b. Social and economic justification. The person shall demonstrate to the Director that significant degradation is necessary to accommodate important economic or social development in the local area. The person seeking authorization for the discharge shall prepare a written social and economic justification that includes a description of the following:
- i. The geographic area where significant degradation of existing water quality will occur;
 - ii. The current baseline social and economic conditions in the local area;
 - iii. The net positive social and economic effects of development associated with the regulated discharge and allowing significant degradation;
 - iv. The negative social, environmental, and economic effects of allowing significant degradation of existing water quality; and
 - v. Alternatives to the regulated discharge that do not significantly degrade water quality yet may yield comparable social and economic benefits;
- c. Baseline characterization. A person seeking authorization to discharge under an individual AZPDES permit to a perennial water shall provide baseline water quality data on pollutants of concern where no data exist or there are insufficient data to characterize baseline water quality and to determine available assimilative capacity. A discharger shall characterize baseline water quality at a location upstream of the proposed discharge location; and
4. For purposes of this Section, the term “pollutant of concern” means a pollutant with either a numeric or narrative water quality standard.
5. Public participation. The Director shall provide public notice and an opportunity to comment on an antidegradation review under subsection (B)(3) and shall provide an opportunity for a public hearing under A.A.C. R18-9-A908(B).
- C. Tier 3 antidegradation protection.**
1. Tier 3 antidegradation protection applies only to an OAW listed in R18-11-112(G).
 2. A new or expanded point-source discharge directly to an OAW is prohibited.
 3. A person seeking authorization for a regulated discharge to a tributary to, or upstream of, an OAW shall demonstrate in a permit application or in other documentation submitted to the Department that the regulated discharge will not degrade existing water quality in the downstream OAW.
 4. A discharge regulated under a § 404 permit that may affect existing water quality of an OAW requires an individual § 401 water quality certification to ensure that existing water quality is maintained and protected and any water quality impacts are temporary. Temporary water quality impacts are those impacts that occur for a period of six months or less.
- D. Antidegradation review of a § 404 permit.** The Director shall conduct the antidegradation review of any discharge authorized under a nationwide or regional § 404 permit as part of the § 401 water quality certification prior to issuance of the nationwide or regional permit. The Director shall conduct the antidegradation review of an individual § 404 permit if the discharge may degrade existing water quality in an OAW or a water listed on the 303(d) List of impaired waters. For regulated discharges that may degrade water quality in an OAW or a water that is on the 303(d) List of impaired waters, the Director shall conduct the antidegradation review as part of the § 401 water quality certification process.
- E.** Antidegradation review of an AZPDES stormwater permit. An individual stormwater permit for a municipal separate storm sewer system (MS4) meets antidegradation requirements if the permittee complies with the permit, including developing a stormwater management plan containing controls that reduce the level of pollutants in stormwater discharges to the maximum extent practicable.
- F.** Antidegradation review of a general permit. The Director shall conduct the antidegradation review of a regulated discharge authorized by a general permit at the time the general permit is issued or renewed. A person seeking authorization to discharge under a general permit is not required to undergo an individual antidegradation review at the time the Notice of Intent is submitted unless the discharge may degrade existing water quality in an OAW or a water listed on the 303(d) List of impaired waters.

Historical Note

New Section made by final rulemaking at 14 A.A.R. 4708, effective January 31, 2009 (Supp. 08-4).

R18-11-108. Narrative Water Quality Standards

- A.** A surface water shall not contain pollutants in amounts or combinations that:
1. Settle to form bottom deposits that inhibit or prohibit the habitation, growth, or propagation of aquatic life;
 2. Cause objectionable odor in the area in which the surface water is located;
 3. Cause off-taste or odor in drinking water;
 4. Cause off-flavor in aquatic organisms;
 5. Are toxic to humans, animals, plants, or other organisms;
 6. Cause the growth of algae or aquatic plants that inhibit or prohibit the habitation, growth, or propagation of other aquatic life or that impair recreational uses;
 7. Cause or contribute to a violation of an aquifer water quality standard prescribed in R18-11-405 or R18-11-406; or
 8. Change the color of the surface water from natural background levels of color.
- B.** A surface water shall not contain oil, grease, or any other pollutant that floats as debris, foam, or scum; or that causes a film or iridescent appearance on the surface of the water; or that causes a deposit on a shoreline, bank, or aquatic vegetation. The discharge of lubricating oil or gasoline associated with the normal operation of a recreational watercraft is not a violation of this narrative standard.
- C.** A surface water shall not contain a discharge of suspended solids in quantities or concentrations that interfere with the treatment processes at the nearest downstream potable water treatment plant or substantially increase the cost of handling solids produced at the nearest downstream potable water treatment plant.
- D.** A surface water shall not contain solid waste such as refuse, rubbish, demolition or construction debris, trash, garbage, motor vehicles, appliances, or tires.
- E.** A wadeable, perennial stream shall support and maintain a community of organisms having a taxa richness, species composition, tolerance, and functional organization comparable to that of a stream with reference conditions in Arizona.

Historical Note

Adopted effective February 18, 1992 (Supp. 92-1).
Amended effective April 24, 1996 (Supp. 96-2).
Amended by final rulemaking at 8 A.A.R. 1264, effective March 8, 2002 (Supp. 02-1). Amended by final rulemaking at 14 A.A.R. 4708, effective January 31, 2009 (Supp. 08-4).

R18-11-108.01. Narrative Biological Criteria for Wadeable, Perennial Streams

- A.** The narrative biological criteria in this Section apply to a wadeable, perennial stream with either an aquatic and wildlife

(cold water) or an aquatic and wildlife (warm water) designated use.

- B. The biological standard in R18-11-108(E) is met when a bioassessment result, as measured by the Arizona Index of Biological Integrity (IBI), for cold or warm water is:
 1. Greater than or equal to the 25th percentile of reference condition, or
 2. Greater than the 10th percentile of reference condition and less than the 25th percentile of reference condition and a verification bioassessment result is greater than or equal to the 25th percentile of reference condition.
- C. Arizona Index of Biological Integrity (IBI) scores:

Bioassessment Result	Index of Biological Integrity Scores	
	A&Wc	A&Ww
Greater than or equal to the 25th percentile of reference condition	≥52	≥50
Greater than the 10th and less than the 25th percentile of reference condition	46 - 51	40 - 49

Historical Note

New Section made by final rulemaking at 14 A.A.R. 4708, effective January 31, 2009 (Supp. 08-4).

R18-11-108.02. Narrative Bottom Deposit Criteria for Wadeable, Perennial Streams

- A. The narrative bottom deposit criteria in this Section apply to wadeable, perennial streams with an aquatic and wildlife (cold water) or an aquatic and wildlife (warm water) designated use.
- B. The narrative water quality standard for bottom deposits at R18-11-108(A)(1) is met when:
 1. The percentage of fine sediments in the riffle habitats of a wadeable, perennial stream with an A&Wc designated use, as determined by a riffle pebble count, is less than or equal to 30 percent.
 2. The percentage of fine sediments in all stream habitats of a wadeable, perennial stream with an A&Ww designated use, as determined by a reach level pebble count, is equal to or less than 50 percent.

Historical Note

New Section made by final rulemaking at 14 A.A.R. 4708, effective January 31, 2009 (Supp. 08-4).

R18-11-108.03. Narrative Nutrient Criteria for Lakes and Reservoirs

- A. The narrative nutrient criteria in this Section apply to those lakes and reservoirs categorized in Appendix B.
- B. The narrative water quality standard for nutrients at R18-11-108(A)(6) is met when, based on a minimum of two lake sample events conducted during the peak season based on lake productivity, the results show an average chlorophyll-*a* value below the applicable threshold for designated use and lake and reservoir category in subsection (D).
 1. The mean chlorophyll-*a* concentration is less than the lower value in the target range chlorophyll-*a* for the lake and reservoir category, or
 2. The mean chlorophyll-*a* concentration is within the target range for the lake and reservoir category and:
 - a. The mean blue green algae count is at or below 20,000 per milliliter, and
 - b. The blue green algae count is less than 50 percent of the total algae count, and
 - c. There is no evidence of nutrient-related impairments such as:
 - i. An exceedance of dissolved oxygen or pH standards;
 - ii. A fish kill coincident with a dissolved oxygen or pH exceedance;
 - iii. A fish kill or other aquatic organism mortality coincident with algal toxicity;
 - iv. Secchi depth is less than the lower value prescribed for the lake and reservoir category;
 - v. A nuisance algal bloom is present in the limnetic portion of the lake or reservoir; or
 - vi. The concentration of total phosphorous, total nitrogen, or total Kjehldal nitrogen (TKN) is greater than the upper value in the range prescribed for the lake and reservoir category; or
 3. For a shallow lake. In addition to meeting the mean chlorophyll-*a* concentrations in subsections (B)(1) or (2), submerged aquatic vegetation covers 50 percent or less of the lake bottom and there is less than a 5 mg/L swing in diel-dissolved oxygen concentration measured within the photic zone.
- C. The following threshold ranges apply during the peak season for lake productivity:
 1. Warm water lakes peak season, April – October;
 2. Cold water lakes peak season, May – September.
- D. The following table lists the numeric targets for lakes and reservoirs.

NUMERIC TARGETS FOR LAKES AND RESERVOIRS										
Designated Use	Lake Category	Chl- <i>a</i> (µg/L)	Secchi Depth (m)	Total Phosphorus (µg/L)	Total Nitrogen (mg/L)	Total Kjehldal Nitrogen (TKN) (mg/L)	Blue-Green Algae (per ml)	Blue-Green Algae (% of total count)	Dissolved Oxygen (mg/L)	pH (SU)
FBC and PBC	Deep	10-15	1.5-2.5	70-90	1.2-1.4	1.0-1.1	20,000			6.5-9.0
	Shallow	10-15	1.5-2.0	70-90	1.2-1.4	1.0-1.1				
	Igneous	20-30	0.5-1.0	100-125	1.5-1.7	1.2-1.4				
	Sedimentary	20-30	1.5-2.0	100-125	1.5-1.7	1.2-1.4				
	Urban	20-30	0.5-1.0	100-125	1.5-1.7	1.2-1.4				

A&Wc	All	5-15	1.5-2.0	50-90	1.0-1.4	0.7-1.1			7 (top m)	
A&Ww	All (except urban lakes)	25-40	0.8-1.0	115-140	1.6-1.8	1.3-1.6		<50	6 (top m)	6.5-9.0
	Urban	30-50	0.7-1.0	125-160	1.7-1.9	1.4-1.7				
A&Wedw	All	30-50	0.7-1.0	125-160	1.7-1.9	1.4-1.7				6.5-9.0
DWS	All	10-20	0.5-1.5	70-100	1.2-1.5	1.0-1.2	20,000			5.0-9.0

Historical Note

New Section made by final rulemaking at 14 A.A.R. 4708, effective January 31, 2009 (Supp. 08-4).

R18-11-109. Numeric Water Quality Standards

A. *E. coli* bacteria. The following water quality standards for *Escherichia coli* (*E. coli*) are expressed in colony forming units per 100 milliliters of water (cfu / 100 ml) or as a Most Probable Number (MPN):

<i>E. coli</i>	FBC	PBC
Geometric mean (minimum of four samples in 30 days)	126	126
Single sample maximum	235	575

B. pH. The following water quality standards for pH are expressed in standard units:

pH	DWS	FBC, PBC, A&W¹	AgI	AgL
Maximum	9.0	9.0	9.0	9.0
Minimum	5.0	6.5	4.5	6.5

C. The maximum allowable increase in ambient water temperature, due to a thermal discharge is as follows:

A&Ww	A&Wedw	A&Wc
3.0° C	3.0° C	1.0° C

D. Suspended sediment concentration.

1. The following water quality standards for suspended sediment concentration, expressed in milligrams per liter (mg/L), are expressed as a median value determined from a minimum of four samples collected at least seven days apart:

A&Wc	A&Ww
25	80

2. The Director shall not use the results of a suspended sediment concentration sample collected during or within 48 hours after a local storm event to determine the median value.

E. Dissolved oxygen. The following water quality standards for dissolved oxygen are expressed in milligrams per liter (mg/L):

1. **Dissolved oxygen**

	A&Ww	A&Wc
Single sample minimum ²	6.0	7.0
2. **Dissolved oxygen in effluent-dependent waters (single sample minimum)**

	A&W edw
Three hours after sunrise to sunset	3.0
Sunset to three hours after sunrise	1.0

3. A surface water meets with the water quality standard for dissolved oxygen if the percent saturation of dissolved oxygen is equal to or greater than 90 percent.

F. Nutrient criteria. The following water quality standards for total phosphorus and total nitrogen are expressed in milligrams per liter (mg/L). A minimum of 10 samples, each taken at least 10 days apart in a consecutive 12-month period, are required to determine a 90th percentile. Not more than 10 percent of the samples may exceed the 90th percentile value listed below:

1. Verde River and its tributaries from the Verde headwaters to Bartlett Lake:

	Annual Mean	90th Percentile	Single Sample Maximum
Surface Water			
Total phosphorus	0.10	0.30	1.00
Total nitrogen	1.00	1.50	3.00

2. Black River, Tonto Creek, and their tributaries that are not located on tribal lands:

	Annual Mean	90th Percentile	Single Sample Maximum
Surface Water			
Total phosphorus	0.10	0.20	0.80
Total nitrogen	0.50	1.00	2.00

3. Salt River and its tributaries above Roosevelt Reservoir, excluding Pinal Creek, that are not located on tribal lands:

	Annual Mean	90th Percentile	Single Sample Maximum
Surface Water			
Total phosphorus	0.12	0.30	1.00
Total nitrogen	0.60	1.20	2.00

4. Salt River below Stewart Mountain Dam to its confluence with the Verde River:

	Annual Mean	90th Percentile	Single Sample Maximum
Surface Water			
Total phosphorus	0.05	–	0.20
Total nitrogen	0.60	–	3.00

5. Little Colorado River and its tributaries above River Reservoir in Greer, South Fork of Little Colorado River above South Fork Campground, and Water Canyon Creek above Apache-Sitgreaves National Forest boundary:

	Annual Mean	90th Percentile	Single Sample Maximum
Surface Water			
Total phosphorus	0.08	0.10	0.75
Total nitrogen	0.60	0.75	1.10

6. Little Colorado River at the crossing of Apache County Road No. 124:

	Annual Mean	90th Percentile	Single Sample Maximum
Surface Water			
Total phosphorus	–	–	0.75
Total nitrogen	–	–	1.80

7. Little Colorado River above Lyman Lake to above the Amity Ditch diversion near crossing of Arizona Highway

273 (applies only when in-stream turbidity is less than 50 NTU):

Surface Water	Annual Mean	90th Percentile	Single Sample Maximum
Total phosphorus	0.20	0.30	0.75
Total nitrogen	0.70	1.20	1.50

- 8. Colorado River at the Northern International Boundary near Morelos Dam:

Surface Water	Annual Mean	90th Percentile	Single Sample Maximum
Total phosphorus	–	0.33	–
Total nitrogen	–	2.50	–

- 9. Oak Creek from its headwaters at 35°01'30"/111°44'12" to its confluence with the Verde River at 34°40'41"/111°56'30" and the West Fork of Oak Creek from its headwaters at 35°02'44"/111°54'48" to its confluence with Oak Creek at 34°59'14"/111°44'46".

Surface Water	Annual Mean	90th Percentile	Single Sample Maximum
Total phosphorus	1.00	1.50	2.50
Total nitrogen	0.10	0.25	0.30

- 10. No discharge of wastewater to Show Low Creek or its tributaries upstream of and including Fools Hollow Lake shall exceed 0.16 mg/L total phosphates as P.
- 11. No discharge of wastewater to the San Francisco River or its tributaries upstream of Luna Lake Dam shall exceed 1.0 mg/L total phosphates as P.

G. Footnotes:

- "1" Includes A&Wc, A&Ww, A&Wedw, and A&We.
- "2" The dissolved oxygen water quality standard for a lake applies below the water surface but not at a depth greater than one meter.

Historical Note

Adopted effective February 18, 1992 (Supp. 92-1).
 Amended effective April 24, 1996 (Supp. 96-2).
 Amended by final rulemaking at 8 A.A.R. 1264, effective March 8, 2002 (Supp. 02-1). Amended by final rulemaking at 14 A.A.R. 4708, effective January 31, 2009 (Supp. 08-4).

R18-11-110. Salinity Standards for the Colorado River

- A. The flow-weighted average annual salinity in the lower main stem of the Colorado River shall not exceed the following criteria:

Location	Total Dissolved Solids
Below Hoover Dam	723 mg/L
Below Parker Dam	747 mg/L
At Imperial Dam	879 mg/L

- B. The plan of implementation contained in the "2005 Review, Water Quality Standards for Salinity, Colorado River System," approved October 2005, is incorporated by reference to preserve the basin-wide approach to salinity control developed by the Colorado River Basin Salinity Control Forum and to ensure compliance with the numeric criteria for salinity in subsection (A). This material does not include any later amendments or editions of the incorporated material. Copies of the incorporated material are available for inspection at the Arizona Department of Environmental Quality, 1110 West Washington Street, Phoenix, Arizona 85007 or may be obtained from the Colorado River Basin Salinity Control Forum, 106 West 500 South, Suite 101, Bountiful, Utah 84010-6232.

Historical Note

Adopted effective February 18, 1992 (Supp. 92-1).
 Amended by final rulemaking at 8 A.A.R. 1264, effective March 8, 2002 (Supp. 02-1). Amended by final rulemaking at 14 A.A.R. 4708, effective January 31, 2009 (Supp. 08-4).

R18-11-111. Analytical Methods

- A. A person conducting an analysis of a sample taken to determine compliance with a water quality standard shall use an analytical method prescribed in A.A.C. R9-14-610, 40 CFR 136.3, or an alternative analytical method approved under A.A.C. R9-14-610(C).
- B. A test result from a sample taken to determine compliance with a water quality standard is valid only if the sample is analyzed by a laboratory that is licensed by the Arizona Department of Health Services, an out-of-state laboratory licensed under A.R.S. § 36-495.14, or a laboratory exempted under A.R.S. § 36-495.02, for the analysis performed.

Historical Note

Adopted effective February 18, 1992 (Supp. 92-1).
 Amended effective April 24, 1996 (Supp. 96-2).
 Amended by final rulemaking at 8 A.A.R. 1264, effective March 8, 2002 (Supp. 02-1). Amended by final rulemaking at 14 A.A.R. 4708, effective January 31, 2009 (Supp. 08-4).

R18-11-112. Outstanding Arizona Waters

- A. The Director shall classify a surface water as an outstanding Arizona water (OAW) by rule.
- B. The Director may adopt, under R18-11-115, a site-specific standard to maintain and protect existing water quality in an OAW.
- C. Any person may nominate a surface water for classification as an OAW by filing a nomination with the Director. The nomination shall include:
 - A map and a description of the surface water;
 - A written statement in support of the nomination, including specific reference to the applicable criteria for an OAW classification prescribed in subsection (D);
 - Supporting evidence demonstrating that the criteria prescribed in subsection (D) are met; and
 - Available water quality data relevant to establishing the baseline water quality of the proposed OAW.
- D. The Director may classify a surface water as an OAW based upon the following criteria:
 - The surface water is a perennial or intermittent water;
 - The surface water is in a free-flowing condition. For purposes of this subsection, "in a free-flowing condition" means that a surface water does not have an impoundment, diversion, channelization, rip-rapping or other bank armor, or another hydrological modification within the reach nominated for an OAW classification;
 - The surface water has good water quality. For purposes of this subsection, "good water quality" means that the surface water has water quality that meets or is better than applicable surface water quality standards. A surface water that is listed as impaired under R18-11-604(E) is ineligible for OAW classification; and
 - The surface water meets one or both of the following conditions:
 - The surface water is of exceptional recreational or ecological significance because of its unique attributes, such as the geology, flora and fauna, water quality, aesthetic value, or the wilderness characteristic of the surface water;
 - An endangered or threatened species is associated with the surface water and the existing water quality is essential to the species' maintenance and propagation or the surface water provides critical habitat for the threatened or endangered species. An endangered or threatened species is identified in "Endangered and Threatened Wildlife," 50 CFR 17.11 (revised 2005), and "Endangered and

Threatened Plants,” 50 CFR 17.12 (revised 2005). This material is incorporated by reference and does not include any later amendments or editions of the incorporated material. Copies of the incorporated material are available for inspection at the Arizona Department of Environmental Quality, 1110 West Washington Street, Phoenix, Arizona 85007 or may be obtained from the National Archives and Records Administration at <http://www.access.gpo.gov/nara/cfr/cfr-table-search.html#page1>.

- E. The Director shall hold at least one public meeting in the local area of a surface water that is nominated for classification as an OAW to solicit public comment on the nomination.
- F. The Director shall consider the following factors when deciding whether to classify a surface water as an OAW:
1. Whether there is the ability to manage the surface water and its watershed to maintain and protect existing water quality;
 2. The social and economic impact of Tier 3 antidegradation protection;
 3. The public comments in support of, or in opposition to, an OAW classification;
 4. The timing of the nomination relative to the triennial review of surface water quality standards;
 5. The consistency of an OAW classification with applicable water quality management plans; and
 6. Whether the nominated surface water is located within a national or state park, national monument, national recreation area, wilderness area, riparian conservation area, area of critical environmental concern, or it has another special use designation (for example, Wild and Scenic River).
- G. The following surface waters are classified as OAWs:
1. The West Fork of the Little Colorado River, from its headwaters at 33°55'02"/109°33'30" to Government Springs at 33°59'33"/109°27'54" (approximately 9.1 river miles);
 2. Oak Creek, from its headwaters at 35°01'30"/111°44'12" to its confluence with the Verde River at 34°40'41"/111°56'30" (approximately 50.3 river miles);
 3. West Fork of Oak Creek, from its headwaters at 35°02'44"/111°54'48" to its confluence with Oak Creek at 34°59'14"/111°44'46" (approximately 15.8 river miles);
 4. Peeples Canyon Creek, from its headwaters at 34°23'57"/113°19'45" to its confluence with the Santa Maria River at 34°20'36"/113°15'12" (approximately 8.1 river miles);
 5. Burro Creek, from its headwaters at 34°52'46.5"/113°05'13.5" to its confluence with Boulder Creek at 34°37'4.5"/113°18'36" (approximately 29.5 miles);
 6. Francis Creek, from its headwaters at 34°54'38"/113°20'30" to its confluence with Burro Creek at 34°44'29"/113°14'37" (approximately 22.9 river miles);
 7. Bonita Creek, from its boundary of the San Carlos Indian Reservation at 33°03'08"/109°33'41" to its confluence with the Gila River at 32°53'36"/109°28'43" (approximately 14.7 river miles);
 8. Cienega Creek, from its confluence with Gardner Canyon and Spring Water Canyon at 31°47'38.5"/110°35'21.5" to the USGS gaging station at 32°02'09"/110°40'34" (approximately 28.3 river miles);
 9. Aravaipa Creek, from its confluence with Stowe Gulch at 32°52'10"/110°22'03" to the downstream boundary of the Aravaipa Canyon Wilderness Area at 32°54'23"/110°33'42" (approximately 15.5 river miles);
 10. Cave Creek, from its headwaters at 31°50'30"/109°17'04.5" to the Coronado National Forest boundary at 31°54'38"/109°08'40" (approximately 10.4 river miles);
 11. South Fork of Cave Creek, from its headwaters at 31°50'20"/109°16'33" to its confluence with Cave Creek at 31°53'04"/109°10'30" (approximately 8.6 river miles);
 12. Buehman Canyon Creek, from its headwaters at 32°52'0.5"/110°39'54.5" to its confluence with unnamed tributary at 32°24'31.5"/110°32'08" (approximately 9.8 river miles);
 13. Lee Valley Creek, from its headwaters at 33°55'49"/109°31'34" to its confluence with Lee Valley Reservoir at 33°56'28"/109°30'15.5" (approximately 1.6 river miles);
 14. Bear Wallow Creek, from its headwaters at 33°35'54"/109°26'54.5" to the boundary of the San Carlos Indian Reservation at 33°37'52"/109°29'44" (approximately 4.25 river miles);
 15. North Fork of Bear Wallow Creek, from its headwaters at 33°34'47.5"/109°21'59.5" to its confluence with Bear Wallow Creek at 33°35'54"/109°26'54.5" (approximately 3.8 river miles);
 16. South Fork of Bear Wallow Creek, from its headwaters at 33°34'38.5"/109°23'58" to its confluence with Bear Wallow Creek at 33°35'54"/109°26'54.5" (approximately 3.8 river miles);
 17. Snake Creek, from its headwaters at 33°37'21.5"/109°26'11" to its confluence with the Black River at 33°40'31.5"/109°28'58.5" (approximately 6.2 river miles);
 18. Hay Creek, from its headwaters at 33°51'00"/109°28'48" to its confluence with the West Fork of the Black River at 33°48'30"/109°25'19" (approximately 5.5 river miles);
 19. Stinky Creek, from the White Mountain Apache Indian Reservation boundary at 33°52'36.5"/109°29'45" to its confluence with the West Fork of the Black River at 33°51'21.5"/109°27'09.5" (approximately 3.0 river miles);
 20. KP Creek, from its headwaters at 33°34'03"/109°21'19" to its confluence with the Blue River at 33°31'44"/109°12'04.5" (approximately 12.7 river miles);
 21. Davidson Canyon, from the unnamed spring at 31°59'00"/110°38'46" to its confluence with Cienega Creek; and
 22. Fossil Creek, from its headwaters at the confluence of Sandrock and Calf Pen Canyons above Fossil Springs at 34°26'48.7"/111°32'25" to its confluence with the Verde River at 34°18'21.8"/111°40'31.6" (approximately 17.2 river miles).
- H. The designation of Fossil Creek as an OAW under subsection (G)(22) takes effect on June 30, 2010.

Historical Note

Adopted effective February 18, 1992 (Supp. 92-1). Amended effective April 24, 1996 (Supp. 96-2). Added "water quality standards" to R18-11-112, previously omitted in error (Supp. 96-3). Amended by final rulemaking at 8 A.A.R. 1264, effective March 8, 2002 (Supp. 02-1). Amended by final rulemaking at 14 A.A.R. 4708, effective January 31, 2009 (Supp. 08-4).

R18-11-113. Effluent-Dependent Waters

- A. The Director shall classify a surface water as an effluent-dependent water by rule.
- B. The Director may adopt, under R18-11-115, a site-specific water quality standard for an effluent-dependent water.
- C. Any person may submit a petition for rule adoption requesting that the Director classify a surface water as an effluent-dependent water. The petition shall include:
1. A map and a description of the surface water;
 2. Information that demonstrates that the surface water consists of a point source discharge of wastewater; and
 3. Information that demonstrates that, without a point source discharge of a wastewater, the receiving water is an ephemeral water.
- D. The Director shall use the water quality standards that apply to an effluent-dependent water to derive water quality-based effluent limits for a point source discharge of wastewater to an ephemeral water.
- E. The Director may use aquatic and wildlife (edw) acute standards only to derive water quality based effluent limits for a sporadic, infrequent, or emergency point source discharge to an ephemeral water or to an effluent-dependent water. The

Director shall consider the following factors when deciding whether to apply A&Wedw (acute) standards:

1. The amount, frequency, and duration of the discharge;
 2. The length of time water may be present in the receiving water;
 3. The distance to a downstream water with aquatic and wildlife chronic standards; and
 4. The likelihood of chronic exposure to pollutants.
- F. The Director may establish alternative water quality-based effluent limits in an AZPDES permit based on seasonal differences in the discharge.

Historical Note

Adopted effective February 18, 1992 (Supp. 92-1).
Amended effective December 18, 1992 (Supp. 92-4).
Amended effective April 24, 1996 (Supp. 96-2).
Amended by final rulemaking at 8 A.A.R. 1264, effective March 8, 2002 (Supp. 02-1). Amended by final rulemaking at 14 A.A.R. 4708, effective January 31, 2009 (Supp. 08-4).

R18-11-114. Mixing Zones

- A. The Director may establish a mixing zone for a point source discharge to a surface water as a condition of an AZPDES permit. A mixing zone is prohibited in an ephemeral water or where there is no water for dilution.
- B. The owner or operator of a point source seeking the establishment of a mixing zone shall submit a request to the Director for a mixing zone as part of an application for an AZPDES permit. The request shall include:
1. An identification of the pollutant for which the mixing zone is requested;
 2. A proposed outfall design;
 3. A definition of the boundary of the proposed mixing zone. For purposes of this subsection, the boundary of a mixing zone means the location where the concentration of wastewater across a transect of the surface water differs by less than five percent; and
 4. A complete and detailed description of the existing physical, biological, and chemical conditions of the receiving water and the predicted impact of the proposed mixing zone on those conditions.
- C. The Director shall review the request for a mixing zone to determine whether the written request is complete. If the request is incomplete, the Director shall provide the applicant with a list of the additional information required.
- D. The Director shall consider the following factors when deciding whether to grant or deny a request for a mixing zone:
1. The assimilative capacity of the receiving water;
 2. The likelihood of adverse human health effects;
 3. The location of drinking water plant intakes and public swimming areas;
 4. The predicted exposure of biota and the likelihood that resident biota will be adversely affected;
 5. Bioaccumulation;
 6. Whether there will be acute toxicity in the mixing zone, and, if so, the size of the zone of initial dilution;
 7. The known or predicted safe exposure levels for the pollutant for which the mixing zone is requested;
 8. The size of the mixing zone;
 9. The location of the mixing zone relative to biologically sensitive areas in the surface water;
 10. The concentration gradient of the pollutant within the mixing zone;
 11. Sediment deposition;
 12. The potential for attracting aquatic life to the mixing zone; and
 13. The cumulative impacts of other mixing zones and other discharges to the surface water.
- E. Director determination.
1. The Director shall deny a request to establish a mixing zone if a water quality standard will be violated outside the boundaries of the proposed mixing zone. The Director

shall notify the owner or operator of the denial in writing and shall state the reason for the denial.

2. If the Director approves the request to establish a mixing zone, the Director shall establish the mixing zone as a condition of an AZPDES permit. The Director shall include any mixing zone condition in the AZPDES permit that is necessary to protect human health and the designated uses of the surface water.
- F. Any person who is adversely affected by the Director's decision to grant or deny a request for a mixing zone may appeal the decision under A.R.S. § 49-321 et seq. and A.R.S. § 41-1092 et seq.
- G. The Director shall reevaluate a mixing zone upon issuance, reissuance, or modification of the AZPDES permit for the point source or a modification of the outfall structure.
- H. Mixing zone requirements.
1. The length of a mixing zone shall not exceed 500 meters in a stream.
 2. The total horizontal area allocated to all mixing zones on a lake shall not exceed 10 percent of the surface area of the lake.
 3. Adjacent mixing zones in a lake shall not overlap or be located closer together than the greatest horizontal dimension of the largest mixing zone.
 4. A mixing zone shall provide for a zone of passage of not less than 50 percent of the cross-sectional area of a river or stream.
 5. The design of any discharge outfall shall maximize initial dilution of the wastewater in a surface water.
 6. The size of the zone of initial dilution in a mixing zone shall prevent lethality to organisms passing through the zone of initial dilution.
- I. The Director shall not establish a mixing zone in an AZPDES permit for the following persistent, bioaccumulative pollutants:
1. Chlordane,
 2. DDT and its metabolites (DDD and DDE),
 3. Dieldrin,
 4. Dioxin,
 5. Endrin,
 6. Endrin aldehyde,
 7. Heptachlor,
 8. Heptachlor epoxide,
 9. Lindane,
 10. Mercury,
 11. Polychlorinated biphenyls (PCBs), and
 12. Toxaphene.

Historical Note

Adopted effective February 18, 1992 (Supp. 92-1).
Amended effective April 24, 1996 (Supp. 96-2).
Amended by final rulemaking at 8 A.A.R. 1264, effective March 8, 2002 (Supp. 02-1). Amended by final rulemaking at 14 A.A.R. 4708, effective January 31, 2009 (Supp. 08-4).

R18-11-115. Site-Specific Standards

- A. The Director shall adopt a site-specific standard by rule.
- B. The Director may adopt a site-specific standard based upon a request or upon the Director's initiative for any of the following reasons:
1. Local physical, chemical, or hydrological conditions of a surface water such as pH, hardness, or temperature alters the biological availability or toxicity of a pollutant;
 2. The sensitivity of resident aquatic organisms that occur in a surface water to a pollutant differs from the sensitivity of the species used to derive the numeric water quality standards to protect aquatic life in Appendix A;
 3. Resident aquatic organisms that occur in a surface water represent a narrower mix of species than those in the dataset used by the Department to derive numeric water quality standards to protect aquatic life in Appendix A; or

4. The natural background concentration of a pollutant is greater than the numeric water quality standard to protect aquatic life prescribed in Appendix A.
- C. Site-specific study. A person shall conduct a study to support the development of a site-specific standard using one of the following procedures:
1. The Recalculation Procedure, Appendix L, pages 90 - 98, Water Quality Standards Handbook, Second Edition, EPA 823-B-94-005b, August 1994. This material is incorporated by reference and does not include any later amendments or editions of the incorporated material. A copy of the incorporated material is available for inspection at the Arizona Department of Environmental Quality, 1110 West Washington Street, Phoenix, Arizona 85007 or: may be obtained from the U.S. Environmental Protection Agency, Office of Water at <http://www.epa.gov/waterscience/standards/handbook/handbookappxL.pdf>.
 2. Water-Effects Ratio for Metals, Appendix L, pages 1 - 89, Water Quality Standards Handbook, Second Edition, EPA 823-B-94-005b, August 1994. This material is incorporated by reference and does not include any later amendments or editions of the incorporated material. A copy of the incorporated material is available for inspection at the Arizona Department of Environmental Quality, 1110 West Washington Street, Phoenix, Arizona 85007 or: may be obtained from the U.S. Environmental Protection Agency, Office of Water at <http://www.epa.gov/waterscience/standards/handbook/handbookappxL.pdf>.
 3. Streamlined Water Effects Ratio Procedure for Discharges of Copper, EPA-822-R-01-005, March 2001. This material is incorporated by reference and does not include any later amendments or editions of the incorporated material. A copy of the incorporated material is available for inspection at the Arizona Department of Environmental Quality, 1110 West Washington Street, Phoenix, Arizona 85007 or: may be obtained from the U.S. Environmental Protection Agency, Office of Water at <http://www.epa.gov/ost/criteria/copper/copper.pdf>.
 4. Natural background.
 - a. A person seeking to develop a site-specific standard based on natural background shall provide a study outline to the Director and obtain the Director's approval before conducting the study.
 - i. The person may use statistical or modeling approaches to determine natural background concentration.
 - ii. Modeling approaches include Better Assessment Science Integrating Source and Nonpoint Sources (Basins), Hydrologic Simulation Program-Fortran (HSPF), and Hydrologic Engineering Center (HEC) programs developed by the U.S. Army Corps of Engineers.
 - b. The Director may establish a site-specific standard at a concentration equal to the natural background concentration.
 - c. For purposes of this subsection, "natural background" means the concentration of a pollutant in a surface water due only to non-anthropogenic sources.

Historical Note

Adopted effective February 18, 1992 (Supp. 92-1).
Amended effective April 24, 1996 (Supp. 96-2). Section repealed by final rulemaking at 8 A.A.R. 1264, effective March 8, 2002 (Supp. 02-1). New Section made by final rulemaking at 14 A.A.R. 4708, effective January 31, 2009 (Supp. 08-4).

R18-11-116. Resource Management Agencies

Nothing in this Article prohibits fisheries management activities by the Arizona Game and Fish Department or the U.S. Fish and Wildlife Service. This Article does not exempt fish hatcheries from AZPDES permit requirements.

Historical Note

Adopted effective February 18, 1992 (Supp. 92-1).
Amended by final rulemaking at 14 A.A.R. 4708, effective January 31, 2009 (Supp. 08-4).

R18-11-117. Canals and Urban Park Lakes

- A. Nothing in this Article prevents the routine physical or mechanical maintenance of canals, drains, and the urban lakes identified in Appendix B. Physical or mechanical maintenance includes dewatering, lining, dredging, and the physical, biological, or chemical control of weeds and algae. Increases in turbidity that result from physical or mechanical maintenance activities are permitted in canals, drains, and the urban lakes identified in Appendix B.
- B. The discharge of lubricating oil associated with the start-up of well pumps that discharge to canals is not a violation of R18-11-108(B).

Historical Note

Adopted effective February 18, 1992 (Supp. 92-1).
Amended effective April 24, 1996 (Supp. 96-2).
Amended by final rulemaking at 14 A.A.R. 4708, effective January 31, 2009 (Supp. 08-4).

R18-11-118. Dams and Flood Control Structures

Increases in turbidity that result from the routine physical or mechanical maintenance of a dam or flood control structure are not violations of this Article. Nothing in this Article requires the release of water from a dam or a flood control structure.

Historical Note

Adopted effective February 18, 1992 (Supp. 92-1).
Amended effective April 24, 1996 (Supp. 96-2).
Amended by final rulemaking at 8 A.A.R. 1264, effective March 8, 2002 (Supp. 02-1). Amended by final rulemaking at 14 A.A.R. 4708, effective January 31, 2009 (Supp. 08-4).

R18-11-119. Natural background

Where the concentration of a pollutant exceeds a water quality standard and the exceedance is not caused by human activity but is due solely to naturally-occurring conditions, the exceedance shall not be considered a violation of the water quality standard.

Historical Note

Adopted effective February 18, 1992 (Supp. 92-1).

R18-11-120. Enforcement

- A. Any person who causes a violation of a water quality standard or any provision of this Article is subject to the enforcement provisions in A.R.S. Title 49, Chapter 2, Article 4.
- B. The Department may establish a numeric water quality standard at a concentration that is below the practical quantitation limit. In such cases, the water quality standard is enforceable at the practical quantitation limit.
- C. The Department shall determine compliance with acute aquatic and wildlife criteria from the analytical result of a grab sample. Compliance with chronic aquatic and wildlife criteria shall be determined from the geometric mean of the analytical results of the last four samples taken at least 24 hours apart.
- D. A person is not subject to penalties for violation of a water quality standard provided that the person is in compliance with the provisions of a compliance schedule issued under R18-11-121.

Historical Note

Adopted effective February 18, 1992 (Supp. 92-1).
Amended effective April 24, 1996 (Supp. 96-2).
Amended by final rulemaking at 8 A.A.R. 1264, effective March 8, 2002 (Supp. 02-1).

R18-11-121. Schedules of Compliance

- A.** The Director may establish a schedule in an AZPDES permit to bring an existing point source into compliance with a new or revised water quality standard. A compliance schedule in an AZPDES permit for an existing point source, other than a stormwater discharge, shall require the permittee to comply with a discharge limitation based upon a new or revised water quality standard no later than three years after the effective date of the AZPDES permit. The permittee shall demonstrate that all requirements under § 301(b) and § 306 of the Clean Water Act [33 U.S.C. 1311(b) and 1316] are achieved and that the point source cannot comply with a discharge limitation based upon the new or revised water quality standard through the application of existing water pollution control technology, operational changes, or source reduction.
- B.** The Director may establish a schedule of compliance in an AZPDES permit for a new point source. The first AZPDES permit issued to a new point source may contain a schedule of compliance only when necessary to allow the permittee to attain compliance with a new or revised water quality standard that becomes effective after commencement of construction but less than three years before the discharge begins. For purposes of this subsection, “commencement of construction” means that the owner or operator of the point source has obtained the federal, state, and local approvals or permits necessary to begin physical construction of the point source and either:
1. Onsite physical construction has begun; or
 2. The owner or operator has entered into a contract for physical construction of the point source and the contract cannot be cancelled or modified without substantial loss. For purposes of this subsection, “substantial loss” means in excess of 10 percent of the total cost incurred for physical construction.
- C.** The Director may establish a schedule of compliance in an AZPDES permit for a recommencing point source discharge. The first AZPDES permit issued to a recommencing point source discharger may contain a schedule of compliance only when necessary to attain compliance with a new or revised water quality standard that is effective less than three years before recommencement of the discharge.
- D.** The Director may establish a schedule to bring a point source discharge of stormwater into compliance with a water quality standard in an AZPDES permit. A compliance schedule for a stormwater discharge shall require implementation of all reasonable and cost-effective best management practices to control the discharge of pollutants in stormwater.

Historical Note

Adopted effective February 18, 1992 (Supp. 92-1).

Amended effective April 24, 1996 (Supp. 96-2).

Amended by final rulemaking at 8 A.A.R. 1264, effective

March 8, 2002 (Supp. 02-1). Amended by final

rulemaking at 14 A.A.R. 4708, effective January 31, 2009 (Supp. 08-4).

R18-11-122. Variances

- A.** The Director shall consider a variance from a water quality standard for a point source discharge if the discharger demonstrates that treatment more advanced than that required to comply with technology-based effluent limitations is necessary to comply with the water quality standard and:
1. It is not technically feasible to achieve compliance within the next five years,
 2. The cost of the treatment would result in substantial and widespread economic and social impact, or
 3. Human-caused conditions or sources of pollution prevent attainment of the water quality standard and cannot be remedied within the next five years.
- B.** If the Director grants a variance for a point source discharge:
1. The Director shall issue the variance for a fixed term not to exceed five years,
 2. The variance shall apply only on a pollutant-specific basis. The point source discharge shall meet all other applicable water quality standards for which a variance is not granted, and
- 3.** The variance shall not modify a water quality standard. Other point source discharges to the surface water shall meet applicable water quality standards.
- C.** Upon expiration of a variance, a point source discharger shall either comply with the water quality standard or apply for renewal of the variance. To renew a variance, the applicant shall demonstrate reasonable progress towards compliance with the water quality standard during the term of the variance.
- D.** The Director shall reevaluate a variance upon the issuance, reissuance, or modification of the AZPDES permit for the point source discharge.
- E.** A person who seeks a variance from a water quality standard shall submit a written request for a variance to the Director. A request for a variance shall include the following information:
1. Identification of the specific pollutant and water quality standard for which a variance is sought;
 2. Identification of the receiving surface water;
 3. For an existing point source discharge, a detailed description of the existing discharge control technologies that are used to achieve compliance with applicable water quality standards. For a new point source discharge, a detailed description of the proposed discharge control technologies that will be used to achieve compliance with applicable water quality standards;
 4. Documentation that the existing or proposed discharge control technologies will comply with applicable technology-based effluent limitations and that more advanced treatment technology is necessary to achieve compliance with the water quality standard for which a variance is sought;
 5. A detailed discussion of the reasons why compliance with the water quality standard cannot be achieved;
 6. A detailed discussion of the discharge control technologies that are available for achieving compliance with the water quality standard for which a variance is sought;
 7. Documentation of one of the following:
 - a. That it is not technically feasible to install and operate any of the available discharge control technologies to achieve compliance with the water quality standard for which a variance is sought,
 - b. That installation and operation of each of the available discharge technologies to achieve compliance with the water quality standard would result in substantial and widespread economic and social impact, or
 - c. That human-caused conditions or sources of pollution prevent the attainment of the water quality standard for which the variance is sought and it is not possible to remedy the conditions or sources of pollution within the next five years,
 8. Documentation that the point source discharger has reduced, to the maximum extent practicable, the discharge of the pollutant for which a variance is sought through implementation of a local pretreatment, source reduction, or waste minimization program; and
 9. A detailed description of proposed interim discharge limitations that represent the highest level of treatment achievable by the point source discharger during the term of the variance.
- F.** The Director shall consider the following factors when deciding whether to grant or deny a variance request:
1. Bioaccumulation,
 2. The predicted exposure of biota and the likelihood that resident biota will be adversely affected,
 3. The known or predicted safe exposure levels for the pollutant for which the variance is requested, and
 4. The likelihood of adverse human health effects.
- G.** The Director shall issue a public notice and provide an opportunity for a public hearing on whether the request for a variance should be granted or denied under A.A.C. R18-9-A907 and A.A.C. R18-9-A908. An interested party may

request a public hearing on a variance under A.A.C. R18-9-A908(B).

- H. Any variance granted by the Director is subject to review and approval by the Regional Administrator.
- I. Any person who is adversely affected by a decision of the Director to grant or deny a variance and who has exercised any right to comment on the decision may appeal the decision under A.R.S. § 49-321 et seq. and A.R.S. § 41-1092 et seq.
- J. The Director shall not grant a variance for a point source discharge to an OAW listed in R18-11-112(G).

Historical Note

Adopted effective April 24, 1996 (Supp. 96-2). Amended by final rulemaking at 8 A.A.R. 1264, effective March 8, 2002 (Supp. 02-1). Amended by final rulemaking at 14 A.A.R. 4708, effective January 31, 2009 (Supp. 08-4).

R18-11-123. Discharge Prohibitions

- A. The discharge of wastewater to the following surface waters is prohibited:
 1. Sabino Canyon Creek;
 2. Vekol Wash, upstream of the Ak-Chin Indian Reservation; and
 3. Smith Wash, upstream of the Ak-Chin Indian Reservation.
- B. The discharge to Lake Powell of human body wastes and the wastes from toilets and other receptacles intended to receive or retain wastes from a vessel is prohibited.

Historical Note

Adopted effective April 24, 1996 (Supp. 96-2). Amended by final rulemaking at 8 A.A.R. 1264, effective March 8, 2002 (Supp. 02-1). Amended by final rulemaking at 14 A.A.R. 4708, effective January 31, 2009 (Supp. 08-4).

APPENDIX A. NUMERIC WATER QUALITY STANDARDS

Table 1. Water Quality Criteria By Designated Use

PARAMETER	CAS NUMBER	DWS (µg/L)	FC (µg/L)	FBC (µg/L)	PBC (µg/L)	A&Wc Acute (µg/L)	A&Wc Chronic (µg/L)	A&Ww Acute (µg/L)	A&Ww Chronic (µg/L)	A&Wedw Acute (µg/L)	A&Wedw Chronic (µg/L)	A&We Acute (µg/L)	AgI (µg/L)	AgL (µg/L)
Acenaphthene	83329	420	198	56,000	56,000	850	550	850	550	850	550			
Acrolein	107028	3.5	1.9	467	467	34	30	34	30	34	30			
Acrylonitrile	107131	0.06	0.2	3	37,333	3,800	250	3,800	250	3,800	250			
Alachlor	15972608	2		9,333	9,333	2,500	170	2,500	170	2,500	170			
Aldrin	309002	0.002	0.00005	0.08	28	3		3		3		4.5	0.003	See (b)
Alpha Particles (Gross) Radioactivity		15 pCi/L												
Ammonia	7664417					See (e) & Table 25	See (e) & Table 26	See (e) & Table 25	See (e) & Table 26	See (e) & Table 25	See (e) & Table 26			
Anthracene	120127	2,100	74	280,000	280,000									
Antimony	7440360	6 T	640 T	747 T	747 T	88 D	30 D	88 D	30 D	1,000 D	600 D			
Arsenic	7440382	10 T	80 T	30 T	280 T	340 D	150 D	340 D	150 D	340 D	150 D	440 D	2,000 T	200 T
Asbestos	1332214	See (a)												
Atrazine	1912249	3		32,667	32,667									
Barium	7440393	2,000 T		98,000 T	98,000 T									
Benz(a)anthracene	56553	0.005	0.02	0.2	0.2									
Benzene	71432	5	114	93	3,733	2,700	180	2,700	180	8,800	560			
3, 4 Benzfluoranthene	205992	0.005	0.02	1.9	1.9									
Benzidine	92875	0.0002	0.0002	0.01	2,800	1,300	89	1,300	89	1,300	89	10,000	0.01	0.01
Benzo(a)pyrene	50328	0.2	0.02	0.2	0.2									
Benzo(k)fluoranthene	207089	0.005	0.02	1.9	1.9									
Beryllium	7440417	4 T	84 T	1,867 T	1,867 T									
Beta particles and photon emitters		4 millirems/year												
Bis(2-chloroethyl) ether	111444	0.03	0.5	1	1	120,000	6,700	120,000	6,700	120,000	6,700			
Bis(2-chloroisopropyl) ether	108601	280	3,441	37,333	37,333									
Boron	7440428	1,400 T		186,667 T	186,667 T								1,000 T	
Bromodichloromethane	75274	TTHM See (g)	17	18,667	18,667									
p-Bromodiphenyl ether	101553					180	14	180	14	180	14			
Bromoform	75252	TTHM See (g)	133	180	18,667	15,000	10,000	15,000	10,000	15,000	10,000			
Bromomethane	74839	9.8	299	1,307	1,307	5,500	360	5,500	360	5,500	360			
Butyl benzyl phthalate	85687	1,400	386	186,667	186,667	1,700	130	1,700	130	1,700	130			
Cadmium	7440439	5 T	84 T	700 T	700 T	See (d) & Table 2	See (d) & Table 3	See (d) & Table 4	See (d) & Table 5	See (d) & Table 4	See (d) & Table 5	See (d) & Table 6	50	50
Carbofuran	1563662	40		4,667	4,667	650	50	650	50	650	50			
Carbon tetrachloride	56235	5	2	11	1,307	18,000	1,100	18,000	1,100	18,000	1,100			
Chlordane	57749	2	0.0008	4	467	2.4	0.004	2.4	0.2	2.4	0.2	3.2		
Chlorine (total residual)	7782505	4,000		4,000	4,000	19	11	19	11	19	11			
Chlorobenzene	108907	100	1,553	18,667	18,667	3,800	260	3,800	260	3,800	260			
2-Chloroethyl vinyl ether	110758					180,000	9,800	180,000	9,800	180,000	9,800			
Chloroform	67663	TTHM See (g)	2,133	9,333	9,333	14,000	900	14,000	900	14,000	900			
p-Chloro-m-cresol	59507					15	4.7	15	4.7	15	4.7	48,000		
Chloromethane	74873					270,000	15,000	270,000	15,000	270,000	15,000			
2-Chloronaphthalene	91587	560	317	74,667	74,667									
2-Chlorophenol	95578	35	30	4,667	4,667	2,200	150	2,200	150	2,200	150			
Chloropyrifos	2921882	21		2,800	2,800	0.08	0.04	0.08	0.04	0.08	0.04			
Chromium III	16065831		75,000 T	1,400,000 T	1,400,000 T	See (d) & Table 7	See (d) & Table 8	See (d) & Table 7	See (d) & Table 8	See (d) & Table 7	See (d) & Table 8	See (d) & Table 9		
Chromium VI	18540299	21 T	150 T	2,800 T	2,800 T	16 D	11 D	16 D	11 D	16 D	11 D	34 D		
Chromium (Total)	7440473	100 T											1,000	1,000
Chrysene	218019	0.005	0.02	19	19									

Department of Environmental Quality – Water Quality Standards

PARAMETER	CAS NUMBER	DWS (µg/L)	FC (µg/L)	FBC (µg/L)	PBC (µg/L)	A&Wc Acute (µg/L)	A&Wc Chronic (µg/L)	A&Ww Acute (µg/L)	A&Ww Chronic (µg/L)	A&Wedw Acute (µg/L)	A&Wedw Chronic (µg/L)	A&We Acute (µg/L)	AgI (µg/L)	AgL (µg/L)
Copper	7440508	1,300 T		1,300 T	1,300 T	See (d) & Table 10	See (d) & Table 11	See (d) & Table 10	See (d) & Table 11	See (d) & Table 10	See (d) & Table 11	See (d) & Table 12	5,000 T	500 T
Cyanide (as free cyanide)	57125	200 T	16,000 T	18,667 T	18,667 T	22 T	5.2 T	41 T	9.7 T	41 T	9.7 T	84 T		200 T
Dalapon	75990	200	8,000	28,000	28,000									
Dibenz (ah) anthracene	53703	0.005	0.02	1.9	1.9									
Dibromochloromethane	124481	TTHM See (g)	13	18,667	18,667									
1,2-Dibromo-3-chloropropane	96128	0.2												
1,2-Dibromoethane	106934	0.05		8,400	8,400									
Dibutyl phthalate	84742	700	899	93,333	93,333	470	35	470	35	470	35	1,100		
1,2-Dichlorobenzene	95501	600	205	84,000	84,000	790	300	1,200	470	1,200	470	5,900		
1,3-Dichlorobenzene	541731					2,500	970	2,500	970	2,500	970			
1,4-Dichlorobenzene	106467	75	5,755	373,333	373,333	560	210	2,000	780	2,000	780	6,500		
3,3'-Dichlorobenzidine	91941	0.08	0.03	3	3									
p,p'-Dichlorodiphenyl-trichloroethane (DDT) and metabolites (DDD) and (DDE)	50293	0.1	0.0002	4	467	1.1	0.001	1.1	0.001	1.1	0.001	1.1	0.001	0.001
1,2-Dichloroethane	107062	5	37	15	186,667	59,000	41,000	59,000	41,000	59,000	41,000			
1,1-Dichloroethylene	75354	7	7,143	46,667	46,667	15,000	950	15,000	950	15,000	950			
1,2-cis-Dichloroethylene	156592	70		70	70									
1,2-trans-Dichloroethylene	156605	100	10,127	18,667	18,667	68,000	3,900	68,000	3,900	68,000	3,900			
Dichloromethane	75092	5	593	190	56,000	97,000	5,500	97,000	5,500	97,000	5,500			
2,4-Dichlorophenol	120832	21	59	2,800	2,800	1,000	88	1,000	88	1,000	88			
2,4-Dichlorophenoxy-acetic acid (2,4-D)	94757	70		9,333	9,333									
1,2-Dichloropropane	78875	5	17,518	84,000	84,000	26,000	9,200	26,000	9,200	26,000	9,200			
1,3-Dichloropropene	542756	0.7	42	420	28,000	3,000	1,100	3,000	1,100	3,000	1,100			
Dieldrin	60571	0.002	0.00005	0.09	47	0.2	0.06	0.2	0.06	0.2	0.06	4	0.003	See (b)
Diethyl phthalate	84662	5,600	8,767	746,667	746,667	26,000	1,600	26,000	1,600	26,000	1,600			
Di (2-ethylhexyl) adipate	103231	400		560,000	560,000									
Di (2-ethylhexyl) phthalate	117817	6	3	1,200	18,667	400	360	400	360	400	360	3,100		
2,4-Dimethylphenol	105679	140	171	18,667	18,667	1,000	310	1,000	310	1,000	310	150,000		
Dimethyl phthalate	131113					17,000	1,000	17,000	1,000	17,000	1,000			
4,6-Dinitro-o-cresol	534521	28	582	3,733	3,733	310	24	310	24	310	24			
2,4-Dinitrophenol	51285	14	1,067	1,867	1,867	110	9.2	110	9.2	110	9.2			
2,4-Dinitrotoluene	121142	14	421	1,867	1,867	14,000	860	14,000	860	14,000	860			
2,6-Dinitrotoluene	606202	0.05		2	3,733									
Di-n-octyl phthalate	117840	2,800		373,333	373,333									
Dinoseb	88857	7		933	933									
1,2-Diphenylhydrazine	122667	0.04	0.2	1.8	1.8	130	11	130	11	130	11			
Diquat	85007	20		2,053	2,053									
Endosulfan sulfate	1031078	42	18	5,600	5,600	0.2	0.06	0.2	0.06	0.2	0.06	3		
Endosulfan (Total)	115297	42	18	5,600	5,600	0.2	0.06	0.2	0.06	0.2	0.06	3		
Endothall	145733	100		18,667	18,667									
Endrin	72208	2	0.06	280	280	0.09	0.04	0.09	0.04	0.09	0.04	0.7	0.004	0.004
Endrin aldehyde	7421933					0.09	0.04	0.09	0.04	0.09	0.04	0.7		
Ethylbenzene	100414	700	2,133	93,333	93,333	23,000	1,400	23,000	1,400	23,000	1,400			
Fluoranthene	206440	280	28	37,333	37,333	2,000	1,600	2,000	1,600	2,000	1,600			
Fluorene	86737	280	1,067	37,333	37,333									
Fluoride	7782414	4,000		140,000	140,000									
Glyphosate	1071836	700	266,667	93,333	93,333									
Guthion	86500						0.01		0.01		0.01			
Heptachlor	76448	0.4	0.00008	0.4	467	0.5	0.004	0.5	0.004	0.6	0.01	0.9		
Heptachlor epoxide	1024573	0.2	0.00004	0.2	12	0.5	0.004	0.5	0.004	0.6	0.01	0.9		
Hexachlorobenzene	118741	1	0.0003	1	747	6	3.7	6	3.7	6	3.7			
Hexachlorobutadiene	87683	0.4	18	18	187	45	8.2	45	8.2	45	8.2			
Hexachlorocyclohexane alpha	319846	0.006	0.005	0.22	7,467	1,600	130	1,600	130	1,600	130	1,600		
Hexachlorocyclohexane beta	319857	0.02	0.02	0.78	560	1,600	130	1,600	130	1,600	130	1,600		
Hexachlorocyclohexane delta	319868					1,600	130	1,600	130	1,600	130	1,600		
Hexachlorocyclohexane gamma (lindane)	58899	0.2	1.8	280	280	1		1		1		11		
Hexachlorocyclopentadiene	77474	50	74	11,200	11,200	3.5	0.3	3.5	0.3	3.5	0.3			
Hexachloroethane	67721	2.5	3.3	100	933	490	350	490	350	490	350	850		
Hydrogen sulfide	7783064						2 See (c)		2 See (c)		2 See (c)			
Indeno (1,2,3-cd) pyrene	193395	0.05	0.2	1.9	1.9									
Iron	7439896						1,000 D		1,000 D		1,000 D			
Isophorone	78591	37	961	1,500	186,667	59,000	43,000	59,000	43,000	59,000	43,000			
Lead	7439971	15 T		15 T	15 T	See (d) & Table 13	See (d) & Table 14	See (d) & Table 13	See (d) & Table 14	See (d) & Table 13	See (d) & Table 14	See (d) & Table 15	10,000 T	100 T
Malathion	121755	140		18,667	18,667		0.1		0.1		0.1			
Manganese	7439965	980		130,667	130,667								10,000	

PARAMETER	CAS NUMBER	DWS (µg/L)	FC (µg/L)	FBC (µg/L)	PBC (µg/L)	A&Wc Acute (µg/L)	A&Wc Chronic (µg/L)	A&Ww Acute (µg/L)	A&Ww Chronic (µg/L)	A&Wedw Acute (µg/L)	A&Wedw Chronic (µg/L)	A&We Acute (µg/L)	AgI (µg/L)	AgL (µg/L)
Mercury	7439976	2 T		280 T	280 T	2.4 D	0.01 D	2.4 D	0.01 D	2.4 D	0.01 D	5 D		10 T
Methoxychlor	72435	40		4,667	4,667		0.03		0.03		0.03			
Methylmercury			0.3 mg/kg											
Mirex	2385855	1		187	187		0.001		0.001		0.001			
Naphthalene	91203	140	1,524	18,667	18,667	1,100	210	3,200	580	3,200	580			
Nickel	7440020	210 T	511 T	28,000 T	28,000 T	See (d) & Table 16	See (d) & Table 17	See (d) & Table 16	See (d) & Table 17	See (d) & Table 16	See (d) & Table 17	See (d) & Table 18		
Nitrate	14797558	10,000		3,733,333	3,733,333									
Nitrite	14797650	1,000		233,333	233,333									
Nitrate + Nitrite		10,000												
Nitrobenzene	98953	3.5	138	467	467	1,300	850	1,300	850	1,300	850			
p-Nitrophenol	100027					4,100	3,000	4,100	3,000	4,100	3,000			
N-nitrosodimethylamine	62759	0.001	3	0.03	0.03									
N-nitrosodi-n-phenylamine	86306	7.1	6	290	290	2,900	200	2,900	200	2,900	200			
N-nitrosodi-n-propylamine	621647	0.005	0.5	0.2	88,667									
Oxamyl	23135220	200		23,333	23,333									
Parathion	56382					0.07	0.01	0.07	0.01	0.07	0.01			
Paraquat	1910425	32		4,200	4,200	100	54	100	54	100	54			
Pentachlorophenol	87865	1	370	12	28,000	See (e) & Table 22	See (e) & Table 23	See (e) & Table 22	See (e) & Table 23	See (e) & Table 22	See (e) & Table 23	See (e) & Table 24		
Permethrin	52645531	350		46,667	46,667	0.3	0.2	0.3	0.2	0.3	0.2			
Phenanthrene	85018					30	6.3	30	6.3	30	6.3			
Phenol	108952	2,100	37	280,000	280,000	5,100	730	7,000	1,000	7,000	1,000	180,000		
Picloram	1918021	500	2,710	65,333	65,333									
Polychlorinated biphenyls (PCBs)	1336363	0.5	0.00006	19	19	2	0.01	2	0.02	2	0.02	11	0.001	0.001
Pyrene	129000	210	800	28,000	28,000									
Radium 226 + Radium 228		5 pCi/L												
Selenium	7782492	50 T	667 T	4,667 T	4,667 T		2 T		2 T		2 T	33 T	20 T	50 T
Silver	7440224	35 T	8,000 T	4,667 T	4,667 T	See (d) & Table 19		See (d) & Table 19		See (d) & Table 19		See (d) & Table 19		
Simazine	112349	4		4,667	4,667									
Styrene	100425	100		186,667	186,667	5,600	370	5,600	370	5,600	370			
2,3,7,8-Tetrachlorodibenzo-p-dioxin (2,3,7,8-TCDD)	1746016	0.00003	5x10-9	0.00003	0.0009	0.01	0.005	0.01	0.005	0.01	0.005	0.1		
1,1,2,2-Tetrachloroethane	79345	0.2	4	7	93,333	4,700	3,200	4,700	3,200	4,700	3,200			
Tetrachloroethylene	127184	5	261	9,333	9,333	2,600	280	6,500	680	6,500	680	15,000		
Thallium	7440280	2 T	1 T	75 T	75 T	700 D	150 D	700 D	150 D	700 D	150 D			
Toluene	108883	1,000	29,907	373,333	373,333	8,700	180	8,700	180	8,700	180			
Toxaphene	8001352	3	0.0003	1.3	933	0.7	0.0002	0.7	0.0002	0.7	0.0002	11	0.005	0.005
Tributyltin						0.5	0.07	0.5	0.07	0.5	0.07			
1,2,4-Trichlorobenzene	120821	70	70	9,333	9,333	750	130	1,700	300	1,700	300			
1,1,1-Trichloroethane	71556	200	428,571	1,866,667	1,866,667	2,600	1,600	2,600	1,600	2,600	1,600		1,000	
1,1,2-Trichloroethane	79005	5	16	25	3,733	18,000	12,000	18,000	12,000	18,000	12,000			
Trichloroethylene	79016	5	29	280,000	280	20,000	1,300	20,000	1,300	20,000	1,300			
2,4,6-Trichlorophenol	88062	3.2	2	130	130	160	25	160	25	160	25	3,000		
2,4,5-Trichlorophenoxypropionic acid (2,4,5-TP)	93721	50		7,467	7,467									
Trihalomethanes (T)		80												
Uranium	7440611	30 D		2,800	2,800									
Vinyl chloride	75014	2	5	2	2,800									
Xylenes (T)	1330207	10,000		186,667	186,667									
Zinc	7440666	2,100 T	5,106 T	280,000 T	280,000 T	See (d) & Table 20	See (d) & Table 20	See (d) & Table 20	See (d) & Table 20	See (d) & Table 20	See (d) & Table 20	See (d) & Table 21	10,000 T	25,000 T

Footnotes

- a. The asbestos standard is 7 million fibers (longer than 10 micrometers) per liter.
- b. The aldrin/dieldrin standard is exceeded when the sum of the two compounds exceeds 0.003 µg/L.
- c. In lakes, the acute criteria for hydrogen sulfide apply only to water samples taken from the epilimnion, or the upper layer of a lake or reservoir.
- d. Hardness, expressed as mg/L CaCO₃, is determined according to the following criteria:
 - i. If the receiving water body has an A&Wc or A&Ww designated use, then hardness is based on the hardness of the receiving water body from a sample taken at the same time that the sample for the metal

- is taken, except that the hardness may not exceed 400 mg/L CaCO₃.
- ii. If the receiving water has an A&Wedw or A&We designated use, then the hardness is based on the hardness of the effluent from a sample taken at the same time that the sample for the metal is taken, except that the hardness may not exceed 400 mg/L CaCO₃.
- e. pH is determined according to the following criteria:
 - i. If the receiving water has an A&Wc or A&Ww designated use, then pH is based on the pH of the receiving water body from a sample taken at the same time that the sample for pentachlorophenol or ammonia is taken.

Department of Environmental Quality – Water Quality Standards

- ii. If the receiving water body has an A&Wedw or A&We designated use, then the pH is based on the pH of the effluent from a sample taken at the same time that the sample for pentachlorophenol or ammonia is taken.
- f. Table 1 abbreviations.
 - i. µg/L = micrograms per liter,
 - ii. mg/kg = milligrams per kilogram,
- iii. pCi/L = picocuries per liter,
- iv. D = dissolved,
- v. T = total recoverable,
- vi. TTHM indicates that the chemical is a trihalomethane.
- g. The total trihalomethane (TTHM) standard is exceeded when the sum of these four compounds exceeds 80 µg/L, as a rolling annual average.

Table 2. Acute Water Quality Standards for Dissolved Cadmium Aquatic and Wildlife coldwater

Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L
1	0.02	41	0.85	81	1.64	121	2.42	161	3.20	201	3.97	241	4.73	281	5.49	321	6.25	361	7.00
2	0.04	42	0.87	82	1.66	122	2.44	162	3.22	202	3.99	242	4.75	282	5.51	322	6.27	362	7.02
3	0.07	43	0.89	83	1.68	123	2.46	163	3.24	203	4.01	243	4.77	283	5.53	323	6.29	363	7.04
4	0.09	44	0.91	84	1.70	124	2.48	164	3.26	204	4.03	244	4.79	284	5.55	324	6.31	364	7.06
5	0.11	45	0.93	85	1.72	125	2.50	165	3.28	205	4.04	245	4.81	285	5.57	325	6.33	365	7.08
6	0.13	46	0.95	86	1.74	126	2.52	166	3.30	206	4.06	246	4.83	286	5.59	326	6.34	366	7.10
7	0.15	47	0.97	87	1.76	127	2.54	167	3.31	207	4.08	247	4.85	287	5.61	327	6.36	367	7.12
8	0.17	48	0.99	88	1.78	128	2.56	168	3.33	208	4.10	248	4.87	288	5.63	328	6.38	368	7.14
9	0.19	49	1.01	89	1.80	129	2.58	169	3.35	209	4.12	249	4.88	289	5.64	329	6.40	369	7.15
10	0.21	50	1.03	90	1.82	130	2.60	170	3.37	210	4.14	250	4.90	290	5.66	330	6.42	370	7.17
11	0.23	51	1.05	91	1.84	131	2.62	171	3.39	211	4.16	251	4.92	291	5.68	331	6.44	371	7.19
12	0.26	52	1.07	92	1.86	132	2.64	172	3.41	212	4.18	252	4.94	292	5.70	332	6.46	372	7.21
13	0.28	53	1.09	93	1.88	133	2.66	173	3.43	213	4.20	253	4.96	293	5.72	333	6.48	373	7.23
14	0.30	54	1.11	94	1.90	134	2.68	174	3.45	214	4.22	254	4.98	294	5.74	334	6.50	374	7.25
15	0.32	55	1.13	95	1.92	135	2.70	175	3.47	215	4.24	255	5.00	295	5.76	335	6.51	375	7.27
16	0.34	56	1.15	96	1.94	136	2.72	176	3.49	216	4.26	256	5.02	296	5.78	336	6.53	376	7.29
17	0.36	57	1.17	97	1.95	137	2.73	177	3.51	217	4.27	257	5.04	297	5.80	337	6.55	377	7.30
18	0.38	58	1.19	98	1.97	138	2.75	178	3.53	218	4.29	258	5.06	298	5.81	338	6.57	378	7.32
19	0.40	59	1.21	99	1.99	139	2.77	179	3.55	219	4.31	259	5.08	299	5.83	339	6.59	379	7.34
20	0.42	60	1.23	100	2.01	140	2.79	180	3.56	220	4.33	260	5.09	300	5.85	340	6.61	380	7.36
21	0.44	61	1.25	101	2.03	141	2.81	181	3.58	221	4.35	261	5.11	301	5.87	341	6.63	381	7.38
22	0.46	62	1.26	102	2.05	142	2.83	182	3.60	222	4.37	262	5.13	302	5.89	342	6.65	382	7.40
23	0.48	63	1.28	103	2.07	143	2.85	183	3.62	223	4.39	263	5.15	303	5.91	343	6.66	383	7.42
24	0.50	64	1.30	104	2.09	144	2.87	184	3.64	224	4.41	264	5.17	304	5.93	344	6.68	384	7.44
25	0.52	65	1.32	105	2.11	145	2.89	185	3.66	225	4.43	265	5.19	305	5.95	345	6.70	385	7.45
26	0.54	66	1.34	106	2.13	146	2.91	186	3.68	226	4.45	266	5.21	306	5.97	346	6.72	386	7.47
27	0.56	67	1.36	107	2.15	147	2.93	187	3.70	227	4.47	267	5.23	307	5.99	347	6.74	387	7.49
28	0.58	68	1.38	108	2.17	148	2.95	188	3.72	228	4.48	268	5.25	308	6.00	348	6.76	388	7.51
29	0.60	69	1.40	109	2.19	149	2.97	189	3.74	229	4.50	269	5.27	309	6.02	349	6.78	389	7.53
30	0.62	70	1.42	110	2.21	150	2.99	190	3.76	230	4.52	270	5.28	310	6.04	350	6.80	390	7.55
31	0.64	71	1.44	111	2.23	151	3.01	191	3.78	231	4.54	271	5.30	311	6.06	351	6.82	391	7.57
32	0.66	72	1.46	112	2.25	152	3.03	192	3.80	232	4.56	272	5.32	312	6.08	352	6.83	392	7.59
33	0.68	73	1.48	113	2.27	153	3.04	193	3.81	233	4.58	273	5.34	313	6.10	353	6.85	393	7.60
34	0.70	74	1.50	114	2.29	154	3.06	194	3.83	234	4.60	274	5.36	314	6.12	354	6.87	394	7.62
35	0.72	75	1.52	115	2.31	155	3.08	195	3.85	235	4.62	275	5.38	315	6.14	355	6.89	395	7.64
36	0.75	76	1.54	116	2.33	156	3.10	196	3.87	236	4.64	276	5.40	316	6.16	356	6.91	396	7.66

Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L
37	0.77	77	1.56	117	2.35	157	3.12	197	3.89	237	4.66	277	5.42	317	6.17	357	6.93	397	7.68
38	0.79	78	1.58	118	2.37	158	3.14	198	3.91	238	4.68	278	5.44	318	6.19	358	6.95	398	7.70
39	0.81	79	1.60	119	2.38	159	3.16	199	3.93	239	4.69	279	5.45	319	6.21	359	6.97	399	7.72
40	0.83	80	1.62	120	2.40	160	3.18	200	3.95	240	4.71	280	5.47	320	6.23	360	6.98	400	7.74

Table 3. Chronic Water Quality Standards for Dissolved Cadmium Aquatic and Wildlife coldwater

Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L
1	0.01	41	0.13	81	0.21	121	0.28	161	0.34	201	0.40	241	0.45	281	0.50	321	0.55	361	0.60
2	0.02	42	0.13	82	0.21	122	0.28	162	0.34	202	0.40	242	0.45	282	0.50	322	0.55	362	0.60
3	0.02	43	0.14	83	0.22	123	0.28	163	0.35	203	0.40	243	0.46	283	0.51	323	0.55	363	0.60
4	0.03	44	0.14	84	0.22	124	0.29	164	0.35	204	0.40	244	0.46	284	0.51	324	0.56	364	0.60
5	0.03	45	0.14	85	0.22	125	0.29	165	0.35	205	0.40	245	0.46	285	0.51	325	0.56	365	0.60
6	0.03	46	0.14	86	0.22	126	0.29	166	0.35	206	0.41	246	0.46	286	0.51	326	0.56	366	0.60
7	0.04	47	0.15	87	0.22	127	0.29	167	0.35	207	0.41	247	0.46	287	0.51	327	0.56	367	0.61
8	0.04	48	0.15	88	0.23	128	0.29	168	0.35	208	0.41	248	0.46	288	0.51	328	0.56	368	0.61
9	0.05	49	0.15	89	0.23	129	0.29	169	0.35	209	0.41	249	0.46	289	0.51	329	0.56	369	0.61
10	0.05	50	0.15	90	0.23	130	0.30	170	0.36	210	0.41	250	0.46	290	0.51	330	0.56	370	0.61
11	0.05	51	0.15	91	0.23	131	0.30	171	0.36	211	0.41	251	0.47	291	0.52	331	0.56	371	0.61
12	0.06	52	0.16	92	0.23	132	0.30	172	0.36	212	0.41	252	0.47	292	0.52	332	0.57	372	0.61
13	0.06	53	0.16	93	0.23	133	0.30	173	0.36	213	0.42	253	0.47	293	0.52	333	0.57	373	0.61
14	0.06	54	0.16	94	0.24	134	0.30	174	0.36	214	0.42	254	0.47	294	0.52	334	0.57	374	0.61
15	0.07	55	0.16	95	0.24	135	0.30	175	0.36	215	0.42	255	0.47	295	0.52	335	0.57	375	0.62
16	0.07	56	0.16	96	0.24	136	0.30	176	0.36	216	0.42	256	0.47	296	0.52	336	0.57	376	0.62
17	0.07	57	0.17	97	0.24	137	0.31	177	0.37	217	0.42	257	0.47	297	0.52	337	0.57	377	0.62
18	0.07	58	0.17	98	0.24	138	0.31	178	0.37	218	0.42	258	0.47	298	0.52	338	0.57	378	0.62
19	0.08	59	0.17	99	0.24	139	0.31	179	0.37	219	0.42	259	0.48	299	0.53	339	0.57	379	0.62
20	0.08	60	0.17	100	0.25	140	0.31	180	0.37	220	0.43	260	0.48	300	0.53	340	0.57	380	0.62
21	0.08	61	0.17	101	0.25	141	0.31	181	0.37	221	0.43	261	0.48	301	0.53	341	0.58	381	0.62
22	0.09	62	0.18	102	0.25	142	0.31	182	0.37	222	0.43	262	0.48	302	0.53	342	0.58	382	0.62
23	0.09	63	0.18	103	0.25	143	0.32	183	0.37	223	0.43	263	0.48	303	0.53	343	0.58	383	0.62
24	0.09	64	0.18	104	0.25	144	0.32	184	0.38	224	0.43	264	0.48	304	0.53	344	0.58	384	0.63
25	0.09	65	0.18	105	0.25	145	0.32	185	0.38	225	0.43	265	0.48	305	0.53	345	0.58	385	0.63
26	0.10	66	0.18	106	0.26	146	0.32	186	0.38	226	0.43	266	0.48	306	0.53	346	0.58	386	0.63
27	0.10	67	0.19	107	0.26	147	0.32	187	0.38	227	0.43	267	0.49	307	0.54	347	0.58	387	0.63
28	0.10	68	0.19	108	0.26	148	0.32	188	0.38	228	0.44	268	0.49	308	0.54	348	0.58	388	0.63
29	0.10	69	0.19	109	0.26	149	0.32	189	0.38	229	0.44	269	0.49	309	0.54	349	0.59	389	0.63
30	0.11	70	0.19	110	0.26	150	0.33	190	0.38	230	0.44	270	0.49	310	0.54	350	0.59	390	0.63
31	0.11	71	0.19	111	0.26	151	0.33	191	0.39	231	0.44	271	0.49	311	0.54	351	0.59	391	0.63
32	0.11	72	0.20	112	0.27	152	0.33	192	0.39	232	0.44	272	0.49	312	0.54	352	0.59	392	0.63
33	0.11	73	0.20	113	0.27	153	0.33	193	0.39	233	0.44	273	0.49	313	0.54	353	0.59	393	0.64
34	0.12	74	0.20	114	0.27	154	0.33	194	0.39	234	0.44	274	0.50	314	0.54	354	0.59	394	0.64
35	0.12	75	0.20	115	0.27	155	0.33	195	0.39	235	0.45	275	0.50	315	0.55	355	0.59	395	0.64

Department of Environmental Quality – Water Quality Standards

Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L
36	0.12	76	0.20	116	0.27	156	0.33	196	0.39	236	0.45	276	0.50	316	0.55	356	0.59	396	0.64
37	0.12	77	0.21	117	0.27	157	0.34	197	0.39	237	0.45	277	0.50	317	0.55	357	0.59	397	0.64
38	0.13	78	0.21	118	0.28	158	0.34	198	0.40	238	0.45	278	0.50	318	0.55	358	0.60	398	0.64
39	0.13	79	0.21	119	0.28	159	0.34	199	0.40	239	0.45	279	0.50	319	0.55	359	0.60	399	0.64
40	0.13	80	0.21	120	0.28	160	0.34	200	0.40	240	0.45	280	0.50	320	0.55	360	0.60	400	0.64

Table 4. Acute Water Quality Standards for Dissolved Cadmium Aquatic and Wildlife warmwater, and edw

Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L
1	0.09	41	3.30	81	6.41	121	9.47	161	12.50	201	15.51	241	18.49	281	21.47	321	24.42	361	27.37
2	0.17	42	3.38	82	6.49	122	9.55	162	12.58	202	15.58	242	18.57	282	21.54	322	24.50	362	27.44
3	0.26	43	3.46	83	6.57	123	9.62	163	12.65	203	15.66	243	18.64	283	21.61	323	24.57	363	27.52
4	0.34	44	3.54	84	6.64	124	9.70	164	12.73	204	15.73	244	18.72	284	21.69	324	24.64	364	27.59
5	0.42	45	3.62	85	6.72	125	9.78	165	12.80	205	15.81	245	18.79	285	21.76	325	24.72	365	27.66
6	0.51	46	3.70	86	6.80	126	9.85	166	12.88	206	15.88	246	18.87	286	21.84	326	24.79	366	27.74
7	0.59	47	3.77	87	6.87	127	9.93	167	12.95	207	15.96	247	18.94	287	21.91	327	24.87	367	27.81
8	0.67	48	3.85	88	6.95	128	10.00	168	13.03	208	16.03	248	19.02	288	21.98	328	24.94	368	27.88
9	0.75	49	3.93	89	7.03	129	10.08	169	13.10	209	16.11	249	19.09	289	22.06	329	25.01	369	27.96
10	0.83	50	4.01	90	7.10	130	10.16	170	13.18	210	16.18	250	19.16	290	22.13	330	25.09	370	28.03
11	0.92	51	4.09	91	7.18	131	10.23	171	13.25	211	16.26	251	19.24	291	22.21	331	25.16	371	28.10
12	1.00	52	4.17	92	7.26	132	10.31	172	13.33	212	16.33	252	19.31	292	22.28	332	25.23	372	28.18
13	1.08	53	4.24	93	7.33	133	10.38	173	13.40	213	16.40	253	19.39	293	22.35	333	25.31	373	28.25
14	1.16	54	4.32	94	7.41	134	10.46	174	13.48	214	16.48	254	19.46	294	22.43	334	25.38	374	28.32
15	1.24	55	4.40	95	7.49	135	10.53	175	13.56	215	16.55	255	19.54	295	22.50	335	25.46	375	28.40
16	1.32	56	4.48	96	7.56	136	10.61	176	13.63	216	16.63	256	19.61	296	22.58	336	25.53	376	28.47
17	1.40	57	4.55	97	7.64	137	10.69	177	13.71	217	16.70	257	19.68	297	22.65	337	25.60	377	28.54
18	1.48	58	4.63	98	7.72	138	10.76	178	13.78	218	16.78	258	19.76	298	22.72	338	25.68	378	28.62
19	1.56	59	4.71	99	7.79	139	10.84	179	13.86	219	16.85	259	19.83	299	22.80	339	25.75	379	28.69
20	1.64	60	4.79	100	7.87	140	10.91	180	13.93	220	16.93	260	19.91	300	22.87	340	25.82	380	28.77
21	1.72	61	4.87	101	7.95	141	10.99	181	14.01	221	17.00	261	19.98	301	22.95	341	25.90	381	28.84
22	1.80	62	4.94	102	8.02	142	11.07	182	14.08	222	17.08	262	20.06	302	23.02	342	25.97	382	28.91
23	1.88	63	5.02	103	8.10	143	11.14	183	14.16	223	17.15	263	20.13	303	23.09	343	26.05	383	28.99
24	1.96	64	5.10	104	8.18	144	11.22	184	14.23	224	17.23	264	20.20	304	23.17	344	26.12	384	29.06
25	2.04	65	5.18	105	8.25	145	11.29	185	14.31	225	17.30	265	20.28	305	23.24	345	26.19	385	29.13
26	2.12	66	5.25	106	8.33	146	11.37	186	14.38	226	17.38	266	20.35	306	23.32	346	26.27	386	29.21
27	2.20	67	5.33	107	8.40	147	11.44	187	14.46	227	17.45	267	20.43	307	23.39	347	26.34	387	29.28
28	2.28	68	5.41	108	8.48	148	11.52	188	14.53	228	17.53	268	20.50	308	23.46	348	26.41	388	29.35
29	2.36	69	5.49	109	8.56	149	11.59	189	14.61	229	17.60	269	20.58	309	23.54	349	26.49	389	29.43
30	2.44	70	5.56	110	8.63	150	11.67	190	14.68	230	17.67	270	20.65	310	23.61	350	26.56	390	29.50
31	2.52	71	5.64	111	8.71	151	11.75	191	14.76	231	17.75	271	20.72	311	23.69	351	26.63	391	29.57
32	2.60	72	5.72	112	8.79	152	11.82	192	14.83	232	17.82	272	20.80	312	23.76	352	26.71	392	29.65
33	2.67	73	5.79	113	8.86	153	11.90	193	14.91	233	17.90	273	20.87	313	23.83	353	26.78	393	29.72
34	2.75	74	5.87	114	8.94	154	11.97	194	14.98	234	17.97	274	20.95	314	23.91	354	26.85	394	29.79

Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L
35	2.83	75	5.95	115	9.01	155	12.05	195	15.06	235	18.05	275	21.02	315	23.98	355	26.93	395	29.87
36	2.91	76	6.03	116	9.09	156	12.12	196	15.13	236	18.12	276	21.09	316	24.05	356	27.00	396	29.94
37	2.99	77	6.10	117	9.17	157	12.20	197	15.21	237	18.20	277	21.17	317	24.13	357	27.08	397	30.01
38	3.07	78	6.18	118	9.24	158	12.27	198	15.28	238	18.27	278	21.24	318	24.20	358	27.15	398	30.08
39	3.15	79	6.26	119	9.32	159	12.35	199	15.36	239	18.35	279	21.32	319	24.28	359	27.22	399	30.16
40	3.23	80	6.33	120	9.40	160	12.43	200	15.43	240	18.42	280	21.39	320	24.35	360	27.30	400	30.23

Table 5. Chronic Water Quality Standards for Dissolved Cadmium Aquatic and Wildlife warmwater, and edw

Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L
1	0.02	41	0.30	81	0.48	121	0.64	161	0.78	201	0.91	241	1.03	281	1.15	321	1.26	361	1.37
2	0.04	42	0.31	82	0.49	122	0.64	162	0.78	202	0.91	242	1.04	282	1.15	322	1.26	362	1.37
3	0.05	43	0.31	83	0.49	123	0.65	163	0.79	203	0.92	243	1.04	283	1.16	323	1.27	363	1.37
4	0.06	44	0.32	84	0.50	124	0.65	164	0.79	204	0.92	244	1.04	284	1.16	324	1.27	364	1.38
5	0.07	45	0.32	85	0.50	125	0.66	165	0.79	205	0.92	245	1.05	285	1.16	325	1.27	365	1.38
6	0.08	46	0.33	86	0.51	126	0.66	166	0.80	206	0.93	246	1.05	286	1.16	326	1.27	366	1.38
7	0.09	47	0.33	87	0.51	127	0.66	167	0.80	207	0.93	247	1.05	287	1.17	327	1.28	367	1.38
8	0.10	48	0.34	88	0.51	128	0.67	168	0.80	208	0.93	248	1.05	288	1.17	328	1.28	368	1.39
9	0.10	49	0.34	89	0.52	129	0.67	169	0.81	209	0.94	249	1.06	289	1.17	329	1.28	369	1.39
10	0.11	50	0.35	90	0.52	130	0.67	170	0.81	210	0.94	250	1.06	290	1.17	330	1.28	370	1.39
11	0.12	51	0.35	91	0.53	131	0.68	171	0.81	211	0.94	251	1.06	291	1.18	331	1.29	371	1.39
12	0.13	52	0.36	92	0.53	132	0.68	172	0.82	212	0.95	252	1.07	292	1.18	332	1.29	372	1.40
13	0.14	53	0.36	93	0.53	133	0.68	173	0.82	213	0.95	253	1.07	293	1.18	333	1.29	373	1.40
14	0.14	54	0.37	94	0.54	134	0.69	174	0.82	214	0.95	254	1.07	294	1.19	334	1.30	374	1.40
15	0.15	55	0.37	95	0.54	135	0.69	175	0.83	215	0.95	255	1.07	295	1.19	335	1.30	375	1.40
16	0.16	56	0.38	96	0.55	136	0.69	176	0.83	216	0.96	256	1.08	296	1.19	336	1.30	376	1.41
17	0.16	57	0.38	97	0.55	137	0.70	177	0.83	217	0.96	257	1.08	297	1.19	337	1.30	377	1.41
18	0.17	58	0.38	98	0.55	138	0.70	178	0.84	218	0.96	258	1.08	298	1.20	338	1.31	378	1.41
19	0.18	59	0.39	99	0.56	139	0.71	179	0.84	219	0.97	259	1.09	299	1.20	339	1.31	379	1.41
20	0.18	60	0.39	100	0.56	140	0.71	180	0.84	220	0.97	260	1.09	300	1.20	340	1.31	380	1.42
21	0.19	61	0.40	101	0.57	141	0.71	181	0.85	221	0.97	261	1.09	301	1.21	341	1.31	381	1.42
22	0.20	62	0.40	102	0.57	142	0.72	182	0.85	222	0.98	262	1.10	302	1.21	342	1.32	382	1.42
23	0.20	63	0.41	103	0.57	143	0.72	183	0.85	223	0.98	263	1.10	303	1.21	343	1.32	383	1.42
24	0.21	64	0.41	104	0.58	144	0.72	184	0.86	224	0.98	264	1.10	304	1.21	344	1.32	384	1.43
25	0.21	65	0.42	105	0.58	145	0.73	185	0.86	225	0.99	265	1.10	305	1.22	345	1.32	385	1.43
26	0.22	66	0.42	106	0.58	146	0.73	186	0.86	226	0.99	266	1.11	306	1.22	346	1.33	386	1.43
27	0.23	67	0.42	107	0.59	147	0.73	187	0.87	227	0.99	267	1.11	307	1.22	347	1.33	387	1.43
28	0.23	68	0.43	108	0.59	148	0.74	188	0.87	228	0.99	268	1.11	308	1.22	348	1.33	388	1.44
29	0.24	69	0.43	109	0.60	149	0.74	189	0.87	229	1.00	269	1.12	309	1.23	349	1.34	389	1.44
30	0.24	70	0.44	110	0.60	150	0.74	190	0.88	230	1.00	270	1.12	310	1.23	350	1.34	390	1.44
31	0.25	71	0.44	111	0.60	151	0.75	191	0.88	231	1.00	271	1.12	311	1.23	351	1.34	391	1.44
32	0.25	72	0.45	112	0.61	152	0.75	192	0.88	232	1.01	272	1.12	312	1.24	352	1.34	392	1.45
33	0.26	73	0.45	113	0.61	153	0.75	193	0.89	233	1.01	273	1.13	313	1.24	353	1.35	393	1.45

Department of Environmental Quality – Water Quality Standards

Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L
34	0.26	74	0.46	114	0.61	154	0.76	194	0.89	234	1.01	274	1.13	314	1.24	354	1.35	394	1.45
35	0.27	75	0.46	115	0.62	155	0.76	195	0.89	235	1.02	275	1.13	315	1.24	355	1.35	395	1.46
36	0.28	76	0.46	116	0.62	156	0.76	196	0.90	236	1.02	276	1.14	316	1.25	356	1.35	396	1.46
37	0.28	77	0.47	117	0.63	157	0.77	197	0.90	237	1.02	277	1.14	317	1.25	357	1.36	397	1.46
38	0.29	78	0.47	118	0.63	158	0.77	198	0.90	238	1.02	278	1.14	318	1.25	358	1.36	398	1.46
39	0.29	79	0.48	119	0.63	159	0.77	199	0.91	239	1.03	279	1.14	319	1.26	359	1.36	399	1.47
40	0.30	80	0.48	120	0.64	160	0.78	200	0.91	240	1.03	280	1.15	320	1.26	360	1.36	400	1.47

Table 6. Acute Water Quality Standards for Dissolved Cadmium Aquatic and Wildlife ephemeral

Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L
1	0.25	41	9.58	81	18.58	121	27.45	161	36.23	201	44.94	241	53.59	281	62.21	321	70.78	361	79.32
2	0.50	42	9.80	82	18.80	122	27.67	162	36.45	202	45.15	242	53.81	282	62.42	322	70.99	362	79.53
3	0.75	43	10.03	83	19.03	123	27.89	163	36.66	203	45.37	243	54.03	283	62.64	323	71.21	363	79.74
4	0.99	44	10.26	84	19.25	124	28.11	164	36.88	204	45.59	244	54.24	284	62.85	324	71.42	364	79.95
5	1.23	45	10.49	85	19.47	125	28.33	165	37.10	205	45.81	245	54.46	285	63.06	325	71.63	365	80.17
6	1.47	46	10.71	86	19.69	126	28.55	166	37.32	206	46.02	246	54.67	286	63.28	326	71.85	366	80.38
7	1.71	47	10.94	87	19.92	127	28.77	167	37.54	207	46.24	247	54.89	287	63.49	327	72.06	367	80.59
8	1.95	48	11.17	88	20.14	128	28.99	168	37.76	208	46.46	248	55.10	288	63.71	328	72.27	368	80.81
9	2.18	49	11.39	89	20.36	129	29.21	169	37.97	209	46.67	249	55.32	289	63.92	329	72.49	369	81.02
10	2.42	50	11.62	90	20.58	130	29.43	170	38.19	210	46.89	250	55.54	290	64.14	330	72.70	370	81.23
11	2.65	51	11.84	91	20.81	131	29.65	171	38.41	211	47.11	251	55.75	291	64.35	331	72.92	371	81.44
12	2.89	52	12.07	92	21.03	132	29.87	172	38.63	212	47.32	252	55.97	292	64.57	332	73.13	372	81.66
13	3.13	53	12.30	93	21.25	133	30.09	173	38.85	213	47.54	253	56.18	293	64.78	333	73.34	373	81.87
14	3.36	54	12.52	94	21.47	134	30.31	174	39.06	214	47.76	254	56.40	294	65.00	334	73.56	374	82.08
15	3.59	55	12.75	95	21.70	135	30.53	175	39.28	215	47.97	255	56.61	295	65.21	335	73.77	375	82.30
16	3.83	56	12.97	96	21.92	136	30.75	176	39.50	216	48.19	256	56.83	296	65.42	336	73.98	376	82.51
17	4.06	57	13.20	97	22.14	137	30.97	177	39.72	217	48.41	257	57.04	297	65.64	337	74.20	377	82.72
18	4.29	58	13.42	98	22.36	138	31.19	178	39.94	218	48.62	258	57.26	298	65.85	338	74.41	378	82.93
19	4.53	59	13.65	99	22.58	139	31.41	179	40.15	219	48.84	259	57.48	299	66.07	339	74.62	379	83.15
20	4.76	60	13.87	100	22.81	140	31.63	180	40.37	220	49.06	260	57.69	300	66.28	340	74.84	380	83.36
21	4.99	61	14.10	101	23.03	141	31.85	181	40.59	221	49.27	261	57.91	301	66.50	341	75.05	381	83.57
22	5.22	62	14.32	102	23.25	142	32.07	182	40.81	222	49.49	262	58.12	302	66.71	342	75.26	382	83.78
23	5.45	63	14.55	103	23.47	143	32.29	183	41.03	223	49.71	263	58.34	303	66.93	343	75.48	383	84.00
24	5.68	64	14.77	104	23.69	144	32.50	184	41.24	224	49.92	264	58.55	304	67.14	344	75.69	384	84.21
25	5.91	65	15.00	105	23.91	145	32.72	185	41.46	225	50.14	265	58.77	305	67.35	345	75.90	385	84.42
26	6.14	66	15.22	106	24.13	146	32.94	186	41.68	226	50.35	266	58.98	306	67.57	346	76.12	386	84.64
27	6.37	67	15.45	107	24.36	147	33.16	187	41.90	227	50.57	267	59.20	307	67.78	347	76.33	387	84.85
28	6.60	68	15.67	108	24.58	148	33.38	188	42.11	228	50.79	268	59.41	308	68.00	348	76.54	388	85.06
29	6.83	69	15.90	109	24.80	149	33.60	189	42.33	229	51.00	269	59.63	309	68.21	349	76.76	389	85.27
30	7.06	70	16.12	110	25.02	150	33.82	190	42.55	230	51.22	270	59.84	310	68.42	350	76.97	390	85.49
31	7.29	71	16.34	111	25.24	151	34.04	191	42.77	231	51.44	271	60.06	311	68.64	351	77.18	391	85.70
32	7.52	72	16.57	112	25.46	152	34.26	192	42.98	232	51.65	272	60.27	312	68.85	352	77.40	392	85.91

Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L
33	7.75	73	16.79	113	25.68	153	34.48	193	43.20	233	51.87	273	60.49	313	69.07	353	77.61	393	86.12
34	7.98	74	17.02	114	25.90	154	34.70	194	43.42	234	52.08	274	60.70	314	69.28	354	77.82	394	86.33
35	8.21	75	17.24	115	26.12	155	34.91	195	43.63	235	52.30	275	60.92	315	69.49	355	78.04	395	86.55
36	8.44	76	17.46	116	26.34	156	35.13	196	43.85	236	52.52	276	61.13	316	69.71	356	78.25	396	86.76
37	8.67	77	17.69	117	26.57	157	35.35	197	44.07	237	52.73	277	61.35	317	69.92	357	78.46	397	86.97
38	8.89	78	17.91	118	26.79	158	35.57	198	44.29	238	52.95	278	61.56	318	70.14	358	78.68	398	87.18
39	9.12	79	18.13	119	27.01	159	35.79	199	44.50	239	53.16	279	61.78	319	70.35	359	78.89	399	87.40
40	9.35	80	18.36	120	27.23	160	36.01	200	44.72	240	53.38	280	61.99	320	70.56	360	79.10	400	87.61

**Table 7. Acute Water Quality Standards for Dissolved Chromium III
Aquatic and Wildlife coldwater, warmwater and edw**

Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L	Hard mg/L	Std. µg/L
1	13	41	275	81	479	121	666	161	842	201	1009	241	1171	281	1328	321	1481	361	1630
2	23	42	280	82	484	122	671	162	846	202	1013	242	1175	282	1332	322	1485	362	1634
3	32	43	285	83	489	123	675	163	850	203	1017	243	1179	283	1336	323	1488	363	1638
4	41	44	291	84	494	124	680	164	854	204	1022	244	1183	284	1340	324	1492	364	1641
5	49	45	296	85	499	125	684	165	859	205	1026	245	1187	285	1343	325	1496	365	1645
6	57	46	302	86	504	126	688	166	863	206	1030	246	1191	286	1347	326	1500	366	1649
7	65	47	307	87	508	127	693	167	867	207	1034	247	1195	287	1351	327	1504	367	1653
8	72	48	312	88	513	128	697	168	871	208	1038	248	1199	288	1355	328	1507	368	1656
9	79	49	318	89	518	129	702	169	876	209	1042	249	1203	289	1359	329	1511	369	1660
10	86	50	323	90	523	130	706	170	880	210	1046	250	1207	290	1363	330	1515	370	1664
11	93	51	328	91	527	131	711	171	884	211	1050	251	1211	291	1367	331	1519	371	1667
12	100	52	334	92	532	132	715	172	888	212	1054	252	1215	292	1370	332	1522	372	1671
13	107	53	339	93	537	133	720	173	893	213	1058	253	1219	293	1374	333	1526	373	1675
14	114	54	344	94	542	134	724	174	897	214	1062	254	1223	294	1378	334	1530	374	1678
15	120	55	349	95	546	135	729	175	901	215	1067	255	1226	295	1382	335	1534	375	1682
16	127	56	354	96	551	136	733	176	905	216	1071	256	1230	296	1386	336	1537	376	1686
17	133	57	360	97	556	137	737	177	909	217	1075	257	1234	297	1390	337	1541	377	1689
18	140	58	365	98	560	138	742	178	914	218	1079	258	1238	298	1393	338	1545	378	1693
19	146	59	370	99	565	139	746	179	918	219	1083	259	1242	299	1397	339	1549	379	1697
20	152	60	375	100	570	140	751	180	922	220	1087	260	1246	300	1401	340	1552	380	1700
21	159	61	380	101	574	141	755	181	926	221	1091	261	1250	301	1405	341	1556	381	1704
22	165	62	385	102	579	142	759	182	930	222	1095	262	1254	302	1409	342	1560	382	1708
23	171	63	390	103	584	143	764	183	935	223	1099	263	1258	303	1413	343	1564	383	1711
24	177	64	395	104	588	144	768	184	939	224	1103	264	1262	304	1416	344	1567	384	1715
25	183	65	400	105	593	145	772	185	943	225	1107	265	1266	305	1420	345	1571	385	1719
26	189	66	405	106	598	146	777	186	947	226	1111	266	1270	306	1424	346	1575	386	1722
27	195	67	410	107	602	147	781	187	951	227	1115	267	1274	307	1428	347	1578	387	1726
28	201	68	415	108	607	148	785	188	955	228	1119	268	1277	308	1432	348	1582	388	1730
29	207	69	420	109	611	149	790	189	960	229	1123	269	1281	309	1435	349	1586	389	1733
30	213	70	425	110	616	150	794	190	964	230	1127	270	1285	310	1439	350	1590	390	1737
31	218	71	430	111	621	151	799	191	968	231	1131	271	1289	311	1443	351	1593	391	1741
32	224	72	435	112	625	152	803	192	972	232	1135	272	1293	312	1447	352	1597	392	1744
33	230	73	440	113	630	153	807	193	976	233	1139	273	1297	313	1451	353	1601	393	1748
34	235	74	445	114	634	154	811	194	980	234	1143	274	1301	314	1454	354	1604	394	1751
35	241	75	450	115	639	155	816	195	985	235	1147	275	1305	315	1458	355	1608	395	1755
36	247	76	455	116	643	156	820	196	989	236	1151	276	1309	316	1462	356	1612	396	1759
37	252	77	460	117	648	157	824	197	993	237	1155	277	1312	317	1466	357	1616	397	1762
38	258	78	465	118	652	158	829	198	997	238	1159	278	1316	318	1470	358	1619	398	1766
39	263	79	470	119	657	159	833	199	1001	239	1163	279	1320	319	1473	359	1623	399	1770
40	269	80	475	120	662	160	837	200	1005	240	1167	280	1324	320	1477	360	1627	400	1773

Department of Environmental Quality – Water Quality Standards

**Table 8. Chronic Water Quality Standards for Dissolved Chromium III
Aquatic and Wildlife coldwater, warmwater and edw**

Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L
1	1.71	41	35.71	81	62.37	121	86.64	161	109.47	201	131.29	241	152.33	281	172.74	321	192.63	361	212.08
2	3.01	42	36.42	82	63.00	122	87.22	162	110.03	202	131.82	242	152.84	282	173.24	322	193.12	362	212.56
3	4.19	43	37.13	83	63.63	123	87.81	163	110.58	203	132.36	243	153.36	283	173.75	323	193.62	363	213.04
4	5.31	44	37.83	84	64.25	124	88.39	164	111.14	204	132.89	244	153.88	284	174.25	324	194.11	364	213.52
5	6.37	45	38.54	85	64.88	125	88.98	165	111.69	205	133.42	245	154.39	285	174.75	325	194.60	365	214.00
6	7.40	46	39.24	86	65.50	126	89.56	166	112.25	206	133.96	246	154.91	286	175.25	326	195.09	366	214.48
7	8.40	47	39.93	87	66.13	127	90.14	167	112.80	207	134.49	247	155.43	287	175.76	327	195.58	367	214.96
8	9.37	48	40.63	88	66.75	128	90.72	168	113.35	208	135.02	248	155.94	288	176.26	328	196.07	368	215.44
9	10.31	49	41.32	89	67.37	129	91.30	169	113.90	209	135.55	249	156.46	289	176.76	329	196.56	369	215.92
10	11.24	50	42.01	90	67.99	130	91.88	170	114.46	210	136.08	250	156.97	290	177.26	330	197.05	370	216.40
11	12.16	51	42.70	91	68.61	131	92.46	171	115.01	211	136.61	251	157.48	291	177.76	331	197.53	371	216.88
12	13.05	52	43.38	92	69.22	132	93.04	172	115.56	212	137.14	252	158.00	292	178.26	332	198.02	372	217.36
13	13.94	53	44.06	93	69.84	133	93.61	173	116.11	213	137.67	253	158.51	293	178.76	333	198.51	373	217.84
14	14.81	54	44.74	94	70.45	134	94.19	174	116.66	214	138.20	254	159.02	294	179.26	334	199.00	374	218.32
15	15.67	55	45.42	95	71.07	135	94.76	175	117.21	215	138.73	255	159.54	295	179.76	335	199.49	375	218.79
16	16.52	56	46.10	96	71.68	136	95.34	176	117.75	216	139.26	256	160.05	296	180.26	336	199.97	376	219.27
17	17.36	57	46.77	97	72.29	137	95.91	177	118.30	217	139.79	257	160.56	297	180.76	337	200.46	377	219.75
18	18.20	58	47.44	98	72.90	138	96.49	178	118.85	218	140.31	258	161.07	298	181.25	338	200.95	378	220.23
19	19.02	59	48.11	99	73.51	139	97.06	179	119.40	219	140.84	259	161.58	299	181.75	339	201.44	379	220.70
20	19.84	60	48.78	100	74.11	140	97.63	180	119.94	220	141.37	260	162.09	300	182.25	340	201.92	380	221.18
21	20.64	61	49.44	101	74.72	141	98.20	181	120.49	221	141.89	261	162.60	301	182.75	341	202.41	381	221.66
22	21.45	62	50.10	102	75.33	142	98.77	182	121.03	222	142.42	262	163.11	302	183.24	342	202.89	382	222.13
23	22.24	63	50.76	103	75.93	143	99.34	183	121.58	223	142.94	263	163.62	303	183.74	343	203.38	383	222.61
24	23.03	64	51.42	104	76.53	144	99.91	184	122.12	224	143.47	264	164.13	304	184.24	344	203.87	384	223.09
25	23.81	65	52.08	105	77.14	145	100.48	185	122.66	225	143.99	265	164.64	305	184.73	345	204.35	385	223.56
26	24.59	66	52.74	106	77.74	146	101.04	186	123.21	226	144.52	266	165.15	306	185.23	346	204.84	386	224.04
27	25.36	67	53.39	107	78.34	147	101.61	187	123.75	227	145.04	267	165.66	307	185.72	347	205.32	387	224.51
28	26.13	68	54.04	108	78.94	148	102.18	188	124.29	228	145.56	268	166.17	308	186.22	348	205.81	388	224.99
29	26.89	69	54.69	109	79.53	149	102.74	189	124.83	229	146.09	269	166.67	309	186.72	349	206.29	389	225.46
30	27.65	70	55.34	110	80.13	150	103.31	190	125.37	230	146.61	270	167.18	310	187.21	350	206.77	390	225.94
31	28.40	71	55.99	111	80.73	151	103.87	191	125.91	231	147.13	271	167.69	311	187.70	351	207.26	391	226.41
32	29.15	72	56.63	112	81.32	152	104.43	192	126.45	232	147.65	272	168.20	312	188.20	352	207.74	392	226.88
33	29.89	73	57.27	113	81.92	153	104.99	193	126.99	233	148.17	273	168.70	313	188.69	353	208.22	393	227.36
34	30.63	74	57.92	114	82.51	154	105.56	194	127.53	234	148.69	274	169.21	314	189.19	354	208.71	394	227.83
35	31.37	75	58.56	115	83.10	155	106.12	195	128.07	235	149.21	275	169.71	315	189.68	355	209.19	395	228.31
36	32.10	76	59.20	116	83.69	156	106.68	196	128.61	236	149.73	276	170.22	316	190.17	356	209.67	396	228.78
37	32.83	77	59.83	117	84.28	157	107.24	197	129.14	237	150.25	277	170.72	317	190.66	357	210.15	397	229.25
38	33.55	78	60.47	118	84.87	158	107.80	198	129.68	238	150.77	278	171.23	318	191.16	358	210.64	398	229.72
39	34.28	79	61.10	119	85.46	159	108.35	199	130.22	239	151.29	279	171.73	319	191.65	359	211.12	399	230.20
40	34.99	80	61.74	120	86.05	160	108.91	200	130.75	240	151.81	280	172.24	320	192.14	360	211.60	400	230.67

**Table 9. Acute Water Quality Standards for Dissolved Chromium III
Aquatic and Wildlife ephemeral**

Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L
1	44	41	921	81	1609	121	2235	161	2824	201	3386	241	3929	281	4456	321	4969	361	5470
2	78	42	939	82	1625	122	2250	162	2838	202	3400	242	3942	282	4469	322	4981	362	5483
3	108	43	958	83	1641	123	2265	163	2852	203	3414	243	3956	283	4481	323	4994	363	5495
4	137	44	976	84	1657	124	2280	164	2867	204	3428	244	3969	284	4494	324	5007	364	5507
5	164	45	994	85	1673	125	2295	165	2881	205	3441	245	3982	285	4507	325	5019	365	5520
6	191	46	1012	86	1690	126	2310	166	2895	206	3455	246	3996	286	4520	326	5032	366	5532
7	217	47	1030	87	1706	127	2325	167	2909	207	3469	247	4009	287	4533	327	5045	367	5545
8	242	48	1048	88	1722	128	2340	168	2924	208	3483	248	4022	288	4546	328	5057	368	5557
9	266	49	1066	89	1738	129	2355	169	2938	209	3496	249	4035	289	4559	329	5070	369	5569
10	290	50	1084	90	1754	130	2370	170	2952	210	3510	250	4049	290	4572	330	5082	370	5582
11	314	51	1101	91	1770	131	2385	171	2966	211	3524	251	4062	291	4585	331	5095	371	5594
12	337	52	1119	92	1785	132	2400	172	2981	212	3537	252	4075	292	4598	332	5108	372	5606
13	360	53	1137	93	1801	133	2415	173	2995	213	3551	253	4088	293	4611	333	5120	373	5619

Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L
14	382	54	1154	94	1817	134	2429	174	3009	214	3565	254	4102	294	4624	334	5133	374	5631
15	404	55	1172	95	1833	135	2444	175	3023	215	3578	255	4115	295	4637	335	5145	375	5643
16	426	56	1189	96	1849	136	2459	176	3037	216	3592	256	4128	296	4649	336	5158	376	5656
17	448	57	1206	97	1865	137	2474	177	3051	217	3606	257	4141	297	4662	337	5171	377	5668
18	469	58	1224	98	1880	138	2489	178	3066	218	3619	258	4155	298	4675	338	5183	378	5680
19	491	59	1241	99	1896	139	2503	179	3080	219	3633	259	4168	299	4688	339	5196	379	5693
20	512	60	1258	100	1912	140	2518	180	3094	220	3646	260	4181	300	4701	340	5208	380	5705
21	532	61	1275	101	1927	141	2533	181	3108	221	3660	261	4194	301	4714	341	5221	381	5717
22	553	62	1292	102	1943	142	2548	182	3122	222	3673	262	4207	302	4726	342	5233	382	5730
23	574	63	1309	103	1958	143	2562	183	3136	223	3687	263	4220	303	4739	343	5246	383	5742
24	594	64	1326	104	1974	144	2577	184	3150	224	3701	264	4234	304	4752	344	5258	384	5754
25	614	65	1343	105	1990	145	2592	185	3164	225	3714	265	4247	305	4765	345	5271	385	5766
26	634	66	1360	106	2005	146	2606	186	3178	226	3728	266	4260	306	4778	346	5283	386	5779
27	654	67	1377	107	2021	147	2621	187	3192	227	3741	267	4273	307	4790	347	5296	387	5791
28	674	68	1394	108	2036	148	2635	188	3206	228	3755	268	4286	308	4803	348	5308	388	5803
29	694	69	1411	109	2051	149	2650	189	3220	229	3768	269	4299	309	4816	349	5321	389	5815
30	713	70	1427	110	2067	150	2665	190	3234	230	3781	270	4312	310	4829	350	5333	390	5828
31	733	71	1444	111	2082	151	2679	191	3248	231	3795	271	4325	311	4841	351	5346	391	5840
32	752	72	1461	112	2098	152	2694	192	3262	232	3808	272	4338	312	4854	352	5358	392	5852
33	771	73	1477	113	2113	153	2708	193	3276	233	3822	273	4351	313	4867	353	5371	393	5864
34	790	74	1494	114	2128	154	2723	194	3289	234	3835	274	4364	314	4880	354	5383	394	5877
35	809	75	1510	115	2143	155	2737	195	3303	235	3849	275	4377	315	4892	355	5396	395	5889
36	828	76	1527	116	2159	156	2752	196	3317	236	3862	276	4390	316	4905	356	5408	396	5901
37	847	77	1543	117	2174	157	2766	197	3331	237	3875	277	4404	317	4918	357	5421	397	5913
38	865	78	1560	118	2189	158	2780	198	3345	238	3889	278	4417	318	4931	358	5433	398	5925
39	884	79	1576	119	2204	159	2795	199	3359	239	3902	279	4430	319	4943	359	5445	399	5938
40	903	80	1592	120	2220	160	2809	200	3372	240	3916	280	4443	320	4956	360	5458	400	5950

**Table 10. Acute Water Quality Standards for Dissolved Copper
Aquatic and Wildlife coldwater, warmwater and edw**

Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L
1	0.18	41	5.80	81	11.02	121	16.08	161	21.05	201	25.94	241	30.78	281	35.57	321	40.33	361	45.05
2	0.34	42	5.93	82	11.15	122	16.21	162	21.17	202	26.07	242	30.90	282	35.69	322	40.45	362	45.16
3	0.49	43	6.07	83	11.28	123	16.33	163	21.30	203	26.19	243	31.02	283	35.81	323	40.56	363	45.28
4	0.65	44	6.20	84	11.40	124	16.46	164	21.42	204	26.31	244	31.14	284	35.93	324	40.68	364	45.40
5	0.80	45	6.33	85	11.53	125	16.58	165	21.54	205	26.43	245	31.26	285	36.05	325	40.80	365	45.52
6	0.95	46	6.47	86	11.66	126	16.71	166	21.66	206	26.55	246	31.38	286	36.17	326	40.92	366	45.63
7	1.10	47	6.60	87	11.79	127	16.83	167	21.79	207	26.67	247	31.50	287	36.29	327	41.04	367	45.75
8	1.24	48	6.73	88	11.91	128	16.96	168	21.91	208	26.79	248	31.62	288	36.41	328	41.16	368	45.87
9	1.39	49	6.86	89	12.04	129	17.08	169	22.03	209	26.92	249	31.74	289	36.53	329	41.27	369	45.99
10	1.54	50	6.99	90	12.17	130	17.21	170	22.16	210	27.04	250	31.86	290	36.65	330	41.39	370	46.10
11	1.68	51	7.13	91	12.30	131	17.33	171	22.28	211	27.16	251	31.98	291	36.77	331	41.51	371	46.22
12	1.82	52	7.26	92	12.42	132	17.46	172	22.40	212	27.28	252	32.10	292	36.89	332	41.63	372	46.34
13	1.97	53	7.39	93	12.55	133	17.58	173	22.52	213	27.40	253	32.22	293	37.00	333	41.75	373	46.46
14	2.11	54	7.52	94	12.68	134	17.71	174	22.65	214	27.52	254	32.34	294	37.12	334	41.86	374	46.57
15	2.25	55	7.65	95	12.81	135	17.83	175	22.77	215	27.64	255	32.46	295	37.24	335	41.98	375	46.69
16	2.39	56	7.78	96	12.93	136	17.96	176	22.89	216	27.76	256	32.58	296	37.36	336	42.10	376	46.81
17	2.53	57	7.91	97	13.06	137	18.08	177	23.02	217	27.89	257	32.70	297	37.48	337	42.22	377	46.92
18	2.67	58	8.04	98	13.19	138	18.20	178	23.14	218	28.01	258	32.82	298	37.60	338	42.34	378	47.04
19	2.81	59	8.17	99	13.31	139	18.33	179	23.26	219	28.13	259	32.94	299	37.72	339	42.45	379	47.16
20	2.95	60	8.31	100	13.44	140	18.45	180	23.38	220	28.25	260	33.06	300	37.84	340	42.57	380	47.28
21	3.09	61	8.44	101	13.57	141	18.58	181	23.50	221	28.37	261	33.18	301	37.96	341	42.69	381	47.39
22	3.23	62	8.57	102	13.69	142	18.70	182	23.63	222	28.49	262	33.30	302	38.07	342	42.81	382	47.51
23	3.37	63	8.70	103	13.82	143	18.82	183	23.75	223	28.61	263	33.42	303	38.19	343	42.93	383	47.63
24	3.50	64	8.83	104	13.95	144	18.95	184	23.87	224	28.73	264	33.54	304	38.31	344	43.04	384	47.74
25	3.64	65	8.96	105	14.07	145	19.07	185	23.99	225	28.85	265	33.66	305	38.43	345	43.16	385	47.86
26	3.78	66	9.09	106	14.20	146	19.20	186	24.12	226	28.97	266	33.78	306	38.55	346	43.28	386	47.98

Department of Environmental Quality – Water Quality Standards

Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L
27	3.91	67	9.22	107	14.32	147	19.32	187	24.24	227	29.09	267	33.90	307	38.67	347	43.40	387	48.10
28	4.05	68	9.34	108	14.45	148	19.44	188	24.36	228	29.22	268	34.02	308	38.79	348	43.52	388	48.21
29	4.19	69	9.47	109	14.58	149	19.57	189	24.48	229	29.34	269	34.14	309	38.91	349	43.63	389	48.33
30	4.32	70	9.60	110	14.70	150	19.69	190	24.60	230	29.46	270	34.26	310	39.02	350	43.75	390	48.45
31	4.46	71	9.73	111	14.83	151	19.82	191	24.73	231	29.58	271	34.38	311	39.14	351	43.87	391	48.56
32	4.59	72	9.86	112	14.95	152	19.94	192	24.85	232	29.70	272	34.50	312	39.26	352	43.99	392	48.68
33	4.73	73	9.99	113	15.08	153	20.06	193	24.97	233	29.82	273	34.62	313	39.38	353	44.10	393	48.80
34	4.86	74	10.12	114	15.20	154	20.19	194	25.09	234	29.94	274	34.74	314	39.50	354	44.22	394	48.92
35	5.00	75	10.25	115	15.33	155	20.31	195	25.21	235	30.06	275	34.86	315	39.62	355	44.34	395	49.03
36	5.13	76	10.38	116	15.46	156	20.43	196	25.34	236	30.18	276	34.98	316	39.74	356	44.46	396	49.15
37	5.27	77	10.51	117	15.58	157	20.56	197	25.46	237	30.30	277	35.10	317	39.85	357	44.58	397	49.27
38	5.40	78	10.63	118	15.71	158	20.68	198	25.58	238	30.42	278	35.22	318	39.97	358	44.69	398	49.38
39	5.53	79	10.76	119	15.83	159	20.80	199	25.70	239	30.54	279	35.34	319	40.09	359	44.81	399	49.50
40	5.67	80	10.89	120	15.96	160	20.93	200	25.82	240	30.66	280	35.46	320	40.21	360	44.93	400	49.62

**Table 11. Chronic Water Quality Standards for Dissolved Copper
Aquatic and Wildlife coldwater, warmwater and edw**

Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L
1	0.18	41	4.18	81	7.48	121	10.54	161	13.45	201	16.26	241	18.99	281	21.65	321	24.26	361	26.82
2	0.32	42	4.27	82	7.56	122	10.61	162	13.52	202	16.33	242	19.06	282	21.72	322	24.33	362	26.89
3	0.45	43	4.35	83	7.64	123	10.69	163	13.60	203	16.40	243	19.13	283	21.78	323	24.39	363	26.95
4	0.57	44	4.44	84	7.72	124	10.76	164	13.67	204	16.47	244	19.19	284	21.85	324	24.45	364	27.01
5	0.69	45	4.53	85	7.79	125	10.84	165	13.74	205	16.54	245	19.26	285	21.92	325	24.52	365	27.08
6	0.81	46	4.61	86	7.87	126	10.91	166	13.81	206	16.61	246	19.33	286	21.98	326	24.58	366	27.14
7	0.92	47	4.70	87	7.95	127	10.99	167	13.88	207	16.68	247	19.39	287	22.05	327	24.65	367	27.20
8	1.03	48	4.78	88	8.03	128	11.06	168	13.95	208	16.75	248	19.46	288	22.11	328	24.71	368	27.27
9	1.14	49	4.87	89	8.11	129	11.13	169	14.02	209	16.81	249	19.53	289	22.18	329	24.78	369	27.33
10	1.25	50	4.95	90	8.18	130	11.21	170	14.09	210	16.88	250	19.59	290	22.24	330	24.84	370	27.39
11	1.36	51	5.04	91	8.26	131	11.28	171	14.16	211	16.95	251	19.66	291	22.31	331	24.91	371	27.46
12	1.46	52	5.12	92	8.34	132	11.35	172	14.24	212	17.02	252	19.73	292	22.38	332	24.97	372	27.52
13	1.57	53	5.21	93	8.42	133	11.43	173	14.31	213	17.09	253	19.80	293	22.44	333	25.03	373	27.58
14	1.67	54	5.29	94	8.49	134	11.50	174	14.38	214	17.16	254	19.86	294	22.51	334	25.10	374	27.65
15	1.77	55	5.37	95	8.57	135	11.57	175	14.45	215	17.23	255	19.93	295	22.57	335	25.16	375	27.71
16	1.87	56	5.46	96	8.65	136	11.65	176	14.52	216	17.29	256	20.00	296	22.64	336	25.23	376	27.77
17	1.97	57	5.54	97	8.73	137	11.72	177	14.59	217	17.36	257	20.06	297	22.70	337	25.29	377	27.83
18	2.07	58	5.62	98	8.80	138	11.79	178	14.66	218	17.43	258	20.13	298	22.77	338	25.35	378	27.90
19	2.17	59	5.71	99	8.88	139	11.87	179	14.73	219	17.50	259	20.20	299	22.83	339	25.42	379	27.96
20	2.26	60	5.79	100	8.96	140	11.94	180	14.80	220	17.57	260	20.26	300	22.90	340	25.48	380	28.02
21	2.36	61	5.87	101	9.03	141	12.01	181	14.87	221	17.64	261	20.33	301	22.96	341	25.55	381	28.09
22	2.46	62	5.95	102	9.11	142	12.08	182	14.94	222	17.70	262	20.40	302	23.03	342	25.61	382	28.15
23	2.55	63	6.03	103	9.18	143	12.16	183	15.01	223	17.77	263	20.46	303	23.09	343	25.68	383	28.21
24	2.65	64	6.12	104	9.26	144	12.23	184	15.08	224	17.84	264	20.53	304	23.16	344	25.74	384	28.28
25	2.74	65	6.20	105	9.34	145	12.30	185	15.15	225	17.91	265	20.60	305	23.22	345	25.80	385	28.34
26	2.83	66	6.28	106	9.41	146	12.37	186	15.22	226	17.98	266	20.66	306	23.29	346	25.87	386	28.40
27	2.93	67	6.36	107	9.49	147	12.45	187	15.29	227	18.04	267	20.73	307	23.35	347	25.93	387	28.46
28	3.02	68	6.44	108	9.56	148	12.52	188	15.36	228	18.11	268	20.79	308	23.42	348	25.99	388	28.53
29	3.11	69	6.52	109	9.64	149	12.59	189	15.43	229	18.18	269	20.86	309	23.48	349	26.06	389	28.59
30	3.20	70	6.60	110	9.72	150	12.66	190	15.50	230	18.25	270	20.93	310	23.55	350	26.12	390	28.65
31	3.29	71	6.68	111	9.79	151	12.74	191	15.57	231	18.32	271	20.99	311	23.61	351	26.19	391	28.72
32	3.38	72	6.76	112	9.87	152	12.81	192	15.64	232	18.38	272	21.06	312	23.68	352	26.25	392	28.78
33	3.47	73	6.84	113	9.94	153	12.88	193	15.71	233	18.45	273	21.13	313	23.74	353	26.31	393	28.84
34	3.56	74	6.92	114	10.02	154	12.95	194	15.78	234	18.52	274	21.19	314	23.81	354	26.38	394	28.90
35	3.65	75	7.00	115	10.09	155	13.02	195	15.85	235	18.59	275	21.26	315	23.87	355	26.44	395	28.97
36	3.74	76	7.08	116	10.17	156	13.10	196	15.92	236	18.65	276	21.32	316	23.94	356	26.50	396	29.03
37	3.83	77	7.16	117	10.24	157	13.17	197	15.99	237	18.72	277	21.39	317	24.00	357	26.57	397	29.09

Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L
38	3.92	78	7.24	118	10.32	158	13.24	198	16.05	238	18.79	278	21.46	318	24.07	358	26.63	398	29.15
39	4.01	79	7.32	119	10.39	159	13.31	199	16.12	239	18.86	279	21.52	319	24.13	359	26.70	399	29.22
40	4.09	80	7.40	120	10.47	160	13.38	200	16.19	240	18.92	280	21.59	320	24.20	360	26.76	400	29.28

Table 12. Acute Water Quality Standards for Dissolved Copper Aquatic and Wildlife ephemeral

Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L
1	0.30	41	10.04	81	19.07	121	27.84	161	36.43	201	44.91	241	53.28	281	61.57	321	69.80	361	77.97
2	0.58	42	10.27	82	19.29	122	28.05	162	36.65	202	45.12	242	53.49	282	61.78	322	70.00	362	78.17
3	0.85	43	10.50	83	19.52	123	28.27	163	36.86	203	45.33	243	53.70	283	61.99	323	70.21	363	78.37
4	1.12	44	10.73	84	19.74	124	28.49	164	37.07	204	45.54	244	53.90	284	62.19	324	70.41	364	78.58
5	1.38	45	10.96	85	19.96	125	28.70	165	37.29	205	45.75	245	54.11	285	62.40	325	70.62	365	78.78
6	1.64	46	11.19	86	20.18	126	28.92	166	37.50	206	45.96	246	54.32	286	62.61	326	70.82	366	78.98
7	1.90	47	11.42	87	20.40	127	29.14	167	37.71	207	46.17	247	54.53	287	62.81	327	71.03	367	79.19
8	2.15	48	11.65	88	20.62	128	29.35	168	37.92	208	46.38	248	54.74	288	63.02	328	71.23	368	79.39
9	2.41	49	11.88	89	20.84	129	29.57	169	38.14	209	46.59	249	54.94	289	63.22	329	71.44	369	79.59
10	2.66	50	12.11	90	21.06	130	29.78	170	38.35	210	46.80	250	55.15	290	63.43	330	71.64	370	79.80
11	2.91	51	12.33	91	21.28	131	30.00	171	38.56	211	47.01	251	55.36	291	63.64	331	71.85	371	80.00
12	3.16	52	12.56	92	21.50	132	30.22	172	38.77	212	47.22	252	55.57	292	63.84	332	72.05	372	80.20
13	3.40	53	12.79	93	21.72	133	30.43	173	38.99	213	47.43	253	55.78	293	64.05	333	72.26	373	80.41
14	3.65	54	13.02	94	21.94	134	30.65	174	39.20	214	47.64	254	55.98	294	64.25	334	72.46	374	80.61
15	3.89	55	13.24	95	22.16	135	30.86	175	39.41	215	47.85	255	56.19	295	64.46	335	72.66	375	80.81
16	4.14	56	13.47	96	22.38	136	31.08	176	39.62	216	48.06	256	56.40	296	64.67	336	72.87	376	81.02
17	4.38	57	13.70	97	22.60	137	31.29	177	39.84	217	48.27	257	56.61	297	64.87	337	73.07	377	81.22
18	4.62	58	13.92	98	22.82	138	31.51	178	40.05	218	48.48	258	56.81	298	65.08	338	73.28	378	81.42
19	4.86	59	14.15	99	23.04	139	31.72	179	40.26	219	48.68	259	57.02	299	65.28	339	73.48	379	81.62
20	5.11	60	14.37	100	23.26	140	31.94	180	40.47	220	48.89	260	57.23	300	65.49	340	73.69	380	81.83
21	5.35	61	14.60	101	23.48	141	32.15	181	40.68	221	49.10	261	57.44	301	65.69	341	73.89	381	82.03
22	5.59	62	14.83	102	23.70	142	32.37	182	40.89	222	49.31	262	57.64	302	65.90	342	74.09	382	82.23
23	5.82	63	15.05	103	23.92	143	32.58	183	41.11	223	49.52	263	57.85	303	66.11	343	74.30	383	82.44
24	6.06	64	15.28	104	24.14	144	32.80	184	41.32	224	49.73	264	58.06	304	66.31	344	74.50	384	82.64
25	6.30	65	15.50	105	24.36	145	33.01	185	41.53	225	49.94	265	58.26	305	66.52	345	74.71	385	82.84
26	6.54	66	15.73	106	24.57	146	33.23	186	41.74	226	50.15	266	58.47	306	66.72	346	74.91	386	83.04
27	6.77	67	15.95	107	24.79	147	33.44	187	41.95	227	50.36	267	58.68	307	66.93	347	75.11	387	83.25
28	7.01	68	16.17	108	25.01	148	33.65	188	42.16	228	50.57	268	58.89	308	67.13	348	75.32	388	83.45
29	7.25	69	16.40	109	25.23	149	33.87	189	42.37	229	50.78	269	59.09	309	67.34	349	75.52	389	83.65
30	7.48	70	16.62	110	25.45	150	34.08	190	42.59	230	50.99	270	59.30	310	67.54	350	75.73	390	83.85
31	7.72	71	16.85	111	25.66	151	34.30	191	42.80	231	51.19	271	59.51	311	67.75	351	75.93	391	84.06
32	7.95	72	17.07	112	25.88	152	34.51	192	43.01	232	51.40	272	59.71	312	67.95	352	76.13	392	84.26
33	8.18	73	17.29	113	26.10	153	34.72	193	43.22	233	51.61	273	59.92	313	68.16	353	76.34	393	84.46
34	8.42	74	17.52	114	26.32	154	34.94	194	43.43	234	51.82	274	60.13	314	68.36	354	76.54	394	84.66
35	8.65	75	17.74	115	26.53	155	35.15	195	43.64	235	52.03	275	60.33	315	68.57	355	76.74	395	84.87
36	8.88	76	17.96	116	26.75	156	35.37	196	43.85	236	52.24	276	60.54	316	68.77	356	76.95	396	85.07
37	9.12	77	18.18	117	26.97	157	35.58	197	44.06	237	52.45	277	60.75	317	68.98	357	77.15	397	85.27
38	9.35	78	18.41	118	27.19	158	35.79	198	44.27	238	52.65	278	60.95	318	69.18	358	77.36	398	85.47
39	9.58	79	18.63	119	27.40	159	36.01	199	44.48	239	52.86	279	61.16	319	69.39	359	77.56	399	85.68
40	9.81	80	18.85	120	27.62	160	36.22	200	44.69	240	53.07	280	61.37	320	69.59	360	77.76	400	85.88

Table 13. Acute Water Quality Standards for Dissolved Lead Aquatic and Wildlife coldwater, warmwater and edw

Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L
1	0.34	41	24.17	81	51.30	121	79.43	161	108.02	201	136.86	241	165.82	281	194.81	321	223.79	361	252.72
2	0.76	42	24.82	82	52.00	122	80.14	162	108.74	202	137.59	242	166.55	282	195.54	322	224.52	362	253.44
3	1.22	43	25.48	83	52.69	123	80.85	163	109.46	203	138.31	243	167.27	283	196.26	323	225.24	363	254.16
4	1.71	44	26.14	84	53.39	124	81.56	164	110.18	204	139.03	244	167.99	284	196.99	324	225.96	364	254.89
5	2.21	45	26.81	85	54.08	125	82.27	165	110.90	205	139.76	245	168.72	285	197.71	325	226.69	365	255.61
6	2.73	46	27.47	86	54.78	126	82.98	166	111.62	206	140.48	246	169.44	286	198.44	326	227.41	366	256.33
7	3.26	47	28.13	87	55.48	127	83.69	167	112.34	207	141.20	247	170.17	287	199.16	327	228.14	367	257.05
8	3.80	48	28.80	88	56.17	128	84.41	168	113.06	208	141.93	248	170.89	288	199.89	328	228.86	368	257.77
9	4.35	49	29.47	89	56.87	129	85.12	169	113.78	209	142.65	249	171.62	289	200.61	329	229.58	369	258.50

Department of Environmental Quality – Water Quality Standards

Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L
10	4.91	50	30.14	90	57.57	130	85.83	170	114.50	210	143.37	250	172.34	290	201.34	330	230.31	370	259.22
11	5.47	51	30.81	91	58.27	131	86.54	171	115.22	211	144.10	251	173.07	291	202.06	331	231.03	371	259.94
12	6.04	52	31.48	92	58.97	132	87.26	172	115.94	212	144.82	252	173.79	292	202.79	332	231.75	372	260.66
13	6.62	53	32.15	93	59.67	133	87.97	173	116.66	213	145.54	253	174.52	293	203.51	333	232.48	373	261.38
14	7.20	54	32.82	94	60.37	134	88.68	174	117.38	214	146.27	254	175.24	294	204.24	334	233.20	374	262.10
15	7.79	55	33.49	95	61.07	135	89.40	175	118.10	215	146.99	255	175.97	295	204.96	335	233.92	375	262.83
16	8.38	56	34.17	96	61.77	136	90.11	176	118.82	216	147.71	256	176.69	296	205.69	336	234.65	376	263.55
17	8.98	57	34.84	97	62.47	137	90.83	177	119.54	217	148.44	257	177.42	297	206.41	337	235.37	377	264.27
18	9.58	58	35.52	98	63.18	138	91.54	178	120.26	218	149.16	258	178.14	298	207.13	338	236.09	378	264.99
19	10.18	59	36.20	99	63.88	139	92.25	179	120.98	219	149.89	259	178.87	299	207.86	339	236.82	379	265.71
20	10.79	60	36.88	100	64.58	140	92.97	180	121.70	220	150.61	260	179.59	300	208.58	340	237.54	380	266.43
21	11.40	61	37.56	101	65.28	141	93.68	181	122.42	221	151.33	261	180.32	301	209.31	341	238.26	381	267.15
22	12.02	62	38.24	102	65.99	142	94.40	182	123.14	222	152.06	262	181.04	302	210.03	342	238.99	382	267.88
23	12.64	63	38.92	103	66.69	143	95.12	183	123.87	223	152.78	263	181.77	303	210.76	343	239.71	383	268.60
24	13.26	64	39.60	104	67.40	144	95.83	184	124.59	224	153.51	264	182.49	304	211.48	344	240.43	384	269.32
25	13.88	65	40.28	105	68.10	145	96.55	185	125.31	225	154.23	265	183.22	305	212.21	345	241.16	385	270.04
26	14.51	66	40.97	106	68.81	146	97.26	186	126.03	226	154.95	266	183.94	306	212.93	346	241.88	386	270.76
27	15.14	67	41.65	107	69.51	147	97.98	187	126.75	227	155.68	267	184.67	307	213.65	347	242.60	387	271.48
28	15.77	68	42.33	108	70.22	148	98.70	188	127.47	228	156.40	268	185.39	308	214.38	348	243.33	388	272.20
29	16.40	69	43.02	109	70.93	149	99.41	189	128.20	229	157.13	269	186.12	309	215.10	349	244.05	389	272.92
30	17.04	70	43.71	110	71.63	150	100.13	190	128.92	230	157.85	270	186.84	310	215.83	350	244.77	390	273.64
31	17.68	71	44.39	111	72.34	151	100.85	191	129.64	231	158.58	271	187.57	311	216.55	351	245.49	391	274.36
32	18.32	72	45.08	112	73.05	152	101.56	192	130.36	232	159.30	272	188.29	312	217.28	352	246.22	392	275.08
33	18.96	73	45.77	113	73.75	153	102.28	193	131.08	233	160.02	273	189.02	313	218.00	353	246.94	393	275.80
34	19.61	74	46.46	114	74.46	154	103.00	194	131.81	234	160.75	274	189.74	314	218.72	354	247.66	394	276.52
35	20.25	75	47.15	115	75.17	155	103.72	195	132.53	235	161.47	275	190.47	315	219.45	355	248.38	395	277.25
36	20.90	76	47.84	116	75.88	156	104.43	196	133.25	236	162.20	276	191.19	316	220.17	356	249.11	396	277.97
37	21.55	77	48.53	117	76.59	157	105.15	197	133.97	237	162.92	277	191.92	317	220.90	357	249.83	397	278.69
38	22.20	78	49.22	118	77.30	158	105.87	198	134.70	238	163.65	278	192.64	318	221.62	358	250.55	398	279.41
39	22.86	79	49.92	119	78.01	159	106.59	199	135.42	239	164.37	279	193.36	319	222.34	359	251.27	399	280.13
40	23.51	80	50.61	120	78.72	160	107.31	200	136.14	240	165.10	280	194.09	320	223.07	360	252.00	400	280.85

Table 14. Chronic Water Quality Standards for Dissolved Lead Aquatic and Wildlife coldwater, warmwater and edw

Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L
1	0.01	41	0.94	81	2.00	121	3.10	161	4.21	201	5.33	241	6.46	281	7.59	321	8.72	361	9.85
2	0.03	42	0.97	82	2.03	122	3.12	162	4.24	202	5.36	242	6.49	282	7.62	322	8.75	362	9.88
3	0.05	43	0.99	83	2.05	123	3.15	163	4.27	203	5.39	243	6.52	283	7.65	323	8.78	363	9.90
4	0.07	44	1.02	84	2.08	124	3.18	164	4.29	204	5.42	244	6.55	284	7.68	324	8.81	364	9.93
5	0.09	45	1.04	85	2.11	125	3.21	165	4.32	205	5.45	245	6.57	285	7.70	325	8.83	365	9.96
6	0.11	46	1.07	86	2.13	126	3.23	166	4.35	206	5.47	246	6.60	286	7.73	326	8.86	366	9.99
7	0.13	47	1.10	87	2.16	127	3.26	167	4.38	207	5.50	247	6.63	287	7.76	327	8.89	367	10.02
8	0.15	48	1.12	88	2.19	128	3.29	168	4.41	208	5.53	248	6.66	288	7.79	328	8.92	368	10.05
9	0.17	49	1.15	89	2.22	129	3.32	169	4.43	209	5.56	249	6.69	289	7.82	329	8.95	369	10.07
10	0.19	50	1.17	90	2.24	130	3.34	170	4.46	210	5.59	250	6.72	290	7.85	330	8.97	370	10.10
11	0.21	51	1.20	91	2.27	131	3.37	171	4.49	211	5.62	251	6.74	291	7.87	331	9.00	371	10.13
12	0.24	52	1.23	92	2.30	132	3.40	172	4.52	212	5.64	252	6.77	292	7.90	332	9.03	372	10.16
13	0.26	53	1.25	93	2.33	133	3.43	173	4.55	213	5.67	253	6.80	293	7.93	333	9.06	373	10.19
14	0.28	54	1.28	94	2.35	134	3.46	174	4.57	214	5.70	254	6.83	294	7.96	334	9.09	374	10.21
15	0.30	55	1.31	95	2.38	135	3.48	175	4.60	215	5.73	255	6.86	295	7.99	335	9.12	375	10.24
16	0.33	56	1.33	96	2.41	136	3.51	176	4.63	216	5.76	256	6.89	296	8.02	336	9.14	376	10.27
17	0.35	57	1.36	97	2.43	137	3.54	177	4.66	217	5.78	257	6.91	297	8.04	337	9.17	377	10.30
18	0.37	58	1.38	98	2.46	138	3.57	178	4.69	218	5.81	258	6.94	298	8.07	338	9.20	378	10.33
19	0.40	59	1.41	99	2.49	139	3.60	179	4.71	219	5.84	259	6.97	299	8.10	339	9.23	379	10.35
20	0.42	60	1.44	100	2.52	140	3.62	180	4.74	220	5.87	260	7.00	300	8.13	340	9.26	380	10.38
21	0.44	61	1.46	101	2.54	141	3.65	181	4.77	221	5.90	261	7.03	301	8.16	341	9.28	381	10.41
22	0.47	62	1.49	102	2.57	142	3.68	182	4.80	222	5.93	262	7.05	302	8.18	342	9.31	382	10.44
23	0.49	63	1.52	103	2.60	143	3.71	183	4.83	223	5.95	263	7.08	303	8.21	343	9.34	383	10.47
24	0.52	64	1.54	104	2.63	144	3.73	184	4.85	224	5.98	264	7.11	304	8.24	344	9.37	384	10.49
25	0.54	65	1.57	105	2.65	145	3.76	185	4.88	225	6.01	265	7.14	305	8.27	345	9.40	385	10.52
26	0.57	66	1.60	106	2.68	146	3.79	186	4.91	226	6.04	266	7.17	306	8.30	346	9.43	386	10.55

Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L
27	0.59	67	1.62	107	2.71	147	3.82	187	4.94	227	6.07	267	7.20	307	8.33	347	9.45	387	10.58
28	0.61	68	1.65	108	2.74	148	3.85	188	4.97	228	6.09	268	7.22	308	8.35	348	9.48	388	10.61
29	0.64	69	1.68	109	2.76	149	3.87	189	5.00	229	6.12	269	7.25	309	8.38	349	9.51	389	10.64
30	0.66	70	1.70	110	2.79	150	3.90	190	5.02	230	6.15	270	7.28	310	8.41	350	9.54	390	10.66
31	0.69	71	1.73	111	2.82	151	3.93	191	5.05	231	6.18	271	7.31	311	8.44	351	9.57	391	10.69
32	0.71	72	1.76	112	2.85	152	3.96	192	5.08	232	6.21	272	7.34	312	8.47	352	9.59	392	10.72
33	0.74	73	1.78	113	2.87	153	3.99	193	5.11	233	6.24	273	7.37	313	8.50	353	9.62	393	10.75
34	0.76	74	1.81	114	2.90	154	4.01	194	5.14	234	6.26	274	7.39	314	8.52	354	9.65	394	10.78
35	0.79	75	1.84	115	2.93	155	4.04	195	5.16	235	6.29	275	7.42	315	8.55	355	9.68	395	10.80
36	0.81	76	1.86	116	2.96	156	4.07	196	5.19	236	6.32	276	7.45	316	8.58	356	9.71	396	10.83
37	0.84	77	1.89	117	2.98	157	4.10	197	5.22	237	6.35	277	7.48	317	8.61	357	9.74	397	10.86
38	0.87	78	1.92	118	3.01	158	4.13	198	5.25	238	6.38	278	7.51	318	8.64	358	9.76	398	10.89
39	0.89	79	1.95	119	3.04	159	4.15	199	5.28	239	6.41	279	7.54	319	8.66	359	9.79	399	10.92
40	0.92	80	1.97	120	3.07	160	4.18	200	5.31	240	6.43	280	7.56	320	8.69	360	9.82	400	10.94

Table 15. Acute Water Quality Standards for Dissolved Lead Aquatic and Wildlife ephemeral

Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L
1	0.72	41	51.00	81	108.27	121	167.63	161	227.98	201	288.85	241	349.96	281	411.15	321	472.30	361	533.35
2	1.61	42	52.39	82	109.74	122	169.13	162	229.50	202	290.37	242	351.49	282	412.68	322	473.83	362	534.87
3	2.58	43	53.78	83	111.21	123	170.63	163	231.01	203	291.90	243	353.02	283	414.21	323	475.36	363	536.40
4	3.61	44	55.18	84	112.67	124	172.13	164	232.53	204	293.42	244	354.54	284	415.73	324	476.89	364	537.92
5	4.67	45	56.57	85	114.14	125	173.63	165	234.05	205	294.95	245	356.07	285	417.26	325	478.41	365	539.45
6	5.76	46	57.97	86	115.61	126	175.13	166	235.57	206	296.48	246	357.60	286	418.79	326	479.94	366	540.97
7	6.88	47	59.38	87	117.08	127	176.63	167	237.08	207	298.00	247	359.13	287	420.32	327	481.47	367	542.49
8	8.02	48	60.78	88	118.55	128	178.13	168	238.60	208	299.53	248	360.66	288	421.85	328	483.00	368	544.02
9	9.18	49	62.19	89	120.03	129	179.64	169	240.12	209	301.05	249	362.19	289	423.38	329	484.52	369	545.54
10	10.35	50	63.60	90	121.50	130	181.14	170	241.64	210	302.58	250	363.72	290	424.91	330	486.05	370	547.06
11	11.54	51	65.01	91	122.98	131	182.65	171	243.16	211	304.11	251	365.25	291	426.44	331	487.58	371	548.59
12	12.75	52	66.43	92	124.45	132	184.15	172	244.68	212	305.64	252	366.78	292	427.97	332	489.10	372	550.11
13	13.97	53	67.85	93	125.93	133	185.66	173	246.20	213	307.16	253	368.31	293	429.50	333	490.63	373	551.63
14	15.20	54	69.26	94	127.41	134	187.16	174	247.72	214	308.69	254	369.84	294	431.03	334	492.16	374	553.16
15	16.44	55	70.69	95	128.89	135	188.67	175	249.24	215	310.22	255	371.37	295	432.56	335	493.68	375	554.68
16	17.69	56	72.11	96	130.37	136	190.17	176	250.76	216	311.74	256	372.90	296	434.09	336	495.21	376	556.20
17	18.95	57	73.54	97	131.85	137	191.68	177	252.28	217	313.27	257	374.43	297	435.62	337	496.74	377	557.72
18	20.21	58	74.96	98	133.33	138	193.19	178	253.80	218	314.80	258	375.96	298	437.15	338	498.26	378	559.25
19	21.49	59	76.39	99	134.81	139	194.70	179	255.32	219	316.33	259	377.49	299	438.68	339	499.79	379	560.77
20	22.77	60	77.83	100	136.30	140	196.21	180	256.85	220	317.85	260	379.02	300	440.20	340	501.32	380	562.29
21	24.07	61	79.26	101	137.78	141	197.72	181	258.37	221	319.38	261	380.55	301	441.73	341	502.84	381	563.81
22	25.36	62	80.70	102	139.27	142	199.23	182	259.89	222	320.91	262	382.08	302	443.26	342	504.37	382	565.34
23	26.67	63	82.13	103	140.75	143	200.74	183	261.41	223	322.44	263	383.61	303	444.79	343	505.90	383	566.86
24	27.98	64	83.57	104	142.24	144	202.25	184	262.93	224	323.97	264	385.14	304	446.32	344	507.42	384	568.38
25	29.30	65	85.01	105	143.73	145	203.76	185	264.46	225	325.49	265	386.67	305	447.85	345	508.95	385	569.90
26	30.62	66	86.46	106	145.21	146	205.27	186	265.98	226	327.02	266	388.20	306	449.38	346	510.47	386	571.42
27	31.95	67	87.90	107	146.70	147	206.78	187	267.50	227	328.55	267	389.73	307	450.91	347	512.00	387	572.94
28	33.28	68	89.35	108	148.19	148	208.29	188	269.03	228	330.08	268	391.26	308	452.44	348	513.53	388	574.47
29	34.62	69	90.79	109	149.68	149	209.80	189	270.55	229	331.61	269	392.79	309	453.96	349	515.05	389	575.99
30	35.96	70	92.24	110	151.18	150	211.32	190	272.07	230	333.14	270	394.32	310	455.49	350	516.58	390	577.51
31	37.31	71	93.69	111	152.67	151	212.83	191	273.60	231	334.67	271	395.85	311	457.02	351	518.10	391	579.03
32	38.66	72	95.14	112	154.16	152	214.34	192	275.12	232	336.19	272	397.38	312	458.55	352	519.63	392	580.55
33	40.02	73	96.60	113	155.65	153	215.86	193	276.65	233	337.72	273	398.91	313	460.08	353	521.15	393	582.07
34	41.38	74	98.05	114	157.15	154	217.37	194	278.17	234	339.25	274	400.44	314	461.61	354	522.68	394	583.59
35	42.74	75	99.51	115	158.64	155	218.89	195	279.69	235	340.78	275	401.97	315	463.13	355	524.20	395	585.11
36	44.11	76	100.97	116	160.14	156	220.40	196	281.22	236	342.31	276	403.50	316	464.66	356	525.73	396	586.63
37	45.48	77	102.43	117	161.64	157	221.92	197	282.74	237	343.84	277	405.03	317	466.19	357	527.25	397	588.15
38	46.86	78	103.89	118	163.13	158	223.43	198	284.27	238	345.37	278	406.56	318	467.72	358	528.78	398	589.67
39	48.24	79	105.35	119	164.63	159	224.95	199	285.79	239	346.90	279	408.09	319	469.25	359	530.30	399	591.19
40	49.62	80	106.81	120	166.13	160	226.46	200	287.32	240	348.43	280	409.62	320	470.77	360	531.83	400	592.71

Department of Environmental Quality – Water Quality Standards

**Table 16. Acute Water Quality Standards for Dissolved Nickel
Aquatic and Wildlife coldwater, warmwater and edw**

Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L
1	10	41	220	81	392	121	550	161	701	201	845	241	985	281	1122	321	1256	361	1387
2	17	42	225	82	396	122	554	162	704	202	849	242	989	282	1126	322	1259	362	1390
3	24	43	229	83	400	123	558	163	708	203	852	243	992	283	1129	323	1263	363	1394
4	31	44	234	84	404	124	562	164	712	204	856	244	996	284	1132	324	1266	364	1397
5	37	45	238	85	408	125	566	165	715	205	859	245	999	285	1136	325	1269	365	1400
6	43	46	243	86	412	126	569	166	719	206	863	246	1003	286	1139	326	1272	366	1403
7	49	47	247	87	416	127	573	167	723	207	867	247	1006	287	1142	327	1276	367	1407
8	55	48	252	88	420	128	577	168	726	208	870	248	1010	288	1146	328	1279	368	1410
9	61	49	256	89	424	129	581	169	730	209	874	249	1013	289	1149	329	1282	369	1413
10	67	50	260	90	428	130	585	170	734	210	877	250	1017	290	1153	330	1286	370	1416
11	72	51	265	91	432	131	588	171	737	211	881	251	1020	291	1156	331	1289	371	1420
12	78	52	269	92	436	132	592	172	741	212	884	252	1023	292	1159	332	1292	372	1423
13	83	53	274	93	440	133	596	173	744	213	888	253	1027	293	1163	333	1296	373	1426
14	89	54	278	94	444	134	600	174	748	214	891	254	1030	294	1166	334	1299	374	1429
15	94	55	282	95	448	135	604	175	752	215	895	255	1034	295	1169	335	1302	375	1433
16	99	56	287	96	452	136	607	176	755	216	898	256	1037	296	1173	336	1305	376	1436
17	105	57	291	97	456	137	611	177	759	217	902	257	1041	297	1176	337	1309	377	1439
18	110	58	295	98	460	138	615	178	763	218	905	258	1044	298	1179	338	1312	378	1442
19	115	59	300	99	464	139	619	179	766	219	909	259	1047	299	1183	339	1315	379	1445
20	120	60	304	100	468	140	622	180	770	220	912	260	1051	300	1186	340	1319	380	1449
21	125	61	308	101	472	141	626	181	774	221	916	261	1054	301	1189	341	1322	381	1452
22	130	62	312	102	476	142	630	182	777	222	919	262	1058	302	1193	342	1325	382	1455
23	135	63	317	103	480	143	634	183	781	223	923	263	1061	303	1196	343	1328	383	1458
24	140	64	321	104	484	144	637	184	784	224	926	264	1064	304	1199	344	1332	384	1462
25	145	65	325	105	488	145	641	185	788	225	930	265	1068	305	1203	345	1335	385	1465
26	150	66	329	106	492	146	645	186	792	226	933	266	1071	306	1206	346	1338	386	1468
27	155	67	334	107	496	147	649	187	795	227	937	267	1075	307	1209	347	1341	387	1471
28	159	68	338	108	500	148	652	188	799	228	940	268	1078	308	1213	348	1345	388	1474
29	164	69	342	109	504	149	656	189	802	229	944	269	1082	309	1216	349	1348	389	1478
30	169	70	346	110	508	150	660	190	806	230	947	270	1085	310	1219	350	1351	390	1481
31	174	71	350	111	511	151	664	191	810	231	951	271	1088	311	1223	351	1355	391	1484
32	179	72	355	112	515	152	667	192	813	232	954	272	1092	312	1226	352	1358	392	1487
33	183	73	359	113	519	153	671	193	817	233	958	273	1095	313	1229	353	1361	393	1490
34	188	74	363	114	523	154	675	194	820	234	961	274	1099	314	1233	354	1364	394	1494
35	193	75	367	115	527	155	678	195	824	235	965	275	1102	315	1236	355	1368	395	1497
36	197	76	371	116	531	156	682	196	827	236	968	276	1105	316	1239	356	1371	396	1500
37	202	77	375	117	535	157	686	197	831	237	972	277	1109	317	1243	357	1374	397	1503
38	207	78	379	118	539	158	689	198	835	238	975	278	1112	318	1246	358	1377	398	1506
39	211	79	384	119	542	159	693	199	838	239	979	279	1115	319	1249	359	1381	399	1510
40	216	80	388	120	546	160	697	200	842	240	982	280	1119	320	1253	360	1384	400	1513

**Table 17. Chronic Water Quality Standards for Dissolved Nickel
Aquatic and Wildlife coldwater, warmwater and edw**

Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L
1	1.06	41	24.46	81	43.51	121	61.11	161	77.81	201	93.88	241	109.46	281	124.64	321	139.50	361	154.07
2	1.90	42	24.96	82	43.97	122	61.53	162	78.22	202	94.27	242	109.84	282	125.02	322	139.86	362	154.43
3	2.68	43	25.47	83	44.42	123	61.96	163	78.63	203	94.67	243	110.23	283	125.39	323	140.23	363	154.79
4	3.42	44	25.97	84	44.87	124	62.39	164	79.03	204	95.06	244	110.61	284	125.77	324	140.60	364	155.15
5	4.12	45	26.47	85	45.33	125	62.81	165	79.44	205	95.46	245	110.99	285	126.14	325	140.96	365	155.51
6	4.81	46	26.96	86	45.78	126	63.24	166	79.85	206	95.85	246	111.38	286	126.52	326	141.33	366	155.87
7	5.48	47	27.46	87	46.23	127	63.66	167	80.26	207	96.24	247	111.76	287	126.89	327	141.70	367	156.23
8	6.14	48	27.95	88	46.68	128	64.09	168	80.66	208	96.64	248	112.14	288	127.26	328	142.07	368	156.59
9	6.78	49	28.44	89	47.12	129	64.51	169	81.07	209	97.03	249	112.52	289	127.64	329	142.43	369	156.95
10	7.41	50	28.93	90	47.57	130	64.93	170	81.47	210	97.42	250	112.91	290	128.01	330	142.80	370	157.31
11	8.04	51	29.42	91	48.02	131	65.35	171	81.88	211	97.81	251	113.29	291	128.38	331	143.16	371	157.67
12	8.65	52	29.91	92	48.46	132	65.78	172	82.28	212	98.21	252	113.67	292	128.76	332	143.53	372	158.03
13	9.26	53	30.39	93	48.91	133	66.20	173	82.69	213	98.60	253	114.05	293	129.13	333	143.90	373	158.39
14	9.86	54	30.88	94	49.35	134	66.62	174	83.09	214	98.99	254	114.43	294	129.50	334	144.26	374	158.75
15	10.45	55	31.36	95	49.80	135	67.04	175	83.50	215	99.38	255	114.81	295	129.88	335	144.63	375	159.11
16	11.03	56	31.84	96	50.24	136	67.46	176	83.90	216	99.77	256	115.19	296	130.25	336	144.99	376	159.47
17	11.61	57	32.32	97	50.68	137	67.88	177	84.30	217	100.16	257	115.57	297	130.62	337	145.36	377	159.82
18	12.19	58	32.80	98	51.13	138	68.30	178	84.71	218	100.55	258	115.95	298	130.99	338	145.72	378	160.18
19	12.76	59	33.28	99	51.57	139	68.71	179	85.11	219	100.94	259	116.33	299	131.36	339	146.09	379	160.54
20	13.33	60	33.76	100	52.01	140	69.13	180	85.51	220	101.33	260	116.71	300	131.74	340	146.45	380	160.90

Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L
21	13.89	61	34.23	101	52.45	141	69.55	181	85.91	221	101.72	261	117.09	301	132.11	341	146.81	381	161.26
22	14.45	62	34.71	102	52.89	142	69.97	182	86.31	222	102.11	262	117.47	302	132.48	342	147.18	382	161.62
23	15.00	63	35.18	103	53.32	143	70.38	183	86.71	223	102.50	263	117.85	303	132.85	343	147.54	383	161.97
24	15.55	64	35.65	104	53.76	144	70.80	184	87.12	224	102.89	264	118.23	304	133.22	344	147.91	384	162.33
25	16.10	65	36.12	105	54.20	145	71.22	185	87.52	225	103.28	265	118.61	305	133.59	345	148.27	385	162.69
26	16.64	66	36.59	106	54.63	146	71.63	186	87.92	226	103.67	266	118.99	306	133.96	346	148.63	386	163.05
27	17.18	67	37.06	107	55.07	147	72.05	187	88.32	227	104.05	267	119.37	307	134.33	347	149.00	387	163.40
28	17.72	68	37.53	108	55.51	148	72.46	188	88.71	228	104.44	268	119.75	308	134.70	348	149.36	388	163.76
29	18.25	69	37.99	109	55.94	149	72.87	189	89.11	229	104.83	269	120.12	309	135.07	349	149.72	389	164.12
30	18.78	70	38.46	110	56.37	150	73.29	190	89.51	230	105.22	270	120.50	310	135.44	350	150.09	390	164.47
31	19.31	71	38.92	111	56.81	151	73.70	191	89.91	231	105.60	271	120.88	311	135.81	351	150.45	391	164.83
32	19.83	72	39.39	112	57.24	152	74.11	192	90.31	232	105.99	272	121.26	312	136.18	352	150.81	392	165.19
33	20.36	73	39.85	113	57.67	153	74.53	193	90.71	233	106.38	273	121.63	313	136.55	353	151.17	393	165.54
34	20.88	74	40.31	114	58.10	154	74.94	194	91.10	234	106.76	274	122.01	314	136.92	354	151.54	394	165.90
35	21.40	75	40.77	115	58.53	155	75.35	195	91.50	235	107.15	275	122.39	315	137.29	355	151.90	395	166.26
36	21.91	76	41.23	116	58.96	156	75.76	196	91.90	236	107.53	276	122.76	316	137.66	356	152.26	396	166.61
37	22.43	77	41.69	117	59.39	157	76.17	197	92.29	237	107.92	277	123.14	317	138.02	357	152.62	397	166.97
38	22.94	78	42.15	118	59.82	158	76.58	198	92.69	238	108.30	278	123.52	318	138.39	358	152.98	398	167.32
39	23.45	79	42.60	119	60.25	159	76.99	199	93.09	239	108.69	279	123.89	319	138.76	359	153.34	399	167.68
40	23.96	80	43.06	120	60.68	160	77.40	200	93.48	240	109.07	280	124.27	320	139.13	360	153.71	400	168.04

Table 18. Acute Water Quality Standards for Dissolved Nickel Aquatic and Wildlife ephemeral

Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L
1	85	41	1956	81	3479	121	4886	161	6221	201	7506	241	8752	281	9966	321	11154	361	12319
2	152	42	1996	82	3516	122	4920	162	6254	202	7538	242	8783	282	9996	322	11183	362	12348
3	214	43	2036	83	3552	123	4954	163	6287	203	7569	243	8813	283	10026	323	11213	363	12377
4	273	44	2076	84	3588	124	4988	164	6319	204	7601	244	8844	284	10056	324	11242	364	12405
5	330	45	2116	85	3624	125	5022	165	6352	205	7632	245	8875	285	10086	325	11271	365	12434
6	385	46	2156	86	3660	126	5056	166	6385	206	7664	246	8905	286	10116	326	11301	366	12463
7	438	47	2195	87	3696	127	5090	167	6417	207	7695	247	8936	287	10146	327	11330	367	12492
8	491	48	2235	88	3732	128	5124	168	6450	208	7727	248	8967	288	10176	328	11359	368	12521
9	542	49	2274	89	3768	129	5158	169	6482	209	7758	249	8997	289	10206	329	11389	369	12549
10	593	50	2313	90	3804	130	5192	170	6514	210	7790	250	9028	290	10235	330	11418	370	12578
11	643	51	2352	91	3839	131	5226	171	6547	211	7821	251	9058	291	10265	331	11447	371	12607
12	692	52	2391	92	3875	132	5259	172	6579	212	7852	252	9089	292	10295	332	11476	372	12636
13	740	53	2430	93	3911	133	5293	173	6612	213	7884	253	9119	293	10325	333	11506	373	12664
14	788	54	2469	94	3946	134	5327	174	6644	214	7915	254	9150	294	10355	334	11535	374	12693
15	835	55	2508	95	3982	135	5360	175	6676	215	7946	255	9180	295	10385	335	11564	375	12722
16	882	56	2546	96	4017	136	5394	176	6708	216	7978	256	9211	296	10414	336	11593	376	12751
17	929	57	2585	97	4053	137	5427	177	6741	217	8009	257	9241	297	10444	337	11622	377	12779
18	975	58	2623	98	4088	138	5461	178	6773	218	8040	258	9272	298	10474	338	11652	378	12808
19	1020	59	2661	99	4123	139	5494	179	6805	219	8071	259	9302	299	10504	339	11681	379	12837
20	1066	60	2699	100	4158	140	5528	180	6837	220	8102	260	9332	300	10533	340	11710	380	12865
21	1110	61	2737	101	4193	141	5561	181	6869	221	8133	261	9363	301	10563	341	11739	381	12894
22	1155	62	2775	102	4229	142	5594	182	6901	222	8165	262	9393	302	10593	342	11768	382	12922
23	1199	63	2813	103	4264	143	5628	183	6934	223	8196	263	9423	303	10622	343	11797	383	12951
24	1243	64	2851	104	4299	144	5661	184	6966	224	8227	264	9454	304	10652	344	11826	384	12980
25	1287	65	2888	105	4334	145	5694	185	6998	225	8258	265	9484	305	10682	345	11855	385	13008
26	1330	66	2926	106	4368	146	5727	186	7030	226	8289	266	9514	306	10711	346	11884	386	13037
27	1374	67	2963	107	4403	147	5761	187	7062	227	8320	267	9544	307	10741	347	11913	387	13065
28	1416	68	3001	108	4438	148	5794	188	7093	228	8351	268	9575	308	10770	348	11943	388	13094
29	1459	69	3038	109	4473	149	5827	189	7125	229	8382	269	9605	309	10800	349	11972	389	13123
30	1502	70	3075	110	4508	150	5860	190	7157	230	8413	270	9635	310	10830	350	12001	390	13151
31	1544	71	3112	111	4542	151	5893	191	7189	231	8444	271	9665	311	10859	351	12030	391	13180
32	1586	72	3149	112	4577	152	5926	192	7221	232	8475	272	9695	312	10889	352	12059	392	13208
33	1628	73	3186	113	4611	153	5959	193	7253	233	8506	273	9726	313	10918	353	12088	393	13237
34	1669	74	3223	114	4646	154	5992	194	7285	234	8536	274	9756	314	10948	354	12116	394	13265
35	1711	75	3260	115	4680	155	6025	195	7316	235	8567	275	9786	315	10977	355	12145	395	13294
36	1752	76	3297	116	4715	156	6058	196	7348	236	8598	276	9816	316	11007	356	12174	396	13322
37	1793	77	3333	117	4749	157	6090	197	7380	237	8629	277	9846	317	11036	357	12203	397	13350
38	1834	78	3370	118	4783	158	6123	198	7411	238	8660	278	9876	318	11066	358	12232	398	13379
39	1875	79	3407	119	4818	159	6156	199	7443	239	8691	279	9906	319	11095	359	12261	399	13407
40	1915	80	3443	120	4852	160	6189	200	7475	240	8721	280	9936	320	11124	360	12290	400	13436

Department of Environmental Quality – Water Quality Standards

**Table 19. Water Quality Standards for Dissolved Silver
Aquatic and Wildlife coldwater, warmwater, edw, and ephemeral**

Hard. mg/L	Std. ug/L	Hard. mg/L	Std. ug/L	Hard. mg/L	Std. ug/L	Hard. mg/L	Std. ug/L	Hard. mg/L	Std. ug/L	Hard. mg/L	Std. ug/L	Hard. mg/L	Std. ug/L	Hard. mg/L	Std. ug/L	Hard. mg/L	Std. ug/L	Hard. mg/L	Std. ug/L
1	0.001	41	0.69	81	2.24	121	4.46	161	7.30	201	10.69	241	14.60	281	19.02	321	23.91	361	29.26
2	0.004	42	0.72	82	2.29	122	4.53	162	7.38	202	10.78	242	14.71	282	19.14	322	24.04	362	29.40
3	0.01	43	0.75	83	2.33	123	4.59	163	7.45	203	10.87	243	14.81	283	19.25	323	24.17	363	29.54
4	0.01	44	0.78	84	2.38	124	4.66	164	7.53	204	10.96	244	14.92	284	19.37	324	24.30	364	29.68
5	0.02	45	0.81	85	2.43	125	4.72	165	7.61	205	11.06	245	15.02	285	19.49	325	24.43	365	29.82
6	0.03	46	0.85	86	2.48	126	4.79	166	7.69	206	11.15	246	15.13	286	19.61	326	24.56	366	29.96
7	0.03	47	0.88	87	2.53	127	4.85	167	7.77	207	11.24	247	15.24	287	19.72	327	24.69	367	30.11
8	0.04	48	0.91	88	2.58	128	4.92	168	7.85	208	11.34	248	15.34	288	19.84	328	24.82	368	30.25
9	0.05	49	0.94	89	2.63	129	4.98	169	7.93	209	11.43	249	15.45	289	19.96	329	24.95	369	30.39
10	0.06	50	0.98	90	2.68	130	5.05	170	8.01	210	11.52	250	15.56	290	20.08	330	25.08	370	30.53
11	0.07	51	1.01	91	2.74	131	5.12	171	8.09	211	11.62	251	15.66	291	20.20	331	25.21	371	30.67
12	0.08	52	1.04	92	2.79	132	5.19	172	8.18	212	11.71	252	15.77	292	20.32	332	25.34	372	30.81
13	0.10	53	1.08	93	2.84	133	5.25	173	8.26	213	11.81	253	15.88	293	20.44	333	25.47	373	30.96
14	0.11	54	1.11	94	2.89	134	5.32	174	8.34	214	11.91	254	15.99	294	20.56	334	25.60	374	31.10
15	0.12	55	1.15	95	2.95	135	5.39	175	8.42	215	12.00	255	16.09	295	20.68	335	25.73	375	31.24
16	0.14	56	1.19	96	3.00	136	5.46	176	8.51	216	12.10	256	16.20	296	20.80	336	25.87	376	31.39
17	0.15	57	1.22	97	3.05	137	5.53	177	8.59	217	12.19	257	16.31	297	20.92	337	26.00	377	31.53
18	0.17	58	1.26	98	3.11	138	5.60	178	8.67	218	12.29	258	16.42	298	21.04	338	26.13	378	31.67
19	0.18	59	1.30	99	3.16	139	5.67	179	8.76	219	12.39	259	16.53	299	21.16	339	26.26	379	31.82
20	0.20	60	1.34	100	3.22	140	5.74	180	8.84	220	12.48	260	16.64	300	21.28	340	26.40	380	31.96
21	0.22	61	1.37	101	3.27	141	5.81	181	8.93	221	12.58	261	16.75	301	21.41	341	26.53	381	32.11
22	0.24	62	1.41	102	3.33	142	5.88	182	9.01	222	12.68	262	16.86	302	21.53	342	26.67	382	32.25
23	0.26	63	1.45	103	3.38	143	5.95	183	9.10	223	12.78	263	16.97	303	21.65	343	26.80	383	32.40
24	0.28	64	1.49	104	3.44	144	6.02	184	9.18	224	12.88	264	17.08	304	21.78	344	26.93	384	32.54
25	0.30	65	1.53	105	3.50	145	6.09	185	9.27	225	12.98	265	17.19	305	21.90	345	27.07	385	32.69
26	0.32	66	1.57	106	3.56	146	6.17	186	9.35	226	13.08	266	17.31	306	22.02	346	27.20	386	32.84
27	0.34	67	1.62	107	3.61	147	6.24	187	9.44	227	13.18	267	17.42	307	22.15	347	27.34	387	32.98
28	0.36	68	1.66	108	3.67	148	6.31	188	9.53	228	13.28	268	17.53	308	22.27	348	27.47	388	33.13
29	0.38	69	1.70	109	3.73	149	6.39	189	9.61	229	13.38	269	17.64	309	22.39	349	27.61	389	33.28
30	0.41	70	1.74	110	3.79	150	6.46	190	9.70	230	13.48	270	17.76	310	22.52	350	27.75	390	33.42
31	0.43	71	1.78	111	3.85	151	6.54	191	9.79	231	13.58	271	17.87	311	22.64	351	27.88	391	33.57
32	0.45	72	1.83	112	3.91	152	6.61	192	9.88	232	13.68	272	17.98	312	22.77	352	28.02	392	33.72
33	0.48	73	1.87	113	3.97	153	6.68	193	9.97	233	13.78	273	18.10	313	22.90	353	28.16	393	33.87
34	0.50	74	1.92	114	4.03	154	6.76	194	10.06	234	13.88	274	18.21	314	23.02	354	28.29	394	34.02
35	0.53	75	1.96	115	4.09	155	6.84	195	10.15	235	13.98	275	18.33	315	23.15	355	28.43	395	34.16
36	0.55	76	2.01	116	4.15	156	6.91	196	10.24	236	14.09	276	18.44	316	23.27	356	28.57	396	34.31
37	0.58	77	2.05	117	4.21	157	6.99	197	10.33	237	14.19	277	18.56	317	23.40	357	28.71	397	34.46
38	0.61	78	2.10	118	4.28	158	7.06	198	10.42	238	14.29	278	18.67	318	23.53	358	28.85	398	34.61
39	0.64	79	2.14	119	4.34	159	7.14	199	10.51	239	14.40	279	18.79	319	23.66	359	28.99	399	34.76
40	0.67	80	2.19	120	4.40	160	7.22	200	10.60	240	14.50	280	18.90	320	23.78	360	29.12	400	34.91

**Table 20. Acute and Chronic Water Quality Standards for Dissolved Zinc
Aquatic and Wildlife coldwater, warmwater and edw**

Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L
1	2.4	41	55.1	81	98.0	121	137.7	161	175.4	201	211.7	241	246.9	281	281.2	321	314.8	361	347.7
2	4.3	42	56.2	82	99.0	122	138.7	162	176.4	202	212.6	242	247.8	282	282.1	322	315.6	362	348.5
3	6.0	43	57.3	83	100.1	123	139.6	163	177.3	203	213.5	243	248.6	283	282.9	323	316.4	363	349.4
4	7.7	44	58.4	84	101.1	124	140.6	164	178.2	204	214.4	244	249.5	284	283.8	324	317.3	364	350.2
5	9.3	45	59.6	85	102.1	125	141.6	165	179.1	205	215.3	245	250.4	285	284.6	325	318.1	365	351.0
6	10.8	46	60.7	86	103.1	126	142.5	166	180.0	206	216.2	246	251.2	286	285.5	326	318.9	366	351.8
7	12.3	47	61.8	87	104.1	127	143.5	167	181.0	207	217.1	247	252.1	287	286.3	327	319.8	367	352.6
8	13.8	48	62.9	88	105.2	128	144.4	168	181.9	208	217.9	248	253.0	288	287.1	328	320.6	368	353.4
9	15.2	49	64.0	89	106.2	129	145.4	169	182.8	209	218.8	249	253.8	289	288.0	329	321.4	369	354.2
10	16.7	50	65.1	90	107.2	130	146.4	170	183.7	210	219.7	250	254.7	290	288.8	330	322.2	370	355.1
11	18.1	51	66.2	91	108.2	131	147.3	171	184.6	211	220.6	251	255.6	291	289.7	331	323.1	371	355.9
12	19.4	52	67.3	92	109.2	132	148.3	172	185.5	212	221.5	252	256.4	292	290.5	332	323.9	372	356.7
13	20.8	53	68.4	93	110.2	133	149.2	173	186.4	213	222.4	253	257.3	293	291.4	333	324.7	373	357.5
14	22.1	54	69.5	94	111.2	134	150.2	174	187.4	214	223.3	254	258.1	294	292.2	334	325.6	374	358.3
15	23.5	55	70.6	95	112.2	135	151.1	175	188.3	215	224.1	255	259.0	295	293.0	335	326.4	375	359.1
16	24.8	56	71.7	96	113.2	136	152.1	176	189.2	216	225.0	256	259.9	296	293.9	336	327.2	376	359.9
17	26.1	57	72.8	97	114.2	137	153.0	177	190.1	217	225.9	257	260.7	297	294.7	337	328.0	377	360.7
18	27.4	58	73.9	98	115.2	138	153.9	178	191.0	218	226.8	258	261.6	298	295.6	338	328.9	378	361.5
19	28.7	59	74.9	99	116.2	139	154.9	179	191.9	219	227.7	259	262.4	299	296.4	339	329.7	379	362.4
20	30.0	60	76.0	100	117.2	140	155.8	180	192.8	220	228.6	260	263.3	300	297.2	340	330.5	380	363.2
21	31.2	61	77.1	101	118.2	141	156.8	181	193.7	221	229.4	261	264.2	301	298.1	341	331.3	381	364.0
22	32.5	62	78.2	102	119.2	142	157.7	182	194.6	222	230.3	262	265.0	302	298.9	342	332.2	382	364.8
23	33.7	63	79.2	103	120.2	143	158.7	183	195.5	223	231.2	263	265.9	303	299.8	343	333.0	383	365.6
24	35.0	64	80.3	104	121.1	144	159.6	184	196.4	224	232.1	264	266.7	304	300.6	344	333.8	384	366.4
25	36.2	65	81.3	105	122.1	145	160.5	185	197.3	225	232.9	265	267.6	305	301.4	345	334.6	385	367.2
26	37.4	66	82.4	106	123.1	146	161.5	186	198.3	226	233.8	266	268.4	306	302.3	346	335.4	386	368.0
27	38.6	67	83.5	107	124.1	147	162.4	187	199.2	227	234.7	267	269.3	307	303.1	347	336.3	387	368.8
28	39.9	68	84.5	108	125.1	148	163.3	188	200.1	228	235.6	268	270.2	308	304.0	348	337.1	388	369.6
29	41.1	69	85.6	109	126.1	149	164.3	189	201.0	229	236.5	269	271.0	309	304.8	349	337.9	389	370.4
30	42.2	70	86.6	110	127.0	150	165.2	190	201.9	230	237.3	270	271.9	310	305.6	350	338.7	390	371.2
31	43.4	71	87.7	111	128.0	151	166.2	191	202.8	231	238.2	271	272.7	311	306.5	351	339.5	391	372.1
32	44.6	72	88.7	112	129.0	152	167.1	192	203.7	232	239.1	272	273.6	312	307.3	352	340.4	392	372.9
33	45.8	73	89.8	113	130.0	153	168.0	193	204.6	233	239.9	273	274.4	313	308.1	353	341.2	393	373.7
34	47.0	74	90.8	114	130.9	154	168.9	194	205.5	234	240.8	274	275.3	314	309.0	354	342.0	394	374.5
35	48.1	75	91.8	115	131.9	155	169.9	195	206.3	235	241.7	275	276.1	315	309.8	355	342.8	395	375.3
36	49.3	76	92.9	116	132.9	156	170.8	196	207.2	236	242.6	276	277.0	316	310.6	356	343.6	396	376.1
37	50.5	77	93.9	117	133.9	157	171.7	197	208.1	237	243.4	277	277.8	317	311.5	357	344.5	397	376.9
38	51.6	78	94.9	118	134.8	158	172.7	198	209.0	238	244.3	278	278.7	318	312.3	358	345.3	398	377.7
39	52.8	79	96.0	119	135.8	159	173.6	199	209.9	239	245.2	279	279.5	319	313.1	359	346.1	399	378.5
40	53.9	80	97.0	120	136.8	160	174.5	200	210.8	240	246.0	280	280.4	320	314.0	360	346.9	400	379.3

**Table 21. Acute Water Quality Standards for Dissolved Zinc
Aquatic and Wildlife ephemeral**

Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L
1	22	41	522	81	930	121	1307	161	1665	201	2009	241	2343	281	2669	321	2987	361	3300
2	40	42	533	82	940	122	1316	162	1674	202	2018	242	2351	282	2677	322	2995	362	3307
3	57	43	544	83	950	123	1325	163	1682	203	2026	243	2360	283	2685	323	3003	363	3315
4	73	44	555	84	959	124	1334	164	1691	204	2034	244	2368	284	2693	324	3011	364	3323
5	88	45	565	85	969	125	1343	165	1700	205	2043	245	2376	285	2701	325	3019	365	3331
6	103	46	576	86	979	126	1353	166	1708	206	2051	246	2384	286	2709	326	3027	366	3338
7	117	47	587	87	988	127	1362	167	1717	207	2060	247	2392	287	2717	327	3034	367	3346
8	131	48	597	88	998	128	1371	168	1726	208	2068	248	2401	288	2725	328	3042	368	3354
9	145	49	608	89	1007	129	1380	169	1735	209	2077	249	2409	289	2733	329	3050	369	3362
10	158	50	618	90	1017	130	1389	170	1743	210	2085	250	2417	290	2741	330	3058	370	3369
11	171	51	629	91	1027	131	1398	171	1752	211	2093	251	2425	291	2749	331	3066	371	3377
12	184	52	639	92	1036	132	1407	172	1761	212	2102	252	2433	292	2757	332	3074	372	3385

Department of Environmental Quality – Water Quality Standards

Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L	Hard. mg/L	Std. µg/L
13	197	53	649	93	1046	133	1416	173	1769	213	2110	253	2442	293	2765	333	3082	373	3392
14	210	54	660	94	1055	134	1425	174	1778	214	2119	254	2450	294	2773	334	3089	374	3400
15	223	55	670	95	1065	135	1434	175	1787	215	2127	255	2458	295	2781	335	3097	375	3408
16	235	56	680	96	1074	136	1443	176	1795	216	2135	256	2466	296	2789	336	3105	376	3416
17	248	57	691	97	1084	137	1452	177	1804	217	2144	257	2474	297	2797	337	3113	377	3423
18	260	58	701	98	1093	138	1461	178	1813	218	2152	258	2482	298	2805	338	3121	378	3431
19	272	59	711	99	1103	139	1470	179	1821	219	2161	259	2491	299	2813	339	3129	379	3439
20	284	60	721	100	1112	140	1479	180	1830	220	2169	260	2499	300	2821	340	3136	380	3446
21	296	61	732	101	1121	141	1488	181	1838	221	2177	261	2507	301	2829	341	3144	381	3454
22	308	62	742	102	1131	142	1497	182	1847	222	2186	262	2515	302	2837	342	3152	382	3462
23	320	63	752	103	1140	143	1506	183	1856	223	2194	263	2523	303	2845	343	3160	383	3469
24	332	64	762	104	1150	144	1515	184	1864	224	2202	264	2531	304	2853	344	3168	384	3477
25	344	65	772	105	1159	145	1523	185	1873	225	2211	265	2539	305	2861	345	3175	385	3485
26	355	66	782	106	1168	146	1532	186	1881	226	2219	266	2547	306	2869	346	3183	386	3492
27	367	67	792	107	1178	147	1541	187	1890	227	2227	267	2556	307	2876	347	3191	387	3500
28	378	68	802	108	1187	148	1550	188	1898	228	2236	268	2564	308	2884	348	3199	388	3508
29	390	69	812	109	1196	149	1559	189	1907	229	2244	269	2572	309	2892	349	3207	389	3515
30	401	70	822	110	1206	150	1568	190	1916	230	2252	270	2580	310	2900	350	3214	390	3523
31	412	71	832	111	1215	151	1577	191	1924	231	2260	271	2588	311	2908	351	3222	391	3531
32	423	72	842	112	1224	152	1586	192	1933	232	2269	272	2596	312	2916	352	3230	392	3538
33	435	73	852	113	1233	153	1594	193	1941	233	2277	273	2604	313	2924	353	3238	393	3546
34	446	74	862	114	1243	154	1603	194	1950	234	2285	274	2612	314	2932	354	3245	394	3554
35	457	75	871	115	1252	155	1612	195	1958	235	2294	275	2620	315	2940	355	3253	395	3561
36	468	76	881	116	1261	156	1621	196	1967	236	2302	276	2628	316	2948	356	3261	396	3569
37	479	77	891	117	1270	157	1630	197	1975	237	2310	277	2636	317	2956	357	3269	397	3577
38	490	78	901	118	1279	158	1638	198	1984	238	2318	278	2645	318	2964	358	3276	398	3584
39	501	79	911	119	1289	159	1647	199	1992	239	2327	279	2653	319	2971	359	3284	399	3592
40	512	80	920	120	1298	160	1656	200	2001	240	2335	280	2661	320	2979	360	3292	400	3599

Table 22. Acute Water Quality Standards for Pentachlorophenol Aquatic and Wildlife coldwater, warmwater, and edw

pH	ug/L	pH	ug/L
3	0.163	7	9.070
3.1	0.180	7.1	10.029
3.2	0.199	7.2	11.090
3.3	0.220	7.3	12.262
3.4	0.243	7.4	13.558
3.5	0.269	7.5	14.992
3.6	0.298	7.6	16.577
3.7	0.329	7.7	18.329
3.8	0.364	7.8	20.267
3.9	0.402	7.9	22.410
4	0.445	8	24.779
4.1	0.492	8.1	27.399
4.2	0.544	8.2	30.296
4.3	0.601	8.3	33.498
4.4	0.665	8.4	37.040
4.5	0.735	8.5	40.956
4.6	0.813	8.6	45.286
4.7	0.899	8.7	50.074
4.8	0.994	8.8	55.368
4.9	1.099	8.9	61.222
5	1.215	9	67.694
5.1	1.344	9.1	74.851
5.2	1.486	9.2	82.765
5.3	1.643	9.3	91.515
5.4	1.817	9.4	101.190
5.5	2.009	9.5	111.888
5.6	2.221	9.6	123.717
5.7	2.456	9.7	136.797
5.8	2.716	9.8	151.260
5.9	3.003	9.9	167.252
6	3.320	10	184.934
6.1	3.671	10.1	204.486
6.2	4.059	10.2	226.105
6.3	4.488	10.3	250.010
6.4	4.963	10.4	276.442
6.5	5.488	10.5	305.668
6.6	6.068	10.6	337.984
6.7	6.709	10.7	373.717
6.8	7.419	10.8	413.228
6.9	8.203	10.9	456.916
		11	505.223

Table 23. Chronic Water Quality Standards for Pentachlorophenol Aquatic and Wildlife coldwater, warmwater, and edw

pH	ug/L	pH	ug/L
3	0.103	7	5.726
3.1	0.114	7.1	6.331
3.2	0.126	7.2	7.001
3.3	0.139	7.3	7.741
3.4	0.154	7.4	8.559
3.5	0.170	7.5	9.464
3.6	0.188	7.6	10.465
3.7	0.208	7.7	11.571
3.8	0.230	7.8	12.794
3.9	0.254	7.9	14.147
4	0.281	8	15.643
4.1	0.311	8.1	17.296
4.2	0.343	8.2	19.125
4.3	0.380	8.3	21.147
4.4	0.420	8.4	23.383
4.5	0.464	8.5	25.855
4.6	0.513	8.6	28.588
4.7	0.568	8.7	31.611
4.8	0.628	8.8	34.953
4.9	0.694	8.9	38.648
5	0.767	9	42.734
5.1	0.848	9.1	47.252
5.2	0.938	9.2	52.248
5.3	1.037	9.3	57.772
5.4	1.147	9.4	63.880
5.5	1.268	9.5	70.633
5.6	1.4022	9.6	78.101
5.7	1.550	9.7	86.358
5.8	1.714	9.8	95.488
5.9	1.896	9.9	105.583
6	2.096	10	116.746
6.1	2.318	10.1	129.089
6.2	2.563	10.2	142.736
6.3	2.833	10.3	157.827
6.4	3.133	10.4	174.513
6.5	3.464	10.5	192.963
6.6	3.831	10.6	213.364
6.7	4.235	10.7	235.922
6.8	4.683	10.8	260.864
6.9	5.178	10.9	288.444
		11	318.939

Table 24. Acute Water Quality Standards for Pentachlorophenol Aquatic and Wildlife ephemeral

pH	ug/L	pH	ug/L
3	0.660	7	36.760
3.1	0.730	7.1	40.646
3.2	0.807	7.2	44.943
3.3	0.892	7.3	49.695
3.4	0.986	7.4	54.949
3.5	1.091	7.5	60.758
3.6	1.206	7.6	67.182
3.7	1.334	7.7	74.284
3.8	1.475	7.8	82.138
3.9	1.631	7.9	90.822
4	1.803	8	100.424
4.1	1.994	8.1	111.041
4.2	2.204	8.2	122.781
4.3	2.437	8.3	135.762
4.4	2.695	8.4	150.115
4.5	2.980	8.5	165.985
4.6	3.295	8.6	183.534
4.7	3.643	8.7	202.938
4.8	4.029	8.8	224.393
4.9	4.454	8.9	248.117
5	4.925	9	274.349
5.1	5.446	9.1	303.354
5.2	6.022	9.2	335.426
5.3	6.659	9.3	370.888
5.4	7.363	9.4	410.100
5.5	8.141	9.5	453.457
5.6	9.002	9.6	501.398
5.7	9.953	9.7	554.408
5.8	11.006	9.8	613.021
5.9	12.169	9.9	677.832
6	13.456	10	749.495
6.1	14.878	10.1	828.735
6.2	16.451	10.2	916.351
6.3	18.191	10.3	1013.231
6.4	20.114	10.4	1120.354
6.5	22.240	10.5	1238.802
6.6	24.591	10.6	1369.773
6.7	27.191	10.7	1514.590
6.8	30.066	10.8	1674.718
6.9	33.245	10.9	1851.775
		11	2047.552

Department of Environmental Quality – Water Quality Standards

**Table 25. Acute Criteria for Total Ammonia (in mg/L as N)
Aquatic and Wildlife coldwater, warmwater, and edw**

pH	A&Wc	A&Ww and A&W edw
6.5	32.6	48.8
6.6	31.3	46.8
6.7	29.8	44.6
6.8	28.1	42.0
6.9	26.2	39.1
7.0	24.1	36.1
7.1	22.0	32.8
7.2	19.7	29.5
7.3	17.5	26.2
7.4	15.4	23.0
7.5	13.3	19.9
7.6	11.4	17.0
7.7	9.65	14.4
7.8	8.11	12.1
7.9	6.77	10.1
8.0	5.62	8.40
8.1	4.64	6.95
8.2	3.83	5.72
8.3	3.15	4.71
8.4	2.59	3.88
8.5	2.14	3.20
8.6	1.77	2.65
8.7	1.47	2.20
8.8	1.23	1.84
8.9	1.04	1.56
9.0	0.885	1.32

**Table 26. Chronic Criteria for Total Ammonia (mg/L as N)
Aquatic and Wildlife coldwater, warmwater, and edw**

pH	Temperature, °C									
	0	14	16	18	20	22	24	26	28	30
6.5	6.67	6.67	6.06	5.33	4.68	4.12	3.62	3.18	2.80	2.46
6.6	6.57	6.57	5.97	5.25	4.61	4.05	3.56	3.13	2.75	2.42
6.7	6.44	6.44	5.86	5.15	4.52	3.98	3.50	3.07	2.70	2.37
6.8	6.29	6.29	5.72	5.03	4.42	3.89	3.42	3.00	2.64	2.32
6.9	6.12	6.12	5.56	4.89	4.30	3.78	3.32	2.92	2.57	2.25
7.0	5.91	5.91	5.37	4.72	4.15	3.65	3.21	2.82	2.48	2.18
7.1	5.67	5.67	5.15	4.53	3.98	3.50	3.08	2.70	2.38	2.09
7.2	5.39	5.39	4.90	4.31	3.78	3.33	2.92	2.57	2.26	1.99
7.3	5.08	5.08	4.61	4.06	3.57	3.13	2.76	2.42	2.13	1.87
7.4	4.73	4.73	4.30	3.78	3.33	2.92	2.57	2.26	1.98	1.74
7.5	4.36	4.36	3.97	3.49	3.06	2.69	2.37	2.08	1.83	1.61
7.6	3.98	3.98	3.61	3.18	2.79	2.45	2.16	1.90	1.67	1.47
7.7	3.58	3.58	3.25	2.86	2.51	2.21	1.94	1.71	1.50	1.32
7.8	3.18	3.18	2.89	2.54	2.23	1.96	1.73	1.52	1.33	1.17
7.9	2.80	2.80	2.54	2.24	1.96	1.73	1.52	1.33	1.17	1.03
8.0	2.43	2.43	2.21	1.94	1.71	1.50	1.32	1.16	1.02	0.897
8.1	2.10	2.10	1.91	1.68	1.47	1.29	1.14	1.00	0.879	0.773
8.2	1.79	1.79	1.63	1.43	1.26	1.11	0.973	0.855	0.752	0.661
8.3	1.52	1.52	1.39	1.22	1.07	0.941	0.827	0.727	0.639	0.562
8.4	1.29	1.29	1.17	1.03	0.906	0.796	0.700	0.615	0.541	0.475
8.5	1.09	1.09	0.990	0.870	0.765	0.672	0.591	0.520	0.457	0.401
8.6	0.920	0.920	0.836	0.735	0.646	0.568	0.499	0.439	0.386	0.339

pH	Temperature, °C									
	0	14	16	18	20	22	24	26	28	30
8.7	0.778	0.778	0.707	0.622	0.547	0.480	0.422	0.371	0.326	0.287
8.8	0.661	0.661	0.601	0.528	0.464	0.408	0.359	0.315	0.277	0.244
8.9	0.565	0.565	0.513	0.451	0.397	0.349	0.306	0.269	0.237	0.208
9.0	0.486	0.486	0.442	0.389	0.342	0.300	0.264	0.232	0.204	0.179

Historical Note

Appendix A repealed; new Appendix A adopted effective April 24, 1996 (Supp. 96-2). Amended by final rulemaking at 8 A.A.R. 1264, effective March 8, 2002 (Supp. 02-1). Appendix A, Table 2 amended to correct references to footnotes (Supp. 02-4). Amended by final rulemaking at 9 A.A.R. 716, effective April 8, 2003 (Supp. 03-1). Amended by final rulemaking at 14 A.A.R. 4708, effective January 31, 2009 (Supp. 08-4).

APPENDIX B. SURFACE WATERS AND DESIGNATED USES

Watershed	Surface Waters	Segment Description and Location (Latitude and Longitudes are in NAD 27)	Lake Category	Aquatic and Wildlife				Human Health			Agricultural		
				A&Wc	A&Ww	A&We	A&Wedw	FBC	PBC	DWS	FC	AgI	AgL
BW	Alamo Lake	34°14'45"/113°35'00"	Deep		A&Ww			FBC			FC		AgL
BW	Big Sandy River	Headwaters to confluence at Alamo Lake at 34°18'36"/113°31'34"			A&Ww			FBC			FC		AgL
BW	Bill Williams River	Alamo Lake to confluence with Colorado River at 34°18'04"/114°08'10"			A&Ww			FBC			FC		AgL
BW	Blue Tank	34°40'14"/112°58'16"			A&Ww			FBC			FC		AgL
BW	Boulder Creek	Headwaters to confluence with unnamed tributary at 34°41'14"/113°03'34"		A&Wc				FBC			FC	AgI	AgL
BW	Boulder Creek	Below confluence with unnamed tributary to confluence with Burro Creek at 34°36'47"/113°18'00"			A&Ww			FBC			FC	AgI	AgL
BW	Burro Creek (OAW)	Headwaters to confluence with Boulder Creek at 34°36'47"/113°18'00"			A&Ww			FBC			FC		AgL
BW	Burro Creek	Below confluence with Boulder Creek to confluence with Big Sandy River at 34°32'24"/113°34'19.2"			A&Ww			FBC			FC		AgL
BW	Conger Creek	Headwaters to confluence with unnamed tributary at 34°45'13"/113°05'45"		A&Wc				FBC			FC		AgL
BW	Conger Creek	Below confluence with unnamed tributary to confluence with Burro Creek at 34°46'05"/113°12'54"			A&Ww			FBC			FC		AgL
BW	Coors Lake	34°36'20"/113°11'25"	Igneous		A&Ww			FBC			FC		
BW	Copper Basin Wash	Headwaters to confluence with unnamed tributary at 34°28'11"/112°35'31"		A&Wc				FBC			FC		AgL
BW	Copper Basin Wash	Below confluence with unnamed tributary to Skull Valley Wash at 34°25'55"/112°41'42"				A&We			PBC				AgL
BW	Cottonwood Canyon	Headwaters to Bear Trap Spring at 34°45'10"/112°52'32"		A&Wc				FBC			FC		AgL
BW	Cottonwood Canyon	Below Bear Trap Spring to confluence at Smith Canyon at 34°37'34"/112°54'46.8"			A&Ww			FBC			FC		AgL
BW	Date Creek	Headwaters to confluence with Santa Maria River at 34°18'11"/113°29'53"			A&Ww			FBC			FC		AgL
BW	Francis Creek (OAW)	Headwaters to confluence with Burro Creek at 34°44'28"/113°14'35"			A&Ww			FBC		DWS	FC	AgI	AgL
BW	Kirkland Creek	Headwaters to confluence with Santa Maria River at 34°32'02"/112°59'38"			A&Ww			FBC			FC	AgI	AgL
BW	Knight Creek	Headwaters to confluence with Big Sandy River at 34°55'16"/113°37'30"			A&Ww			FBC			FC		AgL
BW	Peeples Canyon (OAW)	Headwaters to confluence with Santa Maria River at 34°20'35"/113°15'11"			A&Ww			FBC			FC		AgL
BW	Santa Maria River	Headwaters to confluence with Alamo Lake at 34°18'36"/113°31'34"			A&Ww			FBC			FC	AgI	AgL
BW	Trout Creek	Headwaters to confluence with unnamed tributary at 35°06'47"/113°13'01"		A&Wc				FBC			FC		AgL
BW	Trout Creek	Below confluence with unnamed tributary to confluence with Knight Creek at 34°55'16"/113°37'30"			A&Ww			FBC			FC		AgL
CG	Agate Canyon Creek	Headwaters to confluence with the Colorado River at 36°08'38"/112°16'48"			A&Ww			FBC			FC		
CG	Beaver Dam Wash	Headwaters to confluence with the Virgin River at 36°53'42"/113°55'09"			A&Ww			FBC			FC		AgL
CG	Big Springs Tank	36°36'10"/112°20'58"		A&Wc				FBC			FC		AgL
CG	Boucher Creek	Headwaters to confluence with the Colorado River at 36°06'54"/112°13'44"			A&Ww			FBC			FC		
CG	Bright Angel Creek	Headwaters to Roaring Springs Canyon at 36°11'34"/112°01'54"		A&Wc				FBC			FC		
CG	Bright Angel Creek	Below Roaring Spring Canyon to Colorado River at 36°05'56"/112°05'27.6"			A&Ww			FBC			FC		
CG	Bright Angel Wash	Headwaters to South Rim of Grand Canyon WWTP outfall at 36°02'59"/112°09'02"					A&We		PBC				

Department of Environmental Quality – Water Quality Standards

Watershed	Surface Waters	Segment Description and Location (Latitude and Longitudes are in NAD 27)	Lake Category	Aquatic and Wildlife				Human Health				Agricultural		
				A&Wc	A&Ww	A&We	A&Wedw	FBC	PBC	DWS	FC	Agl	AgL	
CG	Bright Angel Wash (EDW)	South Rim Grand Canyon WWTP outfall at 36°00'11"/112°39'06" to Coconino Wash					A&Wedw		PBC					AgL
CG	Bulrush Canyon Wash	Headwaters to confluence with Kanab Creek at 36°46'55"/112°37'08"			A&We				PBC					
CG	Cataract Creek	Headwaters to Santa Fe Reservoir		A&Wc				FBC		DWS	FC	AgL	AgL	
CG	Cataract Creek	Santa Fe Reservoir to Williams WWTP outfall at 35°15'40"/112°10'40"		A&Wc				FBC			FC	AgL	AgL	
CG	Cataract Creek (EDW)	Williams WWTP outfall to 1 km downstream					A&Wedw		PBC					
CG	Cataract Creek	Red Lake Wash to Havasupai Reservation at 33°56'52"/112°30'38.3"				A&We			PBC					AgL
CG	Cataract Lake	35°15'05"/112°12'58"	Igneous	A&Wc				FBC		DWS	FC			AgL
CG	Chuar Creek	Headwaters to confluence with unnamed tributary at 36°11'36"/111°52'17"		A&Wc				FBC			FC			
CG	Chuar Creek	Below unnamed tributary at 36°11'36.4"/111°52'17" to confluence with the Colorado River at 36°08'20.4"/111°48'58.7"			A&Ww			FBC			FC			
CG	City Reservoir	35°13'57"/112°11'23"	Igneous	A&Wc				FBC		DWS	FC			
CG	Clear Creek	Headwaters to confluence with unnamed tributary at 36°09'12"/111°58'25"		A&Wc				FBC			FC			
CG	Clear Creek	Below confluence with unnamed tributary to confluence with Colorado River at 36°04'55"/112°02'09.6"			A&Ww			FBC			FC			
CG	Coconino Wash (EDW)	South Grand Canyon Sanitary District Tusayan WRF outfall at 35°58'39"/112°08'25" to 1 km downstream at 35°58'36"/112°08'54"					A&Wedw		PBC					
CG	Colorado River	Lake Powell to Lake Mead		A&Wc				FBC		DWS	FC	AgL	AgL	
CG	Cottonwood Creek	Headwaters to confluence with unnamed tributary at 35°20'45.5"/113°35'31"		A&Wc				FBC			FC			AgL
CG	Cottonwood Creek	Below confluence with unnamed tributary to confluence with Colorado River at 35°22'05"/113°40'04.8"			A&Ww			FBC			FC			AgL
CG	Crystal Creek	Headwaters to confluence with unnamed tributary at 36°13'42"/112°11'48"		A&Wc				FBC			FC			
CG	Crystal Creek	Below confluence with unnamed tributary to Colorado River at 36°08'06"/112°14'34.8"			A&Ww			FBC			FC			
CG	Deer Creek	Headwaters to confluence with unnamed tributary at 36°26'16"/112°28'15.5"		A&Wc				FBC			FC			
CG	Deer Creek	Below confluence with unnamed tributary to confluence with Colorado River at 36°23'20"/112°30'28.8"			A&Ww			FBC			FC			
CG	Detrital Wash	Headwaters to Lake Mead at 36°02'20"/114°27'47"				A&We			PBC					
CG	Dogtown Reservoir	35°12'40"/112°07'46"	Igneous	A&Wc				FBC		DWS	FC	AgL	AgL	
CG	Dragon Creek	Headwaters to confluence with Milk Creek at 36°12'25"/112°09'33"		A&Wc				FBC			FC			
CG	Dragon Creek	Below confluence with Milk Creek to confluence with Crystal Creek at 36°10'12"/112°12'10.8"			A&Ww			FBC			FC			
CG	Garden Creek	Headwaters to confluence with Pipe Creek at 36°05'35"/112°06'40"			A&Ww			FBC			FC			
CG	Gonzalez Lake	35°15'26"/112°12'07"	Shallow		A&Ww			FBC			FC	AgL	AgL	
CG	Grand Wash	Headwaters to Lake Mead at 36°15'29"/114°00'18"				A&We			PBC					
CG	Grapevine Creek	Headwaters to the Colorado River at 36°03'29"/112°00'00"			A&Ww			FBC			FC			
CG	Grapevine Wash	Headwaters to Lake Mead at 36°06'29"/114°00'07"				A&We			PBC					
CG	Hakatai Canyon Creek	Headwaters to the Colorado River at 36°14'42"/112°22'59"			A&Ww			FBC			FC			
CG	Hance Creek	Headwaters to the Colorado River at 36°02'46"/111°57'07"			A&Ww			FBC			FC			
CG	Havasupai Canyon Creek	From the Havasupai Indian Reservation; boundary to confluence with the Colorado River at 36°18'29"/112°45'43"			A&Ww			FBC			FC			
CG	Hermit Creek	Headwaters to Hermit Pack Trail crossing at 36°03'23"/112°13'25"		A&Wc				FBC			FC			
CG	Hermit Creek	Below Hermit Pack Trail crossing to confluence with the Colorado River at 36°06'00"/112°32'04"			A&Ww			FBC			FC			
CG	Horn Creek	Headwaters to confluence with the Colorado River at 36°05'56"/112°07'59"			A&Ww			FBC			FC			
CG	Hualapai Wash	Headwaters to Lake Mead at 36°00'40"/114°07'37"				A&We			PBC					
CG	Jacob Lake	36°42'26"/112°13'48"	Sedimentary	A&Wc				FBC			FC			
CG	Kaibab Lake	35°17'04"/112°09'17"	Igneous	A&Wc				FBC		DWS	FC	AgL	AgL	
CG	Kanab Creek	Headwaters to confluence with the Colorado River at 36°23'31"/112°37'44"			A&Ww			FBC		DWS	FC			AgL

Watershed	Surface Waters	Segment Description and Location (Latitude and Longitudes are in NAD 27)	Lake Category	Aquatic and Wildlife				Human Health				Agricultural	
				A&Wc	A&Ww	A&We	A&Wedw	FBC	PBC	DWS	FC	AgI	AgL
CG	Kwagunt Creek	Headwaters to confluence with unnamed tributary at 36°13'29"/111°55'24"		A&Wc				FBC			FC		
CG	Kwagunt Creek	Below confluence with unnamed tributary to confluence with the Colorado River at 36°15'47"/111°49'40.8"			A&Ww			FBC			FC		
CG	Lake Mead	36°01'00"/114°44'15"	Deep	A&Wc				FBC		DWS	FC	AgI	AgL
CG	Lake Powell	36°57'00"/111°29'15"	Deep	A&Wc				FBC		DWS	FC	AgI	AgL
CG	Lonetree Canyon Creek	Headwaters to the Colorado River at 36°04'48"/112°01'52"			A&Ww			FBC			FC		
CG	Matkatamiba Creek	Below Havasupai Indian Reservation; to confluence with the Colorado River at 36°20'38"/112°40'19"			A&Ww			FBC			FC		
CG	Monument Creek	Headwaters to the Colorado River at 36°05'53"/112°10'55"			A&Ww			FBC			FC		
CG	Nankoweap Creek	Headwaters to confluence with unnamed tributary at 36°15'30"/111°57'23"		A&Wc				FBC			FC		
CG	Nankoweap Creek	Below confluence with unnamed tributary to Colorado River at 36°18'25"/111°51'28.8"			A&Ww			FBC			FC		
CG	National Canyon Creek	Portion of the creek that flows into the Colorado River at 36°15'25"/112°53'34.8" that is not located on the Hualapai Indian Reservation			A&Ww			FBC			FC		
CG	North Canyon Creek	Headwaters to confluence with unnamed tributary at 36°33'57"/111°55'39"		A&Wc				FBC			FC		
CG	North Canyon Creek	Below confluence with unnamed tributary to Colorado River at 36°37'48"/111°45'46.8"			A&Ww			FBC			FC		
CG	Olo Creek	Headwaters to the Colorado River at 36°22'16"/112°38'56"			A&Ww			FBC			FC		
CG	Parashant Canyon	Headwaters to confluence with unnamed tributary at 36°21'26"/113°28'10"		A&Wc				FBC			FC		
CG	Parashant Canyon	Below confluence with unnamed tributary to the Colorado River			A&Ww			FBC			FC		
CG	Paria River	Utah border to the Colorado River at 36°51'29"/111°36'04"			A&Ww			FBC			FC		
CG	Phantom Creek	Headwaters to confluence with unnamed tributary at 36°10'04"/112°07'50"		A&Wc				FBC			FC		
CG	Phantom Creek	Below confluence with unnamed tributary to Colorado River at 36°06'58"/112°05'09.6"			A&Ww			FBC			FC		
CG	Pipe Creek	Headwaters to the Colorado River at 36°05'56"/112°06'36"			A&Ww			FBC			FC		
CG	Red Canyon Creek	Headwaters to the Colorado River at 36°02'42"/111°55'08"			A&Ww			FBC			FC		
CG	Red Lake	35°40'00"/114°03'45"			A&Ww			FBC			FC		AgL
CG	Redondo Lake	32°44'32"/114°29'02"	Shallow		A&Ww			FBC			FC		
CG	Roaring Springs	Headwaters of Roaring Springs Creek at 36°11'35"/112°01'55.2"		A&Wc				FBC		DWS	FC		
CG	Roaring Springs Canyon	Headwaters to Bright Angel Creek at 36°11'35"/112°01'55"		A&Wc				FBC			FC		
CG	Rock Canyon	Tributary to Truxton Wash at 35°26'56"/113°36'29"				A&We			PBC				
CG	Royal Arch Creek	Tributary to the Colorado River at 36°11'53"/112°26'56"			A&Ww			FBC			FC		
CG	Ruby Canyon Creek	Tributary to the Colorado River at 36°11'24"/112°18'54"			A&Ww			FBC			FC		
CG	Russell Tank	34°52'22"/111°52'44"		A&Wc				FBC			FC		AgL
CG	Saddle Canyon Creek	Headwaters to confluence with unnamed tributary at 36°21'35.5"/112°22'46"		A&Wc				FBC			FC		
CG	Saddle Canyon Creek	Below confluence with unnamed tributary to Colorado River at 36°22'52"/112°23'16.8"			A&Ww			FBC			FC		
CG	Santa Fe Reservoir	35°14'26"/112°11'04"	Igneous	A&Wc				FBC		DWS	FC		
CG	Sapphire Canyon Creek	Headwaters to the Colorado River at 36°08'49"/112°17'28"			A&Ww			FBC			FC		
CG	Serpentine Canyon Creek	Headwaters to the Colorado River at 36°12'22"/112°19'37"			A&Ww			FBC			FC		
CG	Shinumo Creek	Headwaters to confluence with unnamed tributary at 36°18'21"/112°18'03"		A&Wc				FBC			FC		
CG	Shinumo Creek	Below confluence with unnamed tributary to the Colorado River at 36°14'13"/112°20'52.8"			A&Ww			FBC			FC		
CG	Short Creek	Tributary to the Virgin River at 36°58'23"/113°16'08"				A&We			PBC				
CG	Slate Creek	Headwaters to the Colorado River at 36°08'06"/112°14'42"			A&Ww			FBC			FC		
CG	Spring Canyon Creek	Headwaters to the Colorado River at 36°01'08"/113°21'00"			A&Ww			FBC			FC		
CG	Stone Creek	Headwaters to the Colorado River at 36°20'49"/112°27'14"			A&Ww			FBC			FC		
CG	Tapeats Creek	Headwaters to the Colorado River at 36°22'16"/112°28'05"		A&Wc				FBC			FC		

Department of Environmental Quality – Water Quality Standards

Watershed	Surface Waters	Segment Description and Location (Latitude and Longitudes are in NAD 27)	Lake Category	Aquatic and Wildlife				Human Health				Agricultural	
				A&Wc	A&Ww	A&We	A&Wedw	FBC	PBC	DWS	FC	AgI	AgL
CG	Thunder River	Tributary to Tapeats Creek at 36°23'31"/112°27'00"		A&Wc				FBC			FC		
CG	Trail Canyon Creek	Headwaters to the Colorado River at 35°50'20"/113°19'37"			A&Ww			FBC			FC		
CG	Transept Canyon	Headwaters to North Rim WWTP outfall at 36°12'20"/112°03'35"				A&We			PBC				
CG	Transept Canyon (EDW)	North Rim WWTP outfall to 1 km downstream					A&Wedw		PBC				
CG	Transept Canyon	1 km downstream of the North Rim WWTP outfall to Bright Angel Creek				A&We			PBC				
CG	Travertine Canyon Creek	Tributary to the Colorado River at 36°06'11"/112°13'05"			A&Ww			FBC			FC		
CG	Truxton Wash	Tributary to Red Lake at 35°37'23"/114°03'00"				A&We			PBC				
CG	Turquoise Canyon Creek	Tributary to the Colorado River at 36°09'14"/112°18'07"			A&Ww			FBC			FC		
CG	Unkar Creek	Below confluence with unnamed tributary to confluence with Colorado River at 36°04'48"/111°52'22.8"			A&Ww			FBC			FC		
CG	Unnamed Wash (EDW)	Grand Canyon NP Desert View WWTP outfall to Cedar Canyon					A&Wedw		PBC				
CG	Unnamed Wash (EDW)	Valle Airpark WRF outfall at 35°38'34"/112°09'22" to confluence with Spring Valley Wash at 35°38'29"/112°10'47"					A&Wedw		PBC				
CG	Vasey's Paradise	A spring at 36°26'49"/111°50'46"		A&Wc				FBC			FC		
CG	Virgin River	Tributary to the Colorado River at 36°47'28"/114°06'11"			A&Ww			FBC			FC	AgI	AgL
CG	Vishnu Creek	Tributary to the Colorado River at 36°03'18"/111°59'42"			A&Ww			FBC			FC		
CG	Warm Springs Creek	Tributary to the Colorado River at 36°11'49"/113°04'55"			A&Ww			FBC			FC		
CG	West Cataract Creek	Tributary to Cataract Creek at 35°15'40"/112°11'38"		A&Wc				FBC			FC		AgL
CG	White Creek	Headwaters to confluence with unnamed tributary at 36°18'42"/112°21'03"		A&Wc				FBC			FC		
CG	White Creek	Below confluence with unnamed tributary to the Colorado River at 36°15'22"/112°19'30"			A&Ww			FBC			FC		
CG	Wright Canyon Creek	Headwaters to confluence with unnamed tributary at 35°20'54"/113°30'35"		A&Wc				FBC			FC		AgL
CG	Wright Canyon Creek	Below confluence with unnamed tributary to confluence with Truxton Wash			A&Ww			FBC			FC		AgL
CL	A-10 Backwater	33°31'38"/114°33'19"	Shallow		A&Ww			FBC			FC		
CL	A-7 Backwater	33°34'39"/114°39'42"	Shallow		A&Ww			FBC			FC		
CL	Adobe Lake	33°02'39"/114°39'19"	Shallow		A&Ww			FBC			FC		
CL	Cibola Lake	33°31'38"/114°33'19"	Shallow		A&Ww			FBC			FC		
CL	Clear Lake	33°01'57"/114°31'26"	Shallow		A&Ww			FBC			FC		
CL	Columbus Wash	Tributary to the Gila River at 33°00'25"/113°16'08"				A&We			PBC				
CL	Colorado River	Lake Mead to Topock Marsh		A&Wc				FBC		DWS	FC	AgI	AgL
CL	Colorado River	Topock Marsh to Morelos Dam			A&Ww			FBC		DWS	FC	AgI	AgL
CL	Gila River	Painted Rock Dam to the Colorado River at 32°43'12"/114°33'14"			A&Ww			FBC			FC	AgI	AgL
CL	Holy Moses Wash	Headwaters to Kingman WWTP outfall at 35°10'30"/114°03'43"				A&We			PBC				
CL	Holy Moses Wash (EDW)	Kingman WWTP outfall to 3 km downstream					A&Wedw		PBC				
CL	Holy Moses Wash	3 km downstream of Kingman WWTP outfall to confluence with Sawmill Wash at 35°09'43"/114°04'20"				A&We			PBC				
CL	Hunter's Hole Backwater	32°31'15"/114°48'03"	Shallow		A&Ww			FBC			FC		AgL
CL	Imperial Reservoir	32°53'04"/114°27'40"	Shallow		A&Ww			FBC		DWS	FC	AgI	AgL
CL	Island Lake	33°01'52"/114°35'07"	Shallow		A&Ww			FBC			FC		
CL	Laguna Reservoir	32°51'15"/114°28'38"	Shallow		A&Ww			FBC		DWS	FC	AgI	AgL
CL	Lake Havasu	34°18'15"/114°08'15"	Deep		A&Ww			FBC		DWS	FC	AgI	AgL
CL	Lake Mohave	35°11'45"/114°34'00"	Deep	A&Wc				FBC		DWS	FC	AgI	AgL
CL	Martinez Lake	32°58'52"/114°28'23"	Shallow		A&Ww			FBC			FC	AgI	AgL
CL	Mittry Lake	32°49'11"/114°27'41"	Shallow		A&Ww			FBC			FC		
CL	Mohave Wash	Headwaters to Lake Havasu at 33°28'55"/114°35'56"				A&We			PBC				
CL	Nortons Lake	33°02'35"/114°37'58"	Shallow		A&Ww			FBC			FC		
CL	Painted Rock (Borrow Pit) Lake	33°05'00"/113°01'20"	Sedimentary		A&Ww			FBC			FC	AgI	AgL
CL	Pretty Water Lake	33°19'45"/114°42'15"	Shallow		A&Ww			FBC			FC		
CL	Quigley Ponds	32°43'00"/113°58'00"	Shallow		A&Ww			FBC			FC		

Department of Environmental Quality – Water Quality Standards

Watershed	Surface Waters	Segment Description and Location (Latitude and Longitudes are in NAD 27)	Lake Category	Aquatic and Wildlife				Human Health				Agricultural			
				A&Wc	A&Ww	A&We	A&Wedw	FBC	PBC	DWS	FC	AgI	AgL		
CL	Sacramento Wash	Tributary to Topock Marsh at 34°43'48"/114°29'13"				A&We					PBC				
CL	Sawmill Canyon	Headwaters to abandoned gaging station at 35°09'46.5"/113°57'51"				A&Ww				FBC			FC		AgL
CL	Sawmill Canyon	Below abandoned gaging station to confluence with Sacramento Wash at 35°09'43"/113°58'01.2"				A&We					PBC				AgL
CL	Topock Marsh	34°47'30"/114°31'00"	Shallow			A&Ww				FBC		DWS	FC	AgI	AgL
CL	Tyson Wash (EDW)	Town of Quartzsite WWTP outfall at 33°42'30"/114°13'14" to 1 km downstream at 33°42'30"/114°13'45"					A&Wedw				PBC				
CL	Wellton Canal	Wellton-Mohawk Irrigation District										DWS		AgI	AgL
CL	Wellton Ponds	32°42'15"/114°06'15"				A&Ww				FBC			FC		
CL	YPG Pond	32°50'22"/114°26'25"				A&Ww				FBC			FC		
CL	Yuma Area Canals	Above municipal water treatment plant intakes										DWS		AgI	AgL
CL	Yuma Area Canals	Below municipal water treatment plant intakes and all drains												AgI	AgL
LC	Als Lake	35°02'17"/111°25'13"	Igneous			A&Ww				FBC			FC		AgL
LC	Ashurst Lake	35°01'10"/111°24'09"	Igneous	A&Wc						FBC			FC	AgI	AgL
LC	Atcheson Reservoir	34°00'00"/109°20'41"	Igneous			A&Ww				FBC			FC	AgI	AgL
LC	Auger Creek	Tributary to Nutrioso Creek at 33°57'22"/109°12'58"				A&Wc				FBC			FC		AgL
LC	Barbershop Canyon Creek	Tributary to East Clear Creek at 34°33'00"/111°09'43"				A&Wc				FBC			FC		AgL
LC	Bear Canyon Creek	Tributary to General Springs Canyon at 34°32'18"/111°12'15"				A&Wc				FBC			FC		AgL
LC	Bear Canyon Creek	Tributary to Willow Creek at 34°27'29"/111°00'00"				A&Wc				FBC			FC		AgL
LC	Bear Canyon Lake	34°24'10"/111°00'09"	Sedimentary	A&Wc						FBC			FC	AgI	AgL
LC	Becker Lake	34°09'16"/109°18'18"	Shallow	A&Wc						FBC			FC		AgL
LC	Billy Creek	Tributary to Show Low Creek at 34°12'25"/110°00'00"				A&Wc				FBC			FC		AgL
LC	Black Canyon Creek	Tributary to Chevelon Creek at 34°47'38"/110°36'22"				A&Wc				FBC			FC	AgI	AgL
LC	Black Canyon Lake	34°19'50"/110°41'59"	Sedimentary	A&Wc						FBC		DWS	FC	AgI	AgL
LC	Blue Ridge Reservoir	34°33'15"/111°11'01"	Deep	A&Wc						FBC			FC	AgI	AgL
LC	Boot Lake	34°58'53"/111°20'00"	Igneous	A&Wc						FBC			FC		AgL
LC	Bow and Arrow Wash (EDW)	Estates at Pine Canyon WWTP outfall #1 at 35°09'31"/111°38'24" to confluence with Rio de Flag at 35°10'35"/111°36'42"					A&Wedw				PBC				
LC	Buck Springs Canyon Creek	Tributary to Leonard Canyon Creek at 34°28'52"/111°05'24"				A&Wc				FBC			FC		AgL
LC	Bunch Reservoir	34°02'12"/109°26'45"	Igneous	A&Wc						FBC			FC	AgI	AgL
LC	Camillo Tank	34°55'03"/111°22'41"	Igneous			A&Ww				FBC			FC		AgL
LC	Carnero Lake	34°06'57"/109°31'39"	Shallow	A&Wc						FBC			FC		AgL
LC	Chevelon Canyon Lake	34°30'39"/110°49'28"	Sedimentary	A&Wc						FBC			FC	AgI	AgL
LC	Chevelon Creek	Tributary to the Little Colorado River at 34°57'04"/110°31'30"				A&Wc				FBC			FC	AgI	AgL
LC	Chevelon Creek, West Fork	Tributary to Chevelon Creek at 34°36'58"/110°46'05"				A&Wc				FBC			FC		AgL
LC	Chilson Tank	34°51'46"/111°22'52"	Igneous			A&Ww				FBC			FC		AgL
LC	Clear Creek	Tributary to the Little Colorado River at 34°59'13"/110°38'17"				A&Wc				FBC		DWS	FC		AgL
LC	Clear Creek Reservoir	34°58'10"/110°38'33"	Shallow	A&Wc						FBC		DWS	FC	AgI	AgL
LC	Coconino Reservoir	35°00'16"/111°23'52"	Igneous	A&Wc						FBC			FC	AgI	AgL
LC	Colter Creek	Tributary to Nutrioso Creek at 33°58'19"/109°12'29"				A&Wc				FBC			FC		AgL
LC	Colter Reservoir	33°56'40"/109°28'50"	Shallow	A&Wc						FBC			FC		AgL
LC	Concho Creek	Tributary to Carrizo Wash at 34°36'25"/109°33'54"				A&Wc				FBC			FC		AgL
LC	Concho Lake	34°26'36"/109°37'40"	Shallow	A&Wc						FBC			FC	AgI	AgL
LC	Cow Lake	34°53'19"/111°18'49"	Igneous			A&Ww				FBC			FC		AgL
LC	Coyote Creek	Tributary to the Little Colorado River at 34°18'22"/109°20'53"				A&Wc				FBC			FC	AgI	AgL
LC	Crisis Lake (Snake Tank #2)	34°47'51"/111°17'01"				A&Ww				FBC			FC		AgL
LC	Dane Canyon Creek	Tributary to Barbershop Canyon Creek at 34°30'29"/111°09'07"				A&Wc				FBC			FC		AgL
LC	Daves Tank	34°44'23"/111°17'08"				A&Ww				FBC			FC		AgL
LC	Deep Lake	35°03'30"/111°24'55"	Igneous			A&Ww				FBC			FC		AgL
LC	Dry Lake (EDW)	34°37'52"/110°23'40"	Igneous				A&Wedw				PBC				

Department of Environmental Quality – Water Quality Standards

Watershed	Surface Waters	Segment Description and Location (Latitude and Longitudes are in NAD 27)	Lake Category	Aquatic and Wildlife				Human Health			Agricultural		
				A&Wc	A&Ww	A&We	A&Wedw	FBC	PBC	DWS	FC	AgI	AgL
LC	Ducksnest Lake	34°59'15"/111°23'53"			A&Ww			FBC			FC		AgL
LC	East Clear Creek	Tributary to Clear Creek at 34°38'31"/110°59'49"		A&Wc				FBC			FC	AgI	AgL
LC	Ellis Wiltbank Reservoir	34°05'25"/109°28'24"	Igneous		A&Ww			FBC			FC	AgI	AgL
LC	Fish Creek	Tributary to the Little Colorado River at 34°04'05"/109°26'49"		A&Wc				FBC			FC		AgL
LC	Fool's Hollow Lake	34°16'14"/110°04'15"	Igneous	A&Wc				FBC			FC		AgL
LC	General Springs Canyon Creek	Tributary to East Clear Creek at 34°32'17"/111°12'18"		A&Wc				FBC			FC		AgL
LC	Geneva Reservoir	34°01'44"/109°31'44"	Igneous		A&Ww			FBC			FC		AgL
LC	Hall Creek	Tributary to the Little Colorado River at 34°03'58"/109°27'07"		A&Wc				FBC			FC	AgI	AgL
LC	Hart Canyon Creek	Tributary to Willow Creek at 34°30'40"/110°59'28"		A&Wc				FBC			FC		AgL
LC	Hay Lake	34°00'11"/109°25'55"	Igneous	A&Wc				FBC			FC		AgL
LC	Hog Wallow Lake	33°58'57"/109°25'38"	Igneous	A&Wc				FBC			FC	AgI	AgL
LC	Horse Lake	35°03'53"/111°27'51"			A&Ww			FBC			FC		AgL
LC	Huffer Tank	34°27'45"/111°23'09"			A&Ww			FBC			FC		AgL
LC	Hulsey Creek	Tributary to Nutrioso Creek at 33°56'28"/109°11'28"		A&Wc				FBC			FC		AgL
LC	Hulsey Lake	33°55'57"/109°09'33"	Sedimentary	A&Wc				FBC			FC		AgL
LC	Indian Lake	35°00'38"/111°22'37"			A&Ww			FBC			FC		AgL
LC	Jack's Canyon Creek	Tributary to the Little Colorado River at 35°00'07"/110°39'07"		A&Wc				FBC			FC	AgI	AgL
LC	Jarvis Lake	33°58'59"/109°12'33"	Sedimentary		A&Ww			FBC			FC		AgL
LC	Kinnikinick Lake	34°53'52"/111°18'20"	Igneous	A&Wc				FBC			FC		AgL
LC	Knoll Lake	34°25'38"/111°05'10"	Sedimentary	A&Wc				FBC			FC		AgL
LC	Lake Humphreys (EDW)	35°11'51"/111°35'16"				A&Wedw			PBC				
LC	Lake Mary, Lower	35°06'22"/111°34'20"	Igneous	A&Wc				FBC		DWS	FC		AgL
LC	Lake Mary, Upper	35°04'45"/111°31'56"	Igneous	A&Wc				FBC		DWS	FC		AgL
LC	Lake of the Woods	34°09'39"/109°58'45"	Igneous	A&Wc				FBC			FC	AgI	AgL
LC	Lee Valley Creek (OAW)	Headwaters to Lee Valley Reservoir		A&Wc				FBC			FC		
LC	Lee Valley Creek	From Lee Valley Reservoir to the East Fork of the Little Colorado River at 33°56'35"/109°29'06"		A&Wc				FBC			FC		AgL
LC	Lee Valley Reservoir	33°56'30"/109°30'00"	Igneous	A&Wc				FBC			FC	AgI	AgL
LC	Leonard Canyon Creek	Tributary to Clear Creek at 34°37'26"/111°02'20"		A&Wc				FBC			FC		AgL
LC	Leonard Canyon Creek, East Fork	Tributary to Leonard Canyon Creek at 34°25'52"/111°05'06"		A&Wc				FBC			FC		AgL
LC	Leonard Canyon Creek, Middle Fork	Tributary to Leonard Canyon, West Fork at 34°26'17"/111°06'47"		A&Wc				FBC			FC		AgL
LC	Leonard Canyon Creek, West Fork	Tributary to Leonard Canyon, East Fork at 34°28'01"/111°05'28"		A&Wc				FBC			FC		AgL
LC	Lily Creek	Tributary to Coyote Creek at 33°59'46"/109°03'58"		A&Wc				FBC			FC		AgL
LC	Little Colorado River	Headwaters to Lyman Reservoir		A&Wc				FBC			FC	AgI	AgL
LC	Little Colorado River	Below Lyman Reservoir, to confluence with the Puerco River at 34°53'20"/110°07'41"		A&Wc				FBC		DWS	FC	AgI	AgL
LC	Little Colorado River	Below confluence with Puerco River to the boundary of the Navajo Nation			A&Ww			FBC		DWS	FC	AgI	AgL
LC	Little Colorado River, East Fork	Tributary to the Little Colorado River at 34°00'14"/109°27'22"		A&Wc				FBC			FC		AgL
LC	Little Colorado River, South Fork	Tributary to the Little Colorado River at 34°05'20"/109°24'58"		A&Wc				FBC			FC		AgL
LC	Little Colorado River, West Fork (OAW)	Headwaters to Government Springs at 33°59'33"/109°27'52"		A&Wc				FBC			FC		
LC	Little Colorado River, West Fork	Below Government Springs to the Little Colorado River at 34°00'14"/109°27'21.6"		A&Wc				FBC			FC		AgL
LC	Little George Reservoir	34°00'37"/109°19'15"	Igneous		A&Ww			FBC			FC	AgI	
LC	Little Mormon Lake	34°17'00"/109°58'03"	Igneous		A&Ww			FBC			FC	AgI	AgL

Department of Environmental Quality – Water Quality Standards

Watershed	Surface Waters	Segment Description and Location (Latitude and Longitudes are in NAD 27)	Lake Category	Aquatic and Wildlife				Human Health				Agricultural	
				A&Wc	A&Ww	A&We	A&Wedw	FBC	PBC	DWS	FC	Agl	AgL
LC	Little Ortega Lake	34°22'45"/109°40'00"	Igneous	A&Wc				FBC			FC		
LC	Long Lake, Lower	34°46'45"/111°12'00"	Igneous	A&Wc				FBC			FC	Agl	AgL
LC	Long Lake, Upper	35°00'00"/111°21'00"	Igneous	A&Wc				FBC			FC		AgL
LC	Long Tom Tank	34°20'37"/110°49'20"		A&Wc				FBC			FC		AgL
LC	Lower Walnut Canyon Lake (EDW)	35°12'04"/111°34'07"					A&Wedw		PBC				
LC	Lyman Reservoir	34°21'30"/109°21'30"	Deep	A&Wc				FBC			FC	Agl	AgL
LC	Mamie Creek	Tributary to Coyote Creek at 33°59'24"/109°03'50"		A&Wc				FBC			FC		AgL
LC	Marshall Lake	35°07'10"/111°32'01"	Igneous	A&Wc				FBC			FC		AgL
LC	McKay Reservoir	34°01'27"/110°29'07"		A&Wc				FBC			FC	Agl	AgL
LC	Merritt Draw Creek	Tributary to Barbershop Canyon Creek at 34°29'38"/111°09'54"		A&Wc				FBC			FC		AgL
LC	Mexican Hay Lake	34°01'57"/109°21'25"	Igneous	A&Wc				FBC			FC	Agl	AgL
LC	Milk Creek	Tributary to Hulsey Creek at 33°56'31"/109°11'17"		A&Wc				FBC			FC		AgL
LC	Miller Canyon Creek	Tributary to East Clear Creek at 34°33'00"/111°14'17"		A&Wc				FBC			FC		AgL
LC	Miller Canyon Creek, East Fork	Tributary to Miller Canyon Creek at 34°30'18"/111°14'53"		A&Wc				FBC			FC		AgL
LC	Mineral Creek	Tributary to Little Ortega Lake at 34°22'52"/109°39'50"		A&Wc				FBC			FC	Agl	AgL
LC	Mormon Lake	34°56'40"/111°27'10"	Shallow	A&Wc				FBC		DWS	FC	Agl	AgL
LC	Morton Lake	34°53'36"/111°17'39"	Igneous	A&Wc				FBC			FC		AgL
LC	Mud Lake	34°55'24"/111°21'18"	Shallow		A&Ww			FBC			FC		AgL
LC	Ned Lake (EDW)	32°17'18"/110°03'20"	EDW				A&Wedw		PBC				
LC	Nelson Reservoir	34°03'12"/109°11'18"	Sedimentary	A&Wc				FBC			FC	Agl	AgL
LC	Norton Reservoir	34°03'57"/109°31'21"	Igneous		A&Ww			FBC			FC		AgL
LC	Nutrisio Creek	Tributary to the Little Colorado River at 34°09'04"/109°17'35"		A&Wc				FBC			FC	Agl	AgL
LC	Paddy Creek	Tributary to Nutrisio Creek at 33°54'47"/109°10'16"		A&Wc				FBC			FC		AgL
LC	Phoenix Park Wash	Tributary to Dry Lake at 34°37'30"/110°22'12"				A&We			PBC				
LC	Pierce Seep	34°23'35"/110°31'22"		A&Wc					PBC				
LC	Pine Tank	34°46'49"/111°17'17"	Igneous		A&Ww			FBC			FC		AgL
LC	Pintail Lake (EDW)	34°18'06"/110°01'17"	EDW				A&Wedw		PBC				
LC	Pool Corral Lake	33°58'16"/109°24'53"	Igneous		A&Ww			FBC			FC	Agl	AgL
LC	Porter Creek	Tributary to Show Low Creek at 34°10'16"/109°58'48"		A&Wc				FBC			FC		AgL
LC	Potato Lake	34°27'44"/111°20'42"	Igneous	A&Wc				FBC			FC		AgL
LC	Pratt Lake	34°01'31"/109°04'16"	Sedimentary	A&Wc				FBC			FC		
LC	Puerco River	Tributary to the Little Colorado River at 34°53'20"/110°07'41"			A&Ww			FBC		DWS	FC	Agl	AgL
LC	Puerco River (EDW)	Sanders Unified School District WWTP outfall at 35°12'52"/109°19'40" to 0.5 km downstream at 35°12'39"/109°19'52"					A&Wedw		PBC				
LC	Rainbow Lake	34°09'03"/109°59'01"	Shallow Igneous	A&Wc				FBC			FC	Agl	AgL
LC	Reagan Reservoir	34°02'09"/109°08'43"	Igneous		A&Ww			FBC			FC		AgL
LC	Rio de Flag	Headwaters to Flagstaff WWTP outfall at 35°12'21"/111°39'17"				A&We			PBC				
LC	Rio de Flag (EDW)	Flagstaff WWTP outfall at 35°12'21"/111°39'17" to the confluence with San Francisco Wash					A&Wedw		PBC				
LC	River Reservoir	34°02'01"/109°26'07"	Igneous	A&Wc				FBC			FC	Agl	AgL
LC	Rogers Reservoir	33°58'30"/109°16'18"	Igneous		A&Ww			FBC			FC		AgL
LC	Rudd Creek	Tributary to Nutrisio Creek at 34°04'12"/109°11'56"		A&Wc				FBC			FC		AgL
LC	Russel Reservoir	33°59'29"/109°20'00"	Igneous		A&Ww			FBC			FC	Agl	AgL
LC	Salt House Lake	33°57'06"/109°20'12"	Igneous		A&Ww			FBC			FC		AgL
LC	San Salvador Reservoir	33°58'51"/109°19'51"	Igneous	A&Wc				FBC			FC	Agl	AgL
LC	Scott Reservoir	34°10'27"/109°57'27"	Igneous	A&Wc				FBC			FC	Agl	AgL
LC	Show Low Creek	Tributary to Silver Creek at 34°25'26"/110°04'05"		A&Wc				FBC			FC	Agl	AgL
LC	Show Low Lake	34°11'25"/109°59'55"	Igneous	A&Wc				FBC			FC	Agl	AgL
LC	Silver Creek	Tributary to the Little Colorado River at 34°44'24"/110°02'17"		A&Wc				FBC			FC	Agl	AgL

Department of Environmental Quality – Water Quality Standards

Watershed	Surface Waters	Segment Description and Location (Latitude and Longitudes are in NAD 27)	Lake Category	Aquatic and Wildlife				Human Health				Agricultural	
				A&Wc	A&Ww	A&We	A&Wedw	FBC	PBC	DWS	FC	AgI	AgL
LC	Slade Reservoir	33°59'50"/109°20'00"	Igneous		A&Ww			FBC			FC	AgI	AgL
LC	Soldiers Annex Lake	34°47'13"/111°13'48"	Igneous	A&Wc				FBC			FC	AgI	AgL
LC	Soldiers Lake	34°47'49"/110°13'59"	Igneous	A&Wc				FBC			FC	AgI	AgL
LC	Spaulding Tank	34°30'17"/111°02'03"			A&Ww			FBC			FC		AgL
LC	Sponseller Lake	34°14'10"/109°50'42"	Igneous	A&Wc				FBC			FC		AgL
LC	St Johns Reservoir (Little Reservoir)	34°29'14"/109°21'57"	Igneous		A&Ww			FBC			FC	AgI	AgL
LC	Telephone Lake (EDW)	34°17'35"/110°02'39"	EDW				A&Wedw		PBC				
LC	Tremaine Lake	34°46'00"/111°14'10"	Igneous	A&Wc				FBC			FC		AgL
LC	Tunnel Reservoir	34°01'51"/109°26'32"	Igneous	A&Wc				FBC			FC	AgI	AgL
LC	Turkey Draw (EDW)	High Country Pines II WWTP outfall at 34°25'35"/110°38'13" to confluence of Turkey Draw with Black Canyon Creek at 34°25'20"/110°36'36"					A&Wedw		PBC				
LC	Unnamed Wash (EDW)	Bison Ranch WWTP outfall at 34°23'31"/110°31'41" to Pierce Seep at 34°23'35"/110°31'22"					A&Wedw		PBC				
LC	Unnamed Wash (EDW)	Black Mesa Ranger Station WWTP outfall at 34°23'32"/110°53'32" to confluence of Oklahoma Flat Draw with Pierce Wash at 34°26'47"/110°29'25"					A&Wedw		PBC				
LC	Unnamed Wash (EDW)	Estates at Pine Canyon WWTP outfall at 35°09'17"/111°38'22" to confluence of unnamed wash with Bow Wash and Arrow Wash at 35°09'51"/111°37'29"					A&Wedw		PBC				
LC	Unnamed Wash (EDW)	Estates at Pine Canyon WWTP outfall #3 at 35°09'45"/111°38'48" to confluence with Rio de Flag at 35°10'05"/111°38'37"					A&Wedw		PBC				
LC	Vail Lake	35°05'24"/111°30'42"	Igneous	A&Wc				FBC			FC		AgL
LC	Walnut Creek	Tributary to Billy Creek at 34°09'50"/109°58'48"		A&Wc				FBC			FC		AgL
LC	Water Canyon Creek	Tributary to the Little Colorado River at 34°06'47"/109°18'43"		A&Wc				FBC			FC		AgL
LC	Water Canyon Reservoir	34°00'15"/109°20'05"	Igneous		A&Ww			FBC			FC	AgI	AgL
LC	Whale Lake (EDW)	35°12'32"/111°34'42"	EDW				A&Wedw		PBC				
LC	Whipple Lake	34°16'47"/109°58'28"	Igneous		A&Ww			FBC			FC		AgL
LC	White Mountain Lake	34°21'54"/109°59'38"	Igneous	A&Wc				FBC			FC	AgI	AgL
LC	White Mountain Reservoir	34°00'15"/109°30'48"	Igneous	A&Wc				FBC			FC	AgI	AgL
LC	Willow Creek	Tributary to Clear Creek at 34°38'31"/110°59'49"		A&Wc				FBC			FC		AgL
LC	Willow Springs Canyon Creek	Tributary to Chevelon Creek at 34°21'32"/110°53'20"		A&Wc				FBC			FC		AgL
LC	Willow Springs Lake	34°18'45"/110°52'34"	Sedimentary	A&Wc				FBC			FC	AgI	AgL
LC	Woodland Reservoir	34°07'36"/109°57'06"	Igneous	A&Wc				FBC			FC	AgI	AgL
LC	Woods Canyon Creek	Tributary to Chevelon Creek at 34°21'32"/110°53'20"		A&Wc				FBC			FC		AgL
LC	Woods Canyon Lake	34°20'05"/110°56'35"	Sedimentary	A&Wc				FBC			FC	AgI	AgL
LC	Zuni River	Tributary to the Little Colorado River at 34°38'42"/109°40'26"		A&Wc				FBC			FC	AgI	AgL
MG	Agua Fria River	Headwaters to confluence with unnamed EDW wash at 34°35'43"/112°16'29", receiving treated wastewater from the Prescott Valley WWTP				A&We			PBC				AgL
MG	Agua Fria River (EDW)	Below confluence with unnamed wash receiving treated wastewater from the Prescott Valley WWTP to State Route 169 at 34°31'43"/112°14'7.5"					A&Wedw		PBC				AgL
MG	Agua Fria River	State Route 169 to Lake Pleasant at 34°54'54.7"/112°14'7.5"			A&Ww			FBC		DWS	FC	AgI	AgL
MG	Agua Fria River	Below Lake Pleasant to the El Mirage WWTP at 33°34'36"/112°48'45"				A&We			PBC				AgL
MG	Agua Fria River (EDW)	El Mirage WWTP to 2 km downstream					A&Wedw		PBC				
MG	Agua Fria River	Below 2 km downstream of the El Mirage WWTP to Avondale WWTP outfall				A&We			PBC				
MG	Agua Fria River	Avondale WWTP outfall at 33°23'24"/112°21'50.4" to Gila River at 33°23'22"/112°21'48"					A&Wedw		PBC				
MG	Alvord Park Lake	Urban Lake: 35th Avenue & Baseline Road, Phoenix at 33°22'34"/112°08'11"	Urban		A&Ww				PBC		FC		

Department of Environmental Quality – Water Quality Standards

Watershed	Surface Waters	Segment Description and Location (Latitude and Longitudes are in NAD 27)	Lake Category	Aquatic and Wildlife				Human Health				Agricultural	
				A&Wc	A&Ww	A&We	A&Wedw	FBC	PBC	DWS	FC	AgI	AgL
MG	Andorra Wash (EDW)	Town of Cave Creek WWTP outfall #1 at 33°50'00"/111°56'32" to confluence with Cave Creek Wash at 33°49'54"/111°57'57.4"					A&Wedw		PBC				
MG	Antelope Creek	Tributary to Martinez Creek at 34°16'37"/112°08'46"			A&Ww			FBC			FC		AgL
MG	Arlington Canal	From Gila River at 33°20'54"/112°35'39" to Gila River at 33°13'44"/112°46'15"											AgL
MG	Ash Creek	Headwaters to confluence with Tex Canyon at 34°34'44"/112°07'18"			A&Wc			FBC			FC	AgI	AgL
MG	Ash Creek	Below confluence with Tex Canyon to Agua Fria at 34°19'34"/112°04'30"			A&Ww			FBC			FC	AgI	AgL
MG	Beehive Tank	32°52'36"/111°02'19"			A&Ww			FBC			FC		AgL
MG	Big Bug Creek	Headwaters to confluence with Eugene Gulch at 34°27'11"/112°18'28.5"			A&Wc			FBC			FC	AgI	AgL
MG	Big Bug Creek	Below confluence with Eugene Gulch to confluence with Agua Fria River at 34°18'54"/112°03'58"			A&Ww			FBC			FC	AgI	AgL
MG	Black Canyon Creek	Tributary to the Agua Fria River at 34°04'12"/112°09'29"			A&Ww			FBC			FC		AgL
MG	Blind Indian Creek	Tributary to the Hassayampa River at 34°12'40"/112°32'17"			A&Ww			FBC			FC		AgL
MG	Bonsall Park Lake	Urban Lake; 59th Avenue & Bethany Home Road, Phoenix at 33°31'23"/112°11'05"	Urban		A&Ww				PBC		FC		
MG	Canal Park Lake	Urban Lake; College Avenue & Curry Road, Tempe at 33°26'57"/111°56'14"	Urban		A&Ww				PBC		FC		
MG	Cave Creek	Headwaters to the Cave Creek Dam			A&Ww			FBC			FC		AgL
MG	Cave Creek	Cave Creek Dam to the Arizona Canal at 33°34'24"/112°06'25"				A&We			PBC				
MG	Centennial Wash	Tributary to the Gila River at 33°13'44"/112°46'16"				A&We			PBC				AgL
MG	Centennial Wash Ponds	33°55'10"/113°23'05"			A&Ww			FBC			FC		AgL
MG	Chaparral Park Lake	Urban Lake; Hayden Road & Chaparral Road, Scottsdale at 33°30'41"/111°54'25"	Urban		A&Ww				PBC		FC	AgI	
MG	Cortez Park Lake	Urban Lake; 35th Avenue & Dunlap, Glendale at 33°34'13"/112°07'51"	Urban		A&Ww				PBC		FC	AgI	
MG	Desert Breeze Lake	Urban Lake; Galaxy Drive, West Chandler at 33°18'47.5"/111°55'08"	Urban		A&Ww				PBC		FC		
MG	Devils Canyon	Tributary to Mineral Creek at 33°12'58"/110°59'42"			A&Ww				FBC		FC		AgL
MG	Dobson Lake	Urban Lake; Dobson Road & Los Lagos Vista Avenue, Mesa at 33°22'17"/111°53'12"	Urban		A&Ww				PBC		FC		
MG	Eldorado Park Lake	Urban Lake; Miller Road & Oak Street, Tempe at 33°28'25"/111°54'51"	Urban		A&Ww				PBC		FC		
MG	Encanto Park Lake	Urban Lake; 15th Avenue & Encanto Blvd., Phoenix at 33°28'36"/112°05'17"	Urban		A&Ww				PBC		FC	AgI	
MG	Fain Lake	City of Prescott Valley Park Lake 34°34'29"/112°21'03"	Urban		A&Ww				PBC		FC		
MG	French Gulch	Headwaters to confluence with Hassayampa River			A&Ww				PBC				AgL
MG	Galena Gulch	Tributary to the Agua Fria River at 34°28'37"/112°15'14"				A&We			PBC				AgL
MG	Galloway Wash (EDW)	Town of Cave Creek WWTP outfall #2 at 33°49'58"/111°57'30" to confluence with Andorra Wash at 33°49'59"/111°57'41"					A&Wedw		PBC				
MG	Gila River	San Carlos Indian Reservation to the Ashurst-Hayden Dam at 33°06'01"/111°14'46"			A&Ww			FBC			FC	AgI	AgL
MG	Gila River	Ashurst-Hayden Dam to the Florence WWTP outfall at 33°02'30"/111°24'16"				A&We			PBC				AgL
MG	Gila River (EDW)	Florence WWTP outfall to Felix Road at 33°01'49"/111°17'16"					A&Wedw		PBC				
MG	Gila River	Felix Road to the Gila River Indian Reservation				A&We			PBC				AgL
MG	Gila River (EDW)	From the confluence with the Salt River to the Gillespie Dam at 33°13'45"/112°46'07"					A&Wedw		PBC		FC	AgI	AgL
MG	Gila River	Gillespie Dam to Painted Rock Dam at 33°04'23"/113°00'40"			A&Ww			FBC			FC	AgI	AgL
MG	Granada Park Lake	Urban Lake; 6505 North 20th Street, Phoenix at 33°31'58.6"/112°02'06"	Urban		A&Ww				PBC		FC		
MG	Groom Creek	Tributary to the Hassayampa River at 34°27'14"/112°29'24"			A&Wc			FBC		DWS	FC		AgL
MG	Hank Raymond Lake	33°50'18"/112°16'07"			A&Ww			FBC			FC	AgI	AgL
MG	Hassayampa Lake	34°25'45"/112°25'29"	Igneous		A&Wc			FBC		DWS	FC		
MG	Hassayampa River	Headwaters to confluence with unnamed tributary at 34°26'09"/112°30'32"			A&Wc			FBC			FC	AgI	AgL
MG	Hassayampa River	Below confluence with unnamed tributary to 8 miles south of Wickenburg			A&Ww			FBC			FC	AgI	AgL

Department of Environmental Quality – Water Quality Standards

Watershed	Surface Waters	Segment Description and Location (Latitude and Longitudes are in NAD 27)	Lake Category	Aquatic and Wildlife				Human Health				Agricultural			
				A&Wc	A&Ww	A&We	A&Wedw	FBC	PBC	DWS	FC	Agl	AgL		
MG	Hassayampa River	8 miles south of Wickenburg to the Buckeye Irrigation Company Canal at 33°23'38"/112°22'22.8"				A&We				PBC					AgL
MG	Hassayampa River	Buckeye Irrigation Company canal to the Gila River at 33°19'34"/112°42'39.6"				A&Ww				FBC			FC		AgL
MG	Horsethief Lake	34°09'42"/112°17'56"	Igneous	A&Wc						FBC		DWS	FC		AgL
MG	Indian Bend Wash	Tributary to the Salt River at 33°26'13"/111°54'58"				A&We					PBC				
MG	Indian Bend Wash Lakes	Urban Lakes; Scottsdale at 33°30'31"/111°54'24"	Urban			A&Ww					PBC		FC		
MG	Indian School Park Lake	Urban Lake; Indian School Road & Hayden Road, Scottsdale at 33°29'45"/111°54'33"	Urban			A&Ww					PBC		FC		
MG	Kiwanis Park Lake	Urban Lake; 6000 South Mill Avenue, Tempe at 33°22'27"/111°56'21"	Urban			A&Ww					PBC		FC	AgI	
MG	Lake Pleasant	33°51'15"/112°16'15"	Deep			A&Ww				FBC		DWS	FC	AgI	AgL
MG	Lion Canyon	Tributary to Weaver Creek at 34°10'12"/112°41'49"				A&Ww				FBC			FC		AgL
MG	Little Ash Creek	Tributary to Ash Creek at 34°20'46"/112°04'16"				A&Ww				FBC			FC		AgL
MG	Lynx Creek	Headwaters to confluence with unnamed tributary at 34°34'29"/112°21'05"		A&Wc						FBC			FC		AgL
MG	Lynx Creek	Below confluence with unnamed tributary to Agua Fria River at 34°37'49"/112°14'42"				A&Ww				FBC			FC		AgL
MG	Lynx Lake	34°31'08"/112°23'05"	Deep	A&Wc						FBC		DWS	FC	AgI	AgL
MG	Maricopa Park Lake	33°35'30"/112°18'16"	Urban			A&Ww					PBC		FC		
MG	Martinez Canyon	Tributary to Box Canyon at 33°06'33"/111°12'48"				A&Ww				FBC			FC		AgL
MG	Martinez Creek	Tributary to the Hassayampa River at 33°59'56"/112°44'38"				A&Ww				FBC			FC	AgI	AgL
MG	McKellips Park Lake	Urban Lake; Miller Road & McKellips Road, Scottsdale at 33°27'14"/111°54'45"	Urban			A&Ww					PBC		FC	AgI	
MG	McMicken Wash (EDW)	Jomax WWTP outfall at 33°43'30"/112°20'11" to confluence of McMicken Wash with Agua Fria River at 33°39'39"/112°18'56"						A&Wedw			PBC				
MG	Mineral Creek	Tributary to the Gila River at 34°17'42"/112°13'34"				A&Ww				FBC			FC		AgL
MG	Minnehaha Creek	Tributary to the Hassayampa River at 34°11'49"/112°32'24"				A&Ww				FBC			FC		AgL
MG	Mountain Valley Park Ponds (EDW)	Town of Prescott Valley WWTP outfall 002 at 34°26'07"/112°18'48" to Navajo Wash						A&Wedw			PBC				
MG	New River	Headwaters to I-17 at 33°54'19.5"/112°08'46"				A&Ww				FBC			FC	AgI	AgL
MG	New River	Below I-17 to Agua Fria River at 33°30'47"/112°18'14"						A&We			PBC				AgL
MG	Painted Rock Reservoir	33°04'15"/113°00'30"	Sedimentary			A&Ww				FBC			FC	AgI	AgL
MG	Papago Park Ponds	Urban Lake; Galvin Parkway, Phoenix at 33°26'56"/111°56'50"	Urban			A&Ww					PBC		FC		
MG	Papago Park South Pond	Urban Lake; Curry Road, Tempe	Urban			A&Ww					PBC		FC		
MG	Perry Mesa Tank	34°11'03"/112°01'59"				A&Ww				FBC			FC		AgL
MG	Phoenix Area Canals	Granite Reef Dam to all municipal WTP intakes										DWS		AgI	AgL
MG	Phoenix Area Canals	Below municipal WTP intakes and all other locations												AgI	AgL
MG	Picacho Reservoir	32°51'17"/111°28'49"	Shallow			A&Ww				FBC			FC	AgI	AgL
MG	Poland Creek	Headwaters to confluence with Lorena Gulch at 34°12'32"/112°19'07"		A&Wc						FBC			FC		AgL
MG	Poland Creek	Below confluence with Lorena Gulch to Black Canyon Creek at 34°14'20"/112°12'54"				A&Ww				FBC			FC		AgL
MG	Queen Creek	Headwaters to the Town of Superior WWTP outfall at 33°16'45"/111°17'25"				A&Ww					PBC				AgL
MG	Queen Creek (EDW)	Town of Superior WWTP outfall to confluence with Potts Canyon at 33°17'17"/111°11'36"						A&Wedw			PBC				
MG	Queen Creek	Potts Canyon to Queen Valley golf course at 33°17'55"/111°17'17"				A&Ww				FBC			FC		AgL
MG	Queen Creek	Below Queen Valley golf course to Gila River at 33°09'50"/111°53'16.8"						A&We			PBC				
MG	Riverview Park Lake	Urban Lake; Dobson Road & 8th Street, Mesa at 33°25'50"/111°52'29"	Urban			A&Ww					PBC		FC		
MG	Roadrunner Park Lake	Urban Lake; 36th Street & Cactus, Phoenix at 33°35'57"/112°00'18"	Urban			A&Ww					PBC		FC		
MG	Salt River	Verde River to 2 km below Granite Reef Dam (Granite Reef Dam is at 31°26'23"/111°12'40")				A&Ww				FBC		DWS	FC	AgI	AgL
MG	Salt River	2 km below Granite Reef Dam to City of Mesa NW WRF outfall at 33°26'45"/111°56'35"						A&We			PBC				

Department of Environmental Quality – Water Quality Standards

Watershed	Surface Waters	Segment Description and Location (Latitude and Longitudes are in NAD 27)	Lake Category	Aquatic and Wildlife				Human Health				Agricultural	
				A&Wc	A&Ww	A&We	A&Wedw	FBC	PBC	DWS	FC	AgI	AgL
MG	Salt River (EDW)	City of Mesa NW WRF outfall at 33°26'45"/111°56'35" to Tempe Town Lake at 33°26'01"/111°54'55"					A&Wedw		PBC				
MG	Salt River	Below Tempe Town Lake to I-10 bridge				A&We			PBC				
MG	Salt River	I-10 bridge to the 23rd Avenue WWTP at 33°25'03"/112°06'41.6"			A&Ww				PBC		FC		
MG	Salt River (EDW)	23rd Avenue WWTP to confluence with Gila River at 33°22'55"/112°18'21.6"					A&Wedw		PBC		FC	AgI	AgL
MG	Siphon Draw (EDW)	Superstition Mountains WWTP outfall at 33°21'40"/111°33'30" to 6 km downstream at 32°21'01"/111°36'59"					A&Wedw		PBC				
MG	Sycamore Creek	Headwaters to confluence with Tank Canyon at 34°19'32"/111°50'12"		A&Wc					FBC		FC		AgL
MG	Sycamore Creek	Below confluence with Tank Canyon to the Agua Fria River at 34°19'30"/112°04'12"			A&Ww				FBC		FC		AgL
MG	Tempe Town Lake	At Mill Avenue Bridge at 33°26'30"/111°53'30"	Urban		A&Ww				FBC		FC		
MG	Tule Creek	Tributary to the Agua Fria River at 33°57'25"/112°14'13"			A&Ww				FBC		FC		AgL
MG	Turkey Creek	Headwaters to confluence with unnamed tributary at 34°19'28"/112°21'28"		A&Wc					FBC		FC	AgI	AgL
MG	Turkey Creek	Below confluence with unnamed tributary to Poland Creek at 34°14'20"/112°12'54"			A&Ww				FBC		FC	AgI	AgL
MG	Unnamed Wash (EDW)	City of Phoenix Cave Creek WRF outfall at 33°45'20"/112°00'59" to unnamed wash to 0.5 km downstream at 33°35'07"/112°01'12"					A&Wedw		PBC				
MG	Unnamed Wash (EDW)	Gila Bend WWTP outfall to the Gila River at 32°58'13"/112°43'46"					A&Wedw		PBC				
MG	Unnamed Wash (EDW)	Luke Air Force Base WWTP outfall to the Agua Fria River at 33°32'21"/112°19'15"					A&Wedw		PBC				
MG	Unnamed Wash (EDW)	Florence Gardens WWTP outfall at 33°03'49.54"/111°23'13.28" to confluence with Gila River at 33°02'59"/111°23'15"					A&Wedw		PBC				
MG	Unnamed Wash (EDW)	Prescott Valley WWTP outfall to the Agua Fria River at 34°35'16"/112°16'18"					A&Wedw		PBC				
MG	Unnamed Wash (EDW)	Queen Valley Sanitary District WWTP outfall at 33°17'38"/111°18'31" to the confluence with Queen Creek					A&Wedw		PBC				
MG	Wagner Wash (EDW)	Buckeye Festival Ranch WRF outfall at 33°39'14"/112°40'18" to 2 km downstream					A&Wedw		PBC				
MG	Vista Del Camino Park North	Urban Lake; 7700 East Roosevelt Street, Scottsdale at 33°27'33"/111°54'49.3"			A&Ww				PBC		FC		
MG	Walnut Canyon Creek	Tributary to the Gila River at 33°06'47"/111°05'20"			A&Ww				FBC		FC		AgL
MG	Weaver Creek	Tributary to Martinez Creek at 34°03'18"/112°46'48"			A&Ww				FBC		FC		AgL
MG	White Canyon Creek	Tributary to Walnut Canyon Creek at 33°09'25"/111°04'48"			A&Ww				FBC		FC		AgL
SC	Agua Caliente Lake	Urban Lake; 12325 East Roger Road, Tucson	Urban		A&Ww				PBC		FC		
SC	Agua Caliente Wash	Headwaters to Soldier Trail at 32°17'48"/110°42'58.5"			A&Ww				FBC		FC		AgL
SC	Agua Caliente Wash	Below Soldier Trail to Tanque Verde Creek at 32°14'35"/110°47'17"				A&We			PBC				AgL
SC	Aguirre Wash	Those reaches not located on the Tohono O'odham Indian Reservation				A&We			PBC				
SC	Alambre Wash	Tributary to Brawley Wash at 31°57'47"/111°23'28"				A&We			PBC				
SC	Alamo Wash	Tributary to Rillito Creek at 32°16'23"/110°54'18"				A&We			PBC				
SC	Altar Wash	Tributary to Brawley Wash at 31°57'47"/111°23'28"				A&We			PBC				
SC	Alum Gulch	Headwaters to 31°28'20"/110°43'51"				A&We			PBC				AgL
SC	Alum Gulch	From 31°28'20"/110°43'51" to 31°29'17"/110°44'25"			A&Ww				FBC		FC		AgL
SC	Alum Gulch	Below 31°29'17"/110°44'25" to Sonoita Creek at 31°30'58"/110°47'06"				A&We			PBC				AgL
SC	Arivaca Creek	Tributary to Altar Wash at 31°43'01"/111°25'41"			A&Ww				FBC		FC		AgL
SC	Arivaca Lake	31°31'50"/111°15'05"	Igneous		A&Ww				FBC		FC	AgI	AgL
SC	Atterbury Wash	Tributary to Pantano Wash at 32°10'52"/110°48'50"				A&We			PBC				AgL
SC	Bear Grass Tank	31°33'01"/111°11'32"			A&Ww				FBC		FC		AgL
SC	Big Wash	Tributary to Cañada del Oro at 32°24'47"/110°56'28"				A&We			PBC				
SC	Black Wash (EDW)	Pima County WWMD Avra Valley WWTP at 32°09'50"/111°10'49" to confluence with Brawley Wash at 32°15'00"/111°14'34"					A&Wedw		PBC				
SC	Bog Hole Tank	31°28'34"/110°37'07"			A&Ww				FBC		FC		AgL
SC	Brawley Wash	Tributary to Los Robles Wash at 32°21'54"/111°17'31"				A&We			PBC				

Department of Environmental Quality – Water Quality Standards

Watershed	Surface Waters	Segment Description and Location (Latitude and Longitudes are in NAD 27)	Lake Category	Aquatic and Wildlife				Human Health				Agricultural	
				A&Wc	A&Ww	A&We	A&Wedw	FBC	PBC	DWS	FC	AgI	AgL
SC	California Gulch	South of Ruby			A&Ww			FBC			FC		AgL
SC	Cañada del Oro	Headwaters to Highway 89 at 32°24'48"/110°56'14"			A&Ww			FBC			FC	AgI	AgL
SC	Cañada del Oro	Below Highway 89 to the Santa Cruz River at 32°19'30"/111°03'47"				A&We			PBC				AgL
SC	Cienega Creek	Headwaters to confluence with Gardner Canyon and Spring Water Canyon at 31°47'38"/110°35'17"			A&Ww			FBC			FC		AgL
SC	Cienega Creek (OAW)	From confluence with Gardner Canyon and Spring Water Canyon to USGS gaging station at 32°02'09"/110°40'34" (becomes Pantano Wash below this point)			A&Ww			FBC			FC		AgL
SC	Davidson Canyon	Headwaters to unnamed spring at 31°59'00"/110°38'46"				A&We			PBC				AgL
SC	Davidson Canyon (OAW)	Unnamed Spring to confluence with unnamed tributary at 31°59'32.5"/110°38'43.5"			A&Ww			FBC			FC		AgL
SC	Davidson Canyon (OAW)	From confluence with unnamed tributary to unnamed spring at 32°00'54"/110°38'54"				A&We			PBC				AgL
SC	Davidson Canyon (OAW)	From unnamed spring at 32°00'54"/110°38'54" to confluence with Cienega Creek at 32°01'05"/110°38'32"			A&Ww			FBC			FC		AgL
SC	Empire Gulch	Headwaters to unnamed spring at 31°47'14"/110°38'13"				A&We			PBC				
SC	Empire Gulch	From 31°47'14" / 110°38'13" to 31°47'11" / 110°00'39"			A&Ww			FBC			FC		
SC	Empire Gulch	Below 31°47'11" / 110°00'39" to 31°47'18" / 110°36'57"				A&We			PBC				AgL
SC	Empire Gulch	From 31°47'18" / 110°36'57" to confluence with Cienega Creek at 31°48'32"/110°35'20"			A&Ww			FBC			FC		
SC	Flux Canyon	Tributary to Alum Canyon at 31°30'22"/110°46'41"				A&We			PBC				AgL
SC	Gardner Canyon Creek	Headwaters to confluence with Sawmill Canyon at 31°42'51"/110°44'43"		A&Wc				FBC			FC		
SC	Gardner Canyon Creek	Below Sawmill Canyon to Cienega Creek at 31°47'38"/110°35'17"			A&Ww			FBC			FC		
SC	Greene Wash	Tributary to the Santa Cruz River at 33°00'54"/111°59'46"				A&We			PBC				
SC	Harshaw Creek	Tributary to Sonoita Creek at 31°32'35"/110°44'42"				A&We			PBC				AgL
SC	Hit Tank	32°43'57"/111°03'18"			A&Ww			FBC			FC		AgL
SC	Holden Canyon Creek	Headwaters to Mexico border at 31°23'38"/111°15'54" in the Coronado National Forest			A&Ww			FBC			FC		
SC	Huachuca Tank	31°21'11"/110°30'12"			A&Ww			FBC			FC		AgL
SC	Julian Wash	Tributary to the Santa Cruz River at 32°11'20"/110°59'13"				A&We			PBC				
SC	Kennedy Lake	Urban Lake; Mission Road & Ajo Road, Tucson at 32°10'48.5"/111°00'27"	Urban		A&Ww				PBC		FC		
SC	Lakeside Lake	Urban Lake; 8300 East Stella Road, Tucson at 32°11'10.5"/110°49'00"	Urban		A&Ww				PBC		FC		
SC	Lemmon Canyon Creek	Headwaters to confluence with unnamed tributary at 32°23'47"/110°47'46"		A&Wc				FBC			FC		
SC	Lemmon Canyon Creek	Below unnamed tributary to Sabino Canyon Creek at 32°23'02"/110°47'28"			A&Ww			FBC			FC		
SC	Los Robles Wash	Tributary to the Santa Cruz River at 32°32'13"/111°23'53"				A&We			PBC				
SC	Madera Canyon Creek	Headwaters to confluence with unnamed tributary at 31°43'42"/110°52'50"		A&Wc				FBC			FC		AgL
SC	Madera Canyon Creek	Below unnamed tributary to the Santa Cruz River at 31°46'55"/111°00'58"			A&Ww			FBC			FC		AgL
SC	Mattie Canyon	Tributary to Cienega Creek at 31°51'31"/110°34'25"			A&Ww			FBC			FC		AgL
SC	Nogales Wash	Tributary to Potrero Creek at 31°24'07"/110°57'11"			A&Ww				PBC				
SC	Oak Tree Canyon	Tributary to Cienega Creek at 31°48'43"/110°35'24"				A&We			PBC				
SC	Palisade Canyon Creek	Headwaters to confluence with unnamed tributary at 32°22'34"/110°45'35"		A&Wc				FBC			FC		
SC	Palisade Canyon Creek	Below unnamed tributary to Sabino Canyon Creek at 32°21'54"/110°46'23"			A&Ww			FBC			FC		
SC	Pantano Wash	Tributary to Tanque Verde Creek at 32°16'23"/110°54'18"				A&We			PBC				
SC	Paradise Lake	32°44'18"/111°40'42"	Urban		A&Ww				PBC			AgI	
SC	Parker Canyon Creek	Headwaters to confluence with unnamed tributary at 31°24'17"/110°28'44.5"		A&Wc				FBC			FC		
SC	Parker Canyon Creek	Below unnamed tributary to Mexico border at 31°19'59"/110°33'58"			A&Ww			FBC			FC		
SC	Parker Canyon Lake	31°25'35"/110°27'15"	Deep	A&Wc				FBC			FC	AgI	AgL
SC	Patagonia Lake	31°29'30"/110°52'00"	Deep		A&Ww			FBC			FC	AgI	AgL

Watershed	Surface Waters	Segment Description and Location (Latitude and Longitudes are in NAD 27)	Lake Category	Aquatic and Wildlife			Human Health				Agricultural		
				A&Wc	A&Ww	A&We	A&Wedw	FBC	PBC	DWS	FC	AgI	AgL
SC	Peña Blanca Lake	31°24'12"/111°05'04"	Igneous		A&Ww			FBC			FC	AgI	AgL
SC	Potrero Creek	Headwaters to Interstate 19 at 31°23'24"/110°57'30"				A&We			PBC				AgL
SC	Potrero Creek	Below Interstate 19 to Santa Cruz River at 31°27'07"/110°57'40"			A&Ww			FBC			FC		AgL
SC	Puertocito Wash	Tributary to Altar Wash at 31°43'01"/111°25'41"				A&We			PBC				
SC	Quitobaquito Spring	(Pond and Springs) 31°56'39"/113°01'06"			A&Ww			FBC			FC		AgL
SC	Redrock Canyon Creek	Tributary to Harshaw Creek at 31°32'35"/110°44'13"			A&Ww			FBC			FC		
SC	Rillito Creek	Tributary to the Santa Cruz River at 32°18'50"/111°03'18"				A&We			PBC				AgL
SC	Romero Canyon Creek	Headwaters to confluence with unnamed tributary at 32°24'30"/110°50'35"		A&Wc				FBC			FC		
SC	Romero Canyon Creek	Below unnamed tributary to Sutherland Wash at 32°25'52"/110°53'56"			A&Ww			FBC			FC		
SC	Rose Canyon Creek	Tributary to Rose Canyon Lake at 32°23'10"/110°43'01"		A&Wc				FBC			FC		
SC	Rose Canyon Lake	32°23'13"/110°42'38"	Igneous	A&Wc				FBC			FC		AgL
SC	Ruby Lakes	Near the town of Ruby at 31°26'28.5"/111°14'19"	Igneous		A&Ww			FBC			FC		AgL
SC	Sabino Canyon Creek	Headwaters to confluence with unnamed tributary at 32°23'28"/110°47'00"		A&Wc				FBC		DWS	FC	AgI	
SC	Sabino Canyon Creek	Below unnamed tributary to Tanque Verde River at 32°15'40"/110°49'30"			A&Ww			FBC		DWS	FC	AgI	
SC	Salero Ranch Tank	31°35'42"/110°53'22"			A&Ww			FBC			FC		AgL
SC	Santa Cruz River	Headwaters to the International Boundary at 31°19'58"/110°35'48"			A&Ww			FBC			FC	AgI	AgL
SC	Santa Cruz River	International Boundary to the Nogales International WWTP outfall at 31°27'24"/110°58'05"			A&Ww			FBC		DWS	FC	AgI	AgL
SC	Santa Cruz River (EDW)	Nogales International WWTP outfall to the Tubac Bridge at 31°36'25"/110°02'00"					A&Wedw		PBC				AgL
SC	Santa Cruz River	The Tubac Bridge to Roger Road WWTP outfall				A&We			PBC				AgL
SC	Santa Cruz River (EDW)	Roger Road WWTP outfall to Baumgartner Road at 32°35'37"/111°28'08"					A&Wedw		PBC				
SC	Santa Cruz Wash	Baumgartner Road to the Ak Chin Indian Reservation				A&We			PBC				AgL
SC	Santa Cruz Wash, West Branch	Tributary to the Santa Cruz Wash at 32°12'07"/110°59'20"				A&We			PBC				AgL
SC	Santa Cruz Wash, North Branch	Tributary to the Santa Cruz Wash at 32°55'55"/111°53'10"				A&We			PBC				
SC	Santa Cruz Wash, North Branch (EDW)	City of Casa Grande WRF outfall at 32°54'57"/111°47'13" to 1 km downstream at 32°54'49"/111°47'48"					A&Wedw		PBC				
SC	Santa Rosa Wash	Below Tohono O'odham Indian Reservation to the Ak Chin Indian Reservation				A&We			PBC				
SC	Santa Rosa Wash (EDW)	Palo Verde Utilities WWTP outfall at 33°04'20"/112°01'47" to the Gila River Indian Reservation					A&Wedw		PBC				
SC	Soldier Lake	32°25'34"/110°44'41"		A&Wc				FBC			FC		AgL
SC	Sonoita Creek	Headwaters to the Town of Patagonia WWTP outfall at 31°32'15"/110°45'30"				A&We			PBC				AgL
SC	Sonoita Creek (EDW)	Town of Patagonia WWTP outfall to permanent groundwater upwelling point approximately 1600 feet downstream of outfall					A&Wedw		PBC				AgL
SC	Sonoita Creek	Below 1600 feet downstream of Town of Patagonia WWTP outfall to the Santa Cruz River at 31°29'43"/110°58'37"			A&Ww			FBC			FC	AgI	AgL
SC	Split Tank	31°28'15"/111°05'15"			A&Ww			FBC			FC		AgL
SC	Sutherland Wash	Tributary to Cañada del Oro at 32°25'05"/110°55'26"			A&Ww			FBC			FC		
SC	Sycamore Canyon	From 32°21'36" / 110°45'21" to Sycamore Reservoir			A&Ww			FBC			FC		
SC	Sycamore Canyon Creek	Headwaters to the U.S./Mexico border at 31°22'48"/111°13'19"			A&Ww			FBC			FC		AgL
SC	Sycamore Reservoir	32°20'57"/110°44'52"		A&Wc				FBC			FC		AgL
SC	Tanque Verde Creek	Headwaters to Houghton Road at 32°14'13"/110°46'04"			A&Ww			FBC			FC		AgL
SC	Tanque Verde Creek	Below Houghton Road to Rillito Creek at 32°16'08"/110°52'30"				A&We			PBC				AgL
SC	The Lake Tank	32°54'14"/111°04'14"			A&Ww			FBC			FC		AgL
SC	Three R Canyon	Headwaters to 31°28'35"/110°46'19"				A&We			PBC				AgL

Department of Environmental Quality – Water Quality Standards

Watershed	Surface Waters	Segment Description and Location (Latitude and Longitudes are in NAD 27)	Lake Category	Aquatic and Wildlife				Human Health				Agricultural	
				A&Wc	A&Ww	A&We	A&Wedw	FBC	PBC	DWS	FC	AgI	AgL
SC	Three R Canyon	From 31°28'35"/110°46'19" to 31°28'27"/110°47'12"			A&Ww			FBC			FC		AgL
SC	Three R Canyon	From 31°28'27"/110°47'12" to Sonoita Creek at 31°29'56"/110°48'54"				A&We			PBC				AgL
SC	Tinaja Wash	Headwaters to the Santa Cruz River at 31°32'58.4"/111°02'45.7"				A&We			PBC				AgL
SC	Unnamed Wash (EDW)	Oracle Sanitary District WWTP outfall at 32°36'54"/110°48'02" to 5 km downstream					A&Wedw		PBC				
SC	Unnamed Wash	5 km downstream of the Oracle Sanitary District WWTP outfall				A&We			PBC				
SC	Unnamed Wash (EDW)	Arizona City Sanitary District WWTP outfall at 32°45'47"/111°44'20" to confluence with Santa Cruz Wash at 35°45'45"/111°46'43"					A&Wedw		PBC				
SC	Unnamed Wash (EDW)	Saddlebrook WWTP outfall at 32°32'00"/110°52'59" to confluence with Cañada del Oro at 32°30'20"/110°52'27"					A&Wedw		PBC				
SC	Vekol Wash	Those reaches not located on the Ak-Chin, Tohono O'odham and Gila River Indian Reservations				A&We			PBC				
SC	Wakefield Canyon	Headwaters to confluence with unnamed tributary 31°52'47"/110°26'25"		A&Wc				FBC			FC		AgL
SC	Wakefield Canyon	Below confluence with unnamed tributary to Cienea Creek at 31°52'47.5"/110°26'25"			A&Ww			FBC			FC		AgL
SC	Wild Burro Canyon	Headwaters to confluence with unnamed tributary at 32°28'36"/111°05'18"			A&Ww			FBC			FC		AgL
SC	Wild Burro Canyon	Below confluence with unnamed tributary to Santa Cruz River at 32°28'34"/111°05'15.5"				A&We			PBC				AgL
SC	Williams Ranch Tanks	31°55'15"/110°25'30"			A&Ww			FBC			FC		AgL
SP	Abbot Canyon	Headwaters to confluence with Whitewater Draw at 31°33'32"/109°48'39.6"			A&Ww			FBC			FC		AgL
SP	Aravaipa Creek	Headwaters to confluence with Stowe Gulch at 32°52'10"/110°22'00"			A&Ww			FBC			FC		AgL
SP	Aravaipa Creek (OAW)	Stowe Gulch confluence to downstream boundary of Aravaipa Canyon Wilderness Area at 32°54'23"/110°33'40"			A&Ww			FBC			FC		AgL
SP	Aravaipa Creek	Below downstream boundary of Aravaipa Canyon Wilderness Area to the San Pedro River at 32°50'20"/110°42'50"			A&Ww			FBC			FC		AgL
SP	Ash Creek	Chiricahua Mountains, near Whitewater Draw at 31°50'28"/109°40'01.2"			A&Ww			FBC			FC	AgI	AgL
SP	Babocomari River	Tributary to the San Pedro River at 31°43'19"/110°11'35"			A&Ww			FBC			FC		AgL
SP	Bass Canyon Creek	Headwaters to confluence with unnamed tributary at 32°26'06"/110°13'18"		A&Wc				FBC			FC		AgL
SP	Bass Canyon Creek	Below confluence with unnamed tributary to Hot Springs Canyon Creek at 32°20'53"/110°15'14"			A&Ww			FBC			FC		AgL
SP	Bass Canyon Tank	32°24'00"/110°13'00"			A&Ww			FBC			FC		AgL
SP	Bear Creek	Headwaters to U.S./Mexico border at 31°19'59"/110°22'58.5"			A&Ww			FBC			FC		AgL
SP	Big Creek	Tributary to Pitchfork Canyon at 32°35'24"/109°57'07"		A&Wc				FBC			FC		AgL
SP	Blacktail Pond	Fort Huachuca Military Reservation at 31°24'13"/110°17'21"			A&Ww			FBC			FC		
SP	Blackwater Draw	Headwaters to the U.S./Mexico border at 31°20'02"/109°15'36" in the San Bernardino Valley			A&Ww			FBC			FC		AgL
SP	Booger Canyon Creek	Tributary to Aravaipa Creek at 32°54'54"/110°29'35"			A&Ww			FBC			FC		AgL
SP	Buck Canyon	Headwaters to Buck Creek Tank at 31°33'06"/109°52'43"			A&Ww			FBC			FC		AgL
SP	Buck Canyon	Below Buck Creek Tank to Dry Creek at 31°31'08"/109°18'25"				A&We			PBC				AgL
SP	Buehman Canyon Creek (OAW)	Headwaters to confluence with unnamed tributary at 32°24'31.5"/110°32'08"			A&Ww			FBC			FC		AgL
SP	Buehman Canyon Creek	Below confluence with unnamed tributary at 32°25'41"/110°29'53"			A&Ww			FBC			FC		AgL
SP	Bull Tank	32°31'15"/110°12'45"			A&Ww			FBC			FC		AgL
SP	Bullock Canyon	Tributary to Buehman Canyon at 32°23'00"/110°33'04"			A&Ww			FBC			FC		AgL
SP	Carr Canyon Creek	Headwaters to confluence with unnamed tributary at 31°27'00"/110°15'45"		A&Wc				FBC			FC		AgL
SP	Carr Canyon Creek	Below confluence with unnamed tributary to the San Pedro River at 31°30'32"/110°07'37"			A&Ww			FBC			FC		AgL
SP	Copper Creek	Headwaters to confluence with Prospect Canyon at 32°44'48"/110°30'18"			A&Ww			FBC			FC		AgL
SP	Copper Creek	Below confluence with Prospect Canyon to the San Pedro River at 32°41'17"/110°36'43"				A&We			PBC				AgL

Watershed	Surface Waters	Segment Description and Location (Latitude and Longitudes are in NAD 27)	Lake Category	Aquatic and Wildlife				Human Health				Agricultural	
				A&Wc	A&Ww	A&We	A&Wedw	FBC	PBC	DWS	FC	AgI	AgL
SP	Deer Creek	Headwaters to confluence with unnamed tributary at 32°59'56"/110°20'09"		A&Wc				FBC			FC		AgL
SP	Deer Creek	Below confluence with unnamed tributary to Aravaipa Creek at 32°54'25"/110°28'01"			A&Ww			FBC			FC		AgL
SP	Dixie Canyon	Headwaters to Mexican Canyon at 31°29'02"/109°45'04" in the Mule Mountains			A&Ww			FBC			FC		AgL
SP	Double R Canyon Creek	Tributary to Bass Canyon at 32°21'06"/110°14'23"			A&Ww			FBC			FC		
SP	Dry Canyon	Headwaters to Abbot Canyon at 31°33'25"/109°43'23" in the Mule Mountains			A&Ww			FBC			FC		AgL
SP	East Gravel Pit Pond	Fort Huachuca Military Reservation at 31°30'54"/110°19'42"	Sedimentary		A&Ww			FBC			FC		
SP	Espiritu Canyon Creek	Tributary to Soza Wash at 32°18'52"/110°28'35"			A&Ww			FBC			FC		AgL
SP	Fly Pond	Fort Huachuca Military Reservation at 31°32'53"/110°21'14"			A&Ww			FBC			FC		
SP	Fourmile Canyon Creek	Tributary to Aravaipa Creek at 32°50'14"/110°20'08"			A&Ww			FBC			FC		AgL
SP	Fourmile Canyon, Left Prong	Headwaters to confluence with unnamed tributary at 32°43'14"/110°23'43"		A&Wc				FBC			FC		AgL
SP	Fourmile Canyon, Left Prong	Below confluence with unnamed tributary to Fourmile Canyon Creek at 32°47'33"/110°22'36"			A&Ww			FBC			FC		AgL
SP	Fourmile Canyon, Right Prong	Tributary to Fourmile Canyon at 32°47'33"/110°22'36"			A&Ww			FBC			FC		AgL
SP	Gadwell Canyon	Headwaters to Whitewater Draw at 31°36'50"/109°43'41" in the Mule Mountains			A&Ww			FBC			FC		AgL
SP	Garden Canyon Creek	Headwaters to confluence with unnamed tributary at 31°29'00"/110°19'42"		A&Wc				FBC		DWS	FC	AgI	
SP	Garden Canyon Creek	Below confluence with unnamed tributary to the San Pedro River at 31°41'46"/110°12'40"			A&Ww			FBC		DWS	FC	AgI	
SP	Glance Creek	Headwaters to Whitewater Draw at 31°27'04"/109°42'29" in the Mule Mountains			A&Ww			FBC			FC		AgL
SP	Gold Gulch	Headwaters to U.S./Mexico border at 31°20'10"/109°50'06" in the Mule Mountains			A&Ww			FBC			FC		AgL
SP	Golf Course Pond	Fort Huachuca Military Reservation at 31°32'14"/110°18'49"	Sedimentary		A&Ww				PBC		FC		
SP	Goudy Canyon Creek	Headwaters to Grant Creek at 32°35'13"/109°58'37" in the Pinaleno Mountains		A&Wc				FBC			FC		AgL
SP	Grant Creek	Headwaters to confluence with unnamed tributary at 32°38'09.5"/109°56'35"		A&Wc				FBC		DWS	FC		AgL
SP	Grant Creek	Below confluence with unnamed tributary to terminus near Willcox Playa at 32°33'43"/109°58'55"			A&Ww			FBC			FC		AgL
SP	Gravel Pit Pond	Fort Huachuca Military Reservation at 31°30'51"/110°19'47.6"	Sedimentary		A&Ww			FBC			FC		
SP	Greenbrush Draw	From Mexican border to confluence with San Pedro River				A&We			PBC				
SP	Hidden Pond	Fort Huachuca Military Reservation at 32°30'30"/109°22'17"			A&Ww			FBC			FC		
SP	High Creek	Headwaters to confluence with unnamed tributary at 32°33'07"/110°14'40"		A&Wc				FBC			FC		AgL
SP	High Creek	Below confluence with unnamed tributary to terminus near Willcox Playa at 32°31'41"/109°02'38"			A&Ww			FBC			FC		AgL
SP	Horse Camp Canyon Creek	Tributary to Aravaipa Creek at 32°55'07"/110°30'56"			A&Ww			FBC			FC		AgL
SP	Hot Springs Canyon Creek	Tributary to the San Pedro River at 32°17'24"/110°22'55"			A&Ww			FBC			FC		AgL
SP	Johnson Canyon	Headwaters to Whitewater Draw at 31°32'56"/109°46'19" in the Chiricahua Mountains			A&Ww			FBC			FC		AgL
SP	Lake Cochise (EDW)	South of Twin Lakes Municipal Golf Course at 32°13'58"/109°49'25"				A&Wedw			PBC				
SP	Leslie Canyon Creek	Headwaters to Whitewater Draw at 31°32'10"/109°40'12" in the Chiricahua Mountains			A&Ww			FBC			FC		AgL
SP	Lower Garden Canyon Pond	Fort Huachuca Military Reservation			A&Ww			FBC			FC		
SP	Mexican Canyon	Headwaters to Whitewater Draw at 31°29'13"/109°46'30" in the Mule Mountains			A&Ww			FBC			FC		AgL
SP	Miller Canyon Creek	Headwaters to Broken Arrow Ranch Road at 31°25'33"/110°15'08"		A&Wc				FBC		DWS	FC		AgL
SP	Miller Canyon Creek	Below Broken Arrow Ranch Road to the San Pedro River at 31°29'56"/110°07'37"			A&Ww			FBC		DWS	FC		AgL
SP	Moonshine Creek	Tributary to Post Creek at 32°40'52"/109°54'25"		A&Wc				FBC			FC		AgL
SP	Mule Gulch	Headwaters to just above the Lavender Pit at 31°26'23.7"/109°45'36.7"			A&Ww				PBC		FC		
SP	Mule Gulch	Just above the Lavender Pit to the Bisbee WWTP outfall at 31°25'30"/109°52'40"				A&We			PBC				

Department of Environmental Quality – Water Quality Standards

Watershed	Surface Waters	Segment Description and Location (Latitude and Longitudes are in NAD 27)	Lake Category	Aquatic and Wildlife				Human Health				Agricultural		
				A&Wc	A&Ww	A&We	A&Wedw	FBC	PBC	DWS	FC	AgI	AgL	
SP	Mule Gulch (EDW)	Below the Bisbee WWTP outfall to the Highway 80 bridge at 31°26'30"/109°49'28"					A&Wedw			PBC				
SP	Mule Gulch	Below the Highway 80 bridge to Whitewater Draw at 31°28'03"/109°42'21"				A&We				PBC				AgL
SP	Oak Grove Creek	Tributary to Turkey Creek at 32°45'32"/110°14'06"				A&Ww				FBC			FC	AgL
SP	Officers Club Pond	Fort Huachuca Military Reservation at 31°32'51"/110°21'35"	Sedimentary			A&Ww				PBC			FC	
SP	Paige Canyon Creek	Tributary to the San Pedro River at 32°17'10"/110°22'48"				A&Ww				FBC			FC	AgL
SP	Parsons Canyon Creek	Tributary to Aravaipa Creek at 32°54'11"/110°27'40"				A&Ww				FBC			FC	AgL
SP	Pinery Creek	Headwaters to State Highway 181 at 32°00'24"/109°25'16"				A&Wc				FBC		DWS	FC	AgL
SP	Pinery Creek	Below State Highway 181 to terminus near Willcox Playa at 32°01'05"/109°34'23"				A&Ww				FBC		DWS	FC	AgL
SP	Post Creek	Tributary to Grant Creek at 32°40'05"/109°54'58"				A&Wc				FBC			FC	AgI AgL
SP	Ramsey Canyon Creek	Headwaters to Forest Service Road #110 at 31°27'44"/110°17'27"				A&Wc				FBC			FC	AgI AgL
SP	Ramsey Canyon Creek	Below Forest Service Road #110 to Carr Wash at 31°30'04"/110°09'11"				A&Ww				FBC			FC	AgI AgL
SP	Rattlesnake Canyon	Headwaters to confluence with Brush Canyon at 32°38'27"/110°21'24"				A&Wc				FBC			FC	AgL
SP	Rattlesnake Canyon	Below confluence with Brush Canyon to Aravaipa Creek at 32°48'00"/110°17'32"				A&Ww				FBC			FC	AgL
SP	Redfield Canyon Creek	Headwaters to confluence with unnamed tributary at 32°33'39"/110°18'41"				A&Wc				FBC			FC	AgL
SP	Redfield Canyon Creek	Below confluence with unnamed tributary to the San Pedro River at 32°09'32"/110°17'56"				A&Ww				FBC			FC	AgL
SP	Riggs Flat Lake	32°42'27"/109°57'51"	Igneous			A&Wc				FBC			FC	AgI AgL
SP	Rock Creek	Tributary to Turkey Creek at 31°53'20"/109°30'00" Alc								FBC			FC	AgL
SP	Rucker Canyon Creek	Headwaters to Whitewater Draw at 31°44'46"/109°26'06"	Igneous			A&Wc				FBC			FC	AgL
SP	Rucker Canyon Lake	31°46'46"/109°18'30"	Shallow			A&Wc				FBC			FC	AgL
SP	San Pedro River	U.S./ Mexico Border to Redington at 32°25'39"/110°29'33"				A&Ww				FBC			FC	AgI AgL
SP	San Pedro River	Redington to the Gila River at 32°59'02"/110°46'55"				A&Ww				FBC			FC	AgL
SP	Snow Flat Lake	32°39'09"/109°51'52"	Igneous			A&Wc				FBC			FC	AgI AgL
SP	Soldier Creek	Tributary to Post Creek at 32°40'52"/109°54'40"				A&Wc				FBC			FC	AgL
SP	Soldier Creek (EDW)	Fort Huachuca WWTP outfall to unnamed wash at 31°34'48"/110°18'35" to confluence with Soldier Creek to confluence with Babocomari River at 31°39'46"/110°17'24"					A&Wedw			PBC				
SP	Soto Canyon	Headwaters to Dixie Canyon at 31°29'46"/109°55'37" in the Mule Mountains				A&Ww				FBC			FC	AgL
SP	Swamp Springs Canyon Creek	Tributary to Redfield Canyon at 32°26'10"/110°19'30"				A&Ww				FBC			FC	AgL
SP	Sycamore Pond I	Fort Huachuca Military Reservation at 31°35'12"/110°26'09"	Sedimentary			A&Ww				FBC			FC	
SP	Sycamore Pond II	Fort Huachuca Military Reservation at 31°34'38.6"/110°26'07"	Sedimentary			A&Ww				FBC			FC	
SP	Turkey Creek	Tributary to Aravaipa Creek at 32°53'49"/110°26'35"				A&Ww				FBC			FC	AgL
SP	Turkey Creek	Headwaters to confluence with Rock Creek at 31°53'20"/109°30'00"				A&Wc				FBC			FC	AgI AgL
SP	Turkey Creek	Below confluence with Rock Creek to terminus near Willcox Playa at 31°59'56"/109°49'01"				A&Ww				FBC			FC	AgI AgL
SP	Unnamed Wash (EDW)	Mt. Lemmon WWTP outfall to 0.25 km downstream					A&Wedw			PBC				
SP	Virgus Canyon Creek	Tributary to Aravaipa Creek at 32°54'58"/110°31'16"				A&Ww				FBC			FC	AgL
SP	Walnut Gulch	Headwaters to Tombstone WWTP outfall at 31°43'47"/110°04'06"					A&We			PBC				
SP	Walnut Gulch (EDW)	Tombstone WWTP outfall to the confluence of Tombstone Wash at 31°44'02"/110°05'58"					A&Wedw			PBC				
SP	Walnut Gulch	Tombstone Wash to San Pedro River at 31°43'19"/110°11'35"					A&We			PBC				
SP	Ward Canyon Creek	Tributary to Turkey Creek at 31°51'47"/109°20'13"				A&Wc				FBC			FC	AgL
SP	Whitewater Draw	Headwaters to confluence with unnamed tributary at 31°20'36"/109°34'46"					A&We			PBC				AgL
SP	Whitewater Draw	Below confluence with unnamed tributary to U.S./Mexico border at 31°20'02"/109°34'44"				A&Ww				FBC			FC	AgL
SP	Willcox Playa	32°08'19"/109°50'59" in the Sulphur Springs Valley	Sedimentary			A&Ww				FBC			FC	AgL

Watershed	Surface Waters	Segment Description and Location (Latitude and Longitudes are in NAD 27)	Lake Category	Aquatic and Wildlife				Human Health				Agricultural	
				A&Wc	A&Ww	A&We	A&Wedw	FBC	PBC	DWS	FC	AgI	AgL
SP	Woodcutters Pond	Fort Huachuca Military Reservation at 31°3'11.5"/110°20'15"	Igneous		A&Ww			FBC			FC		
SR	Ackre (Judge) Lake	33°37'00"/109°20'37"		A&Wc				FBC			FC	AgI	AgL
SR	Apache Lake	33°35'30"/111°20'30"	Deep		A&Ww			FBC		DWS	FC	AgI	AgL
SR	Barnhardt Creek	Headwaters to confluence with unnamed tributary at 34°05'36"/111°26'38"		A&Wc				FBC			FC		AgL
SR	Barnhardt Creek	Below confluence with unnamed tributary to Rye Creek at 34°06'58"/111°21'32"			A&Ww			FBC			FC		AgL
SR	Basin Lake	33°55'00"/109°26'05"	Igneous		A&Ww			FBC			FC		AgL
SR	Bear Creek	Tributary to the Black River at 33°43'26"/109°22'30"		A&Wc				FBC			FC	AgI	AgL
SR	Bear Wallow Creek (OAW)	Tributary to the Black River at 33°37'44"/109°31'23"		A&Wc				FBC			FC		AgL
SR	Bear Wallow Creek, North Fork (OAW)	Tributary to Bear Wallow Creek at 33°35'53"/109°26'49"		A&Wc				FBC			FC		AgL
SR	Bear Wallow Creek, South Fork (OAW)	Tributary to Bear Wallow Creek at 33°35'53"/109°26'49"		A&Wc				FBC			FC		AgL
SR	Beaver Creek	Tributary to the Black River at 33°43'44"/109°21'07"		A&Wc				FBC			FC	AgI	AgL
SR	Big Lake	33°52'45"/109°25'00"	Igneous	A&Wc				FBC		DWS	FC	AgI	AgL
SR	Black River	Tributary to the Salt River at 33°44'20"/110°13'30"		A&Wc				FBC		DWS	FC	AgI	AgL
SR	Black River, East Fork	Tributary to the Black River at 33°45'07"/109°21'43"		A&Wc				FBC		DWS	FC	AgI	AgL
SR	Black River, North Fork of East Fork	Tributary to Black River, East Fork at 33°56'17"/109°24'11"		A&Wc				FBC		DWS	FC	AgI	AgL
SR	Black River, West Fork	Tributary to the Black River at 33°45'07"/109°21'43"		A&Wc				FBC		DWS	FC	AgI	AgL
SR	Bloody Tanks Wash	Headwaters to Schultze Ranch at 33°22'29"/110°54'39"				A&We			PBC				AgL
SR	Bloody Tanks Wash	Schultze Ranch to Miami Wash at 33°25'05"/110°50'02"				A&We			PBC				
SR	Boggy Creek	Tributary to the Black River at 33°44'31"/109°26'20"		A&Wc				FBC			FC	AgI	AgL
SR	Boneyard Creek	Tributary to Black River, East Fork at 33°51'22"/109°18'50"		A&Wc				FBC			FC	AgI	AgL
SR	Boulder Creek	Tributary to LaBarge Creek at 33°30'54"/111°24'40"			A&Ww			FBC			FC		
SR	Campaign Creek	Tributary to Roosevelt Lake at 33°37'30"/111°00'04"			A&Ww			FBC			FC		AgL
SR	Canyon Creek	Headwaters to the White Mountain Apache Reservation at 33°57'53"/110°47'00"		A&Wc				FBC		DWS	FC	AgI	AgL
SR	Canyon Lake	33°33'15"/111°26'30"	Deep		A&Ww			FBC		DWS	FC	AgI	AgL
SR	Centerfire Creek	Tributary to the Black River at 33°42'47"/109°26'17"		A&Wc				FBC			FC	AgI	AgL
SR	Chambers Draw Creek	Tributary to North Fork of the East Fork of Black River at 33°53'03"/109°20'13"		A&Wc				FBC			FC		AgL
SR	Cherry Creek	Headwaters to confluence with unnamed tributary at 34°05'09"/110°56'04"		A&Wc				FBC			FC	AgI	AgL
SR	Cherry Creek	Below unnamed tributary to the Salt River at 33°40'16"/110°48'03.6"			A&Ww			FBC			FC	AgI	AgL
SR	Christopher Creek	Tributary to Tonto Creek at 34°18'36"/111°04'23"		A&Wc				FBC			FC	AgI	AgL
SR	Cold Spring Canyon Creek	Headwaters to confluence with unnamed tributary at 33°49'50"/110°52'55"		A&Wc				FBC			FC		AgL
SR	Cold Spring Canyon Creek	Below confluence with unnamed tributary to Cherry Creek at 33°50'06"/110°51'28.8"			A&Ww			FBC			FC		AgL
SR	Conklin Creek	Tributary to the Black River at 33°41'49"/109°27'36"		A&Wc				FBC			FC	AgI	AgL
SR	Coon Creek	Headwaters to confluence with unnamed tributary at 33°46'42"/110°54'25"		A&Wc				FBC			FC		AgL
SR	Coon Creek	Below confluence with unnamed tributary to Salt River at 33°39'47"/110°50'24"			A&Ww			FBC			FC		AgL
SR	Corduroy Creek	Tributary to Fish Creek at 33°59'46"/110°17'31"		A&Wc				FBC			FC	AgI	AgL
SR	Coyote Creek	Tributary to the Black River, East Fork at 33°50'53"/109°18'18"		A&Wc				FBC			FC	AgI	AgL
SR	Crescent Lake	33°54'36"/109°25'08"	Shallow	A&Wc				FBC			FC	AgI	AgL
SR	Deer Creek	Tributary to the Black River, East Fork at 33°48'07"/109°19'26"		A&Wc				FBC			FC		AgL
SR	Del Shay Creek	Tributary to Gun Creek at 34°00'22"/111°15'43"			A&Ww			FBC			FC		AgL
SR	Devils Chasm Creek	Headwaters to confluence with unnamed tributary at 33°48'46"/110°52'33"		A&Wc				FBC			FC		AgL
SR	Devils Chasm Creek	Below confluence with unnamed tributary to Cherry Creek at 33°49'34"/110°54'18"			A&Ww			FBC			FC		AgL

Department of Environmental Quality – Water Quality Standards

Watershed	Surface Waters	Segment Description and Location (Latitude and Longitudes are in NAD 27)	Lake Category	Aquatic and Wildlife				Human Health				Agricultural	
				A&Wc	A&Ww	A&We	A&Wedw	FBC	PBC	DWS	FC	AgI	AgL
SR	Dipping Vat Reservoir	33°55'54"/109°25'15"	Igneous		A&Ww			FBC			FC		AgL
SR	Double Cienega Creek	Tributary to Fish Creek at 33°38'35"/109°22'08"		A&Wc				FBC			FC		AgL
SR	Fish Creek	Tributary to the Black River at 33°42'40"/109°26'31"		A&Wc				FBC			FC	AgI	AgL
SR	Fish Creek	Tributary to the Salt River at 33°34'37"/111°21'11"			A&Ww			FBC			FC		
SR	Gold Creek	Headwaters to confluence with unnamed tributary at 33°59'47"/111°25'07"		A&Wc				FBC			FC		AgL
SR	Gold Creek	Below confluence with unnamed tributary to Tonto Creek at 33°58'55"/111°18'03.6"			A&Ww			FBC			FC		AgL
SR	Gordon Canyon Creek	Headwaters to confluence with Hog Canyon at 34°13'49"/111°00'27"		A&Wc				FBC			FC		AgL
SR	Gordon Canyon Creek	Below confluence with Hog Canyon to Haigler Creek at 34°11'56"/111°03'21"			A&Ww			FBC			FC		AgL
SR	Greenback Creek	Tributary to Tonto Creek at 33°47'38"/111°15'22"			A&Ww			FBC			FC		AgL
SR	Haigler Creek	Headwaters to confluence with unnamed tributary at 34°12'23.5"/111°00'11"		A&Wc				FBC			FC	AgI	AgL
SR	Haigler Creek	Below confluence with unnamed tributary to Tonto Creek at 34°12'54"/111°05'45.6"			A&Ww			FBC			FC	AgI	AgL
SR	Hannagan Creek	Tributary to Beaver Creek at 33°42'07"/109°14'46"		A&Wc				FBC			FC		AgL
SR	Hay Creek (OAW)	Tributary to the Black River, West Fork at 33°48'32"/109°25'16"		A&Wc				FBC			FC		AgL
SR	Home Creek	Tributary to the Black River, West Fork at 33°45'43"/109°22'48"		A&Wc				FBC			FC		AgL
SR	Horse Creek	Tributary to the Black River, West Fork at 33°45'11"/109°21'50"		A&Wc				FBC			FC		AgL
SR	Horse Camp Creek	Headwaters to confluence with unnamed tributary at 33°53'53"/110°50'10"		A&Wc				FBC			FC		AgL
SR	Horse Camp Creek	Below confluence with unnamed tributary to Cherry Creek at 33°52'08"/110°52'33.6"			A&Ww			FBC			FC		AgL
SR	Horton Creek	Tributary to Tonto Creek at 34°20'24"/111°05'42"		A&Wc				FBC			FC	AgI	AgL
SR	Houston Creek	Tributary to Tonto Creek at 34°07'30"/111°15'25"			A&Ww			FBC			FC		AgL
SR	Hunter Creek	Tributary to Christopher Creek at 34°18'29"/111°01'55"		A&Wc				FBC			FC		AgL
SR	LaBarge Creek	Headwaters to Canyon Lake at 33°31'34"/111°25'15.6"			A&Ww			FBC			FC		
SR	Lake Sierra Blanca	33°52'25"/109°16'05"		A&Wc				FBC			FC	AgI	AgL
SR	Miami Wash	Tributary to Pinal Creek at 33°27'04"/110°50'17"				A&We			PBC				
SR	Mule Creek	Tributary to Canyon Creek at 34°16'34"/110°48'00"		A&Wc				FBC		DWS	FC	AgI	AgL
SR	Open Draw Creek	Tributary to the East Fork of Black River at 33°49'52"/109°18'18"		A&Wc				FBC			FC		AgL
SR	P B Creek	Headwaters to Forest Service Road #203 at 33°57'08"/110°56'09"		A&Wc				FBC			FC		AgL
SR	P B Creek	Below Forest Service Road #203 to Cherry Creek at 33°55'34"/110°54'18"			A&Ww			FBC			FC		AgL
SR	Pinal Creek	Headwaters to confluence with unnamed EDW wash (Globe WWTP) at 33°25'29"/110°48'18"				A&We			PBC				AgL
SR	Pinal Creek (EDW)	Globe WWTP outfall on unnamed wash at 33°25'46"/110°47'28" to confluence with Pinal Creek to Radium at 33°26'54"/110°49'02"					A&Wedw		PBC				
SR	Pinal Creek	Radium to lower Pinal Creek water treatment plant discharge at 33°32'05"/110°52'17"				A&We			PBC				AgL
SR	Pinal Creek	Lower Pinal Creek WTP outfall #1 at 33°31'56"/110°52'14" to See Ranch Crossing at 33°32'25"/110°52'28"					A&Wedw		PBC				
SR	Pinal Creek	See Ranch Crossing to 33°35'33"/110°54'33"			A&Ww			FBC					
SR	Pinal Creek	From 33°35'33"/110°54'33" to Salt River			A&Ww			FBC			FC		
SR	Pine Creek	Tributary to the Salt River at 33°36'04"/111°12'36"			A&Ww			FBC			FC		
SR	Pinto Creek	Headwaters to confluence with unnamed tributary at 33°19'27"/110°54'56"		A&Wc				FBC			FC	AgI	AgL
SR	Pinto Creek	Below confluence with unnamed tributary to Roosevelt Lake at 33°39'11"/111°00'43"			A&Ww			FBC			FC	AgI	AgL
SR	Pueblo Canyon Creek	Headwaters to confluence with unnamed tributary at 33°50'30"/110°53'13"		A&Wc				FBC			FC		AgL
SR	Pueblo Canyon Creek	Below confluence with unnamed tributary to Cherry Creek at 33°52'30"/110°52'55"			A&Ww			FBC			FC		AgL
SR	Reevis Creek	Tributary to Pine Creek at 33°33'07"/111°09'40"			A&Ww			FBC			FC		

Watershed	Surface Waters	Segment Description and Location (Latitude and Longitudes are in NAD 27)	Lake Category	Aquatic and Wildlife				Human Health				Agricultural	
				A&Wc	A&Ww	A&We	A&Wedw	FBC	PBC	DWS	FC	AgI	AgL
SR	Reservation Creek	Tributary to the Black River at 33°41'42"/109°28'26"		A&Wc				FBC			FC		AgL
SR	Reynolds Creek	Tributary to Workman Creek at 33°52'16"/111°00'14"		A&Wc				FBC			FC		AgL
SR	Roosevelt Lake	33°40'45"/111°09'15"	Deep		A&Ww			FBC		DWS	FC	AgI	AgL
SR	Russell Gulch	From headwaters to confluence with Miami Wash				A&We			PBC				
SR	Rye Creek	Tributary to Tonto Creek at 34°01'41"/111°17'06"			A&Ww			FBC			FC		AgL
SR	Saguaro Lake	33°34'00"/111°32'06"	Deep		A&Ww			FBC		DWS	FC	AgI	AgL
SR	Salome Creek	Tributary to the Salt River at 33°41'56"/111°05'46"			A&Ww			FBC			FC	AgI	AgL
SR	Salt River	Confluence of White River and Black River to Roosevelt Lake			A&Ww			FBC			FC	AgI	AgL
SR	Salt River	Theodore Roosevelt Dam to 2 km below Granite Reef Dam			A&Ww			FBC		DWS	FC	AgI	AgL
SR	Slate Creek	Tributary to Tonto Creek at 33°56'24"/111°18'25"			A&Ww			FBC			FC		AgL
SR	Snake Creek (OAW)	Tributary to the Black River at 33°40'30"/109°28'55"		A&Wc				FBC			FC		AgL
SR	Spring Creek	Tributary to Tonto Creek at 34°09'54"/111°10'08"			A&Ww			FBC			FC		AgL
SR	Stinky Creek (OAW)	Tributary to the Black River, West Fork at 33°51'22"/109°27'07"		A&Wc				FBC			FC		AgL
SR	Thomas Creek	Tributary to Beaver Creek at 33°42'29"/109°15'11"		A&Wc				FBC			FC		AgL
SR	Thompson Creek	Tributary to the West Fork of the Black River at 33°53'24"/109°28'48"		A&Wc				FBC			FC		AgL
SR	Tonto Creek	Headwaters to confluence with unnamed tributary at 34°18'10"/111°04'14"		A&Wc				FBC			FC	AgI	AgL
SR	Tonto Creek	Below confluence with unnamed tributary to Roosevelt Lake at 33°45'14"/111°14'17"			A&Ww			FBC			FC	AgI	AgL
SR	Turkey Creek	Tributary to Rock Creek at 33°58'30"/111°06'47"		A&Wc				FBC			FC		
SR	Unnamed Wash (EDW)	Cobre Valley Plaza WWTP at 33°24'56"/110°49'43" to confluence with Russell Gulch					A&Wedw		PBC				
SR	Wildcat Creek	Tributary to Centerfire Creek at 33°43'41"/109°26'28"		A&Wc				FBC			FC		AgL
SR	Willow Creek	Tributary to Beaver Creek at 33°43'52"/109°18'04"		A&Wc				FBC			FC		AgL
SR	Workman Creek	Headwaters to confluence with Reynolds Creek at 33°52'17"/111°00'14.5"		A&Wc				FBC			FC	AgI	AgL
SR	Workman Creek	Below confluence with Reynolds Creek to Salome Creek at 33°52'37"/111°02'20"			A&Ww			FBC			FC	AgI	AgL
UG	Apache Creek	Tributary to the Gila River at 32°52'08"/109°11'53"			A&Ww			FBC			FC		AgL
UG	Ash Creek	Headwaters to confluence with unnamed tributary at 32°45'37"/109°52'22"		A&Wc				FBC			FC		AgL
UG	Ash Creek	Below confluence with unnamed tributary to Gila River at 32°53'35"/109°47'34.8"			A&Ww			FBC			FC		AgL
UG	Bennett Wash (EDW)	ADOC-Safford WWTP outfall at 32°50'20"/109°34'44" to the Gila River					A&Wedw		PBC				
UG	Bitter Creek	Tributary to the Gila River at 32°50'17"/109°10'59"			A&Ww			FBC			FC		
UG	Blue River	Headwaters to confluence with Strayhorse Creek at 33°29'02"/110°12'12"		A&Wc				FBC			FC	AgI	AgL
UG	Blue River	Below confluence with Strayhorse Creek to San Francisco River at 33°12'36"/109°11'27.6"			A&Ww			FBC			FC	AgI	AgL
UG	Bonita Creek (OAW)	San Carlos Indian Reservation to the Gila River at 32°53'35"/109°28'41"			A&Ww			FBC		DWS	FC		AgL
UG	Buckalou Creek	Tributary to Castle Creek at 33°43'34"/109°09'07"		A&Wc				FBC			FC		AgL
UG	Campbell Blue Creek	Tributary to the Blue River at 33°43'30"/109°02'46"		A&Wc				FBC			FC		AgL
UG	Castle Creek	Tributary to Campbell Blue Creek at 33°44'06"/109°08'10"		A&Wc				FBC			FC		AgL
UG	Cave Creek (OAW)	Headwaters to confluence with South Fork Cave Creek at 31°53'04"/109°10'27"		A&Wc				FBC			FC	AgI	AgL
UG	Cave Creek (OAW)	Below confluence with South Fork Cave Creek to Coronado National Forest boundary			A&Ww			FBC			FC	AgI	AgL
UG	Cave Creek	Below Coronado National Forest boundary to New Mexico border at 31°58'19"/109°03'00"			A&Ww			FBC			FC	AgI	AgL
UG	Cave Creek, South Fork	Tributary to Cave Creek at 31°53'04"/109°10'27"		A&Wc				FBC			FC	AgI	AgL
UG	Chase Creek	Headwaters to the Phelps-Dodge Morenci Mine			A&Ww			FBC			FC		AgL
UG	Chase Creek	Below the Phelps-Dodge Morenci Mine to San Francisco River				A&We			PBC				

Department of Environmental Quality – Water Quality Standards

Watershed	Surface Waters	Segment Description and Location (Latitude and Longitudes are in NAD 27)	Lake Category	Aquatic and Wildlife				Human Health				Agricultural	
				A&Wc	A&Ww	A&We	A&Wedw	FBC	PBC	DWS	FC	AgI	AgL
UG	Chitty Canyon Creek	Tributary to Salt House Creek at 33°30'32"/109°24'04"		A&Wc				FBC			FC		AgL
UG	Cima Creek	Tributary to Cave Creek at 31°52'19"/109°14'02"		A&Wc				FBC			FC		AgL
UG	Cluff Ranch Pond #1	32°48'55"/109°49'15"	Sedimentary		A&Ww			FBC			FC	AgI	AgL
UG	Cluff Ranch Pond #2	32°49'15"/109°50'33"	Sedimentary		A&Ww			FBC			FC	AgI	AgL
UG	Cluff Ranch Pond #3	32°48'20"/109°51'43"	Sedimentary		A&Ww			FBC			FC	AgI	AgL
UG	Coleman Creek	Tributary to Campbell Blue Creek at 33°44'20"/109°09'32"		A&Wc				FBC			FC		AgL
UG	Dankworth Ponds	32°43'15"/109°42'15"	Sedimentary	A&Wc				FBC			FC		
UG	Deadman Canyon Creek	Headwaters to confluence with unnamed tributary at 32°43'50"/109°49'01"		A&Wc				FBC		DWS	FC		AgL
UG	Deadman Canyon Creek	Below confluence with unnamed tributary to confluence with Graveyard Wash at 32°46'48"/109°44'13"			A&Ww			FBC		DWS	FC		AgL
UG	Eagle Creek	Headwaters to confluence with unnamed tributary at 33°23'24"/109°29'35"		A&Wc				FBC		DWS	FC	AgI	AgL
UG	Eagle Creek	Below confluence with unnamed tributary to Eagle Creek at 32°57'36"/109°24'21.6"			A&Ww			FBC		DWS	FC	AgI	AgL
UG	East Eagle Creek	Tributary to Eagle Creek at 33°29'38"/109°28'05"		A&Wc				FBC			FC		AgL
UG	East Turkey Creek	Headwaters to confluence with unnamed tributary at 31°58'22"/109°12'17"		A&Wc				FBC			FC		AgL
UG	East Turkey Creek	Below confluence with unnamed tributary to terminus near San Simon River at 31°59'53"/109°07'37"			A&Ww			FBC			FC		AgL
UG	East Whitetail	Headwaters to terminus near San Simon River at 32°08'52"/109°09'25" in the Chiricahua Mountains			A&Ww			FBC			FC		AgL
UG	Emigrant Canyon	Headwaters to terminus near San Simon River at 32°17'02"/109°20'27.6" in the Chiricahua Mountains			A&Ww			FBC			FC		AgL
UG	Evans Pond	32°49'15"/109°51'15"	Sedimentary		A&Ww			FBC			FC		
UG	Fishhook Creek	Tributary to the Blue River at 33°35'13"/109°10'01"		A&Wc				FBC			FC		AgL
UG	Foote Creek	Tributary to the Blue River at 33°35'24"/109°08'49"		A&Wc				FBC			FC		AgL
UG	Frye Canyon Creek	Headwaters to Frye Mesa Reservoir at 32°45'09.5"/109°50'02"		A&Wc				FBC		DWS	FC		AgL
UG	Frye Canyon Creek	Below Frye Mesa Reservoir to Highline Canal Headwaters to terminus near San Simon River at 32°50'10"/109°45'43"			A&Ww			FBC			FC		AgL
UG	Frye Mesa Reservoir	32°45'13"/109°50'00"	Igneous	A&Wc				FBC		DWS	FC		
UG	Gibson Creek	Tributary to Marijilda Creek at 32°41'24"/109°48'11"		A&Wc				FBC			FC		AgL
UG	Gila River	New Mexico border to the San Carlos Indian Reservation at 33°05'37"/110°03'21"			A&Ww			FBC			FC	AgI	AgL
UG	Grant Creek	Tributary to the Blue River at 33°34'16"/109°10'37"		A&Wc				FBC			FC		AgL
UG	Judd Lake	33°51'15"/109°09'15"	Sedimentary	A&Wc				FBC			FC		
UG	K P Creek (OAW)	Tributary to the Blue River at 33°31'44"/109°12'04"		A&Wc				FBC			FC		AgL
UG	Lanphier Canyon Creek	Tributary to the Blue River at 33°35'42"/109°07'52"		A&Wc				FBC			FC		AgL
UG	Little Blue Creek	Headwaters to confluence with Dutch Blue Creek at 33°24'26.5"/109°09'18"		A&Wc				FBC			FC		AgL
UG	Little Blue Creek	Below confluence with Dutch Blue Creek to Blue Creek at 32°22'30"/109°10'30"			A&Ww			FBC			FC		AgL
UG	Little Creek	Tributary to the San Francisco River at 33°49'41"/109°04'26"		A&Wc				FBC			FC		
UG	Lower George's Reservoir	33°51'23.5"/109°08'28"	Sedimentary	A&Wc				FBC			FC		AgL
UG	Luna Lake	33°49'45"/109°05'15"	Sedimentary	A&Wc				FBC			FC		AgL
UG	Marijilda Creek	Headwaters to confluence with Gibson Creek at 32°41'23"/109°48'13"		A&Wc				FBC			FC		AgL
UG	Marijilda Creek	Below confluence with Gibson Creek to Stockton Wash at 32°46'30"/109°40'51.6"			A&Ww			FBC			FC	AgI	AgL
UG	Markham Creek	Tributary to the Gila River at 32°56'17"/109°53'13"			A&Ww			FBC			FC		AgL
UG	Pigeon Creek	Tributary to the Blue River at 33°16'08"/109°11'42"			A&Ww			FBC			FC		AgL
UG	Raspberry Creek	Tributary to the Blue River at 33°30'07"/109°12'32"		A&Wc				FBC			FC		
UG	Roper Lake	32°45'20"/109°42'11"	Sedimentary		A&Ww			FBC			FC		
UG	San Francisco River	Headwaters to the New Mexico border at 33°49'24.5"/109°02'46"		A&Wc				FBC			FC	AgI	AgL

Watershed	Surface Waters	Segment Description and Location (Latitude and Longitudes are in NAD 27)	Lake Category	Aquatic and Wildlife				Human Health				Agricultural	
				A&Wc	A&Ww	A&We	A&Wedw	FBC	PBC	DWS	FC	AgI	AgL
UG	San Francisco River	New Mexico border to the Gila River at 33°14'25"/109°02'49"			A&Ww			FBC			FC	AgI	AgL
UG	San Simon River	Tributary to the Gila River at 32°49'52"/109°38'53"				A&We			PBC				AgL
UG	Sheep Tank	32°46'15"/109°48'08"	Sedimentary		A&Ww			FBC			FC		AgL
UG	Smith Pond	32°49'09"/109°50'26"	Sedimentary		A&Ww			FBC			FC		
UG	Squaw Creek	Tributary to Thomas Creek at 33°23'38"/109°12'22"		A&Wc				FBC			FC		AgL
UG	Stone Creek	Tributary to the San Francisco River at 33°50'38"/109°02'46"		A&Wc				FBC			FC	AgI	AgL
UG	Strayhorse Creek	Tributary to the Blue River at 33°29'02"/109°12'11"		A&Wc				FBC			FC		
UG	Thomas Creek	Headwaters to confluence with Rousensock Creek at 33°23'45"/109°13'13"		A&Wc				FBC			FC		AgL
UG	Thomas Creek	Below confluence with Rousensock Creek to Blue River at 33°23'20"/109°11'20"			A&Ww			FBC			FC		AgL
UG	Tinny Pond	33°47'49"/109°04'23"	Sedimentary		A&Ww			FBC			FC		AgL
UG	Turkey Creek	Tributary to Campbell Blue Creek at 33°44'10"/109°04'05"		A&Wc				FBC			FC		AgL
UG	Unnamed Wash (EDW)	ADOC-Globe WWTP outfall at 33°24'55"/110°42'35" to the San Carlos Indian Reservation					A&Wedw		PBC				
VR	American Gulch	Headwaters to the Northern Gila County Sanitary District WWTP outfall (Payson) at 34°14'05"/111°22'18"			A&Ww			FBC			FC	AgI	AgL
VR	American Gulch (EDW)	Northern Gila County Sanitary District WWTP outfall (Payson) to the East Verde River at 34°14'42"/111°25'08"					A&Wedw		PBC				
VR	Apache Creek	Tributary to Walnut Creek at 34°55'12"/112°50'42"			A&Ww			FBC			FC		AgL
VR	Ashbrook Wash	Headwaters to the Fort McDowell Reservation at 33°36'54"/111°42'06"				A&We			PBC				
VR	Aspen Creek	Tributary to Granite Creek at 34°31'55"/112°28'19"			A&Ww			FBC			FC		
VR	Bar Cross Tank	35°00'40"/112°05'34"			A&Ww			FBC			FC		AgL
VR	Barrata Tank	35°02'43"/112°24'17"			A&Ww			FBC			FC		AgL
VR	Bartlett Lake	33°49'00"/111°37'45"	Deep		A&Ww			FBC		DWS	FC	AgI	AgL
VR	Beaver Creek	Tributary to the Verde River at 34°34'26"/111°51'14"			A&Ww			FBC			FC		AgL
VR	Big Chino Wash	Tributary to Sullivan Lake at 34°52'37"/112°28'37"				A&We			PBC				AgL
VR	Bitter Creek	Headwaters to the Jerome WWTP outfall at 34°45'08"/112°06'25"				A&We			PBC				AgL
VR	Bitter Creek (EDW)	Jerome WWTP outfall to the Yavapai Apache Indian Reservation at 34°45'45.5"/112°04'44"					A&Wedw		PBC				AgL
VR	Bitter Creek	Below the Yavapai Apache Indian Reservation to the Verde River at 34°46'37"/112°02'53"			A&Ww			FBC			FC	AgI	AgL
VR	Black Canyon Creek	Headwaters to confluence with unnamed tributary at 34°39'20"/112°05'05"		A&Wc				FBC			FC		AgL
VR	Black Canyon Creek	Below confluence with unnamed tributary to the Verde River at 34°40'59"/111°57'28.8"			A&Ww			FBC			FC		AgL
VR	Bonita Creek	Tributary to Ellison Creek at 34°20'56"/111°14'20"		A&Wc				FBC			FC		
VR	Bray Creek	Tributary to Webber Creek at 34°22'37"/111°20'53"		A&Wc				FBC			FC		AgL
VR	Camp Creek	Tributary to the Verde River at 33°45'32"/111°30'14"			A&Ww			FBC			FC		AgL
VR	Carter Tank	34°52'27"/112°57'28"			A&Ww			FBC			FC		AgL
VR	Cereus Wash	Headwaters to the Fort McDowell Indian Reservation at 33°34'13"/111°42'28"				A&We			PBC				
VR	Chase Creek	Tributary to the East Verde River at 34°22'48"/111°16'59"		A&Wc				FBC		DWS	FC		
VR	Clover Creek	Tributary to headwaters of West Clear Creek at 34°33'04"/111°24'11"		A&Wc				FBC			FC		AgL
VR	Coffee Creek	Tributary to Spring Creek at 34°48'18"/111°55'41"			A&Ww			FBC			FC		AgL
VR	Colony Wash	Headwaters to the Fort McDowell Indian Reservation at 33°35'42"/111°42'15"				A&We			PBC				
VR	Dead Horse Lake	34°45'00"/112°00'30"	Shallow		A&Ww			FBC			FC		
VR	Deadman Creek	Tributary to Horseshoe Reservoir at 34°00'00"/111°42'36"			A&Ww			FBC			FC		AgL
VR	Del Rio Dam Lake	34°48'55"/112°28'00"	Sedimentary		A&Ww			FBC			FC		AgL
VR	Dry Beaver Creek	Tributary to Beaver Creek at 34°37'59"/111°49'34"			A&Ww			FBC			FC	AgI	AgL
VR	Dry Creek (EDW)	Sedona Ventures WWTP outfall at 34°50'45"/111°52'15" to confluence with Dry Creek at 34°50'31"/111°52'39"					A&Wedw		PBC				

Department of Environmental Quality – Water Quality Standards

Watershed	Surface Waters	Segment Description and Location (Latitude and Longitudes are in NAD 27)	Lake Category	Aquatic and Wildlife				Human Health				Agricultural	
				A&Wc	A&Ww	A&We	A&Wedw	FBC	PBC	DWS	FC	AgI	AgL
VR	Dude Creek	Tributary to the East Verde River at 34°23'06"/111°16'26"		A&Wc				FBC			FC	AgI	AgL
VR	East Verde River	Headwaters to confluence with Ellison Creek at 34°21'10"/111°16'47.5"		A&Wc				FBC		DWS	FC	AgI	AgL
VR	East Verde River	Below confluence with Ellison Creek to the Verde River at 34°17'02"/111°40'19"			A&Ww			FBC		DWS	FC	AgI	AgL
VR	Ellison Creek	Tributary to the East Verde River at 34°21'11"/111°16'48"		A&Wc				FBC			FC		AgL
VR	Fossil Creek (OAW)	Tributary to the Verde River at 34°18'22"/111°40'30"			A&Ww			FBC			FC		AgL
VR	Fossil Springs (OAW)	34°25'24"/111°34'25"			A&Ww			FBC		DWS	FC		
VR	Foxboro Lake	34°53'48"/111°40'00"			A&Ww			FBC			FC		AgL
VR	Fry Lake	35°03'45"/111°48'02"			A&Ww			FBC			FC		AgL
VR	Gap Creek	Headwaters to Government Spring at 34°23'23"/111°50'53.5"		A&Wc				FBC			FC		AgL
VR	Gap Creek	Below Government Spring to the Verde River at 34°24'50"/111°46'51.6"			A&Ww			FBC			FC		AgL
VR	Garrett Tank	35°18'57"/112°42'16"			A&Ww			FBC			FC		AgL
VR	Goldwater Lake, Lower	34°29'55"/112°27'18"	Sedimentary	A&Wc				FBC		DWS	FC		
VR	Goldwater Lake, Upper	34°29'51"/112°26'55"	Igneous	A&Wc				FBC		DWS	FC		
VR	Granite Basin Lake	34°37'01"/112°42'16"	Igneous	A&Wc				FBC			FC	AgI	AgL
VR	Granite Creek	Headwaters to Watson Lake at 34°35'15"/112°25'05"		A&Wc				FBC			FC	AgI	AgL
VR	Granite Creek	Below Watson Lake to the Verde River at 34°52'54"/112°25'05"			A&Ww			FBC			FC	AgI	AgL
VR	Heifer Tank	35°20'28"/112°32'56"			A&Ww			FBC			FC		AgL
VR	Hell Canyon Tank	35°05'00"/112°24'06"	Igneous		A&Ww			FBC			FC		AgL
VR	Homestead Tank	35°21'23"/112°41'32"	Igneous		A&Ww			FBC			FC		AgL
VR	Horse Park Tank	34°58'15"/111°36'29"			A&Ww			FBC			FC		AgL
VR	Horseshoe Reservoir	33°59'00"/111°42'30"	Sedimentary		A&Ww			FBC			FC	AgI	AgL
VR	Houston Creek	Tributary to the Verde River at 34°16'55"/111°41'06"			A&Ww			FBC			FC		AgL
VR	J.D. Dam Lake	35°04'01"/112°01'40"	Shallow	A&Wc				FBC			FC	AgI	AgL
VR	Jacks Canyon Wash	Headwaters to Big Park WWTP outfall at 34°45'32"/111°45'10"				A&We				PBC			
VR	Jacks Canyon Wash (EDW)	Big Park WWTP outfall to Dry Beaver Creek at 34°44'28"/111°46'01"					A&Wedw			PBC			
VR	Lime Creek	Tributary to Horseshoe Reservoir at 33°59'20"/111°44'13"			A&Ww			FBC			FC		AgL
VR	McLellan Reservoir	35°13'15"/112°17'05"	Igneous		A&Ww			FBC			FC	AgI	AgL
VR	Meath Dam Tank	35°07'46"/112°27'35"			A&Ww			FBC			FC		AgL
VR	Mullican Place Tank	34°44'16"/111°36'08"	Igneous		A&Ww			FBC			FC		AgL
VR	Oak Creek (OAW)	Headwaters to confluence with unnamed tributary at 34°57'08.5"/111°45'13"		A&Wc				FBC		DWS	FC	AgI	AgL
VR	Oak Creek (OAW)	Below confluence with unnamed tributary at 34°57'08.5"/111°45'13" to Verde River			A&Ww			FBC		DWS	FC	AgI	AgL
VR	Oak Creek, West Fork (OAW)	Tributary to Oak Creek at 34°59'13"/111°44'46"		A&Wc				FBC			FC		AgL
VR	Odell Lake	34°56'02"/111°37'52"	Igneous	A&Wc				FBC			FC		
VR	Peck's Lake	34°47'07"/112°02'30"	Shallow		A&Ww			FBC			FC	AgI	AgL
VR	Perkins Tank	35°06'42"/112°04'08"	Shallow	A&Wc				FBC			FC		AgL
VR	Pine Creek	Headwaters to confluence with unnamed tributary at 34°21'51"/111°26'46"		A&Wc				FBC		DWS	FC	AgI	AgL
VR	Pine Creek	Below confluence with unnamed tributary to East Verde River at 34°13'19"/111°29'27.6"			A&Ww			FBC		DWS	FC	AgI	AgL
VR	Red Creek	Tributary to the Verde River at 34°09'47"/111°43'12"			A&Ww			FBC			FC		AgL
VR	Red Lake	35°12'19"/113°03'55"	Sedimentary		A&Ww			FBC			FC		AgL
VR	Reservoir #1	35°13'05"/111°50'07"	Igneous		A&Ww			FBC			FC		
VR	Reservoir #2	35°13'16"/111°50'36"	Igneous		A&Ww			FBC			FC		
VR	Roundtree Canyon Creek	Tributary to Tangle Creek at 34°09'04"/111°48'18"			A&Ww			FBC			FC		AgL
VR	Scholze Lake	35°11'53"/112°00'31"	Igneous	A&Wc				FBC			FC		AgL
VR	Spring Creek	Headwaters to confluence with unnamed tributary at 34°57'23.5"/111°57'19"		A&Wc				FBC			FC	AgI	AgL
VR	Spring Creek	Below confluence with unnamed tributary at 34°44'38"/111°54'19" to Oak Creek			A&Ww			FBC			FC	AgI	AgL
VR	Steel Dam Lake	35°13'36"/112°24'51"	Igneous	A&Wc				FBC			FC		AgL
VR	Stehr Lake	34°21'59"/111°40'00"	Sedimentary		A&Ww			FBC			FC		AgL

Watershed	Surface Waters	Segment Description and Location (Latitude and Longitudes are in NAD 27)	Lake Category	Aquatic and Wildlife				Human Health			Agricultural		
				A&Wc	A&Ww	A&We	A&Wedw	FBC	PBC	DWS	FC	AgI	AgL
VR	Stone Dam Lake	35°13'36"/112°24'16"		A&Wc				FBC			FC	AgI	AgL
VR	Stoneman Lake	34°46'44"/111°31'05"	Shallow	A&Wc				FBC			FC	AgI	AgL
VR	Sullivan Lake	34°51'46"/112°27'41"			A&Ww			FBC			FC	AgI	AgL
VR	Sycamore Creek	Headwaters to confluence with unnamed tributary at 35°03'40"/111°57'28"		A&Wc				FBC			FC	AgI	AgL
VR	Sycamore Creek	Below confluence with unnamed tributary to Verde River at 34°51'47"/112°04'41"			A&Ww			FBC			FC	AgI	AgL
VR	Sycamore Creek	Tributary to Verde River at 33°37'55"/111°39'58"			A&Ww			FBC			FC	AgI	AgL
VR	Sycamore Creek	Tributary to Verde River at 34°04'42"/111°42'14"			A&Ww			FBC			FC		AgL
VR	Tangle Creek	Tributary to Verde River at 34°05'06"/111°42'36"			A&Ww			FBC			FC	AgI	AgL
VR	Trinity Tank	35°27'44"/112°47'56"			A&Ww			FBC			FC		AgL
VR	Unnamed Wash	Flagstaff Meadows WWTP outfall at 36°14'17"/111°49'28" to Volunteer Wash at 35°11'55"/111°49'42"					A&Wedw		PBC				
VR	Verde River	Above Bartlett Dam from confluence of Chino Wash and Granite Creek to Bartlett Lake			A&Ww			FBC			FC	AgI	AgL
VR	Verde River	Below Bartlett Lake Dam to Salt River			A&Ww			FBC		DWS	FC	AgI	AgL
VR	Walnut Creek	Tributary to Big Chino Wash at 34°58'12"/112°34'55"			A&Ww			FBC			FC		AgL
VR	Watson Lake	34°35'15"/112°25'05"	Igneous		A&Ww			FBC			FC	AgI	AgL
VR	Webber Creek	Tributary to the East Verde River at 34°18'50"/111°19'55"		A&Wc				FBC			FC		AgL
VR	West Clear Creek	Headwaters to confluence with Meadow Canyon at 34°33'40"/111°31'30"		A&Wc				FBC			FC		AgL
VR	West Clear Creek	Below confluence with Meadow Canyon to the Verde River at 34°30'14"/111°49'41"			A&Ww			FBC			FC	AgI	AgL
VR	Wet Beaver Creek	Headwaters to unnamed springs at 34°41'17"/111°34'34"		A&Wc				FBC			FC	AgI	AgL
VR	Wet Beaver Creek	Below unnamed springs to Dry Beaver Creek at 34°37'59"/111°49'33.6"			A&Ww			FBC			FC	AgI	AgL
VR	Whitehorse Lake	35°07'00"/112°00'47"	Igneous	A&Wc				FBC		DWS	FC	AgI	AgL
VR	Williamson Valley Wash	Headwaters to confluence with Mint Wash at 34°49'05"/112°37'55"					A&We		PBC				AgL
VR	Williamson Valley Wash	Confluence of Mint Wash to 10.5 km downstream at 34°49'05"/111°37'55"			A&Ww			FBC			FC		AgL
VR	Williamson Valley Wash	Below 10.5 km downstream of Mint Wash confluence to Big Chino Wash at 32°52'52"/112°28'48"					A&We		PBC				AgL
VR	Williscraft Tank	35°11'23"/112°35'38"			A&Ww			FBC			FC		AgL
VR	Willow Creek	Above Willow Creek Reservoir	Shallow	A&Wc				FBC			FC		AgL
VR	Willow Creek	Below Willow Creek Reservoir to confluence with Granite Creek			A&Ww			FBC			FC		AgL
VR	Willow Creek Reservoir	34°36'17"/112°26'19"	Shallow		A&Ww			FBC			FC	AgI	AgL
VR	Willow Valley Lake	34°41'08"/111°19'57"	Sedimentary		A&Ww			FBC			FC		AgL

Watersheds

BW = Bill Williams
 CG = Colorado – Grand Canyon
 CL = Colorado – Lower Gila
 LC = Little Colorado
 MG = Middle Gila
 SC = Santa Cruz – Rio Magdalena – Rio Sonoyta
 SP = San Pedro – Willcox Playa – Rio Yaqui

SR = Salt River
 UG = Upper Gila
 VR = Verde River

Other Abbreviations

WWTP = Wastewater Treatment Plant
 Km = kilometers

Historical Note

Adopted effective February 18, 1992 (Supp. 92-1). Appendix B repealed, new Appendix B adopted effective April 24, 1996 (Supp. 96-2). Amended by final rulemaking at 8 A.A.R. 1264, effective March 8, 2002 (Supp. 02-1). Amended by final rulemaking at 14 A.A.R. 4708, effective January 31, 2009 (Supp. 08-4).

APPENDIX C. SITE-SPECIFIC STANDARDS

Watershed	Surface Water	Surface Water Description & Location	Parameter	Site-Specific Criterion
LC	Rio de Flag (EDW)	Flagstaff WWTP outfall to the confluence with San Francisco Wash at 35°14'04"/111°28'02.5"	Copper (D)	36 µg/L

Watershed	Surface Water	Surface Water Description & Location	Parameter	Site-Specific Criterion
CL	Yuma East Wetlands	From inlet culvert from Colorado River into restored channel to Ocean bridge	Selenium (T) Total residual chlorine	2.2 mg/L 33 µg/L (A&Ww acute) 20 µg/L (A&Ww chronic)

Historical Note

Adopted effective February 18, 1992 (Supp. 92-1). Appendix C repealed effective April 24, 1996 (Supp. 96-2). New Appendix C made by final rulemaking at 14 A.A.R. 4708, effective January 31, 2009 (Supp. 08-4).

ARTICLE 2. REPEALED**R18-11-201. Repealed****Historical Note**

Amended effective January 29, 1980 (Supp. 80-1). Amended subsection A. effective April 17, 1984 (Supp. 84-2). Former Section R9-21-201 repealed, former Section R9-21-203 renumbered as Section R9-21-201 and amended effective January 7, 1985 (Supp. 85-1). Amended effective August 12, 1986 (Supp. 86-4). Former Section R9-21-201 renumbered without change as Section R18-11-201 (Supp. 87-3). Amended effective December 1, 1988 (Supp. 88-4). Section repealed effective February 18, 1992 (Supp. 92-1).

R18-11-202. Repealed**Historical Note**

Former Section R9-21-202 repealed, former Section R9-21-102 renumbered as Section R9-21-202 and amended effective January 7, 1985 (Supp. 85-1). Amended subsections (B), (D), and (E) effective August 12, 1986 (Supp. 86-4). Former Section R9-21-202 renumbered without change as Section R18-11-202 (Supp. 87-3). Section repealed, new Section adopted effective February 18, 1992 (Supp. 92-1). Section repealed effective April 24, 1996 (Supp. 96-2).

R18-11-203. Repealed**Historical Note**

Amended effective January 29, 1980 (Supp. 80-1). Amended subsection (B) by adding paragraphs (27) and (28) effective October 14, 1981 (Supp. 81-5). Former Section R9-21-203 renumbered as Section R9-21-201, former Section R9-21-204 renumbered as Section R9-21-203 and amended effective January 7, 1985 (Supp. 85-1). Former Section R9-21-203 renumbered and amended as Section R9-21-204, new Section R9-21-203 adopted effective August 12, 1986 (Supp. 86-4). Former Section R9-21-203 renumbered without change as Section R18-11-203 (Supp. 87-3). Amended subsection (B) effective December 1, 1988 (Supp. 88-4). Section repealed, new Section adopted effective February 18, 1992 (Supp. 92-1). Section repealed effective April 24, 1996 (Supp. 96-2).

R18-11-204. Repealed**Historical Note**

Former Section R9-21-204 renumbered and amended as Section R9-21-207, former Section R9-21-206 renumbered and amended as Section R9-21-204 effective January 29, 1980 (Supp. 80-1). Former Section R9-21-204 renumbered as Section R9-21-203, former Section R9-21-205 renumbered as Section R9-21-204

and amended effective January 7, 1985 (Supp. 85-1). Former Section R9-21-204 renumbered and amended as Section R9-21-205, former Section R9-21-203 renumbered and amended as Section R9-21-204 effective August 12, 1986 (Supp. 86-4). Former Section R9-21-204 renumbered without change as Section R18-11-204 (Supp. 87-3). Section repealed effective February 18, 1992 (Supp. 92-1).

R18-11-205. Repealed**Historical Note**

Former Section R9-21-205 repealed, new Section R9-21-205 adopted effective January 29, 1980 (Supp. 80-1). Former Section R9-21-205 renumbered as Section R9-21-204, former Section R9-21-206 renumbered as Section R9-21-205 and amended effective January 7, 1985 (Supp. 85-1). Former Section R9-21-205 renumbered and amended as Section R9-21-206, former Section R9-21-204 renumbered and amended as Section R9-21-205 effective August 12, 1986 (Supp. 86-4). Former Section R9-21-205 renumbered without change as Section R18-11-205 (Supp. 87-3). Section repealed, new Section adopted effective February 18, 1992 (Supp. 92-1). Section repealed April 24, 1996 (Supp. 96-2).

R18-11-206. Repealed**Historical Note**

Former Section R9-21-206 renumbered and amended as Section R9-21-204, new Section R9-21-206 adopted effective January 29, 1980 (Supp. 80-1). Amended by adding subsection (B) effective October 14, 1981 (Supp. 81-5). Amended subsection (B) and Table 1 effective January 29, 1982 (Supp. 82-1). Amended subsection (B) and Table 1 effective August 13, 1982 (Supp. 82-4). Former Section R9-21-206 renumbered as Section R9-21-205, former Section R9-21-207 renumbered as Section R9-21-206 and amended effective January 7, 1985 (Supp. 85-1). Former Section R9-21-206 renumbered and amended as Section R9-21-207, former Section R9-21-205 renumbered and amended as Section R9-21-206 effective August 12, 1986 (Supp. 86-4). Former Section R9-21-206 renumbered without change as Section R18-11-206 (Supp. 87-3).

R18-11-207. Repealed**Historical Note**

Former Section R9-21-207 repealed, former Section R9-21-204 renumbered and amended as Section R9-21-207 effective January 29, 1980 (Supp. 80-1). Former Section R9-21-207 renumbered as Section R9-21-206, former Section R9-21-208 renumbered as Section R9-21-207 and amended effective January 7,

1985 (Supp. 85-1). Former Section R9-21-207 renumbered without change as Section R9-21-208, former Section R9-21-206 renumbered and amended as Section R9-21-207 effective August 12, 1986 (Supp. 86-4). Former Section R9-21-207 renumbered without change as Section R18-11-207 (Supp. 87-3). Section repealed effective February 18, 1992 (Supp. 92-1).

R18-11-208. Repealed**Historical Note**

Former Section R9-21-208 repealed, new Section R9-21-208 adopted effective January 29, 1980 (Supp. 80-1). Former Section R9-21-208 renumbered as Section R9-21-207, Appendices 1 through 9 amended as Appendix A (now shown following R9-21-213), former Section

R9-21-209 renumbered as R9-21-208 and amended effective January 7, 1985 (Supp. 85-1). Former Section R9-21-208 renumbered and amended as Section R9-21-209, former Section R9-21-207 renumbered without change as Section R9-21-208 effective August 12, 1986 (Supp. 86-4). Former Section R9-21-208 renumbered without change as Section R18-11-208 (Supp. 87-3). Section repealed effective February 18, 1992 (Supp. 92-1).

R18-11-209. Repealed**Historical Note**

Former Section R9-21-209 renumbered and amended as Section R9-21-210, new Section R9-21-209 adopted effective January 29, 1980 (Supp. 80-1). Former Section R9-21-209 renumbered as Section R9-21-208, Tables I and II amended as Appendix B (now shown following R9-21-213 and Appendix A), former Section R9-21-210 renumbered as Section R9-21-209 and amended effective January 7, 1985 (Supp. 85-1). Former Section R9-21-209 renumbered and amended as Section R9-21-210, former Section R9-21-208 renumbered and amended as Section R9-21-209 effective August 12, 1986 (Supp. 86-4). Former Section R9-21-209 renumbered without change as Section R18-11-209 (Supp. 87-3). Section repealed effective February 18, 1992 (Supp. 92-1).

R18-11-210. Repealed**Historical Note**

Former Section R9-21-210 renumbered and amended as Section R9-21-211, former Section R9-21-209 renumbered and amended as Section R9-21-210 effective January 29, 1980 (Supp. 80-1). Amended subsection (A) effective April 17, 1984 (Supp. 84-2). Former Section R9-21-210 renumbered as Section R9-21-209, former Section R9-21-211 renumbered as Section R9-21-210 and amended effective January 7, 1985 (Supp. 85-1). Former Section R9-21-210 renumbered and amended as Section R9-21-211, former Section R9-21-209 renumbered and amended as Section R9-21-210 effective August 12, 1986 (Supp. 86-4). Former Section R9-21-210 renumbered without change as Section R18-11-210 (Supp. 87-3). Section repealed effective February 18, 1992 (Supp. 92-1).

R18-11-211. Repealed**Historical Note**

Former Section R9-21-210 renumbered and amended as Section R9-21-211 effective January 29, 1980 (Supp. 80-

1). Amended subsections (D), (G) three (I), and added (J) effective October 14, 1981 (Supp. 81-5). Former Section R9-21-211 renumbered as Section R9-21-210, former Section R9-21-212 renumbered as Section R9-21-211 and amended effective January 7, 1985 (Supp. 85-1). Former Section R9-21-211 renumbered and amended as Section R9-21-212, former Section R9-21-210 renumbered and amended as Section R9-21-211 effective August 12, 1986 (Supp. 86-4). Former Section R9-21-211 renumbered without change as Section R18-11-211 (Supp. 87-3). Section repealed effective February 18, 1992 (Supp. 92-1).

R18-11-212. Repealed**Historical Note**

Adopted effective January 29, 1980 (Supp. 80-1). Former Section R9-21-212 renumbered as Section R9-21-211, former Section R9-21-213 renumbered as Section R9-21-212 and amended effective January 7, 1985 (Supp. 85-1). Former Section R9-21-212 repealed, former Section R9-21-211 renumbered and amended as Section R9-21-212 effective August 12, 1986 (Supp. 86-4). Former Section R9-21-212 renumbered without change as Section R18-11-212 (Supp. 87-3). Section repealed effective February 18, 1992 (Supp. 92-1).

R18-11-213. Repealed**Historical Note**

Adopted effective January 29, 1980 (Supp. 80-1). Amended effective April 17, 1984 (Supp. 84-2). Former Section R9-21-213 renumbered as Section R9-21-212, former Section R9-21-103 renumbered as Section R9-21-213 and amended effective January 7, 1985 (Supp. 85-1). Former Section R9-21-213 renumbered without change as Section R9-21-214, new Section R9-21-213 adopted effective August 12, 1986 (Supp. 86-4). Former Section R9-21-213 renumbered without change as Section R18-11-213 (Supp. 87-3). Amended effective December 1, 1988 (Supp. 88-4). Section repealed effective February 18, 1992 (Supp. 92-1).

R18-11-214. Repealed**Historical Note**

Former Section R9-21-213 renumbered without change as Section R9-21-214 effective August 12, 1986 (Supp. 86-4). Former Section R9-21-214 renumbered without change as Section R18-11-214 (Supp. 87-3). Section repealed effective February 18, 1992 (Supp. 92-1).

Appendix A. Repealed**Historical Note**

Former Section R9-21-208, Appendices 1 through 9 renumbered and amended as new Appendix A adopted effective January 7, 1985 (Supp. 85-1). Amended effective August 12, 1986 (Supp. 86-4). Appendix repealed effective February 18, 1992 (Supp. 92-1).

Appendix B. Repealed**Historical Note**

Former R9-21-209, Table 1 and Table 2 renumbered and amended as Appendix B adopted effective January 7, 1985 (Supp. 85-1). Amended effective August 12, 1986 (Supp. 86-4). Appendix repealed effective February 18, 1992 (Supp. 92-1).

ARTICLE 3. RECLAIMED WATER QUALITY STANDARDS

R18-11-301. Definitions

The terms in this Article have the following meanings:

- “Direct reuse” has the meaning prescribed in R18-9-701(1).
- “Disinfection” means a treatment process that uses oxidants, ultraviolet light, or other agents to kill or inactivate pathogenic organisms in wastewater.
- “Filtration” means a treatment process that removes particulate matter from wastewater by passage through porous media.
- “Gray water” means wastewater, collected separately from a sewage flow, that originates from a clothes washer, bathtub, shower, or sink, but it does not include wastewater from a kitchen sink, dishwasher, or a toilet.
- “Industrial wastewater” means wastewater generated from an industrial process.
- “Landscape impoundment” means a manmade lake, pond, or impoundment of reclaimed water where swimming, wading, boating, fishing, and other water-based recreational activities are prohibited. A landscape impoundment is created for storage, landscaping, or for aesthetic purposes only.
- “NTU” means nephelometric turbidity unit.
- “On-site wastewater treatment facility” has the meaning prescribed in A.R.S. § 49-201(24).
- “Open access” means that access to reclaimed water by the general public is uncontrolled.
- “Reclaimed water” has the meaning prescribed in A.R.S. § 49-201(31).
- “Recreational impoundment” means a manmade lake, pond, or impoundment of reclaimed water where boating or fishing is an intended use of the impoundment. Swimming and other full-body recreation activities (for example, water-skiing) are prohibited in a recreational impoundment.
- “Restricted access” means that access to reclaimed water by the general public is controlled.
- “Secondary treatment” means a biological treatment process that achieves the minimum level of effluent quality defined by the federal secondary treatment regulation at 40 CFR § 133.102.
- “Sewage” means untreated wastes from toilets, baths, sinks, lavatories, laundries, and other plumbing fixtures in places of human habitation, employment, or recreation.

Historical Note

Adopted effective July 9, 1981 (Supp. 81-4). Former Section R9-21-301 renumbered without change as Section R18-11-301 (Supp. 87-3). Section repealed effective February 18, 1992 (Supp. 92-1). New Section adopted by final rulemaking at 7 A.A.R. 870, effective January 22, 2001 (Supp. 01-1).

R18-11-302. Applicability

This Article applies to the direct reuse of reclaimed water, except for:

1. The direct reuse of gray water, or
2. The direct reuse of reclaimed water from an onsite wastewater treatment facility regulated by a general Aquifer Protection Permit under 18 A.A.C. 9, Article 3.

Historical Note

Adopted effective June 8, 1981 (Supp. 81-3). Amended effective January 7, 1985 (Supp. 85-1). Former Section

R9-21-302 renumbered without change as Section R18-11-302 (Supp. 87-3). Section repealed effective February 18, 1992 (Supp. 92-1). New Section adopted by final rulemaking at 7 A.A.R. 870, effective January 22, 2001 (Supp. 01-1).

R18-11-303. Class A+ Reclaimed Water

- A.** Class A+ reclaimed water is wastewater that has undergone secondary treatment, filtration, nitrogen removal treatment, and disinfection. Chemical feed facilities to add coagulants or polymers are required to ensure that filtered effluent before disinfection complies with the 24-hour average turbidity criterion prescribed in subsection (B)(1). Chemical feed facilities may remain idle if the 24-hour average turbidity criterion in (B)(1) is achieved without chemical addition.
- B.** An owner of a facility shall ensure that:
1. The turbidity of Class A+ reclaimed water at a point in the wastewater treatment process after filtration and immediately before disinfection complies with the following:
 - a. The 24-hour average turbidity of filtered effluent is two NTUs or less, and
 - b. The turbidity of filtered effluent does not exceed five NTUs at any time.
 2. Class A+ reclaimed water meets the following criteria after disinfection treatment and before discharge to a reclaimed water distribution system:
 - a. There are no detectable fecal coliform organisms in four of the last seven daily reclaimed water samples taken, and
 - b. The single sample maximum concentration of fecal coliform organisms in a reclaimed water sample is less than 23 / 100 ml.
 - c. If alternative treatment processes or alternative turbidity criteria are used, or reclaimed water is blended with other water to produce Class A+ reclaimed water under subsection (C), there are no detectable enteric virus in four of the last seven monthly reclaimed water samples taken.
 3. The 5-sample geometric mean concentration of total nitrogen in a reclaimed water sample is less than 10 mg / L.
- C.** An owner of a facility may use alternative treatment methods other than those required by subsection (A), or comply with alternative turbidity criteria other than those required by subsection (B)(1), or blend reclaimed water with other water to produce Class A+ reclaimed water provided the owner demonstrates through pilot plant testing, existing water quality data, or other means that the alternative treatment methods, alternative turbidity criteria, or blending reliably produces a reclaimed water that meets the disinfection criteria in subsection (B)(2) and the total nitrogen criteria in subsection (B)(3) before discharge to a reclaimed water distribution system.
- D.** Class A+ reclaimed water is not required for any type of direct reuse. A person may use Class A+ reclaimed water for any type of direct reuse listed in Table A.

Historical Note

Adopted effective January 7, 1985 (Supp. 85-1). Amended effective August 12, 1986 (Supp. 86-4). Former Section R9-21-303 renumbered without change as Section R18-11-303 (Supp. 87-3). Section repealed effective February 18, 1992 (Supp. 92-1). New Section adopted by final rulemaking at 7 A.A.R. 870, effective January 22, 2001 (Supp. 01-1).

R18-11-304. Class A Reclaimed Water

- A.** Class A reclaimed water is wastewater that has undergone secondary treatment, filtration, and disinfection. Chemical feed facilities to add coagulants or polymers are required to ensure that filtered effluent before disinfection complies with the 24-hour average turbidity criterion prescribed in subsection (B)(1). Chemical feed facilities may remain idle if the 24-hour average turbidity criterion in subsection (B)(1) is achieved without chemical addition.
- B.** An owner of a facility shall ensure that:
1. The turbidity of Class A reclaimed water at a point in the wastewater treatment process after filtration and immediately before disinfection complies with the following:
 - a. The 24-hour average turbidity of filtered effluent is two NTUs or less, and
 - b. The turbidity of filtered effluent does not exceed five NTUs at any time.
 2. Class A reclaimed water meets the following criteria after disinfection treatment and before discharge to a reclaimed water distribution system:
 - a. There are no detectable fecal coliform organisms in four of the last seven daily reclaimed water samples taken, and
 - b. The single sample maximum concentration of fecal coliform organisms in a reclaimed water sample is less than 23 / 100 ml.
 - c. If alternative treatment processes or alternative turbidity criteria are used, or reclaimed water is blended with other water to produce Class A reclaimed water under subsection (C), there are no detectable enteric virus in four of the last seven monthly reclaimed water samples taken.
- C.** An owner of a facility may use alternative treatment methods other than those required by subsection (A), or comply with alternative turbidity criteria other than those required by subsection (B)(1), or blend reclaimed water with other water to produce Class A reclaimed water provided the owner demonstrates through pilot plant testing, existing water quality data, or other means that the alternative treatment methods, alternative turbidity criteria, or blending reliably produces a reclaimed water that meets the disinfection criteria in subsection (B)(2) before discharge to a reclaimed water distribution system.
- D.** A person shall use Class A reclaimed water for a type of direct reuse listed as Class A in Table A. A person may use Class A reclaimed water for a type of direct reuse listed as Class B or Class C in Table A.

Historical Note

Adopted effective January 7, 1985 (Supp. 85-1).

Amended effective August 12, 1986 (Supp. 86-4).

Former Section R9-21-304 renumbered without change as Section R18-11-304 (Supp. 87-3). Section repealed effective February 18, 1992 (Supp. 92-1). New Section adopted by final rulemaking at 7 A.A.R. 870, effective January 22, 2001 (Supp. 01-1).

R18-11-305. Class B+ Reclaimed Water

- A.** Class B+ reclaimed water is wastewater that has undergone secondary treatment, nitrogen removal treatment, and disinfection.
- B.** An owner of a facility shall ensure that:
1. Class B+ reclaimed water meets the following criteria after disinfection treatment and before discharge to a reclaimed water distribution system:
 - a. The concentration of fecal coliform organisms in four of the last seven daily reclaimed water samples is less than 200 / 100 ml.
 - b. The single sample maximum concentration of fecal coliform organisms in a reclaimed water sample is less than 800 / 100 ml.
 2. The 5-sample geometric mean concentration of total nitrogen in a reclaimed water sample is less than 10 mg / L.

- C.** Class B+ reclaimed water is not required for a type of direct reuse. A person may use Class B+ reclaimed water for a type of direct reuse listed as Class B or Class C in Table A. A person shall not use Class B+ reclaimed water for a type of direct reuse listed as Class A in Table A.

Historical Note

New Section adopted by final rulemaking at 7 A.A.R. 870, effective January 22, 2001 (Supp. 01-1).

R18-11-306. Class B Reclaimed Water

- A.** Class B reclaimed water is wastewater that has undergone secondary treatment and disinfection.
- B.** An owner of a facility shall ensure that Class B reclaimed water meets the following criteria after disinfection treatment and before discharge to a reclaimed water distribution system:
 1. The concentration of fecal coliform organisms in four of the last seven daily reclaimed water samples is less than 200 / 100 ml.
 2. The single sample maximum concentration of fecal coliform organisms in a reclaimed water sample is less than 800 / 100 ml.
- C.** A person shall use a minimum of Class B reclaimed water for a type of direct reuse listed as Class B in Table A. A person may use Class B reclaimed water for a type of direct reuse listed as Class C in Table A. A person shall not use Class B reclaimed water for a type of direct reuse listed as Class A in Table A.

Historical Note

New Section adopted by final rulemaking at 7 A.A.R. 870, effective January 22, 2001 (Supp. 01-1).

R18-11-307. Class C Reclaimed Water

- A.** Class C reclaimed water is wastewater that has undergone secondary treatment in a series of wastewater stabilization ponds, including aeration, with or without disinfection.
- B.** The owner of a facility shall ensure that:
 1. The total retention time of Class C reclaimed water in wastewater stabilization ponds is at least 20 days.
 2. Class C reclaimed water meets the following criteria after treatment and before discharge to a reclaimed water distribution system:
 - a. The concentration of fecal coliform organisms in four of the last seven reclaimed water samples taken is less than 1000 / 100 ml.
 - b. The single sample maximum concentration of fecal coliform organisms in a reclaimed water sample is less than 4000 / 100 ml.
- C.** A person shall use a minimum of Class C reclaimed water for a type of direct reuse listed as Class C in Table A. A person shall not use Class C reclaimed water for a type of direct reuse listed as Class A or Class B in Table A.

Historical Note

New Section adopted by final rulemaking at 7 A.A.R. 870, effective January 22, 2001 (Supp. 01-1).

R18-11-308. Industrial Reuse

- A. The reclaimed water quality requirements for the following direct reuse applications are industry-specific and shall be determined by the Department on a case-by-case basis in a reclaimed water permit issued by the Department under 18 A.A.C. 9, Article 7:
 1. Direct reuse of industrial wastewater containing sewage.
 2. Direct reuse of industrial wastewater for the production or processing of any crop used as human or animal food.
- B. The Department shall use best professional judgment to determine the reclaimed water quality requirements needed to protect public health and the environment for a type of direct reuse specified in subsection (A).

Historical Note

New Section adopted by final rulemaking at 7 A.A.R. 870, effective January 22, 2001 (Supp. 01-1).

R18-11-309. Reclaimed Water Quality Standards for an Unlisted Type of Direct Reuse

- A. The Department may prescribe in an individual reclaimed water permit issued under 18 A.A.C. 9, Article 7, reclaimed water quality requirements for a type of direct reuse not listed in Table A. Before permitting a direct reuse of reclaimed water not listed in Table A, the Department shall, using its best professional judgment, determine and require compliance with reclaimed water quality requirements needed to protect public health and the environment.
- B. Department may determine that Class A+, A, B+, B, or C reclaimed water is appropriate for a new type of direct reuse.
- C. The Department shall consider the following factors when prescribing reclaimed water quality requirements for a new type of direct reuse:
 1. The risk to public health;
 2. The degree of public access to the site where the reclaimed water is reused and human exposure to the reclaimed water;
 3. The level of treatment necessary to ensure that the reclaimed water is aesthetically acceptable;
 4. The level of treatment necessary to prevent nuisance conditions;
 5. Specific water quality requirements for the intended type of direct reuse;
 6. The means of application of the reclaimed water;
 7. The degree of treatment necessary to avoid a violation of surface water quality standards or aquifer water quality standards;
 8. The potential for improper or unintended use of the reclaimed water;
 9. The reuse guidelines, criteria, or standards adopted or recommended by the U.S. Environmental Protection Agency or other federal or state agencies that apply to the new type of direct reuse; and
 10. Similar wastewater reclamation experience of reclaimed water providers in the United States.

Historical Note

New Section adopted by final rulemaking at 7 A.A.R. 870, effective January 22, 2001 (Supp. 01-1).

Table A. Minimum Reclaimed Water Quality Requirements for Direct Reuse

Type of Direct Reuse	Minimum Class of Reclaimed Water Required
Irrigation of food crops	A

Recreational impoundments	A
Residential landscape irrigation	A
Schoolground landscape irrigation	A
Open access landscape irrigation	A
Toilet and urinal flushing	A
Fire protection systems	A
Spray irrigation of an orchard or vineyard	A
Commercial closed loop air conditioning systems	A
Vehicle and equipment washing (does not include self-service vehicle washes)	A
Snowmaking	A
Surface irrigation of an orchard or vineyard	B
Golf course irrigation	B
Restricted access landscape irrigation	B
Landscape impoundment	B
Dust control	B
Soil compaction and similar construction activities	B
Pasture for milking animals	B
Livestock watering (dairy animals)	B
Concrete and cement mixing	B
Materials washing and sieving	B
Street cleaning	B
Pasture for non-dairy animals	C
Livestock watering (non-dairy animals)	C
Irrigation of sod farms	C
Irrigation of fiber, seed, forage, and similar crops	C
Silviculture	C

Note: Nothing in this Article prevents a wastewater treatment plant from using a higher quality reclaimed water for a type of direct reuse than the minimum class of reclaimed water listed in Table A. For example, a wastewater treatment plant may provide Class A reclaimed water for a type of direct reuse where Class B or Class C reclaimed water is acceptable.

Historical Note

New Table adopted by final rulemaking at 7 A.A.R. 870, effective January 22, 2001 (Supp. 01-1).

ARTICLE 4. AQUIFER WATER QUALITY STANDARDS

R18-11-401. Definitions

In addition to the definitions contained in A.R.S. §§ 49-101 and 49-201, the terms of this Article shall have the following meanings:

1. “Beta particle and photon radioactivity from man-made radionuclides” means all radionuclides emitting beta particles or photons, except Thorium-232, Uranium-235, Uranium-238 and their progeny.
2. “Dose equivalent” means the product of the absorbed dose from ionizing radiation and such factors as account for differences in biological effectiveness due to the type of radiation and its distribution in the body as specified by the International Commission on Radiological Units and Measurements.
3. “Drinking water protected use” means the protection and maintenance of aquifer water quality for human consumption.

4. "Gross alpha particle activity" means the total radioactivity due to alpha particle emission as inferred from measurements on a dry sample.
5. "Mg/l" means milligrams per liter.
6. "Millirem" means 1/1000 of a rem. A rem means the unit of dose equivalent from ionizing radiation to the total body or any internal organ or organ system.
7. "Non-drinking water protected use" means the protection and maintenance of aquifer water quality for a use other than for human consumption.
8. "pCi" means picocurie, or the quantity of radioactive material producing 2.22 nuclear transformations per minute.
9. "Total trihalomethanes" means the sum of the concentrations of the following trihalomethane compounds: trichloromethane (chloroform), dibromochloromethane, bromodichloromethane and tribromomethane (bromoform).

Historical Note

Adopted effective January 4, 1990 (Supp. 90-1).
Amended effective August 14, 1992 (Supp. 92-3).

R18-11-402. Repealed**Historical Note**

Adopted effective January 4, 1990 (Supp. 90-1).
Repealed effective August 14, 1992 (Supp. 92-3).

R18-11-403. Analytical Methods

Analysis of a sample to determine compliance with an aquifer water quality standard shall be in accordance with an analytical method specified in A.A.C. Title 9, Chapter 14, Article 6 or an alternative analytical method that is approved by the Director of the Arizona Department of Health Services pursuant to A.A.C. R9-14-607(B).

Historical Note

Adopted effective January 4, 1990 (Supp. 90-1).
Amended effective August 14, 1992 (Supp. 92-3).

R18-11-404. Laboratories

A test result from a sample taken to determine compliance with an aquifer water quality standard shall be valid only if the sample has been analyzed by a laboratory that is licensed by the Arizona Department of Health Services for the analysis performed.

Historical Note

Adopted effective January 4, 1990 (Supp. 90-1).
Amended effective August 14, 1992 (Supp. 92-3).

R18-11-405. Narrative Aquifer Water Quality Standards

- A. A discharge shall not cause a pollutant to be present in an aquifer classified for a drinking water protected use in a concentration which endangers human health.
- B. A discharge shall not cause or contribute to a violation of a water quality standard established for a navigable water of the state.
- C. A discharge shall not cause a pollutant to be present in an aquifer which impairs existing or reasonably foreseeable uses of water in an aquifer.

Historical Note

Adopted effective January 4, 1990 (Supp. 90-1).
Amended effective August 14, 1992 (Supp. 92-3).

R18-11-406. Numeric Aquifer Water Quality Standards: Drinking Water Protected Use

- A. The aquifer water quality standards in this Section apply to aquifers that are classified for drinking water protected use.

- B. The following are the aquifer water quality standards for inorganic chemicals:

Pollutant	mg/L)
Antimony	0.006
Arsenic	0.05
Asbestos	7 million fibers/liter (longer than 10 mm)
Barium	2
Beryllium	0.004
Cadmium	0.005
Chromium	0.1
Cyanide (As Free Cyanide)	0.2
Fluoride	4.0
Lead	0.05
Mercury	0.002
Nickel	0.1
Nitrate (as N)	10
Nitrite (as N)	1
Nitrate and nitrite (as N)	10
Selenium	0.05
Thallium	0.002

- C. The following are the aquifer water quality standards for organic chemicals:

Pollutant	(mg/L)
Benzene	0.005
Benzo (a) pyrene	0.0002
Carbon Tetrachloride	0.005
o-Dichlorobenzene	0.6
para-Dichlorobenzene	0.075
1,2-Dichloroethane	0.005
1,1-Dichloroethylene	0.007
cis-1,2-Dichloroethylene	0.07
trans-1,2-Dichloroethylene	0.1
1,2-Dichloropropane	0.005
Dichloromethane	0.005
Di (2-ethylhexyl) adipate	0.4
Di (2-ethylhexyl) pthalate	0.006
Ethylbenzene	0.7
Hexachlorobenzene	0.001
Hexachlorocyclopentadiene	0.05
Monochlorobenzene	0.1
Pentachlorophenol	0.001
Styrene	0.1
2,3,7,8-TCDD (Dioxin)	0.0000003
Tetrachloroethylene	0.005
Toluene	1
Trihalomethanes (Total)	0.10
1,2,4-Trichlorobenzene	0.07
1,1,1-Trichloroethane	0.20
1,1,2-Trichloroethane	0.005
Trichloroethylene	0.005
Vinyl Chloride	0.002
Xylenes (Total)	10

Department of Environmental Quality – Water Quality Standards

D. The following are the aquifer water quality standards for pesticides and polychlorinated biphenyls (PCBs):

Pollutant	(mg/L)
Alachlor	0.002
Atrazine	0.003
Carbofuran	0.04
Chlordane	0.002
Dalapon	0.2
1,2-Dibromo-3-Chloropropane (DBCP)	0.0002
2,4,-Dichlorophenoxyacetic Acid(2,4-D)	0.07
Dinoseb	0.007
Diquat	0.02
Endothall	0.1
Endrin	0.002
Ethylene Dibromide (EDB)	0.00005
Glyphosate	0.7
Heptachlor	0.0004
Heptachlor Epoxide	0.0002
Lindane	0.0002
Methoxychlor	0.04
Oxamyl	0.2
Picloram	0.5
Polychlorinated Biphenols (PCBs)	0.0005
Simazine	0.004
Toxaphene	0.003
2,4,5-Trichlorophenoxypropionic Acid (2,4,5-TP or Silvex)	0.05

E. The following are the aquifer water quality standards for radionuclides:

1. The maximum concentration for gross alpha particle activity, including Radium-226 but excluding radon and uranium, shall not exceed 15 pCi/l.
2. The maximum concentration for combined Radium-226 and Radium-228 shall not exceed 5 pCi/l.
3. The average annual concentration of beta particle and photon radioactivity from man-made radionuclides shall not produce an annual dose equivalent to the total body or any internal organ greater than 4 millirem/year.
4. Except for the radionuclides listed in this subsection, the concentration of man-made radionuclides causing 4 millirem total body or organ dose equivalents shall be calculated on the basis of a 2-liter-per-day drinking water intake using the 168-hour data listed in "Maximum Permissible Body Burdens and Maximum Permissible Concentration of Radionuclides in Air or Water for Occupational Exposure," National Bureau of Standards Handbook 69, National Bureau of Commerce, as amended August 1963 (and no future editions), incorporated herein by reference and on file with the Office of the Secretary of State and with the Department. If two or more radionuclides are present, the sum of their annual dose equivalent to the total body or to any organ shall not exceed 4 millirem/year. The following average annual concentrations are assumed to produce a total body or organ dose of 4 millirem/year:

Radionuclide	Critical Organ	pCi/l
Tritium	Total body	20,000
Strontium-90	Bone Marrow	8

F. The aquifer water quality standard for microbiological contaminants is based upon the presence or absence of total

coliforms in a 100-milliliter sample. If a sample is total coliform-positive, a 100-milliliter repeat sample shall be taken within two weeks of the time the sample results are reported. Any total coliform-positive repeat sample following a total coliform-positive sample constitutes a violation of the aquifer water quality standard for microbiological contaminants.

G. The following are the aquifer water quality standards for turbidity:

1. One nephelometric turbidity unit as determined by a monthly average except that five or fewer nephelometric turbidity units may be allowed if it can be determined that the higher turbidity does not interfere with disinfection, prevent maintenance of effective disinfectant agents in water supply distribution systems, or interfere with microbiological determinations.
2. Five nephelometric turbidity units based on an average of two consecutive days.

Historical Note

Adopted effective January 4, 1990 (Supp. 90-1).
Amended effective August 14, 1992 (Supp. 92-3).
Amended effective May 26, 1994 (Supp. 94-2).

R18-11-407. Aquifer Water Quality Standards in Reclassified Aquifers

- A. All aquifers in the state are classified for drinking water protected use except for aquifers which are reclassified to a non-drinking water protected use pursuant to A.R.S. § 49-224 and A.A.C. R18-11-503.
- B. Aquifer water quality standards for drinking water protected use apply to reclassified aquifers except where expressly superseded by aquifer water quality standards adopted pursuant to subsection (C) of this Section.
- C. The Director shall adopt, by rule, aquifer water quality standards for reclassified aquifers within one year of the date of the order reclassifying the aquifer to a nondrinking water protected use. The Director shall adopt aquifer water quality standards for reclassified aquifers only for pollutants that are specifically identified in a petition for reclassification as prescribed by A.R.S. § 49-223(D) and A.A.C. R18-11-503(B). Aquifer water quality standards for reclassified aquifers shall be sufficient to protect the use of the reclassified aquifer.

Historical Note

Adopted effective January 4, 1990 (Supp. 90-1).
Amended effective August 14, 1992 (Supp. 92-3).

R18-11-408. Petition for Adoption of a Numeric Aquifer Water Quality Standard

- A. Any person may petition the Director to adopt, by rule, a numeric aquifer water quality standard for a pollutant for which no numeric aquifer water quality standard exists.
- B. Petitions for adoption of a numeric aquifer water quality standard shall be filed with the Department and shall comply with the requirements applicable to petitions for rule adoption as provided by A.R.S. § 41-1033 and A.A.C. R18-1-302, except as otherwise provided by A.R.S. § 49-223 or this Section.
- C. In addition to the requirements of A.A.C. R18-1-302, a petition for rule adoption to establish a numeric aquifer water quality standard shall include specific reference to:
 1. Technical information that the pollutant is a toxic pollutant.
 2. Technical information upon which the Director reasonably may base the establishment of a numeric aquifer water quality standard.
 3. Evidence that the pollutant that is the subject of the petition is or may in the future be present in an aquifer or

part of an aquifer that is classified for drinking water protected use. Evidence may include, but is not limited to, any of the following:

- a. A laboratory analysis of a water sample by a laboratory licensed by the Arizona Department of Health Services which indicates the presence of the pollutant in the aquifer.
 - b. A hydrogeological study which demonstrates that the pollutant that is the subject of the petition may be present in an aquifer in the future. The hydrogeological study shall include the following:
 - i. A description of the use that results in a discharge of the pollutant that is the subject of the petition.
 - ii. A description of the mobility of the pollutant in the vadose zone and in the aquifer.
 - iii. A description of the persistence of the pollutant in the vadose zone and in the aquifer.
- D.** Within 180 calendar days of the receipt of a complete petition for rule adoption to establish a numeric aquifer water quality standard, the Director shall make a written determination of whether the petition should be granted or denied. The Director shall give written notice by regular mail of the determination to the petitioner.
- E.** If the petition for rule adoption is granted, the Director shall initiate rulemaking proceedings to adopt a numeric aquifer water quality standard. The Director shall, within one year of the date that the petition for adoption of a numeric aquifer water quality standard is granted, either adopt a rule establishing a numeric aquifer water quality standard or publish a notice of termination of rulemaking in the Arizona Administrative Register.
- F.** If the petition for rule adoption is denied, the Director shall issue a denial letter to the petitioner which explains the reasons for the denial. The denial of a petition for rule adoption to establish a numeric aquifer water quality standard is not subject to judicial review.

Historical Note

Adopted effective January 4, 1990 (Supp. 90-1).

Appendix 1. Repealed

Historical Note

Adopted effective January 4, 1990 (Supp. 90-1).
Repealed effective August 14, 1992 (Supp. 92-3).

Appendix 2. Repealed

Historical Note

Adopted effective January 4, 1990 (Supp. 90-1).
Repealed effective August 14, 1992 (Supp. 92-3).

Appendix 3. Repealed

Historical Note

Adopted effective January 4, 1990 (Supp. 90-1).
Repealed effective August 14, 1992 (Supp. 92-3).

Appendix 4. Repealed

Historical Note

Adopted effective January 4, 1990 (Supp. 90-1).
Repealed effective August 14, 1992 (Supp. 92-3).

Appendix 5. Repealed

Historical Note

Adopted effective January 4, 1990 (Supp. 90-1).
Repealed effective August 14, 1992 (Supp. 92-3).

Appendix 6. Repealed

Historical Note

Adopted effective January 4, 1990 (Supp. 90-1).
Repealed effective August 14, 1992 (Supp. 92-3).

Appendix 7. Repealed

Historical Note

Adopted effective January 4, 1990 (Supp. 90-1).
Repealed effective August 14, 1992 (Supp. 92-3).

ARTICLE 5. AQUIFER BOUNDARY AND PROTECTED USE CLASSIFICATION

R18-11-501. Definitions

In addition to the definitions contained in A.R.S. § 49-201, the words and phrases of this Article shall have the following meaning:

1. “Drinking water protected use” means the protection and maintenance of aquifer water quality for human consumption.
2. “Hardrock areas containing little or no water” means areas of igneous or metamorphic rock which do not yield usable quantities of water.
3. “Nondrinking water protected use” means the protection and maintenance of aquifer water quality for a use other than human consumption.
4. “Usable quantities” means five gallons of water per day.

Historical Note

Adopted effective October 22, 1987 (Supp. 87-4).

R18-11-502. Aquifer boundaries

- A.** Except as provided in subsection (B) of this rule, aquifer boundaries for the aquifers in this state are identified and defined as being identical to the hydrologic basin and subbasin boundaries, as found by the Director of the Department of Water Resources, Findings and Order In the Matter of The Designation of Groundwater Basins and Subbasins In The State of Arizona (dated June 21, 1984), pursuant to A.R.S. §§ 45-403 and 45-404, which is incorporated herein by reference and on file with the Department of Environmental Quality and the Office of the Secretary of State.
- B.** Excluded from the boundaries of the aquifers are hard rock areas which contain little or no water, as identified in Plate 1 of the Department of Water Resources, Water Resource Hydrologic Map Series Report Number 2 (dated January 1981) and as further identified in the Bureau of Mines, University of Arizona County Geologic Map Series (individual county maps dated 1957 through 1960), which are incorporated herein by reference and on file with the Department of Environmental Quality and the Office of the Secretary of State.
- C.** The Director may, by rule, modify or add an aquifer boundary provided that one or more of the following applies:
 1. The Department of Water Resources modifies the boundaries of its basins or subbasins.
 2. The Director is made aware of new technical information or data which supports refinement of an aquifer boundary.
- D.** Facilities located outside of the boundaries defined in these rules shall be subject to A.R.S. § 49-241 except as provided therein.

Historical Note

Adopted effective October 22, 1987 (Supp. 87-4).

R18-11-503. Petition for reclassification

- A.** Any person may petition the Director to reclassify an aquifer from a drinking water protected use to a nondrinking water protected use pursuant to A.R.S. § 49-224(C).
- B.** A written petition for reclassification pursuant to A.R.S. § 49-224(C) or A.R.S. § 49-224(D) shall be filed with the Department and shall include the following categories of information:
1. The proposed protected use for which the reclassification is being requested.
 2. The pollutant and affected aquifer water quality standards for which the reclassification is being requested.
 3. A hydrogeologic report which demonstrates that the aquifer proposed for reclassification is or will be hydrologically isolated, to the extent described in A.R.S. § 49-224(C)(1). This report and demonstration of hydrologic isolation for the area containing such aquifer, and immediate adjacent geologic units, shall include at least the following:
 - a. Hydrogeologic area maps and cross sections.
 - b. An analysis of subsurface geology, including geologic and hydrologic separation.
 - c. Water level elevation or piezometric level contour maps.
 - d. Analysis of hydrologic characteristics of the aquifer and the immediate adjacent geologic units.
 - e. Description of existing water quality and analysis of water chemistry.
 - f. Projected annual quantity of water to be withdrawn.
 - g. Identification of pumping centers, cones of depression and areas of recharge.
 - h. A water balance.
 - i. Existing flow direction and evaluation of the effects of seasonal and future pumping on flow.
 - j. An evaluation as to whether the reclassification will contribute to or cause a violation of aquifer water quality standards in other aquifers, or in parts of the aquifer not being proposed for reclassification.
 4. Documentation demonstrating that water from the aquifer or part of the aquifer for which reclassification is proposed is not being used as drinking water. This documentation shall include at least the following:
 - a. A list of all wells or springs including their location, ownership and use within the aquifer or part of the aquifer being proposed for reclassification.
 - b. Identification of groundwater withdrawal rights, on file with the Department of Water Resources, within the aquifer or part of the aquifer being proposed for reclassification.
 - c. A comprehensive list of agencies, persons and other information sources consulted for aquifer use documentation.
 5. A cost-benefit analysis developed pursuant to the requirements of A.R.S. § 49-224(C)(3), except for petitions submitted pursuant to A.R.S. § 49-224(D). This analysis shall identify potential future uses of the aquifer being proposed for reclassification, as well as other opportunity costs associated with reclassification, and shall contain a description of the cost-benefit methodology used, including all assumptions, data, data sources and criteria considered and all supporting statistical analyses.

Historical Note

Adopted effective October 22, 1987 (Supp. 87-4).

R18-11-504. Agency action on petition

- A.** Upon receipt of a petition for reclassification, the Director shall review the petition for compliance with the requirements of R18-11-503. If additional information is necessary, the petitioner shall be notified of specific deficiencies in writing within 30 calendar days of receipt of the petition.
- B.** Within 120 calendar days after receipt of a complete petition, and after consultation with the appropriate advisory council pursuant to A.R.S. §§ 49-224(C) and 49-204, the Director shall make a final decision to grant or deny the petition and shall notify the petitioner of such decision and the reason for such determination in writing.
- C.** Upon a decision to grant a petition for aquifer reclassification, the Director shall initiate proceedings for promulgation of aquifer water quality standards and, if applicable, for aquifer boundary designation for the reclassified aquifers.

Historical Note

Adopted effective October 22, 1987 (Supp. 87-4).

R18-11-505. Public participation

- A.** Within 30 days of receipt of a complete petition for reclassification filed pursuant to A.R.S. § 49-224(D), or if the Director deems it necessary to consider a reclassification under A.R.S. § 49-224(C), the Director shall give public notice of the proposed reclassification pursuant to A.A.C. R18-1-401.
- B.** The Director shall hold at least one public hearing at a location as near as practicable to the aquifer proposed for reclassification. The Director shall give notice of each public hearing and conduct the public hearing in accordance with the provisions of A.A.C. R18-1-402.

Historical Note

Adopted effective June 29, 1989 (Supp. 89-2).

R18-11-506. Rescission of reclassification

The Director may, by rule, rescind an aquifer reclassification and return an aquifer to a drinking water protected use if he determines that any of the conditions under which the reclassification was granted are no longer valid. If the Director initiates a change under this Section, he shall consult with the appropriate advisory council pursuant to A.R.S. §§ 49-224(C) and 49-204.

Historical Note

Adopted effective October 22, 1987 (Supp. 87-4).

ARTICLE 6. IMPAIRED WATER IDENTIFICATION

Article 6, consisting of Sections R18-11-601 through R18-11-606, made by final rulemaking at 8 A.A.R. 3380, effective July 12, 2002 (Supp. 02-3).

R18-11-601. Definitions

In addition to the definitions established in A.R.S. §§ 49-201 and 49-231, and A.A.C. R18-11-101, the following terms apply to this Article:

1. "303(d) List" means the list of surface waters or segments required under section 303(d) of the Clean Water Act and A.R.S. Title 49, Chapter 2, Article 2.1, for which TMDLs are developed and submitted to EPA for approval.
2. "Attaining" means there is sufficient, credible, and scientifically defensible data to assess a surface water or segment and the surface water or segment does not meet the definition of impaired or not attaining.
3. "AZPDES" means the Arizona Pollutant Elimination Discharge System.
4. "Credible and scientifically defensible data" means data submitted, collected, or analyzed using:

- a. Quality assurance and quality control procedures under A.A.C. R18-11-602;
 - b. Samples or analyses representative of water quality conditions at the time the data were collected;
 - c. Data consisting of an adequate number of samples based on the nature of the water in question and the parameters being analyzed; and
 - d. Methods of sampling and analysis, including analytical, statistical, and modeling methods that are generally accepted and validated by the scientific community as appropriate for use in assessing the condition of the water.
5. “Designated use” means those uses specified in 18 A.A.C. 11, Article 1 for each surface water or segment whether or not they are attaining.
 6. “EPA” means the U.S. Environmental Protection Agency.
 7. “Impaired water” means a Navigable water for which credible scientific data exists that satisfies the requirements of A.R.S. § 49-232 and that demonstrates that the water should be identified pursuant to 33 United States Code § 1313(d) and the regulations implementing that statute. A.R.S. § 49-231(1).
 8. “Laboratory detection limit” means a “Method Reporting Limit” (MRL) or “Reporting Limit” (RL). These analogous terms describe the laboratory reported value, which is the lowest concentration level included on the calibration curve from the analysis of a pollutant that can be quantified in terms of precision and accuracy.
 9. “Monitoring entity” means the Department or any person who collects physical, chemical, or biological data used for an impaired water identification or a TMDL decision.
 10. “Naturally occurring condition” means the condition of a surface water or segment that would have occurred in the absence of pollutant loadings as a result of human activity.
 11. “Not attaining” means a surface water is assessed as impaired, but is not placed on the 303(d) List because:
 - a. A TMDL is prepared and implemented for the surface water;
 - b. An action, which meets the requirements of R18-11-604(D)(2)(h), is occurring and is expected to bring the surface water to attaining before the next 303(d) List submission; or
 - c. The impairment of the surface water is due to pollution but not a pollutant, for which a TMDL load allocation cannot be developed.
 12. “NPDES” means National Pollutant Discharge Elimination System.
 13. “Planning List” means a list of surface waters and segments that the Department will review and evaluate to determine if the surface water or segment is impaired and whether a TMDL is necessary.
 14. “Pollutant” means dredged spoil, solid waste, incinerator residue, sewage, garbage, sewage sludge, munitions, chemical wastes, biological materials, radioactive materials, heat, wrecked or discarded equipment, rock, sand, cellar dirt and industrial, municipal, and agricultural waste discharged into water. 33 U.S.C. 1362(6). Characteristics of water, such as dissolved oxygen, pH, temperature, turbidity, and suspended sediment are considered pollutants if they result or may result in the non-attainment of a water quality standard.
 15. “Pollution” means “the man-made or man-induced alteration of the chemical, physical, biological, and radiological integrity of water.” 33 U.S.C. 1362(19).
 16. “QAP” means a quality assurance plan detailing how environmental data operations are planned, implemented, and assessed for quality during the duration of a project.
 17. “Sampling event” means one or more samples taken under consistent conditions on one or more days at a distinct station or location.
 18. “SAP” means a site specific sampling and analysis plan that describes the specifics of sample collection to ensure that data quality objectives are met and that samples collected and analyzed are representative of surface water conditions at the time of sampling.
 19. “Spatially independent sample” means a sample that is collected at a distinct station or location. The sample is independent if the sample was collected:
 - a. More than 200 meters apart from other samples, or
 - b. Less than 200 meters apart, and collected to characterize the effect of an intervening tributary, outfall or other pollution source, or significant hydrographic or hydrologic change.
 20. “Temporally independent sample” means a sample that is collected at the same station or location more than seven days apart from other samples.
 21. “Threatened” means that a surface water or segment is currently attaining its designated use, however, trend analysis, based on credible and scientifically defensible data, indicates that the surface water or segment is likely to be impaired before the next listing cycle.
 22. “TMDL” means total maximum daily load.
 23. “TMDL decision” means a decision by the Department to:
 - a. Prioritize an impaired water for TMDL development,
 - b. Develop a TMDL for an impaired water, or
 - c. Develop a TMDL implementation plan.
 24. “*Total maximum daily load*” means an estimation of the total amount of a pollutant from all sources that may be added to a water while still allowing the water to achieve and maintain applicable surface water quality standards. Each total maximum daily load shall include allocations for sources that contribute the pollutant to the water, as required by section 303(d) of the clean water act (33 United States Code section 1313(d)) and regulations implementing that statute to achieve applicable surface water quality standards. A.R.S. § 49-231(4).
 25. “Water quality standard” means a standard composed of designated uses (classification of waters), the numerical and narrative criteria applied to the specific water uses or classification, the antidegradation policy, and moderating provisions, for example, mixing zones, site-specific alternative criteria, and exemptions, in A.A.C. Title 18, Chapter 11, Article 1.
 26. “WQARF” means the water quality assurance revolving fund established under A.R.S. § 49-282.

Historical Note

New Section made by final rulemaking at 8 A.A.R. 3380, effective July 12, 2002 (Supp. 02-3).

R18-11-602. Credible Data

- A. Data are credible and relevant to an impaired water identification or a TMDL decision when:
 1. Quality Assurance Plan. A monitoring entity, which contribute data for an impaired water identification or a TMDL decision, provides the Department with a QAP that contains, at a minimum, the elements listed in subsections (A)(1)(a) through (A)(1)(f). The Department may accept a QAP containing less than the required

Department of Environmental Quality – Water Quality Standards

- elements if the Department determines that an element is not relevant to the sampling activity and that its omission will not impact the quality of the results based upon the type of pollutants to be sampled, the type of surface water, and the purpose of the sampling.
- a. An approval page that includes the date of approval and the signatures of the approving officials, including the project manager and project quality assurance manager;
 - b. A project organization outline that identifies all key personnel, organizations, and laboratories involved in monitoring, including the specific roles and responsibilities of key personnel in carrying out the procedures identified in the QAP and SAP, if applicable;
 - c. Sampling design and monitoring data quality objectives or a SAP that meets the requirements of subsection (A)(2) to ensure that:
 - i. Samples are spatially and temporally representative of the surface water,
 - ii. Samples are representative of water quality conditions at the time of sampling, and
 - iii. The monitoring is reproducible;
 - d. The following field sampling information to assure that samples meet data quality objectives:
 - i. Sampling and field protocols for each parameter or parametric group, including the sampling methods, equipment and containers, sample preservation, holding times, and any analysis proposed for completion in the field or outside of a laboratory;
 - ii. Field and laboratory methods approved under subsection (A)(5);
 - iii. Handling procedures to identify samples and custody protocols used when samples are brought from the field to the laboratory for analysis;
 - iv. Quality control protocols that describe the number and type of field quality control samples for the project that includes, if appropriate for the type of sampling being conducted, field blanks, travel blanks, equipment blanks, method blanks, split samples, and duplicate samples;
 - v. Procedures for testing, inspecting, and maintaining field equipment;
 - vi. Field instrument calibration procedures that describe how and when field sampling and analytical instruments will be calibrated;
 - vii. Field notes and records that describe the conditions that require documentation in the field, such as weather, stream flow, transect information, distance from water edge, water and sample depth, equipment calibration measurements, field observations of watershed activities, and bank conditions. Indicate the procedures implemented for maintaining field notes and records and the process used for attaching pertinent information to monitoring results to assist in data interpretation;
 - viii. Minimum training and any specialized training necessary to do the monitoring, that includes the proper use and calibration of field equipment used to collect data, sampling protocols, quality assurance/quality control procedures, and how training will be achieved;
 - e. Laboratory analysis methods and quality assurance/quality control procedures that assure that samples meet data quality objectives, including:
 - i. Analytical methods and equipment necessary for analysis of each parameter, including identification of approved laboratory methods described in subsection (A)(5), and laboratory detection limits for each parameter;
 - ii. The name of the designated laboratory, its license number, if licensed by the Arizona Department of Health Services, and the name of a laboratory contact person to assist the Department with quality assurance questions;
 - iii. Quality controls that describe the number and type of laboratory quality control samples for the project, including, if appropriate for the type of sampling being conducted, field blanks, travel blanks, equipment blanks, method blanks, split samples, and duplicate samples;
 - iv. Procedures for testing, inspecting, and maintaining laboratory equipment and facilities;
 - v. A schedule for calibrating laboratory instruments, a description of calibration methods, and a description of how calibration records are maintained; and
 - vi. Sample equipment decontamination procedures that outline specific methods for sample collection and preparation of equipment, identify the frequency of decontamination, and describe the procedures used to verify decontamination;
 - f. Data review, management, and use that includes the following:
 - i. A description of the data handling process from field to laboratory, from laboratory to data review and validation, and from validation to data storage and use. Include the role and responsibility of each person for each step of the process, type of database or other storage used, and how laboratory and field data qualifiers are related to the laboratory result;
 - ii. Reports that describe the intended frequency, content, and distribution of final analysis reports and project status reports;
 - iii. Data review, validation, and verification that describes the procedure used to validate and verify data, the procedures used if errors are detected, and how data are accepted, rejected, or qualified; and
 - iv. Reconciliation with data quality objectives that describes the process used to determine whether the data collected meets the project objectives, which may include discarding data, setting limits on data use, or revising data quality objectives.
2. Sampling and analysis plan.
 - a. A monitoring entity shall develop a SAP that contains, at a minimum, the following elements:
 - i. The experimental design of the project, the project goals and objectives, and evaluation criteria for data results;
 - ii. The background or historical perspective of the project;
 - iii. Identification of target conditions, including a discussion of whether any weather, seasonal

- variations, stream flow, lake level, or site access may affect the project and the consideration of these factors;
- iv. The data quality objectives for measurement of data that describe in quantitative and qualitative terms how the data meet the project objectives of precision, accuracy, completeness, comparability, and representativeness;
 - v. The types of samples scheduled for collection;
 - vi. The sampling frequency;
 - vii. The sampling periods;
 - viii. The sampling locations and rationale for the site selection, how site locations are benchmarked, including scaled maps indicating approximate location of sites; and
 - ix. A list of the field equipment, including tolerance range and any other manufacturer's specifications relating to accuracy and precision.
- b. The Department may accept a SAP containing less than the required elements if the Department determines that an element is not relevant to the sampling activity and that its omission will not impact the quality of the results based upon the type of pollutants to be samples, the type of surface water, and the purpose of the sampling.
3. The monitoring entity may include any of the following in the QAP or SAP:
 - a. The name, title, and role of each person and organization involved in the project, identifying specific roles and responsibilities for carrying out the procedures identified in the QAP and SAP;
 - b. A distribution list of each individual and organization receiving a copy of the approved QAP and SAP;
 - c. A table of contents;
 - d. A health and safety plan;
 - e. The inspection and acceptance requirements for supplies;
 - f. The data acquisition that describes types of data not obtained through this monitoring activity, but used in the project;
 - g. The audits and response actions that describe how field, laboratory, and data management activities and sampling personnel are evaluated to ensure data quality, including a description of how the project will correct any problems identified during these assessments; and
 - h. The waste disposal methods that identify wastes generated in sampling and methods for disposal of those wastes.
 4. Exceptions. The Department may determine that the following data are also credible and relevant to an impaired water identification or TMDL decision when data were collected, provided the conditions in subsections (A)(5), (A)(6), and (B) are met, and where the data were collected in the surface water or segment being evaluated for impairment:
 - a. The data were collected before July 12, 2002 and the Department determines that the data yield results of comparable reliability to the data collected under subsections (A)(1) and (A)(2);
 - b. The data were collected after July 12, 2002 as part of an ongoing monitoring effort by a governmental agency and the Department determines that the data yield results of comparable reliability to the data collected under subsections (A)(1) and (A)(2); or
 - c. The instream water quality data were or are collected under the terms of a NPDES or AZPDES permit or a compliance order issued by the Department or EPA, a consent decree signed by the Department or EPA, or a sampling program approved by the Department or EPA under WQARF or CERCLA, and the Department determines that the data yield results of comparable reliability to data collected under subsections (A)(1) and (A)(2).
 5. Data collection, preservation, and analytical procedures. The monitoring entity shall collect, preserve, and analyze data using methods of sample collection, preservation, and analysis established under A.A.C. R9-14-610.
 6. Laboratory. The monitoring entity shall ensure that chemical and toxicological samples are analyzed in a state-licensed laboratory, a laboratory exempted by the Arizona Department of Health Services for specific analyses, or a federal or academic laboratory that can demonstrate proper quality assurance/quality control procedures substantially equal to those required by the Arizona Department of Health Services, and shall ensure that the laboratory uses approved methods identified in A.A.C. R9-14-610.
- B.** Documentation for data submission. The monitoring entity shall provide the Department with the following information either before or with data submission:
 1. A copy of the QAP or SAP, or both, revisions to a previously submitted QAP or SAP, and any other information necessary for the Department to evaluate the data under subsection (A)(4);
 2. The applicable dates of the QAP and SAP, including any revisions;
 3. Written assurance that the methods and procedures specified in the QAP and SAP were followed;
 4. The name of the laboratory used for sample analyses and its certification number, if the laboratory is licensed by the Arizona Department of Health Services;
 5. The quality assurance/quality control documentation, including the analytical methods used by the laboratory, method number, detection limits, and any blank, duplicate, and spike sample information necessary to properly interpret the data, if different from that stated in the QAP or SAP;
 6. The data reporting unit of measure;
 7. Any field notes, laboratory comments, or laboratory notations concerning a deviation from standard procedures, quality control, or quality assurance that affects data reliability, data interpretation, or data validity; and
 8. Any other information, such as complete field notes, photographs, climate, or other information related to flow, field conditions, or documented sources of pollutants in the watershed, if requested by the Department for interpreting or validating data.
 - C.** Recordkeeping. The monitoring entity shall maintain all records, including sample results, for the duration of the listing cycle. If a surface water or segment is added to the Planning List or to the 303(d) List, the Department shall coordinate with the monitoring entity to ensure that records are kept for the duration of the listing.

Historical Note

New Section made by final rulemaking at 8 A.A.R. 3380, effective July 12, 2002 (Supp. 02-3).

R18-11-603. General Data Interpretation Requirements

- A. The Department shall use the following data conventions to interpret data for impaired water identifications and TMDL decisions:
1. Data reported below laboratory detection limits.
 - a. When the analytical result is reported as <X, where X is the laboratory detection limit for the analyte and the laboratory detection limit is less than or equal to the surface water quality standard, consider the result as meeting the water quality standard:
 - i. Use these statistically derived values in trend analysis, descriptive statistics or modeling if there is sufficient data to support the statistical estimation of values reported as less than the laboratory detection limit; or
 - ii. Use one-half of the value of the laboratory detection limit in trend analysis, descriptive statistics, or modeling, if there is insufficient data to support the statistical estimation of values reported as less than the laboratory detection limit.
 - b. When the sample value is less than or equal to the laboratory detection limit but the laboratory detection limit is greater than the surface water quality standard, shall not use the result for impaired water identifications or TMDL decisions;
 2. Identify the field equipment specifications used for each listing cycle or TMDL developed. A field sample measurement within the manufacturer's specification for accuracy meets surface water quality standards;
 3. Resolve a data conflict by considering the factors identified under the weight-of-evidence determination in R18-11-605(B);
 4. When multiple samples from a surface water or segment are not spatially or temporally independent, or when lake samples are from multiple depths, use the following resultant value to represent the specific dataset:
 - a. The appropriate measure of central tendency for the dataset for:
 - i. A pollutant listed in the surface water quality standards 18 A.A.C. 11, Article 1, Appendix A, Table 1, except for nitrate or nitrate/nitrite;
 - ii. A chronic water quality standard for a pollutant listed in 18 A.A.C. 11, Article 1, Appendix A, Table 2;
 - iii. A surface water quality standard for a pollutant that is expressed as an annual or geometric mean;
 - iv. The surface water quality standard for temperature or the single sample maximum water quality standard for suspended sediment concentration, nitrogen, and phosphorus in R18-11-109;
 - v. The surface water quality standard for radiochemicals in R18-11-109(G); or
 - vi. Except for chromium, all single sample maximum water quality standards in R18-11-112.
 - b. The maximum value of the dataset for:
 - i. The acute water quality standard for a pollutant listed in 18 A.A.C. 11, Article 1, Appendix A, Table 2 and acute water quality standard in R18-11-112;
 - ii. The surface water quality standard for nitrate or nitrate/nitrite in 18 A.A.C. 11, Article 1, Appendix A, Table 1;
 - iii. The single sample maximum water quality standard for bacteria in subsections R18-11-109(A); or
 - iv. The 90th percentile water quality standard for nitrogen and phosphorus in R18-11-109(F) and R18-11-112.
 - c. The worst case measurement of the dataset for:
 - i. Surface water quality standard for dissolved oxygen under R18-11-109(E). For purposes of this subsection, worst case measurement means the minimum value for dissolved oxygen;
 - ii. Surface water quality standard for pH under R18-11-109(B). For purposes of this subsection, "worst case measurement" means both the minimum and maximum value for pH.
- B. The Department shall not use the following data for placing a surface water or segment on the Planning List, the 303(d) List, or in making a TMDL decision.
1. Any measurement outside the range of possible physical or chemical measurements for the pollutant or measurement equipment,
 2. Uncorrected data transcription errors or laboratory errors, and
 3. An outlier identified through statistical procedures, where further evaluation determines that the outlier represents a valid measure of water quality but should be excluded from the dataset.
- C. The Department may employ fundamental statistical tests if appropriate for the collected data and type of surface water when evaluating a surface water or segment for impairment or in making a TMDL decision. The statistical tests include descriptive statistics, frequency distribution, analysis of variance, correlation analysis, regression analysis, significance testing, and time series analysis.
- D. The Department may employ modeling when evaluating a surface water or segment for impairment or in making a TMDL decision, if the method is appropriate for the type of waterbody and the quantity and quality of available data meet the requirements of R18-11-602. Modeling methods include:
1. Better Assessment Science Integrating Source and Nonpoint Sources (BASINS),
 2. Fundamental statistics, including regression analysis,
 3. Hydrologic Simulation Program-Fortran (HSPF),
 4. Spreadsheet modeling, and
 5. Hydrologic Engineering Center (HEC) programs developed by the Army Corps of Engineers.

Historical Note

New Section made by final rulemaking at 8 A.A.R. 3380, effective July 12, 2002 (Supp. 02-3).

R18-11-604. Types of Surface Waters Placed on the Planning List and 303(d) List

- A. The Department shall evaluate, at least every five years, Arizona's surface waters by considering all readily available data.
1. The Department shall place a surface water or segment on:
 - a. The Planning List if it meets any of the criteria described in subsection (D), or
 - b. The 303(d) List if it meets the criteria for listing described in subsection (E).
 2. The Department shall remove a surface water or segment from the Planning List based on the requirements in R18-11-605(E)(1) or from the 303(d) List, based on the requirements in R18-11-605(E)(2).

3. The Department may move surface waters or segments between the Planning List and the 303(d) List based on the criteria established in R18-11-604 and R18-11-605.
- B.** When placing a surface water or segment on the Planning List or the 303(d) List, the Department shall list the stream reach, derived from EPA's Reach File System or National Hydrography Dataset, or the entire lake, unless the data indicate that only a segment of the stream reach or lake is impaired or not attaining its designated use, in which case, the Department shall describe only that segment for listing.
- C.** Exceptions. The Department shall not place a surface water or segment on either the Planning List or the 303(d) List if the non-attainment of a surface water quality standard is due to one of the following:
1. Pollutant loadings from naturally occurring conditions alone are sufficient to cause a violation of applicable water quality standards;
 2. The data were collected within a mixing zone or under a variance or nutrient waiver established in a NPDES or AZPDES permit for the specific parameter and the result does not exceed the alternate discharge limitation established in the permit. The Department may use data collected within these areas for modeling or allocating loads in a TMDL decision; or
 3. An activity exempted under R18-11-117, R18-11-118, or a condition exempted under R18-11-119.
- D.** Planning List.
1. The Department shall:
 - a. Use the Planning List to prioritize surface waters for monitoring and evaluation as part of the Department's watershed management approach;
 - b. Provide the Planning List to EPA; and
 - c. Evaluate each surface water and segment on the Planning List for impairment based on the criteria in R18-11-605(D) to determine the source of the impairment.
 2. The Department shall place a surface water or segment on the Planning List based the criteria in R18-11-605(C). The Department may also include a surface water or segment on the Planning List when:
 - a. A TMDL is completed for the pollutant and approved by EPA;
 - b. The surface water or segment is on the 1998 303(d) List but the dataset used for the listing:
 - i. Does not meet the credible data requirements of R18-11-602, or
 - ii. Contains insufficient samples to meet the data requirements under R18-11-605(D);
 - c. Some monitoring data exist but there are insufficient data to determine whether the surface water or segment is impaired or not attaining, including:
 - i. A numeric surface water quality standard is exceeded, but there are not enough samples or sampling events to fulfill the requirements of R18-11-605(D);
 - ii. Evidence exists of a narrative standard violation, but the amount of evidence is insufficient, based on narrative implementation procedures and the requirements of R18-11-605(D)(3);
 - iii. Existing monitoring data do not meet credible data requirements in R18-11-602; or
 - iv. A numeric surface water quality standard is exceeded, but there are not enough sample results above the laboratory detection limit to support statistical analysis as established in R18-11-603(A)(1).
- E.** 303(d) List. The Department shall:
1. Place a surface water or segment on the 303(d) List if the Department determines:
 - a. Based on R18-11-605(D), that the surface water or segment is impaired due to a pollutant and that a TMDL decision is necessary; or
 - b. That the surface water or segment is threatened due to a pollutant and, at the time the Department submits a final 303(d) List to EPA, there are federal regulations implementing section 303(d) of the Clean Water Act that require threatened waters be included on the list.
 2. Provide public notice of the 303(d) List according to the requirements of A.R.S. § 49-232 and submit the 303(d) List according to section 303(d) of the Clean Water Act.

Historical Note

New Section made by final rulemaking at 8 A.A.R. 3380, effective July 12, 2002 (Supp. 02-3).

R18-11-605. Evaluating A Surface Water or Segment For Listing and Delisting

- A.** The Department shall compile and evaluate all reasonably current, credible, and scientifically defensible data to determine whether a surface water or segment is impaired or not attaining.
- B.** Weight-of-evidence approach.
1. The Department shall consider the following concepts when evaluating data:
 - a. Data or information collected during critical conditions may be considered separately from the complete dataset, when the data show that the surface water or segment is impaired or not attaining its designated use during those critical conditions, but attaining its uses during other periods. Critical conditions may include stream flow, seasonal periods, weather conditions, or anthropogenic activities;
 - b. Whether the data indicate that the impairment is due to persistent, seasonal, or recurring conditions. If the data do not represent persistent, recurring, or seasonal conditions, the Department may place the surface water or segment on the Planning List;
 - c. Higher quality data over lower quality data when making a listing decision. Data quality is established by the reliability, precision, accuracy, and representativeness of the data, based on factors identified in R18-11-602(A) and (B), including monitoring methods, analytical methods, quality control procedures, and the documented field and laboratory quality control information submitted with the data. The Department shall consider the following factors when determining higher quality data:
 - i. The age of the measurements. Newer measurements are weighted heavier than older measurements, unless the older measurements are more representative of critical flow conditions;
 - ii. Whether the data provide a direct measure of an impact on a designated use. Direct measurements are weighted heavier than measurements of an indicator or surrogate parameter; or
 - iii. The amount or frequency of the measurements. More frequent data collection are weighted heavier than nominal datasets.
 2. The Department shall evaluate the following factors to determine if the water quality evidence supports a finding that the surface water or segment is impaired or not attaining:
 - a. An exceedance of a numeric surface water quality standard based on the criteria in subsections (C)(1), (C)(2), (D)(1), and (D)(2);
 - b. An exceedance of a narrative surface water quality standard based on the criteria in subsections (C)(3) and (D)(3);
 - c. Additional information that determines whether a water quality standard is exceeded due to a pollutant, suspected pollutant, or naturally occurring condition:
 - i. Soil type, geology, hydrology, flow regime, biological community, geomorphology, climate, natural process, and anthropogenic influence in the watershed;
 - ii. The characteristics of the pollutant, such as its solubility in water, bioaccumulation potential, sediment sorption potential, or degradation characteristics, to assist in determining which data more accurately indicate the pollutant's presence and potential for causing impairment; and
 - iii. Available evidence of direct or toxic impacts on aquatic life, wildlife, or human health, such as fish kills and beach closures, where there is sufficient evidence that these impacts occurred due to water quality conditions in the surface water.
 - d. Other available water quality information, such as NPDES or AZPDES water quality discharge data, as applicable.
 - e. If the Department determines that a surface water or segment does not merit listing under numeric water quality standards based on criteria in subsections (C)(1), (C)(2), (D)(1), or (D)(2) for a pollutant, but there is evidence of a narrative standard exceedance in that surface water or segment under subsection (D)(3) as a result of the presence of the same pollutant, the Department shall list the surface water or segment as impaired only when the evidence indicates that the numeric water quality standard is insufficient to protect the designated use of the surface water or segment and the Department justifies the listing based on any of the following:
 - i. The narrative standard data provide a more direct indication of impairment as supported by professionally prepared and peer-reviewed publications;
 - ii. Sufficient evidence of impairment exists due to synergistic effects of pollutant combinations or site-specific environmental factors; or
 - iii. The pollutant is bioaccumulative, relatively insoluble in water, or has other characteristics that indicate it is occurring in the specific surface water or segment at levels below the laboratory detection limits, but at levels sufficient to result in an impairment.
 3. The Department may consider a single line of water quality evidence when the evidence is sufficient to demonstrate that the surface water or segment is impaired or not attaining.
- C.** Planning List.
1. When evaluating a surface water or segment for placement on the Planning List.
 - a. Consider at least ten spatially or temporally independent samples collected over three or more temporally independent sampling events; and
 - b. Determine numeric water quality standards exceedances. The Department shall:
 - i. Place a surface water or segment on the Planning List following subsection (B), if the number of exceedances of a surface water quality standard is greater than or equal to the number listed in Table 1, which provides the number of exceedances that indicate a minimum of a 10 percent exceedance frequency with a minimum of a 80 percent confidence level using a binomial distribution for a given sample size; or
 - ii. For sample datasets exceeding those shown in Table 1, calculate the number of exceedances

using the following equation: $(X \geq x | n, p)$ where n = number of samples; p = exceedance probability of 0.1; x = smallest number of

exceedances required for listing with “ n ” samples; and confidence level ≥ 80 percent.

Table 1.

MINIMUM NUMBER OF SAMPLES EXCEEDING THE NUMERIC STANDARD								
Number of Samples		Number of Samples Exceeding Standard	Number of Samples		Number of Samples Exceeding Standard	Number of Samples		Number of Samples Exceeding Standard
From	To		From	To		From	To	
10	15	3	173	181	22	349	357	41
16	23	4	182	190	23	358	367	42
24	31	5	191	199	24	368	376	43
32	39	6	200	208	25	377	385	44
40	47	7	209	218	26	386	395	45
48	56	8	219	227	27	396	404	46
57	65	9	228	236	28	405	414	47
66	73	10	237	245	29	415	423	48
74	82	11	246	255	30	424	432	49
83	91	12	256	264	31	433	442	50
92	100	13	265	273	32	443	451	51
101	109	14	274	282	33	452	461	52
110	118	15	283	292	34	462	470	53
119	126	16	293	301	35	471	480	54
127	136	17	302	310	36	481	489	55
137	145	18	311	320	37	490	499	56
146	154	19	321	329	38	500		57
155	163	20	330	338	39			
164	172	21	339	348	40			

2. When there are less than ten samples, the Department shall place a surface water or segment on the Planning List following subsection (B), if three or more temporally independent samples exceed the following surface water quality standards:
 - a. The surface water quality standard for a pollutant listed in 18 A.A.C. 11, Article 1, Appendix A, Table 1, except for nitrate or nitrate/nitrite;
 - b. The surface water quality standard for temperature or the single sample maximum water quality standard for suspended sediment concentration, nitrogen, and phosphorus in R18-11-109;
 - c. The surface water quality standard for radiochemicals in R18-11-109(G);
 - d. The surface water quality standard for dissolved oxygen under R18-11-109(E);
 - e. The surface water quality standard for pH under R18-11-109(B); or
 - f. The following surface water quality standards in R18-11-112:
 - i. Single sample maximum standards for nitrogen and phosphorus,
 - ii. All metals except chromium, or
 - iii. Turbidity.
3. The Department shall place a surface water or segment on the Planning List if information in subsections (B)(2)(c), (B)(2)(d), and (B)(2)(e) indicates that a narrative water quality standard violation exists, but no narrative

- implementation procedure required under A.R.S. § 49-232(F) exists to support use of the information for listing.
- D. 303(d) List.
 1. When evaluating a surface water or segment for placement on the 303(d) List.
 - a. Consider at least 20 spatially or temporally independent samples collected over three or more temporally independent sampling events; and
 - b. Determine numeric water quality standards exceedances. The Department shall:
 - i. Place a surface water or segment on the 303(d) List, following subsection (B), if the number of exceedances of a surface water quality standard is greater than or equal to the number listed in Table 2, which provides the number of exceedances that indicate a minimum of a 10 percent exceedance frequency with a minimum of a 90 percent confidence level using a binomial distribution, for a given sample size; or
 - ii. For sample datasets exceeding those shown in Table 2, calculate the number of exceedances using the following equation: $(X \geq x | n, p)$ where n = number of samples; p = exceedance probability of 0.1; x = smallest number of exceedances required for listing with “ n ” samples; and confidence level ≥ 90 percent.

Table 2.

MINIMUM NUMBER OF SAMPLES EXCEEDING THE NUMERIC STANDARD								
Number of Samples		Number of Samples Exceeding Standard	Number of Samples		Number of Samples Exceeding Standard	Number of Samples		Number of Samples Exceeding Standard
From	To		From	To		From	To	
20	25	5	174	182	24	344	352	43
26	32	6	183	191	25	353	361	44
33	40	7	192	199	26	362	370	45
41	47	8	200	208	27	371	379	46
48	55	9	209	217	28	380	388	47
56	63	10	218	226	29	389	397	48
64	71	11	227	235	30	398	406	49
72	79	12	236	244	31	407	415	50
80	88	13	245	253	32	416	424	51
89	96	14	254	262	33	425	434	52
97	104	15	263	270	34	435	443	53
105	113	16	271	279	35	444	452	54
114	121	17	280	288	36	453	461	55
122	130	18	289	297	37	462	470	56
131	138	19	298	306	38	471	479	57
139	147	20	307	315	39	480	489	58
148	156	21	316	324	40	490	498	59
157	164	22	325	333	41	499	500	60
165	173	23	334	343	42			

2. The Department shall place a surface water or segment on the 303(d) List, following subsection (B) without the required number of samples or numeric water quality standard exceedances under subsection (D)(1), if either the following conditions occur:
 - a. More than one temporally independent sample in any consecutive three-year period exceeds the surface water quality standard in:
 - i. The acute water quality standard for a pollutant listed in 18 A.A.C. 11, Article 1, Appendix A, Table 2 and the acute water quality standards in R18-11-112;
 - ii. The surface water quality standard for nitrate or nitrate/nitrite in 18 A.A.C. 11, Article 1, Appendix A, Table 1; or
 - iii. The single sample maximum water quality standard for bacteria in subsections R18-11-109(A).
 - b. More than one exceedance of an annual mean, 90th percentile, aquatic and wildlife chronic water quality standard, or a bacteria 30-day geometric mean water quality standard occurs, as specified in R18-11-109, R18-11-110, R18-11-112, or 18 A.A.C. 11, Article 1, Appendix A, Table 2.
 3. Narrative water quality standards exceedances. The Department shall place a surface water or segment on the Planning List if the listing requirements are met under A.R.S. § 49-232(F).
- E. Removing a surface water, segment, or pollutant from the Planning List or the 303(d) List.**
1. Planning List. The Department shall remove a surface water, segment, or pollutant from the Planning List when:
 - a. Monitoring activities indicate that:
 - i. There is sufficient credible data to determine that the surface water or segment is impaired under subsection (D), in which case the Department shall place the surface water or segment on the 303(d) List. This includes surface waters with an EPA approved TMDL when the Department determines that the TMDL strategy is insufficient for the surface water or segment to attain water quality standards; or
 - ii. There is sufficient credible data to determine that the surface water or segment is attaining all designated uses and standards.
 - b. All pollutants for the surface water or segment are delisted.
 2. 303(d) List. The Department shall:
 - a. Remove a pollutant from a surface water or segment from the 303(d) List based on one or more of the following criteria:
 - i. The Department developed, and EPA approved, a TMDL for the pollutant;
 - ii. The data used for previously listing the surface water or segment under R18-11-605(D) is superseded by more recent credible and scientifically defensible data meeting the requirements of R18-11-602, showing that the surface water or segment meets the applicable numeric or narrative surface water quality standard. When evaluating data to remove a pollutant from the 303(d) List, the monitoring entity shall collect the more recent data under similar hydrologic or climatic conditions as occurred when the samples were taken that indicated impairment, if those conditions still exist;
 - iii. The surface water or segment no longer meets the criteria for impairment based on a change in

- the applicable surface water quality standard or a designated use approved by EPA under section 303(c)(1) of the Clean Water Act;
- iv. The surface water or segment no longer meets the criteria for impairment for the specific narrative water quality standard based on a change in narrative water quality standard implementation procedures;
 - v. A re-evaluation of the data indicate that the surface water or segment does not meet the criteria for impairment because of a deficiency in the original analysis; or
 - vi. Pollutant loadings from naturally occurring conditions alone are sufficient to cause a violation of applicable water quality standards;
- b. Remove a surface water, segment, or pollutant from the 303(d) List, based on criteria that are no more stringent than the listing criteria under subsection (D);
 - c. Remove a surface water or segment from the 303(d) List if all pollutants for the surface water or segment are removed from the list;
 - d. Remove a surface water, segment, or pollutant, from the 303(d) List and place it on the Planning List, if:
 - i. The surface water, segment or pollutant was on the 1998 303(d) List and the dataset used in the original listing does not meet the credible data requirements under R18-11-602, or contains insufficient samples to meet the data requirements under subsection (D); or
 - ii. The monitoring data indicate that the impairment is due to pollution, but not a pollutant.

Historical Note

New Section made by final rulemaking at 8 A.A.R. 3380, effective July 12, 2002 (Supp. 02-3).

R18-11-606. TMDL Priority Criteria for 303(d) Listed Surface Waters or Segments

- A. In addition to the factors specified in A.R.S. § 49-233(C), the Department shall consider the following when prioritizing an impaired water for development of TMDLs:
 1. A change in a water quality standard;
 2. The date the surface water or segment was added to the 303(d) List;
 3. The presence in a surface water or segment of species listed as threatened or endangered under section 4 of the Endangered Species Act;
 4. The complexity of the TMDL;
 5. State, federal, and tribal policies and priorities; and
 6. The efficiencies of coordinating TMDL development with the Department's surface water monitoring program, the watershed monitoring rotation, or with remedial programs.
- B. The Department shall prioritize an impaired surface water or segment for TMDL development based on the factors specified in A.R.S. § 49-233(C) and subsection (A) as follows:
 1. Consider an impaired surface water or segment a high priority if:
 - a. The listed pollutant poses a substantial threat to the health and safety of humans, aquatic life, or wildlife based on:
 - i. The number and type of designated uses impaired;
 - ii. The type and extent of risk from the impairment to human health, aquatic life, or wildlife;
 - iii. The pollutant causing the impairment, or
 - iv. The severity, magnitude, and duration the surface water quality standard was exceeded;
 2. Consider an impaired surface water or segment a medium priority if:
 - a. A new or modified individual NPDES or AZPDES permit is sought for a new or modified discharge to the impaired water;
 - b. The listed surface water or segment is listed as a unique water in A.A.C. R18-11-112 or is part of an area classified as a "wilderness area," "wild and scenic river," or other federal or state special protection of the water resource;
 - c. The listed surface water or segment contains a species listed as threatened or endangered under the federal Endangered Species Act and the presence of the pollutant in the surface water or segment is likely to jeopardize the listed species;
 - d. A delay in conducting the TMDL could jeopardize the Department's ability to gather sufficient credible data necessary to develop the TMDL;
 - e. There is significant public interest and support for the development of a TMDL;
 - f. The surface water or segment has important recreational and economic significance to the public; or
 - g. The pollutant is listed for eight years or more.
 3. Consider an impaired surface water or segment a low priority if:
 - a. The surface water or segment fails to meet more than one designated use;
 - b. The pollutant exceeds more than one surface water quality standard;
 - c. A surface water quality standard exceedance is correlated to seasonal conditions caused by natural events, such as storms, weather patterns, or lake turnover;
 - d. It will take more than two years for proposed actions in the watershed to result in the surface water attaining applicable water quality standards;
 - e. The type of pollutant and other factors relating to the surface water or segment make the TMDL complex; or
 - f. The administrative needs of the Department, including TMDL schedule commitments with EPA, permitting requirements, or basin priorities that require completion of the TMDL.

Department of Environmental Quality – Water Quality Standards

- ii. Discharges or activities related to the impairment have ceased, or
 - iii. Actions have been taken and controls are in place or scheduled for implementation that will likely to bring the surface water back into compliance;
 - d. The surface water or segment is ephemeral or intermittent. The Department shall re-prioritize the surface water or segment if the presence of the pollutant in the listed water poses a threat to the health and safety of humans, aquatic life, or wildlife using the water, or the pollutant is contributing to the impairment of a downstream perennial surface water or segment;
 - e. The pollutant poses a low ecological and human health risk;
 - f. Insufficient data exist to determine the source of the pollutant load;
 - g. The uncertainty of timely coordination with national and international entities concerning international waters;
 - h. Naturally occurring conditions are a major contributor to the impairment; and
 - i. No documentation or effective analytical tools exist to develop a TMDL for the surface water or segment with reasonable accuracy.
- C. The Department will target surface waters with high priority factors in subsections (B)(1)(a) through (B)(1)(d) for initiation of TMDLs within two years following EPA approval of the 303(d) List.
- D. The Department may shift priority ranking of a surface water or segment for any of the following reasons:
- 1. A change in federal, state, or tribal policies or priorities that affect resources to complete a TMDL;
 - 2. Resource efficiencies for coordinating TMDL development with other monitoring activities, including the Department's ambient monitoring program that monitors watersheds on a five-year rotational basis;
 - 3. Resource efficiencies for coordinating TMDL development with Department remedial or compliance programs;
 - 4. New information is obtained that will revise whether the surface water or segment is a high priority based on factors in subsection (B); and
 - 5. Reduction or increase in staff or budget involved in the TMDL development.
- E. The Department may complete a TMDL initiated before July 12, 2002 for a surface water or segment that was listed as impaired on the 1998 303(d) List but does not qualify for listing under the criteria in R18-11-605, if:
- 1. The TMDL investigation establishes that the water quality standard is not being met and the allocation of loads is expected to bring the surface water into compliance with standards,
 - 2. The Department estimates that more than 50 percent of the cost of completing the TMDL has been spent,
 - 3. There is community involvement and interest in completing the TMDL, or
 - 4. The TMDL is included within an EPA-approved state workplan initiated before July 12, 2002.

Historical Note

New Section made by final rulemaking at 8 A.A.R. 3380, effective July 12, 2002 (Supp. 02-3).